INCH-POUND

MIL-T-63263 (AR)
AMENDMENT 3
20 November 1988
SUPERSEDING
AMENDMENT 2
11 October 1979

MILITARY SPECIFICATION

TEST SET, ELECTRONICS SYSTEMS: M91

This Amendment forms a part of Military Specification MIL-T-63263 (AR), dated 3 May 1978, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

STANDARDS, MILITARY: Delete the following:

"MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For"

PAGE 3

3.4: Delete "except for temperature humidity which is contained in MIL-STD-331".

3.4.1, Add to end of paragraph: "using curve AW of Figure 514.2-7".

3.4.2: Delete in its entirety.

3.4.3: Delete "Test 105.1 of MIL-STD-331 ..." and substitute "Method 507.1, Procedure I".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

PAGE 5

TABLE I:

Delete the following line:

"Helicopter vibration 2 100% 3.4.2 4.4.3.1".

PAGE 11

4.4.2.5: Delete "9326142" and substitute "9326146".

PAGE 15

4.4.2.9: Delete Minor Defect 201.

PAGE 20

4.4.2.14: Delete Major Defect 102.

PAGE 24

4.4.3.2: Delete in its entirety.

PAGE 28

4.5.1:

Line 4: Delete "conttractor" and substitute "contractor".

Pre-Setting Requirement: Add the following:

"5. Test Set Tester. Set Dispenser Counter M1 to 'thirty'."

PAGE 30

* 4.5.1, 9d, line 3: Delete "--(red)--".

4.5.2: Delete in its entirety.

4.5.3, Add after "Procedure X": "using curve AW of Figure 514.2-7".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

4.5.4: Delete in its entirety and substitute:

"4.5.4 Temperature humidity. Using equipment in accordance with 4.4.4, subject each first article unit to Test Method 507.1, Procedure I of MIL-STD-810. Replace Step 6 and 7 of test method with the following:

Step 6. At the end of the tenth cycle, remove and inspect the test item and condition the test item as 25±5°C (ambient) for at least one (1) hour, operate the test item and obtain results in accordance with General Requirements, 3.2.

If any item fails to meet any of the applicable requirements the first article sample to be rejected."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 4925-A049)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.