MIL-W-63388 (AR)
AMENDMENT 3
3 November 1981
SUPERSEDING
AMENDMENT 2
7 July 1981

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M207E1 BODY AND BOATTAIL BUSHING FOR

This Amendment forms a part of Military Specification MIL-W-63388 (AR) dated 7 January 1980 and is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under "SPECIFICATIONS", Federal: Delete in entirety.

PAGE 2

3.3: Delete in its entirety.

PAGE 4

TABLE 1, under "Body (Dwg. 9332486)": Delete the following:

"Adhesive and Mar Resistance of Paint, 20, 3.3, 4.5.2"

Add new pages 6 and 7 as attached.

PAGE 7

* 4.4.2.1, Add Major defect 123 as follows:

"123 Evidence of raised hanging burrs on exit hole surface of 6 threaded holes, 100%, 3.2, 10X Magnifier"

Page 9

4.5.2, 4.5.2.1 and 4.5.2.2, delete in their entirety.

FSC 1336

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document and relationship to the last previous amendment.

Custodian: Army-AR	Preparing activity: Army-AR
	(Project 1336-A419)

QUALITY CONFORMANCE INSPECTION

MIL-W-63388 (AR)
AMENDMENT 3

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Body	1 OF 2	9332486
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Large inside diameter		0.25%	3.2	Gage
102	True position of small holes		100%	3.2	Gage
103	Diameter of small holes		0.25%	3.2	Gage
104	Perpendicularity of aft shoulder with outside diameter		0.40%	3.2	Gage
105	Large aft diameter		100%	3.2	Gage
106	Runout of large aft diameter with datum		0.40%	3.2	Gage
107	Pitch diameter of large aft thread		0.40%	3.2	Gage
108	Length of ring retaining full thread		0.40%	3.2	Gage
109	True position of small aft holes		100%	3.2	Gage
110	Pitch diameter of small internal threads		0.40%	3.2	Gage
111	Location of wireway slot		0.25%	3.2	Gage
112	Location of boattail positioning slot		0.40%	3.2	Gage
113	Wall thickness, aft end		0.25%	3.2	Gage
114	Small inside diameter at aft end		0.40%	3.2	Gage
115	Runout of small inside diameter at aft end with datums		0.40%	3.2	Gage
116	Inside corner radius, large aft mounting shoulder		0.40%	3.2	Gage
117	Length next to large basic dimension aft end		0.40%	3.2	Gage
118	Length to large basic dimension aft end		0.40%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

QUALITY CONFORMANCE INSPECTION

MIL-W-63388
AMENDMENT 3

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE			SHEET	DRAWING NUMBER
4.4.2.1	Body			2 OF 2	9332486 NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR (Continued)					
119	Length to small basic dimension aft end		0.40%	3.2	Gage
120	Runout between two basic dimensions with datum		0.40%	3.2	Gage
121	Perpendicularity of front face with datum		0.40%	3.2	Gage
122	Runout of O.D. with datums		0.40%	3.2	Gage
MINOR					
201	Distance from front face to missile mounting diameter face		0.65%	3.2	Gage
202	Distance from front face to shoulder		0.65%	3.2	Gage
203	Distance from front face to inside shoulder		0.65%	3.2	Gage
204	Overall length		0.65%	3.2	Gage
205	Minor diameter of small aft threads, max		0.65%	3.2	Gage
206	Major diameter of large aft threads, min		0.65%	3.2	Gage
207	Protective finish, inadequate, scratched or damaged		0.65%	3.2	Visual
208	Identification missing or illegible		0.65%	3.2	Visual
209	Evidence of poor workmanship		1.00%	3.5	Visual

NOTES: