MIL-B-62117G
12 April 1984
SUPERSEDING
MIL-B-62117F
1 September 1981

MILITARY SPECIFICATION

BUSES, MOTOR: COMPACT, FORWARD CONTROL, 8,300 TO 10,900 POUNDS GVW, 12, 16 AND 20 PASSENGER, 4X2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers gasoline engine driven, four-wheel, two wheel drive, compact, forward control type buses having minimum gross vehicle weights (GVW) of 8,300 to 10,900 pounds, for shuttle and short haul usage. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in procurement documents.

1.2 Classification. Buses shall be of the following styles and types, as specified (see 6.2):

Style A - Low headroom - van conversion or wide body.
  Type I - 12 adult passengers.

Style B - High headroom - wide body.
  Type I - 12 adult passengers.
  Type II - 16 adult passengers.
  Type III - 20 adult passengers.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: DRSTA-GBS.1, Warren, MI 48090, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC-2310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Deparment of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

O-E-915	- Extinguishers, Fire, Dry-Chemical (Portable).
W-B-131	- Battery, Storage: Vehicular, Ignition, Lighting and Starting.
* ZZ-T-381	- Tires, Pneumatic, Vehicular (Highway).
LLL-T-1238	- Floor Covering, Linoleum.

MILITARY

* MIL-B-46176	- Brake Fluid, Silicone, Automotive, All Weather, Operational and Preservative.

STANDARDS

FEDERAL

FED. STD. No. 595	- Colors.

MILITARY

MIL-STD-1223	- Nontactical Wheeled Vehicles Treatment, Painting, Rustproofing, Identification Marking and Data Plate Standards.

* 2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DoT)

Compliance with Interstate Motor Carrier Noise Emission Standard.
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

(Application for copies should be addressed to the Department of Transportation, Federal Highway Administration, Washington, D.C. 20591.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)
Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.
Interstate Motor Carrier Noise Emission Standards.

(Application for copies should reference the Code of Federal Regulations, 40 CFR and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)
ASTM STANDARDS
ASTM Designation: A525 - Specifications for General Requirements for Delivery of Zinc-Coated (Galvanized) Iron or Steel Sheets, Coils and Cut Lengths Coated by the Hot-Dip Method.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

* SAE, INC.
SAE Standards and Recommended Practices.

J245	- Engine Rating Code - Spark Ignition.
J381	- Windshield Defrosting Systems Test Procedure - Trucks, Buses, and Multipurpose Vehicles.
J382	- Windshield Defrosting Systems Performance Requirements - Trucks, Buses, and Multi-purpose Vehicles.
J537	- Storage Batteries (DoD adopted).
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (20-1000 MHz).
J583	- Fog Lamps.
J588	- Turn Signal Lamps.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

	J589	- Turn Signal Switch.
	J688	- Truck Ability Prediction Procedure (DoD adopted).
*	J1349	- Engine Power Test Code - Spark Ignition and Diesel.

(Application for copies should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.6, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity prior to delivery of the item.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

3.1.1.1 Painting and marking. As specified by the procuring activity for the appropriate service (see 6.2), treatment, painting, identification marking and data plates shall be in accordance with MIL-STD-1223; except, when specified (see 6.2), the exterior color shall be gloss yellow matching color chip No. 13432 of FED. STD. No. 595.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with MIL-STD-1223. When specified (see 6.2), tropical rustproofing in accordance with MIL-STD-1223 shall be furnished.

3.1.1.3 Heavy duty cooling system. A heavy duty cooling system shall be furnished that will maintain coolant at a temperature below the boiling point, with vehicle loaded to rated gross vehicle weight (GVW) and operated at 10,000 feet above sea level, or in ambient air temperatures of not less than 125 degrees Fahrenheit (°F).

* 3.1.1.4 Coolant recovery system. The coolant system shall include a de-aeration system, a surge tank, or a coolant recovery reservoir of not less than two-quart capacity.

3.1.1.5 Wood treatment. Wood flooring (see 3.5.4) shall be treated in accordance with MIL-STD-1223.

* 3.1.1.6 Silicone brake fluid. When specified (see 6.2), and if available as the manufacturer's standard or optional brake fluid, silicone brake fluid conforming to MIL-B-46176 shall be provided in the hydraulic brake system. A tag shall be placed near the master cylinder stating "CAUTION: USE SILICONE BRAKE FLUID ONLY, MIL-B-46176."

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture, including standards applicable only to school buses, except:

(a) Exterior color shall be as specified in 3.1.1.1.
(b) School bus signal lamps may be omitted when specified (see 3.4.2.8).
(c) Compliance with Federal Motor Vehicle Safety Standard No. 222 is not required. Seats shall be in accordance with 3.5.8 in lieu of Federal Motor Vehicle Safety Standard No. 222.

3.2.2 Air pollution control. The vehicle shall comply with EPA regulations governing control of air pollution from new motor vehicles and new motor vehicle engines in effect on the date of manufacture. In addition, vehicles destined for California shall comply with State of California regulations governing air pollution control in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.2.3 Sound level. The vehicle exterior sound level shall conform to EPA Interstate Motor Carrier Noise Emission Standards when tested in accordance with the Regulations of the Department of Transportation, Part 325. The vehicle interior sound level shall conform to Federal Motor Carrier Safety Regulation 393.94.

3.2.4 Curb weight. The curb weight shall include the weight of the chassis, with all attachments, accessories, and equipment; and a full complement of fuel, lubricants and coolants.

3.2.5 Payload. Vehicle payload shall consist of one operator plus the number of passengers specified (see 1.2), computed at 175 pounds each.

3.2.6 Gross vehicle weight. Gross vehicle weight (GVW) shall be the combined curb weight and payload weight. Maximum rated GVW shall not exceed chassis manufacturer's rating, and shall be not less than the following:

(a) Style A - 8,300 pounds
(b) Style B, type I - 9,000 pounds
(c) Style B, type II - 9,700 pounds
(d) Style B, type III - 10,900 pounds.

3.2.7 Dimensions. Bus interior body dimensions shall be as specified in 3.5.2 and bus external dimensions shall be as follows:

(a) Overall width shall be not less than 79 inches for style A bus, not less than 84 inches for style B bus, and not greater than 96 inches for either style A or style B bus. The body width at the driver's station for style B bus shall be not less than 79 inches, but need not be equal to the passenger compartment width;
(b) Overall height shall be not greater than 117 inches;
(c) Wheelbase shall be not less than 125 inches, except style B, type III bus shall be not less than 157 inches;
(d) Overall length shall be not greater than 230 inches, except style B, type III bus shall be not greater than 253 inches;
(e) Ground clearance shall be not less than seven inches under axles and not less than nine inches under all other parts.

3.2.8 Ratings. Vehicle ratings shall be manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.2.9 Accessibility. The design of the vehicle and optional equipment shall permit ready accessibility for routine servicing and shall permit accessibility for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.3 Performance.

3.3.1 Speeds and gradeability. High and low speed requirements shall be met with the vehicle loaded with specified payload.

3.3.1.1 High speed gradeability. The vehicle shall ascend a 2.0 percent grade at 50 miles per hour (mph). Gradeability shall be verified with calculations in accordance with SAE J688 (see 6.3).

3.3.1.2 Low speed. Low speed shall be calculated with the engine operating at not less than 35 percent of the recommended operating speed, and shall provide a vehicle speed not greater than 4 mph.

3.3.2 Service brakes. The service brakes shall control and hold the vehicle, when loaded to its required GVW, on a 30 percent grade. The service brakes shall stop the vehicle, loaded to required GVW, within the stopping distance requirements of Federal Motor Carrier Safety Regulation 393.52.

3.3.3 Turning radius. The turning radius, defined as the distance from the turning center to the centerline of the tire describing the largest circle while the vehicle is executing its sharpest practicable turn, shall be not greater than 30 feet.

3.4 Chassis components.

* 3.4.1 Engine. The engine shall be a liquid cooled, internal combustion, four-stroke cycle gasoline type, with not less than six cylinders. The engine shall produce the required vehicle performance when operated on unleaded fuel with a research octane rating of 91, at engine speeds not more than manufacturer's recommended operating speed. The engine shall be capable of warranted operation on unleaded fuel, when used in accordance with the operator's manual. Engine net horsepower used in performance prediction calculations shall be determined in accordance with SAE J245 or SAE J1349.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.1.1 Oil filter. A full flow oil filter shall be furnished.

3.4.1.2 Governor. When available as standard or optional equipment, an engine governor shall be furnished, set and sealed to limit the engine to its maximum recommended operating speed.

3.4.1.3 Power plant heaters. When specified (see 6.2), coolant and engine oil heaters shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided when power plant heaters are specified. Heaters shall operate on 120-volt alternating current (ac), and shall be wired through a junction block to a single three pronged (male), weatherproof, slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, weatherproof, three pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60°F) without cracking or loss of dielectric capacity. All heater wires shall be installed without interfering with vehicle component operation, and without loose excess wire. A carrier for the connecting cable shall be mounted within the cab or engine compartment and shall provide positive cable retention during vehicle operation. Heaters shall be furnished as follows:

(a) Coolant heater, 1500-watt minimum rating, shall be installed in the engine block or lower coolant inlet hose. Engine thermostat with an operating range of 170°F to 195°F shall be installed;
(b) Immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in oil pan through any convenient opening;
(c) Battery heater shall have a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperatures as low as minus 60°F, and shall embody a thermostat to limit the temperature of the electrolyte to not more than 80°F.

3.4.2 Electrical system. The electrical system shall be in accordance with Federal Motor Carrier Safety Regulation 393.27 through 393.31 and 393.33.

* 3.4.2.1 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.2.2 Ignition system. A 12-volt direct current (dc) ignition system with a 55-ampere (minimum) alternator, which provides not less than 16 amperes dc output at normal engine idle speed, shall be furnished.

* 3.4.2.3 Battery. The battery furnished shall be of 12-volt potential. The total reserve capacity rating, measured in accordance with SAE J537, shall be not less than 100 minutes. The total cold cranking rating at 0°F, measured in accordance with SAE J537, shall be not less than 450 amperes. The battery shall be of the maintenance free type having maintenance free characteristics listed in W-B-131. The battery shall be located in an accessible location in the engine compartment or on a sliding tray in an enclosed compartment. The tray shall be coated with acid-resistant material. The battery compartment shall be provided with an access door on the side of the body, and the sliding tray, with battery mounted, shall be capable of being pulled out for inspection without detaching the battery. When air conditioning is specified (see 3.5.10.4), additional battery capacity shall be furnished, if required to meet total electrical power requirements.

3.4.2.4 Battery cables. The battery cables shall be routed and secured in such a manner as to preclude chafing of the cable at any point. The vehicle shall be furnished with a one-piece battery-ground cable and a one-piece battery-to-solenoid cable. Cables shall be mounted, fastened, and protected so that they will not become loose during service. The edges of all holes in metal members through which the cables pass shall be bushed with rubber grommets.

3.4.2.5 Lighting. Vehicle lights, reflectors, and wiring shall conform to Federal Motor Carrier Safety Regulations 393.12, 393.19, 393.20 and 393.22 through 393.26. Electrical system shall be 12 volts. Lights and reflectors shall not be mounted on rub rails (unless recessed and fully protected) or vehicle bumpers. An illuminated rear license plate holder shall be provided. When specified (see 6.2), two fog lamps, in accordance with SAE J583, shall be furnished.

3.4.2.5.1 Turn signals. Turn signal lamps shall conform to SAE J588. Operating units shall conform to SAE J589, class A, and shall be mounted on the steering column. The vehicle shall be provided with double-faced front signal units or single-faced front signal units in conjunction with armored, amber turn signals over the front wheelwells, and with single-faced rear signal units. Signal units shall be installed in accordance with SAE J588, except that turn signals shall not be mounted on the engine compartment hood. Operating units shall be provided with a visible and audible flash indicator. Turn signals shall be of the self-cancelling type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.2.5.2 Interior lighting. Interior lighting shall include 15-candlepower domelights, of grade and quality providing not less than 12 square inches of polished reflecting surface, fitted with frosted translucent lens providing not less than 30 square inches area. For style A bus, not less than two domelights shall be installed in the passenger area. For style B bus, domelights shall be installed over each row of two-passenger seats, placed over the first or second seat from the front, and thereafter over each second seat. One domelight shall be installed over the driver area and controlled with a separate switch. Door operated step lamp(s) shall be furnished and installed to provide illumination of stepwell and ground adjacent to steps. An emergency door identification red light with not less than a three-inch diameter lens shall be provided in accordance with Federal Motor Carrier Safety Regulation 393.92.

3.4.2.6 Passenger signal buzzer. When specified (see 6.2), manufacturer's standard signal buzzer equipment shall be furnished, operated by pull cords on both sides of the bus, and provided with a driver's cut-out switch.

3.4.2.7 Horn. An electric horn, suitable for bus service, shall be furnished.

3.4.2.8 School bus red signal lamps. Unless otherwise specified (see 6.2), the vehicle shall be equipped with four red signal lamps conforming to Federal Motor Carrier Safety Standard No. 108.

3.4.3 Fuel system. The fuel system shall conform to Federal Motor Carrier Safety Regulations 393.65 and 393.67.

3.4.3.1 Air cleaner. An air cleaner shall be furnished. When equipped with an oil-bath type air cleaner, oil capacity shall be not less than one quart.

3.4.3.2 Fuel tank. A single safety fuel tank conforming to Federal Motor Carrier Safety Regulations 393.65 and 393.67 shall be furnished. Fuel tank shall have not less than 22 gallons capacity and shall be located under the floor of the bus. Tank filler shall be arranged for safe and convenient filling from exterior of body. The access for the filler neck shall be designed to prevent the entry of spilled gasoline to any point inside the exterior body panel. Sealing may be accomplished by use of a neoprene rubber thimble or grommet, or other device installed in the access hole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

* 3.4.4 Exhaust system. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83. The exhaust tailpipe shall extend to the rear bumper and shall be located to minimize the possibility of exhaust fumes entering the body.

3.4.5 Transmission. Transmission input torque capacity shall be at least equal to the maximum torque delivered by the engine. Rear axle ratios and transmission ratios shall provide the specified speeds and gradeability (see 3.3.1).

3.4.5.1 Automatic transmission. Unless otherwise specified (see 3.4.5.2), a continuous drive, automatic transmission shall be provided. The transmission shall include a hydraulic torque converter and not less than three forward gear ratios. Normal driving range selector position shall provide not less than three gear ratios without movement of the selector.

3.4.5.2 Manual transmission. When specified (see 6.2), the manufacturer's standard manual synchromesh transmission shall be furnished. The transmission shall provide one reverse speed and not less than three forward speeds. The transmission shall provide for maximum ease of shifting with synchronized shift in all gear ranges.

3.4.5.2.1 Clutch. The clutch shall be the largest capacity clutch offered for the size of engine furnished with torque capacity exceeding maximum delivered engine torque.

3.4.6 Drive line components. Drive line components shall be adequate to transmit the maximum delivered torque of the engine, as developed through the maximum gear train reduction. Propeller shaft guards shall be provided in accordance with Federal Motor Carrier Safety Regulation 393.89.

3.4.7 Chassis frame. The chassis frame for bus mounting shall be so designed and constructed as to support body and load and to maintain stability under all operating conditions.

3.4.8 Suspension. The vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with vehicle loaded with specified payload. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted. The vehicle shall be equipped with hydraulic double-acting shock absorbers on the front and rear wheels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.9 Axles. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, when the vehicle is loaded with the specified payload. A single reduction rear axle shall be furnished.

3.4.9.1 Positive traction differential. When specified (see 6.2), the drive axle shall be furnished with positive traction, limited slip, or automatic locking differential.

3.4.10 Wheels, rims, tires and tubes. The vehicle shall be equipped with single front and single or dual rear wheels. Rim size shall be the same for all wheels on the vehicle. Tire size and ply rating shall be the same for all tires on the vehicle. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished.

* 3.4.10.1 Tires. Tires shall be tube or tubeless truck type with highway tread. Steel belted radial or, when specified (see 6.2), bias ply tires shall be furnished. Tires shall have a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded with specified payload. Tires shall conform to Tire and Rim Association recommendations or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.10.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of heavy duty type, and shall be of proper size for the tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

3.4.10.3 Balancing. Each tire shall balance within practicable limits. Wheels, hubs, and brake drums shall be effectively in balance. Balancing shall be adequate to preclude wheel shimmy at all vehicle speeds.

* 3.4.10.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be installed in a readily accessible location. When a spare tire assembly is furnished (see 3.4.10.5), a spare wheel or rim shall be furnished.

* 3.4.10.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same type, size, tread design and ply rating as the tires in use on the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.4.11 Brakes. Brakes shall conform to Federal Motor Carrier Safety Regulations 393.40 through 393.42(b), 393.43 and 393.45 through 393.51. The vehicle shall be equipped with vacuum assisted, hydraulic actuated service brakes on all wheels.

3.4.11.1 Split hydraulic brake system. The vehicle shall be equipped with a service brake system so arranged as to provide separate systems for at least two wheels and so designed and constructed that rupture or leakage type failure of any single pressure component of the service brake system, except structural failures of the brake master cylinder body, effectiveness indicator body, or other housing common to the divided system, will not result in complete loss of function of the vehicle brakes when force on the brake pedal is continued. "Pressure component" means any internal component of the brake master cylinder or master control unit, wheel brake cylinder, brake line, brake hose, or equivalent, except vacuum assist components.

3.4.11.2 Indicator light. Split hydraulic brake system shall be equipped with an electrically operated red light mounted on the instrument panel to indicate system effectiveness. The light shall have an area of not less than 0.196 square inch. It shall illuminate before or upon application of the brakes when an actuating-pressure component of the system has sustained a loss of pressure. The indicator light system shall include a means for testing by the vehicle operator to assure that the light bulb is operable.

3.4.12 Steering. Manufacturer's standard power steering shall be furnished.

3.4.13 Windshield wipers and washers. The vehicle shall be equipped with dual electric windshield wipers with not less than two operating speeds. Wipers and arms furnished with the bus shall sweep the maximum practicable area of windshield surface. Location and method of mounting shall not comprise a safety hazard or interfere with entrance or exit of the driver or passengers. Windshield washers shall be provided. Washers shall be electric or vacuum operated with a control on the instrument panel.

3.4.14 Bumpers. A front bumper shall be provided. The rear bumper shall conform to Federal Motor Carrier Safety Regulation 393.86 and shall be as specified in 3.5.11.6.

3.4.15 Tools. When specified (see 6.2), the vehicle shall be furnished with the tools required for exchanging a mounted tire assembly with a spare assembly (see 3.4.10.5), and shall include at least a hydraulic jack, jack handle, and wheel nut wrench. The jack shall be of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.4.16 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left-hand drive. Controls shall be complete and conveniently operable by the driver when in a seated position. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's seat. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. Instruments shall be panel mounted.

3.4.17 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, charging indicator or voltmeter
(c) Fuel gage
(d) Oil pressure gage or indicator
(e) Engine temperature gage or indicator
(f) Speedometer with recording odometer.

3.5 Body. The bus shall provide adequate seating for 12, 16, or 20 adult passengers, as specified (see 1.2). The bus body shall exclude engine fumes and exhaust gases from the bus interior, and shall provide safe and comfortable transportation for passengers and driver.

3.5.1 Body styles. The style A bus shall be a forward control van conversion with a low headroom raised roof and the chassis manufacturer's standard body width at the beltline; or a wide body with low headroom, mounted on a forward control chassis. The style B bus shall be a high headroom, constant beltline width body mounted on a forward control chassis; or the passenger area of the body shall be wider than the driver's cab and mounted on a commercial cutaway van chassis.

3.5.2 Inside body dimensions. At the top of the passenger seat back, the body inside width shall be not less than 72 inches for style A bus; not less than 78 inches for style B, type I bus; and not less than 85.5 inches for style B, type II and type III buses. At the aisle centerline, the inside height shall be not less than 60 inches for style

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

A bus and not less than 72 inches for style B bus. The length of the passenger compartment shall be sufficient to provide not less than the minimum seat spacing.

3.5.3 Construction. Body and roof framing shall be constructed of formed steel sections or tubing. Wood shall not be used for structural framing or panels, but may be used over metal flooring. Outside body panels and other sheet metal shall be aluminum alloy or steel and of proper gages, not less than the gages, as applicable, regularly furnished by the body manufacturer in buses of the model offered. The body, roof and panel joints shall be watertight and leakproof. Unless zinc coated steel panels are used, joints shall be sealed with Alumelastic compound or equivalent. All steel used by the bus body builder 12 gage (0.1046 inch) and lighter shall be zinc coated in accordance with ASTM Designation: A525, and Table 1, Coating Class G60. All parts, where applicable, shall be fastened together in a manner which will preclude loosening of bolts, screws, and rivets, and cracking of welded joints when the vehicle is properly maintained and operated under the intended service conditions. Self-tapping screws shall not be used where subjected to stress.

3.5.4 Floor. The floor frame and floor plates, with entrance step and wheelhousings, shall be of substantial construction properly integrated with the body structure, and shall conform to Federal Motor Carrier Safety Regulation 393.84. Wood parts, including plywood, shall be treated as specified in 3.1.1.5. Plywood used in floor panels shall be water-resistant, exterior grade, fir or dense southern pine. Floor panels shall be not less than 1/2-inch, 5-ply plywood, applied over steel of not less than the gage regularly furnished by the body manufacturer in buses of the model offered. Steel channels, not less than two inches in depth and spaced to provide support for the loads imposed, shall be furnished under the floor.

3.5.4.1 Stepwell. The stepwell shall be of the enclosed two-step type constructed of steel, covered with 3/16-inch thick rubber or synthetic rubber blend ribbed material. The height of the bottom step shall not exceed 16 inches. Padding shall be provided above the stepwell to provide head protection for exiting passengers.

3.5.4.2 Wheelhousings. Rear wheelhousings shall include splash shields under the body. Splash shields shall extend around the top of the wheel and to the bottom of the body side skirting, front and rear. Ample clearance for the use of tire chains on at least the outside driving wheels shall be provided.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

3.5.4.3 Floor coverings. The underseat floor area and the wheelhousings shall be covered with not less than 1/8-inch thick rubber or synthetic rubber blend material; or linoleum conforming to type I, class I, grade B of LLL-F-1238. The aisle and entrance shall be covered with not less than 3/16-inch thick rubber or synthetic rubber blend ribbed material. Coverings shall be properly installed and adequately sealed at the joints. The floor in the driver's area shall be covered with a mat or with the same materials used in the underseat or aisle areas.

3.5.5 Roof. The roof exterior and interior panels shall be of steel sheet, aluminum sheet, or molded fiberglass construction. All panels shall be fully integrated into the body shell and securely fastened to the framing or roof bows, as applicable.

3.5.5.1 Rollover protection. The bus roof structure shall be in accordance with Federal Motor Vehicle Safety Standard 220.

3.5.5.2 Insulation. Nonsettling, nonhygroscopic, fungus resistant, fireproof insulation shall be installed in roof, side, and end walls. In addition, a coat of material shall be applied to the inner (not exposed) surfaces of exterior panels and other sheet metal as added insulation and to prevent drumming.

3.5.5.3 Destination sign compartment. When specified (see 6.2), a destination sign compartment shall be installed at front center of the roof above the windshield. The compartment shall provide not less than 180 square inches of glass enclosed frontal area, of a height to permit reading of six-inch letters on the sign roller, and shall be readily accessible, through the latched door, from inside the bus. The compartment shall be illuminated to permit reading of the destination sign at night. The destination sign shall be a roller type of a capacity to apply 15 listings of six-inch high letters and shall be operable from the interior of the bus. Unless otherwise specified (see 6.2), the destination sign roll will be furnished blank.

3.5.6 Doors. Not less than two doors shall be provided in the bus. The service door shall be at the front, on the side opposite the driving controls, for use by entering and departing passengers. The emergency exit door shall be centrally located in the rear. Each shall be provided with effective compression or overlapping seals to minimize entry of dust, water, and cold air.

3.5.6.1 Service door. The service door shall be either sedan type or two-leaf type, with manual control conveniently located for driver use. The operating linkage shall be installed within the body or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

enclosed to preclude accumulation of mud, ice, or snow. Minimum dimensions for style B bus door clear opening shall be 24 by 70 inches, unobstructed by door seals or door operating mechanisms.

3.5.6.2 Emergency door. The emergency door shall be located in the center at the rear for convenient exit. A permanently installed handle, recessed flush with the side of the body, shall be provided for opening the emergency door from outside the bus. A switch operated by the door bolt shall be connected to a buzzer in the driver's area to indicate to the driver when the emergency door is not safely latched. A red emergency door identification light (see 3.4.2.5.2) shall be installed on the emergency door header. The red warning light shall activate when the ignition switch is in the "on" position. The header shall be marked with the following in block letters not less than two inches high: EMERGENCY DOOR.

3.5.6.3 Door locking provisions. When specified (see 6.2), locking provisions shall be furnished for the service and emergency doors. The sedan type service door shall be key locked and two-leaf doors shall be provided with a hasp for padlocking. A locking bolt shall be provided for the emergency door, with an interlock to prevent the engine from starting when the emergency door is locked.

3.5.7 Windshield. A windshield affording maximum practicable driver vision shall be installed at a slope sufficient to minimize external glare or reflections from inside the body. If the windshield is not cleanable from ground level, a step and a grab handle shall be provided on each side of the bus to facilitate cleaning the windshield.

3.5.7.1 Windows. Windows shall be provided with fingertip control, permitting ready opening and adjustment to various desired openings. Windows shall be rattleproof and, when closed, rainproof, waterproof, and windproof. Driver's windows shall permit use for signaling and ventilation. Safety glass shall be used in all windows. All windows shall be fitted with locking devices. When air conditioning is furnished, or when specified (see 6.2), manufacturer's standard tinted windows and windshield shall be furnished.

3.5.8 Seating. Seating shall be provided for the number of adult passengers specified (see 1.2).

3.5.8.1 Seating arrangement. The seating arrangement shall consist of three, four, or five rows of forward facing seats mounted on each side of an aisle of not less than 14 inches in width. For styles A and B, type I buses, two-passenger seats shall be furnished on both sides of the aisle, or there shall be two-passenger seats on one side of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

the aisle and one-passenger seats on the other. On style B, types II and III buses, two-passenger seats shall be furnished on both sides of the aisle. The aisle and seating locations shall be arranged to provide adequate access to the front streetside door and rear emergency door. Individual seat locations in one row may be staggered with respect to the other row, if required to maximize seat spacing or improve access.

3.5.8.2 Seating dimensions. Seats shall be spaced on not less than 30-inch centers for style A, 32-inch centers for style B, type I, and 29-inch centers for style B, types II and III buses. There shall be not less than 10 inches between the forward edge of the seat cushions and the back of the seat or barrier panel ahead. Seat width for two-passenger seats shall be not less than 36 inches. Width for single-passenger seats shall be not less than 22 inches. Seat back width may be reduced at the emergency door to provide clear access to the door. Seat cushions shall have a free depth of not less than 17 inches from the forward edge of the cushion to the seat back. Seat back height from the seat cushion shall be not less than 18 inches.

* 3.5.8.3 Passenger seat construction. Passenger seat frames shall be of formed metal tube construction. Seat backs shall be inclined, shaped, and padded to provide passenger support and comfort. The top, the upper corners, and the upper 10 inches of the rear surface of each passenger seat back (except the rearmost seats) shall be constructed of or covered with force distributing material. The material shall minimize force and spread the area of contact upon impact by an occupant in the next seat to the rear. The rear surface of the seat back below the force distributing material shall be upholstered or covered with aluminized steel or bright finish zinc coated steel. Seat cushions shall be solid foam padding tapering from a minimum of five inches at the front to three inches at the rear or not less than two inches of padding on a spring base.

3.5.8.4 Seat covering. Seat and force distributing cover material shall be first grade, heavy duty, plastic-coated, grained surface fabric of not less than 35 ounce weight per lineal yard of 54-inch width. All seat material shall be in accordance with the flameproof requirements of Federal Motor Vehicle Safety Standard No. 302. Color of upholstery shall be appropriate with exterior color and shall coordinate with interior colors.

3.5.8.5 Driver's seat. The driver's seat shall be the chassis or body manufacturer's standard seat, and shall be adjustable fore and aft without the use of tools. The seat shall be positioned for convenient and safe operation of all controls by the driver. The seat cushion and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

back shall be padded, contoured to provide maximum driver comfort, and covered with heavy duty vinyl or polyester material. A seat belt shall be provided.

3.5.9 Stanchion and barriers. A stanchion or grab rail shall be provided at the service door to assist entering passengers. When the stanchion is located to the rear of the service door, it shall be padded. A padded barrier shall be provided ahead of the right front seat between the seat and the entrance step. The barrier width shall be approximately equal to the seat width.

3.5.10 Heating, defrosting and ventilating. The heating, defrosting, and ventilating system shall conform to Federal Motor Carrier Safety Regulation 393.77 and 393.79.

3.5.10.1 Heater. A hot water heater system, having a total capacity of not less than 35,000 Btu per hour for style A bus and 60,000 Btu per hour for style B bus at 150°F water to ambient air temperature differential, shall be installed. Adjustable manual controls shall be provided to permit outside air, recirculated air, or variable mixtures as desired, to circulate through at least the main heater core. Heater(s) shall be located to assure flow of heated air to the driver's area and to all parts of the passenger compartment, and so that no objectionable flow is directed toward any passenger. Heater hoses shall be shielded from the passenger compartment and located in protected positions. An auxiliary recirculating heater shall be provided if required to maintain a comfortable temperature for all passengers.

3.5.10.2 Defroster. Defroster outlets with suitable connections and independent blower(s) shall be furnished for the driver's side and a fan or blower for the opposite side of the windshield to provide an adequate flow of air to both halves of the windshield. The windshield defrosting systems shall conform to SAE J381 and SAE J382.

3.5.10.3 Ventilator. Ventilator(s) of the static type, capable of providing an adequate supply of fresh air and of properly ejecting foul air under all conditions of operation, shall be provided in the roof. Outside openings for heaters and ventilators shall be located to minimize entry of fumes, rain, road dust, and road wash. Vent openings shall be provided with a weatherproof cover with means of opening and closing from inside the vehicle.

3.5.10.4 Air conditioning. When specified (see 6.2), the manufacturer's standard air conditioning system shall be furnished. The system shall provide adequate cooling for all passenger locations. The

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

air conditioning system shall include, but shall be not limited to, any necessary insulation, increased engine cooling capacity, alternator and battery capacities, and tinted windshield, window and door glass if available.

3.5.11 Body equipment. Body equipment shall be complete with all accessories listed by the body manufacturer as standard equipment, and in addition shall include items specified in 3.5.11.1 through 3.5.11.9.

3.5.11.1 Mirrors. Two outside rearview combination (flat and convex) mirrors, enclosed in a common housing, shall be furnished. Each combination mirror shall have at least 50 square inches of flat reflective area and a convex surface having at least 20 square inches of reflective area. Inside rearview mirror shall be furnished having a reflective surface area of not less than 80 square inches.

3.5.11.1.1 Crossview mirror(s). When specified (see 6.2), the manufacturer's standard convex crossview mirror(s) shall be mounted on the front of the bus to provide a driver's view of the front bumper and the area in front of the bus.

3.5.11.2 Sunvisor. An adjustable sunvisor, not less than 6 by 16 inches, shall be furnished.

3.5.11.3 Emergency reflective triangles. Three emergency reflective triangles conforming to Federal Motor Carrier Safety Regulation 393.95(f)(2)(i) shall be furnished and properly stowed.

* 3.5.11.4 Emergency equipment. A five-pound dry chemical type fire extinguisher conforming to Federal Motor Carrier Safety Regulation 393.95(a) shall be mounted convenient to the driver. The fire extinguisher shall have an Underwriter's Laboratory rating of 10B:C or more, shall include a metal safety pin and wire, and shall conform to type I or type II, class 2, size 5 of O-E-915. The fire extinguisher shall permit visual determination of condition of charge.

3.5.11.5 Stowage compartment(s). Provisions shall be made for weatherproof stowage of tools and tire chains, when carried, to be secured by a padlock. The padlock is not required to be furnished.

3.5.11.6 Rear bumper. The chassis manufacturer's standard bumper may be furnished for style A. For style B, the rear bumper shall be of the heavy steel channel type with anti-ride and anti-hitch features, attached in a manner to permit the bus to be pushed without permanent distortion of bumper, body, or chassis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

3.5.11.7 Keys. Keys in duplicate, for all key-operated locks, properly identified, shall be safely packed and secured to the vehicle steering wheel or otherwise stowed in an approved manner for shipment. All locks on the same vehicle shall be of the same key code, except the ignition.

3.5.11.8 Signs. Signs to read "DANGER - DO NOT EXTEND ARMS FROM WINDOWS" shall be affixed to the interior of the body, in not less than four appropriate locations, legible at a distance of 20 feet: one at the front, one at the rear, and one on each side.

3.5.11.9 Standee line. Areas prohibited to standees shall be marked in accordance with Federal Motor Carrier Safety Regulation 393.90.

3.5.12 Body mounting. Heavy rubber cushions or antisqueak material shall be utilized between the body frame and attaching chassis parts on forward control chassis. Reinforcements or filler blocks shall be used where mounting devices might otherwise deform frame flanges. Mounting devices shall be locked units which will minimize loosening, but which may be tightened if necessary. Cutaway van chassis may use direct mounting of the body to the frame.

* 3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust the vehicle for operational use including at least the following: alining of lights; adjustment of the engine and brake systems; filling and charging of battery; alinement of front wheels; inflation of all tires; complete lubrication of body, chassis, engine, and running gear, with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of cooling system with a solution of ethylene glycol type antifreeze and water in equal parts by volume; and servicing of windshield washer reservoir with water and appropriate additives.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.3.1 Radio frequency suppression verification. The vehicle manufacturer shall furnish, with the questionnaire (commercial vehicle engineering data), a description of all interference suppression devices used to suppress vehicle electromagnetic radiation in accorance with SAE J551. Data shall be sufficient for visual determination that all required suppression devices are installed on the vehicle.

4.3.2 Wood treatment certification. Manufacturer's records, acceptable to the Government, shall be furnished to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

4.3.3 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and distribution of curb weight on front and rear axles. The imposed loading on front and rear axles will be computed using the curb weight and the specified payload, uniformly distributed over the vehicle load area. Calculated imposed loads on front and rear axles will be utilized to ascertain that suspension, axles, and tires furnished are of adequate capacity to meet contractual requirements.

4.3.4 Road test. The first production vehicle shall be examined and road tested with payload by the contractor to assure that the vehicle will operate in accordance with the contractual requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:23Z
Check the source to verify that this is the current version before use.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in a serviceable condition for the duration of the contract.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. Each production vehicle, less payload, shall be examined and driven on approximately level road surfaces by the contractor to assure that the vehicle will operate in accordance with the contractual requirements. The contractor may authorize his sub-contractor, who will perform the final assembly work on the vehicle, to make such examination and tests, but this shall not relieve the contractor of his obligation to deliver an acceptable vehicle or constitute a waiver of any warranty provision. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 has been accomplished.

4.4.1 Rejection. Deficiencies of workmanship and nonconformance to any requirement of the contract shall be cause for rejection until corrective action has been taken.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for general nontactical use by the Government in transporting adults over roads and highways encountered by the Military services in the continental United States and overseas areas and for operation in all climates. The principal use of the vehicles will be in stop and go, short haul, medium and low speed operation.

* 6.2 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

(a) Title, number, and date of this specification.
(b) Style and type of vehicle required (see 1.2).
(c) Identification of appropriate service for painting and marking (see 3.1.1.1).
(d) Gloss yellow exterior color, if required (see 3.1.1.1).
(e) Concealed markings, if required (see 3.1.1.1).
(f) Rustproofing, if required (see 3.1.1.2).
(g) Tropical rustproofing, if required (see 3.1.1.2).
(h) Silicone brake fluid, if required (see 3.1.1.6).
(i) Power plant heaters, if required (see 3.4.1.3).
(j) If a battery heater is not required (see 3.4.1.3).
(k) A pair of fog lights, if required (see 3.4.2.5).
(l) Signal buzzer, if required (see 3.4.2.6).
(m) If red signal lamps are not required (see 3.4.2.8).
(n) Manual transmission, if required (see 3.4.5.2).
(o) Positive traction differential, if required (see 3.4.9.1).
(p) Bias ply tires, if required (see 3.4.10.1).
(q) Spare wheel or rim, if required (see 3.4.10.4).
(r) Spare tire assembly, if required (see 3.4.10.5).
(s) Tools, if required (see 3.4.15).
(t) Destination sign compartment, if required (see 3.5.5.3).
(u) If other than a blank destination sign roll is required (see 3.5.5.3).
(v) Door locking provisions, if required (see 3.5.6.3).
(w) Tinted windows, if required (see 3.5.7.1).
(x) Air conditioning, if required (see 3.5.10.4).
(y) Crossview mirrors, if required (see 3.5.11.1.1).

6.3 Performance prediction. Completed copies of SAE Truck Ability Prediction Procedure form and computation for low speed requirement for each vehicle model furnished under contract should be submitted as specified in the contract. Unless other conditions are cited in the contract, computations should be made for normal atmospheric pressure, normal ambient air temperature, and still, dry, air. The factors to be used in predicting truck ability (see 3.3.1.1) are established as follows for the corresponding SAE J688, Truck Ability Prediction Procedure Tables:

Table 1	- Tire Factor. This factor must relate to the size of tires furnished by the contractor in accordance with this specification.
Table 2	- Altitude Factor. 1.00
Table 3	- Rolling Factor. 1.613
Table 4	- Area Factor. 0.145
Table 5	- Velocity Factor. 250.00

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.

Table 6	- Altitude Factor. 1.00
Table 7	- Chassis Friction Horsepower. Use applicable power unit GVW (to nearest, higher, 1,000 pounds) and the engine rpm (to nearest 100 revolutions) which is required for 50 mph geared speed. For GVW and engine speed beyond the range of this table, the following formula shall be used: FHP = 1 + (0.0000002 rpm)(GVW).
Table 8	- Grade Factor. 0.75
Table 8A	- Correction Factor. Not required.
Table 9	- Road Factor. 0.0.

6.4 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - AT
Navy - YD
Air Force - 99

Preparing activity:
Army - AT

Project No. 2310-0427

Review activities:
Navy - MC
Air Force - 85, 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:23Z
Check the source to verify that this is the current version before use.