MIL-C-60380A (MU)
10 January 1972
SUPERSEDING
MIL-C-60380 (MU)
13 June 1966

MILITARY SPECIFICATION

CARTRIDGE, 105MM, SEMI-FIXED, SMOKE, WP, M60 LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type cartridge designated as Cartridge, 105MM, WP, M60.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 -Ammunition and Special Weapons, General Specification for

STANDARDS

MILITARY

MIL-STD-105 -Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 -Quality Assurance Terms and Definitions
MIL-STD-414 -Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1168 -Lot Numbering of Ammunition
MIL-STD-1235 -Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

7549072	-	Box, Packing, Ammunition, for 105 Howitzer Ammunition in Fiber Container, M105A2
7549073	-	Container, Ammunition, Fiber, M105A2, for 105MM Howitzer Ammunition
9216521	-	Cartridge, 105MM, Semi-Fixed, Smoke, WP, M60, Dualgran, with Fuze, PD, M557, for 105MM Howitzer M2 and M4, Assembly and Marking Diagram
9257991	-	Cartridge, 105MM, Semi-Fixed, Smoke, WP, M60, Dualgran, w/o Fuze, for 155MM Howitzer M2A1, M2A2, M103, and M137
9258026	-	Container, Ammunition, Fiber, PA55, for 105MM Howitzer Ammunition, w/o Fuze
9258027	-	Box, Packing, Ammunition for 105MM Howitzer, Ammunition, w/o Fuze in Fiber Container PA55

PUBLICATIONS

ARMY

ET-9216521 - Equipment Tabulation Number

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Material and parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridges.-The cartridges shall comply with all requirements specified on Drawing (dwg.) 9216521 or 9257991 and with all requirements specified in applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

3.3 Primer.-The primers shall have the required number and location of flash holes as specified on the appropriate primer drawing.

3.4 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.1.

3.4.1 Muzzle velocity.-The corrected muzzle velocity of the projectile at ambient temperature shall be not more than 473 meters per second nor less than 457 meters per second and the standard deviation of the lot shall be not greater than 2.5 meters per second.

3.4.2 Premature functioning.-There shall be no premature functioning in the gun bore or in flight before impact.

3.4.3 Functioning.-There shall be visible evidence of functioning upon impact as indicated by presence of a smoke cloud with a minimum loss of screening effect due to pillaring action.

3.4.4 Safety.-There shall be no premature burst or indication of metal parts separation in the gun bore or in flight when fired with propellant adjusted to give 112 percent of the rated maximum pressure for the cartridge.

3.5 Workmanship

3.5.1 Cartridge.-All manufacturing, processing and assembly operations of the cartridge shall be correctly performed in a thoroughly workmanlike manner. Parts shall be free of cracks, burrs, chips, dirt, grease, rust or other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall they be contaminated by the cleaning agents.

3.5.2 The painting and marking shall be restored by the assembling contractor on any component furnished to him painted and marked, when such paintings and markings have been marred or obliterated.

3.5.3 Care shall be exercised at all times so that the rotating band of the projectile is not nicked, burred, or otherwise damaged.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect number and paragraph, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contactual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revision, same specifications and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determine by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Cartridge cases of one lot interfix number from one manufacturer.
b. Filled projectiles of one lot interfix number from one manufacturer.
c. Propelling charges from not more than one lot from one manufacturer.
d. Loaded projectile of same weight zone.
e. Loaded fuzes of one lot interfix number from one manufacturer.
f. Loaded burster, projectile of one lot interfix number from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Projectile as received from WP loading facility (see dwg. 9216522 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:		
1.	WP leakage or evidence of leakage	Visual
Major:	AQL 0.40 percent	
101.	Foreign matter in fuze and burster cavity	Visual
Minor:	AQL 0.65 percent	
201.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.2 Fuze well cup (see dwg. 9210894 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical: None defined.		
Major:	AQL 0.40 percent	
101.	Pitch diameter of thread	Gage
102.	Major diameter of thread	Gage
Minor:	AQL 2.5 percent	
201.	Total length	Gage
202.	Outside diameter	Gage
203.	Inside diameter	Gage
204.	Concentricity of inside diameter with pitch diameter of threads	Gage
205.	Thickness of bottom	Gage
206.	Evidence of poor workmanship (see 3.5)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.2.3 Projectile burster, prior to assembly to projectile (see dwg. 9223129 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:	AQL 0.65 percent	
201.	Evidence of poor workmanship (see 3.5).....	Visual

4.2.2.4 Projectile, prior to assembly of fuze well cup (see dwg. 9216522 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:		
1.	Projectile burster inverted.....	Visual
2.	Closure on Projectile burster below flush.....	Visual
Major:	AQL 0.40 percent	
101.	Projectile burster missing.....	Visual
Minor:	AQL 1.0 percent	
201.	Compound missing from threads....	Visual
202.	Evidence of poor workmanship (see 3.5).....	Visual

4.2.2.5 Projectile prior to assembly of fuze (see dwg. 9216522 covering a detail of dwg. 9216521).

Categories	Defects	Method Of Inspection
Critical:		
1.	Projectile zone weight incorrect by two zones.....	Balance
2.	Zone stenciling incorrect by two zones.....	Visual
Major:	AQL 0.40 percent	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

101. Depth of fuze well, minimum (min)...Gage
102. Total length, maximum (max.).....Gage
103. Projectile zone weight incorrect by one zone.....Balance
104. Zone stenciling incorrect by one zone.....Visual

Minor: AQL 1.5 percent
201. Compound missing from threads.....Visual
202. Protective coating with total damaged area in excess of 1/4 square inch...Visual
203. Marking missing, misleading or unidentifiable (except for zones), including incorrect color code.....Visual
204. Evidence of poor workmanship (see 3.5).....Visual

4.2.2.6 Projectile assembly (when applicable) (see dwg. 9216522 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
	101. Torque test of plug	Test
Minor:	None defined	

4.2.2.7 Primer, prior to assembly to cartridge case (see dwg. 8838130 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:		
	1. One or more flash holes missing	Visual
Major:	None defined	
Minor:	None defined	

4.2.2.8 Cartridge case, prior to assembling propelling charge (see 8595386 covering a detail of dwg. 9216521 or 9257991).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method Of Inspection
Critical:	None defined	
Major:	AQL 0.40 percent	
101.	Primer missing or damaged	Visual
Minor:	AQL 1.0 percent	
201.	Foreign matter in interior of case	Visual
202.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.9 Propelling charge, prior to assembly to cartridge case (see dwg. 9205472 covering a detail of dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:	None defined	
Major:	AQL 0.40 percent	
101.	Increment missing	Visual
102.	Any opening in bag large enough to permit escape of propellant	Visual
Minor:	AQL 1.0 percent	
201.	Lacing cord broken	Visual
202.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.10 Cartridge case with propelling charge, prior to assembling to projectile (see dwg. 9216521 or 9257991).

Categories	Defects	Method Of Inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Incorrect sequence of increments	Visual
102.	Foil side of bag, charge 5 not facing primer	Visual
Minor:	None defined.	

4.2.2.11 Cartridge assembly (see dwg. 9216521 or 9257991).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method Of Inspection
Critical:		
1.	Primer above flush	Gage
Major:	AQL 0.65 percent	
101.	Torque test failure of fuze or plug	Test
102.	Gap between fuze and body	Visual
103.	Rotating band damaged	Visual
Minor:	AQL 1.5 percent	
201.	Exterior coating of shell with an aggregate of bare spot in excess of 1/4 square inch	Visual
202.	Marking missing, misleading or unidentifiable including incorrect color	Visual
203.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.12 Unsealed fiber container (see dwg. 7549073 or 9253026).

Categories	Defects	Method Of Inspection
Critical: None defined		
Major:	AQL 0.40 percent	
101.	Packing component missing	Visual
Minor:	AQL 1.5 percent	
201.	Cartridge cannot be removed by hand	Manual
202.	Container cap cannot be removed by hand	Manual
203.	Glue or asphalt on cartridge	Visual
204.	Any packing component improperly assembled	Visual

4.2.2.13 Sealed fiber container (see dwg. 7549073 or 9258026).

Categories	Defects	Method Of Inspection
Critical: None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.65 percent	
101.	Container cut or damaged through all asphalt impregnated layers	Visual-Manual
102.	Metal end loose or distorted	Visual-Manual
103.	Tape incomplete or badly wrinkled	Visual
Minor:	AQL 2.5 percent	
201.	Tear tab length, min	Gage
202.	Contents loose	Manual
203.	Gap between cover and body container exceeding 1/8 inch	Visual
204.	Cuts scuffs, or gouges in outer layers	Visual
205.	Marking misleading, missing or unidentifiable	Visual

4.2.2.14 Sealed, wood packing box (see dwg. 7549072 or 9258027).

Categories	Defects	Method Of Inspection
Critical:	None defined	
Major:	AQL 0.65 percent	
101.	Box damaged exposing contents	Visual
102.	Hardware or strapping missing, broken or loose	Manual-Visual
103.	DOD symbol missing or incorrect	Visual
104.	Board broken	Visual
Minor:	AQL 1.5 percent	
201.	Strapping or hardware improperly assembled	Visual-Manual
202.	Handle missing or insecure	Visual-Manual
203.	Car seal missing, unsealed or improperly positioned	Visual
204.	Marking misleading, missing or unidentifiable	Visual

4.2.3 Testing

4.2.3.1 Check test for possible deterioration of primer percussion, M28A2, (see specification MIL-P-46565). If the total elapsed time between original acceptance of the M28A2 primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the M28A2 primers have been subjected to adverse

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in specification MIL-P-46465 immediately before the M28A2 primer lot is assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges (see 6.3).

4.2.3.2 Bourrelet diameter (see dwg. 9216521 or 9257991) major defect. The projectiles shall be gaged 100 percent for maximum diameter of bourrelet. Any projectile which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.3 Proving ground test.-The following test shall be performed as specified in 4.3.1 (see 3.4).

4.2.3.3.1 Muzzle velocity - Major defect

4.2.3.3.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter I and AQL 1.0 percent. In addition, if the standard deviation of the sample projectile multiplied by the factor 0.75 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.3.1.2 After the three consecutive lots have met the criteria of 4.2.3.3.1.1, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter F, and AQL 1.0 percent. In addition, if the standard deviation of the sample projectile multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.3.2 Functioning - Major defect

4.2.3.3.2.1 The sample cartridges used in the test for muzzle velocity (see 4.2.3.3.1.1) shall be tested for functioning. If more than two projectiles fail the specified requirement, the lot shall be rejected.

4.2.3.3.2.2 The sample cartridges used in the test for muzzle velocity (see 4.2.3.3.1.2) shall be tested for functioning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

If more than one projectile fails the specified requirement, the lot shall be rejected.

4.2.3.3.3 Safety-critical defect.-Ten sample cartridges shall be selected from each lot for this test. If any cartridge fails to comply with the requirement the lot shall be rejected.

4.2.3.3.4 Premature functioning-critical defect.-If during any of the proving ground tests any sample projectile fails to comply with the requirement for premature functioning, the lot shall be rejected.

4.2.3.3.5 Retest.-If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional sample rounds as required.

4.2.3.4 Fit of projectile with cartridge case (see dwg. 9216521 or 9247991) Major defect. The cartridge cases shall be gaged 100 percent for profile and diameter of the mouth to assure a proper fit with the projectile. Any case which fails to comply with the applicable requirements shall be classed defective and removed from the lot. Inspection equipment shall be in accordance with 4.2.4 (Note: This inspection shall not be required if it is determined that the cartridge cases have been previously gaged 100 percent for these characteristics).

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-9216521 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirments of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 Proving ground.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedures. The sample cartridges shall be fired with M67 propelling charges in a gun for which the ammunition is standard. Observation shall be made for conformance to all requirements. (see 6.4).

4.3.1.1 Muzzle velocity and functioning.-The sample cartridges shall be fired at zone 7 for this test and observed for velocity and functioning.

4.3.1.2 Safety.-The sample cartridges shall be fired with propelling charges adjusted to give 112 percent of the rated maximum pressure in a weapon with M103 or M137 tube. In addition, for the first three production lots from each manufacturer (loading facility), a smear camera shall be used to observe the projectile in flight, in order to record any possible malfunction.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packing

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 7549073 or 9258026.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 7549072 or 9258027.

5.3 Marking.-Marking of the wood box shall be in accordance with dwg. 7549072 or 9258027. The fiber container shall be marked in accordance with dwg. 7549073 or 92758026.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.
b. Data Cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.2.1 through 6.2.5.

6.2.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.2.2. Design action required of the contractor is described in paragraphs 6.2.3 and 6.2.4. The contractor will be required to prepare detailed drawings in accordance with 6.2.4 for all the equipment codes as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.2.5.

6.2.2 Inspection equipment lists codes.-The inspection equipment as defined in 6.2.3 and 6.2.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment
MU - Army design, mandatory for use

6.2.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.2.5.

6.2.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employed in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.2.5.

6.2.5 Submission of contractor designs.-All submitted designs shall contain a reference to the appliable paragraph and defect Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the DL, all design of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-A. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.3 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where determination has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.4 Submission of test data.-In addition to normal distribution of records, when the cartridge is procured by the Department of the Army, one copy of all ballistic test data will be forwarded to the following:

Commanding Officer
Picatinny Arsenal
Dover, New Jersey
ATTN: SMUPA-QA-A-A and SMUPA-AD-E-A

Custodian:
ARMY-MU

Preparing Activity
ARMY-MU

Project Number: 1315-A-011

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.