MIL-C-60393A (MU)
30 August 1968
SUPERSEDING
MIL-C-60393 (MU)
30 November 1966
(SEE 6.5)

MILITARY SPECIFICATION

CARTRIDGE, DELAY: 20 SECOND DELAY, XM252 PARTS, LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the parts, loading, assembling and packing for one type of time delay cartridge designated as Cartridge, Delay: 20 Second Delay, XM252.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-P-20444 - Primer, Percussion, M42, Loading, Assembling and Packing
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U. S. ARMY MUNITIONS COMMAND

8865428 - Box, Set-up, Packing, Ammunition for Cartridge, Delay: 20 Second Delay, XM252
8865429 - Box, Packing, Ammunition for Cartridge, Delay: 20 Second Delay, XM252
8886478 - Cartridge, Delay: 20 Second Delay, XM252

PUBLICATIONS

U. S. ARMY MUNITIONS COMMAND

ET - 8886478 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.- Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assemblies.- The cartridge assemblies shall comply with all the requirements specified on Drawing (dwg.) 8886478 and with all the requirements specified in applicable specifications.

3.3 Explosive cartridge.- The cartridge shall have sufficient explosive force to activate the spinner of a fully loaded cargo parachute release.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

3.4 Transportation-vibration.- The cartridge shall withstand the transportation-vibration test when tested as specified in 4.4.1.

3.5 Waterproofness.- The cartridge shall show no evidence of leakage while submerged in a vacuum chamber under a minimum (min.) of 2 inches of water at an absolute pressure of ten (10) pounds per square inch (p.s.i.) plus or minus .3 p.s.i. applied for five (5) seconds, minimum. The test shall be performed as specified in 4.4.2.

3.6 Functioning

3.6.1 The cartridge shall function on the first attempt within 18 to 27 seconds, after being conditioned for sixteen (16) hours minimum at minus 65 degrees Fahrenheit (F.), plus or minus 5 degrees Fahrenheit (F.) when tested as specified in 4.4.3.

3.6.2 The cartridge shall function on the first attempt, within 16 to 22 seconds, after being conditioned for sixteen (16) hours minimum at plus 125 degrees Fahrenheit (F.), plus or minus 5 degrees Fahrenheit (F.) when tested as specified in 4.4.3.

3.7 Workmanship.- All parts and assemblies shall be fabricated in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, unblended radii, surface defects, chips, cracks, dirt, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.8 First article inspection.- This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.- At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Statement of findings (qualitative and quantitative analysis) on the delay and output materials; certificates of conformance on all other material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2 First article inspection (see 6.1c)

4.2.1 Part 1 - Metal parts

4.2.1.1 Submission.- The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.1.2. The first article sample shall consist of fifty (50) complete sets of parts which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials (see 4.1.1e). A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.1.2 Inspections to be performed.- The parts shall be subjected by the Government to any or all of the examinations specified in 4.3.2 of this specification and any or all requirements of the applicable drawings.

4.2.1.3 Rejection.- If any part fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of a component to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.2 Part 2 - Loaded assemblies

4.2.2.1 Submission.- Subsequent to approval of metal parts submitted in accordance with 4.2.1, the contractor shall submit a sample of one hundred and thirty (130) loaded assemblies to the Government for testing as specified in 4.2.2.2. A statement of findings for the delay and output materials and a certificate of conformance for the igniter composition shall be submitted with the loaded assemblies.

4.2.2.2 Inspections to be performed.- The assemblies will be subjected to the following tests in the sequence indicated:

Test Description	Test Method	Test Quantity
Transportation-vibration (see 3.4)	4.4.1	130
Waterproofness (see 3.5)	4.4.2	130
Functioning at minus 65 degrees F. (See 3.3 and 3.6.1)	4.4.3	65
Functioning at 125 degrees F. (see 3.3 and 3.6.2)	4.4.3	65

4.2.2.3 Rejection.- The first article sample shall be rejected if two or more assemblies fail to comply with any of the above specified requirements.

4.3 Inspection provisions

4.3.1 Lot formation.- The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specifications, or drawings not affecting safety,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or sub-assemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of loaded delay cartridges shall contain:

a. Primers from not more than one lot interfix number from one manufacturer.

b. Delay composition from one batch or blending of batches which results in homogeneity of all delay composition used in loading the entire delay cartridge lot.

c. Metal parts from not more than one lot interfix number from one manufacturer in accordance with the same specification, same specification revision, same drawing and same drawing revision

4.3.2 Examination.- Sampling plans and procedures for the following classifications of defects shall be in accordance with MIL-STD-105 except that inspection for critical defects (and majors, when so specified) shall be 100 percent. Contractor's sampling plans, if used, shall be approved by the Government and shall provide, as a minimum, the protection afforded the Government by the sampling plans in MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 for defects other than critical may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.3.2.1 Body (see dwg. 8886477 covering a detail of dwg. 8886478).

Categories	Defects	Method of Inspection	Code No. (see 6.2
Critical:	None defined		
Major:	AQL 1.00 percent		
101.	Body inside diameter, small minimum (min.)	Gage	01001
102.	Body outside diameter, small	Gage	01002
103.	Body outside diameter, large	Gage	01003
104.	Overall length	Gage	01004
105.	Length, from shoulder to body end	Gage	01005
106.	Concentricity of inside diameter of large counterbore to small inside diameter	Gage	01006
107.	Concentricity of inside diameter of small counterbore to small inside diameter	Gage	01007
108.	Incorrect color	Visual	01008
Minor:	AQL 4.00 percent		
201.	Inside diameter, large counterbore	Gage	01009
202.	Inside diameter, intermediate counterbore, maximum (max.)	Gage	01010
203.	Inside diameter, small counterbore, min	Gage	01011
204.	Depth, large counterbore, min	Gage	01012
205.	Depth to bottom of intermediate counterbore, max	Gage	01013
206.	Depth, small counterbore, min	Gage	01014
207.	Diameter, crimping lip, min	Gage	01015
208.	Length, crimping lip, min	Gage	01016
209.	Concentricity of large outside diameter to small inside diameter	Gage	01017
210.	Concentricity of inside diameter of intermediate counterbore to small inside diameter	Gage	01018

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

211.	Concentricity of crimping lip diameter to small inside diameter	Gage	01019
212.	Concentricity of small outside diameter to small inside diameter	Gage	01020
213.	Evidence of poor workmanship (see 3.7)	Visual	01021

4.3.2.2 Disc, closing (see dwg. 8886475 covering a detail of dwg. 8886478).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.50 percent		
201.	Diameter	Gage	02001
202.	Thickness	Gage	02002
203.	Evidence of poor workmanship (see 3.7)	Visual	02003

4.3.2.3 Seat, primer (see dwg. 8886476 covering a detail of dwg. 8886478).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Inside diameter, counterbore	Gage	03001
102.	Depth of counterbore, min	Gage	03002
103.	Incorrect color	Visual	03003
Minor:	AQL 4.00 percent		
201.	Thickness, small, max	Gage	03004
202.	Thickness, large	Gage	03005
203.	Outside diameter	Gage	03006

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

204.	Outside diameter, crimping lip min.....	Gage	03007
205.	Depth of groove, crimping lip min.....	Gage	03008
206.	Width of groove at base of crimping lip, max.....	Gage	03009
207.	Small inside diameter, min.....	Gage	03010
208.	Concentricity of crimping lip diameter to inside diameter of counterbore.....	Gage	03011
209.	Evidence of poor workmanship (see 3.7).....	Visual	03012

4.3.2.4 Washer (see dwg. 8886480 covering a detail of dwg. 8886478).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 percent		
201.	Outside diameter, max.....	Gage	04001
202.	Inside diameter, min.....	Gage	04002
203.	Thickness, max.....	Gage	04003
204.	Evidence of poor workmanship (see 3.7).....	Visual	04004

4.3.2.5 Assembly, prior to assembly of primer seat (see dwg. 8886478).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Washer missing.....	Visual	05001
102.	Crimp of body to washer missing or inadequate.....	Visual	05002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Minor: None defined

4.3.2.6 Assembly, cartridge (see dwg. 8886478).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 1.00 percent		
101.	Length, maximum (max.).....	Gage	06001
102.	Length to small diameter, max...	Gage	06002
103.	Small diameter, max.....	Gage	06003
104.	Large diameter, max.....	Gage	06004
105.	Crimp, body to primer seat missing or inadequate.....	Visual	06005
106.	Crimp, primer seat to primer missing or inadequate.....	Visual	06006
107.	Closing disc, punctured or wrinkled.....	Visual	06007
108.	Sealant missing or inadequate, either end.....	Visual	06008
109.	Marking omitted, improper or illegible.....	Visual	06009
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.7).....	Visual	06010

4.3.2.7 Box, set-up, prior to sealing (see dwg. 8865428).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Incorrect number of assemblies..	Visual	07001
Minor:	AQL 0.65 percent		
201.	Assembly improperly inserted....	Visual	07002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.3.2.8 Box, set-up, after sealing (see dwg. 8865428).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.65 percent		
101.	Contents loose	Manual	08001
102.	Sealing strips improperly assembled	Visual	08002
103.	Carton damaged	Visual	08003
Minor:	AQL 0.65 percent		
201.	Marking incorrect, incomplete or illegible	Visual	08004

4.3.2.9 Box, packing, prior to closing (see dwg. 8865429).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Barrier bag damaged	Visual	09001
102.	Incorrect number of assemblies	Visual	09002
Minor: None defined			

4.3.2.10 Box, packing (see dwg. 8865429).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 1.00 percent		
101.	Contents loose	Manual	10001
102.	Box damaged to the extent that contents are exposed or liable to become exposed	Visual	10002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

103.	Box improperly closed and sealed.....	Visual	10003
104.	Strapping improperly positioned.	Visual	10004
105.	Strapping loose.....	Manual	10005
Minor:	AQL 0.65 percent		
201.	Marking incorrect, incomplete or illegible.....	Visual	10006

4.3.3 Testing

4.3.3.1 Production acceptance sample tests.- The sample shall be selected in accordance with MIL-STD-105, Table III A, double sampling plans for normal inspection using Code Letter K, and an AQL of 0.40 percent. The sample shall be tested for the following requirements in the quantities and sequence indicated:

Test Description	Test Method	Category	Quantity	Code No
Transportation-vibration (see 3.4)	4.4.1	Major	All	11001
Waterproofness (see 3.5)	4.4.2	Major	All	12001
Functioning at minus 65 degrees F. (see 3.3 and 3.6.1)	4.4.3	Major	Half	13001
Functioning at 125 degrees F. (see 3.3 and 3.6.2)	4.4.3	Major	Half	14001

If two or more assemblies from the first sample size, fail to comply with any of the above specified requirements, the entire lot shall be rejected. If only one assembly fails to comply with any of the above requirements, a second sample shall be selected (see Table III A -, Letter K, MIL-STD-105) and shall be retested for all the above sequenced test requirements. If during retest one or more of the assemblies fail to comply with any of the above require ments, the entire lot shall be rejected. Even if one or more of th test phases fail, the test shall be continued to completion.

4.3.3.2 Check test for possible deterioration of primers - Major defect - Code No. 16001.- If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into the cartridge exceeds two years, or if the primers have

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

been subjected to adverse conditions for any period of time since previous test, the primer lot shall be subjected to and must satisfactorily pass the check test for possible deterioration specified in MIL-P-20444 immediately before the assembly of the primer lot into the cartridges. This test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primer lot into the cartridges and shall be conducted at Government expense without cost to the contractor assembling the primers into the cartridges. Furthermore, this test shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

4.3.4 Inspection equipment.- Equipment Tabulation Number ET - 8886478 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.- Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2 Supply and maintenance.- Supply and maintenance of the equipment listed in the ET shall be in accordance with MIL-I-45607.

4.3.4.3 Government use of contractor's inspection equipment.- The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.4 Test methods and procedures

4.4.1 Transportation vibration.- The cartridge shall be subjected to the transportation-vibration test in accordance with Procedure II, Test 104 of MIL-STD-331. No breakdown inspection shall be performed.

4.4.2 Waterproofness.- The cartridge shall be placed under a minimum of 2 inches of water in a vacuum chamber. The water shall contain the wetting agent Naccon NR (sodium alkyl aryl sulfonate), or equal. The chamber shall be evacuated to the specified absolute pressure and the pressure maintained for the specified time, (see 3.5). Any assembly which shows evidence of leakage by emitting a steady stream of air bubbles shall be classed defective. After completion of the test the element shall be rinsed thoroughly in fresh running water to remove the wetting agent and dried thoroughly at room temperature.

4.4.3 Functioning.- The cartridge assembly shall be assembled to a cargo parachute release. The sear of the cartridge mechanism shall not be bolted to the yoke assembly for this test. The complete cargo parachute release shall then be conditioned as specified in 3.6. Within 2 minutes after removal from the conditioning chamber, the complete cargo parachute release shall be assembled to the applicable test fixture specified in 4.3.4, a load to 5,000 pounds applied to the hook assembly. The cartridge shall be functioned within two minute period by removing the safety pin and applying a load to the eye of the sear along the longitudinal axis of the firing mechanism to function the cartridge. Any cartridge which fails to function or fails to move the spinner to the active position within the time required shall be classed defective.

5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.1 Level A.- Packaging shall be in accordance with dwg. 8865428.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

5.2 Packing

5.2.1 Level A.- Packing shall be in accordance with dwg. 8865429.

5.3 Marking.- Marking shall be in accordance with instructions contained in Drawings 8865428 and 8865429.

6. NOTES

6.1 Ordering data.- Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.- Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Submission of first article quantity.- Instructions as to the location of the facility at which the evaluation of the first article quantity shall be carried out may be obtained from the contracting officer.

6.2 Inspection code numbers.- The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.- The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).- Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

6.3.2 Inspection equipment list codes.- The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.- Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.- Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.- All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NDl. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Check test for deterioration of primers.- The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test.

6.5 Supersession data.- This specification supersedes in its entirety, MIL-C-60391 (MU), dated 15 December 1966, for Cartridge, Delay: 20 Second Delay, XM252, Parts for.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1375-A-017

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:20Z
Check the source to verify that this is the currenversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

343-221 (A-601)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.