MIL-C-60452A (MU)
November 12 1971
SUPERSEDING
MIL-C-60452 (MU)
29 May 1967

MILITARY SPECIFICATION

CARTRIDGE CASE LOADING ASSEMBLY, M195

LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of case, cartridge designated as CARTRIDGE CASE LOADING ASSEMBLY, M195 for use in various 40MM ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116	-	Preservation, Methods of
MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-P-20444	-	Primer, M42
MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

9207988	-	Cartridge Case Loading Assembly, M195

PUBLICATIONS

ARMY

ET-9207988	-	Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49	-	Transportation, Parts 0-190

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402. Orders should specify, "49 CFR 0-190 (latest revision)".)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly.-The assembly shall comply with all requirements specified on Drawing (Dwg) 9207988, and with all requirements specified on applicable specifications.

3.3 Functioning (See 6.7).-The case, cartridge shall function and comply with the following requirements when tested as specified in 4.4.2:

3.3.1 Mean velocity.-The projectile shall have a mean velocity of 245 minimum feet per second.

3.3.2 Firing.-There shall be no primer blow back as evidenced by perforation of the cup and extrusion of the primer around firing pin causing difficulty in opening weapon.

3.4 Production control check on loaded M195 cartridge case.-There shall be no evidence of any of the following when tested as specified in 4.4.4:

a. Primer malfunction.
b. Any primer blows back as evidenced by perforation of the cup and extrusion of the firing pin causing difficulty in opening weapon.
c. Case cartridge cannot be ejected from the launcher by spring operation of the extractor.
d. Case cartridge cannot be ejected from the launcher by hand operation of the extractor.

When the propellant serial lot changes, the requirements of b, c, and d, do not apply.

3.5 Primer functioning.-The primer shall function without evidence of squibbing or handfire when tested as specified in 4.4.5. Paragraph 6.6 of Military Specification MIL-P-20444B, Amendment 3 contains definitions of functioning failures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

3.6 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.7 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract, the specification, or as requested by the Contracting Officer. (See 6.6)

3.8 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.-

4.2.1 Submission.-The contractor shall submit a sample of three-hundred (300) assemblies to a Government proving ground designated by the contracting officer for testing in accordance with the provisions of 4.2.2 (See 6.1). All parts and materials shall be the same as will be used in production and shall be obtained from the same source of supply. Prior to submission, the sample shall be inspected by the contractor to the degree necessary to assure that it conforms to the requirements of the contract.

4.2.2 Inspection to be performed.-Assemblies will be subjected by the Government to the following test:

4.2.2.1 Functioning.-The three-hundred (300) assemblies shall be subjected to this test.

4.2.2.1.1 Rejection.-The first article quantity shall be rejected if:

a. Any primer blow back (as evidenced by perforation of the cup and extrusion of the primer around firing pin causing difficulty in opening weapon).

b. Mean velocity fails to meet the applicable requirement.

c. Primer misfire.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

d. Thirty (30) or more cartridge cases cannot be ejected from the launcher by spring operation of the extractor.

e. One (1) or more cartridge cases cannot be ejected from the launcher by hand operation of the extractor.

In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity. Until the first article quantity is accepted, the contractor is not authorized by the Government to proceed with regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot shall contain:

a. Primers of one serial lot number from one manufacturer.

b. Cartridge case metal parts from one interfix lot number from one manufacturer.

c. Propellant from one serial lot number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Cartridge case loading assembly, prior to assembling base plug and primer (See Dwg. 9207988).-

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical			
1.	Powder charge cup missing	Gage	01001
2.	Spilled powder from cartridge case	Visual	01002
3.	Propellant charge weight obviously incorrect (See 6.8)	Visual	01003
Major	100% Inspection		
101.	Propellant charge weight obviously incorrect (See 6.8)	Visual	01004

Minor: None defined

4.3.2.2 Cartridge case loading assembly (See Dwg. 9207988).-

Categories	Defects	Method of Inspection	Code No.
Critical			
1.	Primer above flush with respect to base of case	Gage	02009

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Major	AQL 0.65 Percent		
101.	Base plug above flush	Gage	02002
102.	Depth to base plug, maximum (max)	Gage	02003
103.	Primer above flush or more than .005 below with respect to base plug	Gage	02010
104.	Primer damaged	Gage	02005
Minor	AQL 1.50 Percent		
201.	Excessive varnish on exterior surface of primer	Visual	02006
202.	Marking misleading or unidentifiable	Visual	02007
203.	Evidence of poor workmanship (See 3.6)	Visual	02008

4.3.2.3 Box, fiber prior to sealing (See Dwg. 9223934).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Number of cartridge case assemblies incorrect	Visual	03001
102.	Insufficient fillers	Visual	03002
103.	Separator missing	Visual	03003
104.	Cartridge case assembly facing wrong way	Visual	03004
Minor:	None defined		

4.3.2.4 Box, fiber packing, prior to sealing bag (when applicable) (See Dwg. 9223934).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Container damaged	Visual	04001
102.	Corners not blunted	Visual	04002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Minor	AQL 1.00 Percent		
201.	Contents loose	Manual	04003
202.	Label or marking missing or unidentifiable	Visual	04004

4.3.2.5 Wooden box, prior to sealing (See Dwg. 9223935).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Number of fiber boxes incorrect	Visual	05001
102.	Marking of bag misleading or unidentifiable (when applicable)	Visual	05002
103.	Bag torn or perforated (when applicable)	Visual	05003
104.	Bag improperly sealed (when applicable)	Visual	05004
Minor:	None defined		

4.3.2.6 Wooden box packing (See Dwg. 9223935).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Box damaged	Visual	06001
102.	Strapping missing or incorrect	Visual	06002
103.	Top improperly assembled	Visual	06003
Minor	AQL 1.00 Percent		
201.	Contents loose	Manual	06004
202.	Marking misleading or unidentifiable	Visual	06005

4.3.3 Testing.-

4.3.3.1 Check test for deterioration of primers (See MIL-P-20444) Major Defect, Code No. (07001).-If the total time between original acceptance of any lot and the assembly of that lot into the cartridge exceeds two years, or if the primers have been

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in MIL-P-20444 immediately before the primer lot is assembled into the cartridge. This test shall be performed by the contractor on primers selected by the Government Inspector at the facility assembling the primers into the cartridge (See 6.4).

4.3.3.2 Holding fixture vent check, Code No. (08001).-The cartridge case holding fixture used in the base plug insertion operation shall have its air vents checked hourly for any obstruction. If a vent is found to be closed or clogged, the vent shall be clearly and the previous hour's production shall be x-rayed 100 percent to ensure that the propellant charge cups have not been damaged. Cartridge cases found to have damaged charge cups shall be classed defective and removed from the lot.

4.3.3.3 Propellant weight of cartridge case, Code No. (09001).-The propellant weight shall be determined and then check weighed 100 percent. The check weighing shall be accomplished independently of the original weighing or determination, using a different balance from that used to make the original weighing and if performed manually, shall be performed by another operator. Any charge which fails to comply with the requirement specified on Dwg. 9207988 shall be classified defective and removed from the lot. (See Para. 4.3.2.1).

4.3.3.4 Security of crimp of base plug on cartridge case assembly (See Dwg 9207988), Major defect, Code No. (10001).-Twenty (20) each of cartridge case, base plug and powder charge cup less propellant shall be selected from each lot and subjected to this test. If the crimped area of one or more assemblies fail to withstand the unseating requirement specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4.

4.3.3.5 Propellant weight of cartridge case, alternate method, Code No. (13001).-At the start of production, three hundred eighty (380) consecutive samples per station per machine shall be selected and weighed 100 percent. All samples shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

comply with the applicable requirement. If all samples comply with the drawing requirement, five (5) samples, per station, per every two (2) hours production shall be selected and the average weight of the five (5) samples must meet the assessed mean propellant weight within ± 4 milligrams. If the average weight fails the requirement, correction shall be made and three hundred eighty (380) consecutive samples weighed from that station. If all meet the applicable requirement, the sampling every two (2) hours will be resumed.

4.3.3.6 Production control check on loaded M195 cartridge case (See 3.4) Major Defect, Code No. (14001).-Ten (10) loaded M195 cases shall be randomly selected from every four (4) hours production from each primer assembly machine. The loaded XM195 cases produced by each primer assembly machine shall be kept segregated and identified. They shall not be used until this test has been performed. If any sample fails to comply with the applicable requirement, the four (4) hours production represented by the sample shall be rejected. The test shall be performed as specified in 4.4.4.

4.3.3.7 Primer functioning (See 3.5), Major defect, Code No. (15001).-Sampling shall be in accordance with Paragraph 4.2.3.2.2 of MIL-P-20444B, except that the sample size shall be eight-hundred (800) primers from each lot. If one or more primers fail to comply with the applicable requirement, the lot of primers shall not be used and disposition requested. Primers not originally purchased to this requirement shall be tested for the requirement of Paragraph 3.8. The test shall be performed as specified in 4.4.5, using equipment in accordance with 4.3.4.

4.3.3.8 Functioning (See Paragraph 3.3), Major defect, Code No. (11001).-The loaded cartridge case assembly shall be observed for any evidence of failure to comply with the requirements as classified in TABLE 1 when tested as specified in 4.4.2. This test applies only when the propulant serial lot changes.

TABLE 1

DEFECT	CLASSIFICATION	CODE NO.
Any primer blows back (as evidenced by perforation of the cup and extrustion of the firing pin causing difficulty in opening weapon)	Critical	11002
Primer misfire	Major	11003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

DEFECT	CLASSIFICATION	CODE NO.
Mean velocity fail to meet the applicable requirement	Major	11007
Case, cartridge cannot be ejected from the launcher by spring operation of the extractor	Major	11005
Case, cartridge cannot be ejected from the launcher by hand operation of the extractor	Major	11006

4.3.3.8.1 The Government Inspector shall select one-hundred and twenty-five (125) loaded cartridge case assemblies from each lot and subjected to this test. The lot shall be rejected if a critical defect occurs, two (2) or more primers misfire, ten (10) or more case cartridges cannot be ejected from the launcher by spring operation of the extractor, or one (1) or more case cartridges cannot be ejected from the launcher by hand operation of the extractor.

4.3.3.9 Heat seal test of packing seals (See Dwg. 9223934), Major defect, Code No. (12001), (when applicable).-Sampling and rejection shall be in accordance with MIL-P-116. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.4 Inspection equipment.-Equipment Tabulation (ET) number 9207988 and Equipment Lists (EL's) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3. Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.4 Test methods and procedures.

4.4.1 Security of crimp of base plug on cartridge case assembly.-The assembly shall be placed in the fixture shown on the Equipment List and the minimum unseating force specified on Dwg. 9207988 shall be applied. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.4.2 Functioning.-The following test shall be performed at a Government-owned proving ground: The sample loaded cartridge case assembly shall be assembled (using the same method as specified in NOTE 2 of Dwg. 9207987) to an inert projectile and fired from an approved launcher placed on an approved mount to impact at 100 meters minimum from the launcher on a six inch thick loose gravel pad. The gravel used shall have a 1/2 inch maximum size. The velocity shall be measured at 20 feet from the muzzle of the launcher using two sets of screens, each set of screens having an electronic counter. One set of screens shall be placed 14 and 26 feet from the launcher and the other set 15 and 25 feet from the launcher. NOTE: To insure that the chronographs are read properly, the ratio of the two times shall not differ from 1,200 by more than plus or minus 0.005. If the ratio differs from 1,200 by more than plus or minus 0.005, the results shall be discarded and another round fired in its place. Observation shall be made and results recorded for functioning and mean velocity. This test applies only when the propellant serial lot changes.

4.4.3 Heat seal test of packing seals.-The test shall be performed in accordance with MIL-P-116. Seals so tested shall not be returned to the lot.

4.4.4 Production control check on loaded M195 cartridge case.-The loaded M195 cartridge case shall be fired from an approved launcher placed on an approved mount. Observation shall be made for primer functioning. This test is a destructive test. Parts so tested shall not be returned to the lot. NOTE: No projectile is required for this test.

4.4.5 Primer functioning.-Each primer of the 800 samples shall be tested as specified in Paragraph 4.3.2.2 of MIL-P-20444B.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging.-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.-The cartridge case assembly shall be preserved and packaged in accordance with Dwg. 9223934.

5.2 Packing.-

5.2.1 Level A.-The cartridge case assembly preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with Dwg. 9223935.

5.3 Marking.-Marking shall be in accordance with Dwg. 9223934, 9223935 and Interstate Commerce Commission Code of Federal Regulations 49 CFR 0-190.

5.4 Shipping.-When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6 NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Equipment lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: Mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army Designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor-prepared designs (see 6.3.4) or commercial equipment selections must be approved by the Government prior to fabrication or procurement of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to Specification MIL-D-1000, Category A, Form 3. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor design.-All submitted designs shall contain a reference to the applicable 5-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND13. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Cost of check test.-The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the primer assemblies. The tests shall be conducted at Government expense without cost to the contractor who loaded the primer assemblies or to the contractor assembling the primer assemblies into the cartridge case, and shall not constitute a basis for rejection against either contractor except where deterioration has occured as a direct result of carelessness in handling, storage, etc, permitted while the primer assembly lot was under the jurisdiction of either contractor.

6.5 Submission of test data.-In addition to the normal distribution of records, when the cartridge case assy is procured by the U.S. Army Munitions Command, one (1) copy of all ballistic data shall be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S.

6.6 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

6.7 When the contractor for loading the cartridge case is also the contractor for loading the complete cartridge used therewith the functioning tests may be combined upon approval by the Contracting Officer.

6.8 If any cartridge case, prior to insertion of the base plug and primer, is suspected of containing an underweight or overweight propellant charge, based on visual inspection, it will be removed from the lot and weighed on suitable scales. Any cartridge case found with less than 75 percent or more than 125 percent of the assessed propellant load will be classified as a critical defect and removed from the lot. Any cartridge case found to have a propellant weight out of drawing tolerance but within ± 25 percent of the assessed propellant load will be classified as a major defect and removed from the lot.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1310-A-008

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.