MIL-S-60907 (MU)
29 March 1968

SUPERSEDING
PA-PD-2583
11 July 1966

MILITARY SPECIFICATION

SHELL, TELEMETRY: T5123E1

1. SCOPE

1.1 This specification covers special requirements not included on the drawings, and provides the quality assurance provisions for the fabrication of parts, assembling, and preparation for delivery for one type telemetry shell used to test sequential timer XM32E1 and designated as telemetry shell: T5123E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-W-343 - Wire, Electrical, Copper, Type S, AWG#20 Drawn and Annealed, Uncoated.
TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.

MILITARY

MIL-I-7798 - Insulation Tape.
MIL-S-60902(MU) - Soldering Electrical Connections for Nuclear Weapons Systems, Procedures for.

STANDARDS

FEDERAL

Federal Test Method Standard No. 151

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

MILITARY

BCTX1-102569 - Screw, Set, Socket, Cup Point.
BCWX1.2-426368 - Screw, Cap, Soc. Head.
BFBX3-589930 - Pin, Straight, Precision.
BFBX3-589933 - Pin, Straight, Precision.
BFBX3-589939 - Pin, Straight, Precision.
BFBX3-589956 - Pin, Straight, Precision.
CKCX2 - "O"-Ring.
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MS35240-74 - Screw, Machine, FH.
MS35337-27 - Washer, Lock, Split.
MS35430-4 - Terminal, Lug.

DRAWINGS

ORDNANCE CORPS

75-4-371 - Grommets for 155m.m., 8 in. and 240m.m. Projectiles, Assembly, List of Parts and List of Spec and Std.
8857439 - Clutch, Half Positive.
8857479 - Clutch, Half Positive.
8857543 - Key, Machine.
8857545 - Pin, Straight, Headless.
8882034 - Screw, Self, Locking.
8882472 - Compound, Potting.
9204598 - T5123E1 Telemetry Shell.
9204599 - Shipping Assembly.
9204600 - Body, Forward.
9204601 - Body, Rear.
9204602 - Collar.
9204603 - Timer Assembly.
9204604 - Shim, Rear.
9204605 - Support.
9204606 - Top Plate Assembly.
9204607 - Screw, Button Head Socket, with Nylock.
9204718 - Housing.
9204719 - Plate.
9204720 - Plate, Shim.
9204721 - Shim.
9204722 - Stanchion Assembly.
9204723 - XM32E1 Sequential Timer, Modified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

9204724 - Connector Assembly.
9204725 - Screw, Socket Set Cone Point.
9204726 - Stanchion.
9204727 - Connector.
9204728 - Potting Compound Parts for.
9204729 - Holder, Jack.
9205333 - Compound, Potting, Poly-Urethane.
9205334 - Electrical Receptical Connector Assembly Instructions.
9205335 - Wire, Polyolefin.
9205656 - TU72 Sonde.
9205698 - Capsule Assembly.
9205699 - Sleeve and Ring Assembly.
9220308 - Connector, Electrical.
9220309 - Connector Body Assembly.
9220310 - Screw, Connector.
9220311 - Screw, Guide.
9220312 - Contact, Connector.
9220313 - Insulator, Top.
9220314 - Body, Connector.
9220315 - Seal, Lower.
9220322 - Adhesive, Sealant.
ET-9204598 - Equipment Tabulation.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. - The contractor shall furnish objective evidence (see 6.2) that the material used to fabricate any part complies with the specifications listed on the applicable drawing.

3.2 Assembly. - The shipping assembly shall comply with all requirements specified on Drawing (dwg) 9204599, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.2.1 T5123E1 Telemetry Shell (see dwg 9204598). - This assembly unless otherwise specified by the procuring agency shall be performed at the firing site.

3.3 First article testing. - Requirements for the submission of first article samples by the contractor shall be as specified in tne contract (see 4.2).

3.4 Serialization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

3.4.1 Not required on drawings. - The contractor may assign serial numbers for internal control purposes at his discretion. The finish or any dimension of the item shall not be altered or damaged by the application of the serial number. The material used for marking shall not be subject to corrosion, fungus, flaking, or other similar adverse action which could prevent proper functioning of the item.

3.4.1.1 Unclassified items. - The contractor may select any number suitable for his purpose.

3.4.2 Required on drawings. - The contractor shall assign serial numbers as required by drawings.

3.4.2.1 Unclassified items. - The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Adjustment of holding ring (see dwgs 9205656 and 9205699). - Upon receipt from the supplier of TU-72 Sonde (see dwg 9205656), the holding ring set screw shall be sealed with a suitable material which shall withstand disassembly (see dwg 9205699) and handling before assembly in projectile (see dwg 9204599) in accordance with 4.4.1. Care shall be taken not to disturb the setting of the holding ring in unpacking, disassembly or assembly in the projectile. A broken seal shall be cause for rejection of the sleeve and ring assembly and associated capsule assembly.

3.6 Circuit Resistance.

3.6.1 Circuit resistance (see dwg 9204722 and 9204603) (Wiring Schematic). - The circuit resistance of any circuit shall not exceed 0.1 ohm when measured as specified in 4.4.2.1.

3.6.2 Circuit Resistance (see dwg 9204723). - The circuit resistance between any pin and any other pin on left connector shall not exceed 0.1 ohm when tested as specified in 4.4.2.2. The circuit resistance between pins 7 and 9 on right connectors shall not exceed 0.7 ohms when measured as specified in 4.4.2.2.

3.6.3 Circuit resistance (see dwg 9204599). - The circuit resistance from pin 8 to ground on forward inside connector shall not exceed 0.7 ohm when measured as specified in 4.4.2.2.

3.7 Insulation resistance.

3.7.1 Insulation resistance (see dwgs 9204722 and 9204603). - The insulation resistance shall not be less than 100 megohms between any circuit and ground when measured as specified in 4.4.3.1.

3.7.2 Insulation resistance (see dwg 9204723). - The insulation resistance shall not be less than 100 megohms between any pin and case on the left connector when measured as specified in 4.4.3.2.

3.7.3 Insulation resistance (see dwg 9204599). - The insulation resistance shall not be less than 100 meghoms when measured as specified in 4.4.3.3.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. - All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

3.8.2 Threads. - Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.8.3 Burrs. - Parts shall be free from burrs.

3.8.4 Foreign matter. - Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. - The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.8.6 Electrical. - Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection plan. - The contractor is responsible for compliance with all dimensions and requirements specified on applicable drawings and herein. The contractor's approved inspection plan shall include, as a minimum, all the inspections specified herein.

4.2 First article inspection.

4.2.1 Quantity to be submitted. - The contractor shall submit 3 complete assemblies, 3 sets of subassemblies and 3 of each part, for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. - The first article inspection sample shall be subjected to the inspections and tests specified in table I. Tests need not be conducted in the order specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

Table I

First article inspection and tests

Examination or test	Contractor's inspection before submission	Non-destructive	Assemblies	Sub-Assemblies	Parts
1. Classification of characteristics (see 4.3.2.1)	X	X	X	X	X
2. Circuit resistance (see 3.6)	X	X	X	X	
3. Insulation resistance (see 3.7)	X	X	X	X	
4. Push (see 4.3.3.4)	X	X			X
5. Paint adhesion (see 4.3.3.9)	X	X	X		

4.2.3 Inspection equipment. - The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. - If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Product acceptance inspection.

4.3.1 Lot formation. - A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. - An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. - Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the currentversion before use.

Major characteristic table II

Lot size	Sample size
1 - 155	100% inspection
156 - 200	155
201 - 250	175
251 - 300	190
301 - 350	200
351 - 400	210
401 - 450	220
451 - 500	225
501 - 550	230
551 - 600	235
601 - 650	240
651 - 700	243
701 - 750	247
751 - 800	250
801 - 900	254
901 - 1000	258
1001 - 1100	261
1101 - 1200	264
1201 - 1300	266
1301 - 1400	268
1401 - 1500	270
1501 - 1600	272

Minor characteristics table III

Lot size	Sample size
1 - 25	100% inspection
26 - 30	25
31 - 35	26
36 - 40	27
41 - 45	28
46 - 50	29
51 - 55	30
56 - 60	31
61 - 65	32
66 - 70	33
71 - 75	34
76 - 85	35
86 - 95	36
96 - 110	37
111 - 130	38
131 - 156	39
157 - 190	40
191 - 240	41
241 - 340	42
341 - 520	43
521 - 1120	44
1121 and over	45

4.3.2.1 Classification of characteristics. - Critical, major, and minor classifications are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Connector (see dwg 9204727 covering a detail of dwg 9204724).

Categories	Characteristics	Method of inspection
Critical:	None defined.	
Major:		
	101. Numbering of sockets	Visual
	102. Objective evidence (see 6.2) available for part in accordance with dwg 9204727	Visual
Minor:		
	201. Serialization (see 3.4.1)	Visual
	202. Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Holder, Jack (see dwg 9204729 covering a detail of 9204724).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Large inside diameter, max	Gage
102.	Large outside diameter, min	Gage
103.	Inside radius present	Visual
104.	No visible cracks	Visual
Minor:		
201.	Marking	Visual
202.	Serialization (see 3.4.2)	Visual
203.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.3 Compound, potting, poly-urethane (see dwg 9205333 covering a detail of dwgs 9204722 and 9204724).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for poly-urethane potting compound in accordance with dwgs 9205333 and 9204728	Visual
Minor:		
201.	Serialization (see 3.4.1)	Visual

4.3.2.1.4 Connector assembly (see dwg 9204724 covering a detail of dwg 9204722) before potting and assembly of connector.

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

Major:

101. Objective evidence (see 6.2) available for wire in accordance with dwgs 9205335 and 9204603.....Visual
102. Wiring (see dwg 9204603).....Visual
103. Soldering in accordance with MIL-S-60902 (MU).....Visual/Manual
104. Objective evidence (see 6.2) available for tape in accordance with MIL-I-7798.....Visual
105. Secure insulation tape around joint of wire.....Manual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.5 Connector assembly (see dwg 9204724 covering a detail of dwg 9204722).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Connector loose.....Manual
102. Objective evidence (see 6.2) available for potting compound in accordance with dwg 8882472.....Visual
103. Proper potting.....Visual
104. Screws below flush.....Visual/Manual

Minor:

201. Etching.....Visual
202. Serialization (see 3.4.2).....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.6 Screw, button head socket, with nylock (see dwg 9204607 covering a detail of dwgs 9204603 and 9204722).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Rockwell hardness.....Gage
102. Nylon insert present.....Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

103. Objective evidence (see 6.2) available for part in accordance with dwg 9204607.....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.7 Insulator (see 9220313 covering a detail of dwg 9220309).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Thickness.....Gage
102. Diameter of 10 small holes.....Gage
103. No tear split or crack.....Visual
104. Flash removed.....Visual
105. Material (see 3.1).....Visual

Minor:

201. Serialization (see 3.4.1).....Visual
202. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.8 Seal, lower (see dwg 9220315 covering a detail of dwg 9220309).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Thickness.....Gage
102. Diameter of small holes, max.....Gage
103. No tear, split or crack.....Visual
104. Flash removed.....Visual
105. Material (see 3.1).....Visual

Minor:

201. Serialization (see 3.4.1).....Visual
202. Workmanship (see 3.8).....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.9 Adhesive sealant (see dwg 9220322 covering a detail of dwg 9220309).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for compound in accordance with dwg 9220322	Visual
Minor:		
201.	Serialization (see 3.4.1)	Visual

4.3.2.1.10 Body, connector (see dwg 9220314 covering a detail of dwg 9220309).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Height of bosses	Gage
102.	Total thickness	Gage
103.	Diameter of small holes, max	Gage
104.	Mold flash removed	Visual
105.	No crack, split or tear	Visual
106.	Material (see 3.1)	Visual
Minor:		
201.	Serialization (see 3.4.1)	Visual
202.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.11 Connector, electrical (see dwg 9220309 covering a detail of dwg 9220308.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Properly bonded	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

Minor:

201. Serialization (see 3.4.1).....Visual
202. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.12 Screw, guide (see dwg 9220311 covering a detail of dwg 9220308).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Left diameter, min	Gage
102.	Total length, min	Gage
103.	Length from head to right face, min	Gage
104.	Length of outside diameter right of head, min	Gage
105.	Length of pilot diameter, min	Gage
106.	Outside diameter right of head, min	Gage
107.	Pitch diameter of thread, min	Gage
108.	Major diameter of thread, min	Gage
109.	Shoulder or thread clearance present	Visual
110.	Inside diameter, max	Gage
111.	Material (see 3.1)	Visual
Minor:		
201.	Serialization (see 3.4.1)	Visual
202.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.13 Screw, connector (see dwg 9220310 covering a detail of dwg 9220308).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Distance from left face to left shoulder, min	Gage
102.	Total length, min	Gage
103.	Length of head, min	Gage
104.	Material (see 3.1)	Visual
Minor:		
201.	Serialization (see 3.4.1)	Visual
202.	Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.14 Contact, connector (see dwg 9220312 covering a detail of dwg 9220308).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with 9220312	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.15 Connector, electrical (see dwg 9220308 covering a detail of dwg 9204722).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Distance from connector body to end of pins	Gage
Minor:		
201.	Serialization (see 3.4.1)	Visual
202.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.16 Screw socket set, cone point (see dwg 9204725 covering a detail of dwg 9204722).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Rockwell hardness	Gage
102.	Nylon insert present	Visual
103.	Objective evidence (see 6.2) available for part in accordance with dwg 9204725	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

Minor:

201. Serialization (see 3.4.1).....Visual
202. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.17 Stanchion (see dwg 9204726 covering a detail of dwg 9204722).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Left outside diameter, min.....Gage
102. Pitch diameter of 3 holes in left outside diameter, max.....Gage
103. Minor diameter of 3 holes in left outside diameter, max.....Gage
104. Length from right face to left of right flange, min.....Gage
105. Length from right face to right of right flange, max.....Gage
106. Diameter of small diameter cavity, max.....Gage
107. Right inside diameter, max.....Gage
108. Concentricity of right inside diameter with outside diameter of right flange.....Gage
109. Diameter right of right flange, min.....Gage
110. Diameter of right flange, min.....Gage
111. Pitch diameter of 4 right tapped holes, max.....Gage
112. Minor diameter of 4 right tapped holes, max.....Gage
113. Outside diameter left flange, min.....Gage
114. Pitch diameter 2 tapped holes bottom of left cavity, max.....Gage
115. Minor diameter 2 tapped holes bottom of left cavity, max.....Gage
116. Pitch diameter of 2 counterbored tapped holes, max.....Gage
117. Minor diameter of 2 counterbored tapped holes, max.....Gage
118. Pitch diameter 1 tapped hole bottom left cavity, max.....Gage
119. Minor diameter 1 tapped hole bottom left cavity, max.....Gage
120. Pitch diameter of 4 large tapped connector holes, max.....Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

121. Minor diameter of 4 large tapped connector holes, max.....Gage
122. Radius present on circumference edges of two holes between flanges.....Visual
123. Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204726.....Visual
124. Material (see 3.1).....Visual

Minor:

201. Radius or chamfer present.....Visual
202. Stamping.....Visual
203. Serialization (see 3.4.2).....Visual
204. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.18 Electrical receptacle connector assembly instructions (see dwg 9205334 covering a detail of dwg 9204722).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Wires and insulation sleeves properly assembled.....Visual/Manual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.19 Stanchion assembly (see dwg 9204722 covering a detail of dwg 9204603), before potting.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.2) available for terminal lug in accordance with MS 35430-4.....Visual
102. Torque on set screws, min.....Visual
103. Wiring (see 9204603)for color code and connections.....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

104. Connectors tight.....Manual
105. Anodize removed from stanchion for ground lugs.....Visual

Minor:

201. Etching.....Visual
202. Serialization (see 3.4.2).....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.20 Stanchion assembly (see dwg 9204722 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Proper potting.....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.21 Screw, self, locking (see dwg 8882034 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Nylon pellet present.....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.22 Screw, machine F.H. (see dwg MS 35240-74); Washer lock, split (see dwg MS 35337-27); Screw, cap, soc. head (see dwg BCWX 1.2-426368) covering a detail of dwg 9204603.

Categories	Characteristics	Method of inspection

Critical: None defined.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

Major:

101. Objective evidence (see 6.2) available for proper part in accordance with applicable standard.....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.23 Shim (see dwg 9204721 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major: None defined.

Minor:

201. Serialization (see 3.4.1).....Visual
202. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.24 Plate, shim (see dwg 9204720 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204720.....Visual

Minor:

201. Serialization (see 3.4.1).....Visual
202. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.25 XM32E1 Sequential Timer, modified (see 9204723 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Proper wiring.....Visual
102. Soldering in accordance with MIL-S-60902(MU).....Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

103. Timer setting mechanism not rotated.....Visual
104. Objective evidence (see 6.2) available for wire in accordance with QQ-W-343.....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.26 Key, machine (see dwg 8857543 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Thickness.....Gage
102. Objective evidence (see 6.2) available for protective finish in accordance with dwg 8857543.....Visual
103. Material (see 3.1 and 4.3.3.8).....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.27 Housing (see dwg 9204718 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Length from left face to left inside shoulder.....Gage
102. Length from left face to middle inside shoulder, max.....Gage
103. Total length.....Gage
104. Right face parallel with left face.....Gage
105. Right inside shoulder parallel with left face.....Gage
106. Pitch diameter of 4 tapped holes left end, max.....Gage
107. Minor diameter of 4 tapped holes left end, max.....Gage
108. Width of keyway, max.....Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

109. Left inside diameter, max.....Gage
110. Concentricity of left inside diameter with outside diameter.....Gage
111. Pitch diameter of 4 tapped holes right end, max.....Gage
112. Minor diameter of 4 tapped holes right end, max.....Gage
113. Diameter of left cavity, max.....Gage
114. Inside diameter of right cavity, max.....Gage
115. Outside diameter, min.....Gage
116. Radius or chamfer present.....Visual
117. Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204718.....Visual
118. Material (see 3.1).....Visual

Minor:

201. Stamping, metal raised by stamping removed.....Visual/Manual
202. Serial number (see 3.4.2).....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.28 Plate (see dwg 9204719 covering a detail of dwg 9204603).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Right face parallel with right shoulder.....Gage
102. Length from right face to right shoulder.....Gage
103. Right outside diameter, min.....Gage
104. Radius or chamfer present.....Visual
105. Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204719.....Visual
106. Material (see 3.1).....Visual

Minor:

201. Stamping, metal raised by stamping removed.....Visual/Manual
202. Serial number (see 3.4.2).....Visual
203. Workmanship (see 3.8).....Visual

4.3.2.1.29 Timer assembly (see dwg 9204603 covering a detail of dwg 9204599), assembly of housing and plate only.

Categories	Characteristics	Method of inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

Critical: None defined.

Major:

101. Any screw tight.....Manual
102. No part missing.....Visual

Minor: None defined.

4.3.2.1.30 Timer assembly (see dwg 9204603 covering a detail of dwg 9204599) after assembly of timer in housing.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Timer correctly assembled (see 4.4.5).....Gage
102. Time setting mechanism not rotated.....Visual

Minor: None defined.

4.3.2.1.31 Timer assembly (see dwg 9204603 covering a detail of dwg 9204599) after assembly of shim and shim plate to stanchion assembly only.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Correct height of shim plate (see 4.4.5).....Gage

Minor: None defined.

4.3.2.1.32 Timer assembly (see dwg 9204603 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Metal to metal contact between housing and stanchion assembly (see 4.4.6).....Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

102. Time setting mechanism not rotated.....Visual

Minor:

201. Etching correct and identifiable.....Visual
202. Serialization (see 3.4.2).....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.33 Body, forward (see dwg 9204600 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Diameter of thread undercut, min	Gage
102.	Left inside diameter, max	Gage
103.	Concentricity of left inside diameter with bourrelet diameter including perpendicularity of left inside diameter with left outside shoulder	Gage
104.	Inside diameter right of left inside diameter, max	Gage
105.	Pitch diameter of left thread, min	Gage
106.	Major diameter of left thread, min	Gage
107.	Width of left thread clearance, max	Gage
108.	Length from left face to left outside shoulder	Gage
109.	Pitch diameter of inside thread left of right inside thread	Gage
110.	Minor diameter of inside thread left of right inside thread, max	Gage
111.	Pitch diameter of 3 right outside holes, max	Gage
112.	Minor diameter of 3 right outside holes, max	Gage
113.	Pitch diameter of threaded outside hole left of 3 threaded holes, max	Gage
114.	Minor diameter of threaded outside hole left of 3 threaded holes, max	Gage
115.	Location of left outside hole	Gage
116.	Pitch diameter of left threaded hole	Gage
117.	Minor diameter of left threaded hole, max	Gage
118.	Depth of thread in left threaded hole, min	Gage
119.	Diameter of left threaded hole, min	Gage
120.	Diameter of left hole, max	Gage
121.	Engraved line present	Visual
122.	Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204600	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

Minor:

201. Chamfer or radius present.....Visual
202. Stamping.....Visual
203. Serialization (see 3.4.2).....Visual
204. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.34 Collar (see dwg 9204602 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Pitch diameter of thread, min.....Gage
102. Major diameter of thread, min.....Gage
103. Total length, max.....Gage
104. Material (see 3.1).....Visual
105. Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204602.....Visual

Minor:

201. Stamping, metal raised by stamping removed.....Visual/Manual
202. Serialization (see 3.4.2).....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.35 Clutch half positive (see dwg 8857479 covering a detail of dwg 8857439).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Diameter of body.....Gage
102. Diameter of groove.....Gage
103. Concentricity of groove diameter with body diameter.....Gage
104. Length of groove.....Gage
105. Width of groove.....Gage
106. Depth of hex hole, min.....Gage
107. Total length.....Gage
108. Parallelism of end surface with flange shoulder.....Gage
109. Length of flange.....Gage
110. Perpendicularity of flange shoulder to body diameter.....Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

111. Diameter of hole in flange.....Gage
112. Width across flats of hex hole, min.....Gage
113. Material (see 3.1).....Visual
114. Objective evidence (see 6.2) available for protective finish in accordance with dwg 8857479.....Visual

Minor:

201. Marking.....Visual
202. Serialization (see 3.4.1).....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.36 Pin, straight, headless (see dwg 8857545 covering a detail of dwg 8857439).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Diameter.....Gage
102. Finish on diameter.....Gage
103. Rockwell hardness.....Gage
104. Objective evidence (see 6.2) available for protective finish in accordance with dwg 8857545.....Visual
105. Material (see 3.1).....Visual

Minor:

201. Radius or chamfer present.....Visual
202. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.37 Clutch half positive (see dwg 8857439 covering a detail of dwg 9204606).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Length of projection of pin.....Gage
102. Pin tight.....Manual

Minor:

201. Dots present.....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

202. Marking.....Visual
203. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.38 Top plate assembly (see dwg 9204606 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Engraved line present	Visual
Minor:		
201.	Former marking obliterated	Visual
202.	Marking	Visual
203.	Serialization (see 3.4.2)	Visual
204.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.39 Grommets for 155MM, 8 in and 240MM projectiles, assembly list of parts and list of spec and std (see dwg 75-14-371 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Staples flat against liner	Visual
102.	No part missing or incorrectly assembled	Visual
Minor:		
201.	Serialization (see 3.4.1)	Visual
202.	Objective evidence (see 6.2) available for protective finish in accordance with dwg 75-14-371	Visual
203.	No paint missing including bare spot	Visual
204.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.40 Body, rear (see dwg 9204601 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection
Critical: None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

Major:

101.	Diameter of small cavity, max	Gage
102.	Concentricity of diameter of rear cavity with bourrelet diameter	Gage
103.	Parallelism of bottom of small cavity with end face	Gage
104.	Length of thread clearance, max	Gage
105.	Perpendicularity of end face with bourrelet diameter	Gage
106.	Diameter of cavity large cavity, max	Gage
107.	Concentricity of large cavity with bourrelet diameter	Gage
108.	Diameter of thread clearance, max	Gage
109.	Pitch diameter of thread, max	Gage
110.	Minor diameter of thread, max	Gage
111.	Depth of thread cavity	Gage
112.	Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204601	Visual
113.	Material (see 3.1)	Visual

Minor:

201.	Radius present	Visual
202.	Stamping	Visual
203.	Serialization (see 3.4.2)	Visual
204.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.41 Support (see dwg 9204605 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection

Major:

101.	Outside diameter, min	Gage
102.	Parallelism of end surfaces	Gage
103.	Chamfer present	Visual
104.	Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204605	Visual
105.	Material (see 3.1)	Visual

Minor:

201.	Stamping, metal raised by stamping removed	Visual
202.	Serialization (see 3.4.2)	Visual
203.	Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.42 Shim, rear (see 9204604 covering a detail of dwg 9204599).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major: None defined.		
Minor:		
	201. Serialization (see 3.4.1)	Visual
	202. Workmanship (see 3.8)	Visual/Manual

4.3.2.1.43 TU 72 Donde (see dwg 9205656 covering a detail of dwgs 9205698 and 9205699).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
	101. Gap between sleeve and front case assembly	Gage
	102. Length from left face to outside shoulder, min	Gage
	103. Length from face of cannon plug to outside shoulder, min	Gage
	104. Inside diameter of holding ring, max	Gage
	105. Outside diameter of sleeve, min	Gage
	106. Pitch diameter of thread, min	Gage
	107. Major diameter of thread, min	Gage
	108. Set screw present	Visual
Minor:		
	201. Serialization (see 3.4.1)	Visual
	202. Workmanship (see 3.8)	Visual/Manual

4.3.2.1.44 Sleeve and ring assembly (see dwg 9205699 covering a detail of dwg 9204599) before disassembly.

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

Major:

101. Seal on holding ring set screw present (see 3.8).....Visual

Minor: None defined.

4.3.2.1.45 Sleeve and ring assembly (see dwg 9205699 covering a detail of 9204599).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Seal on holding ring set screw present (see 3.5).....Visual
102. Set screws present.....Visual
103. Serial number of sleeve and capsule assembly the same.....Visual

Minor:

201. Workmanship (see 3.8).....Visual/Manual

4.3.2.1.46 Pin, straight, precision (see dwgs BFBX3-589930, 589933, 589939, 589956); screw, set, socket, cup point (see dwg BCTX1-102569); "O"-Ring (see dwg CKCX2) covering a detail of dwg 9204599.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.2) available for part in accordance with applicable standard.....Visual

4.3.2.1.47 Shipping assembly (see dwg 9204599 covering a detail of dwg 9204598) forward body assembly before assembly of pins.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Pin hole diameters.....Gage

Minor:

201. Workmanship (see 3.8).....Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.48 Shipping assembly (see dwg 9204599 covering a detail of dwg 9204598) assembly of forward body and timer assembly before assembly rear body assembly of 9205699.

Categories	Characteristics	Method of inspection
Critical:	None defined.	
Major:		
101.	Distance between phenolic face of electrical receptacle and front face of forward body	Gage
102.	Pins flush or more than .020 inch below flush	Gage
103.	Time setting on timer does agree with original recorded number	Visual
104.	Etch mark on top plate assembly in line with etched line on forward body	Visual
105.	Groove in timer setting knob in alignment with pin of top plate assembly	Visual
106.	Timer assembly not rotated in forward body	Visual
107.	Pins staked	Visual
108.	Collar firmly seated against stanchion	Manual
109.	Set screws firmly seated	Manual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.49 Shipping assembly (see 9204599 covering a detail of dwg 9204598) before assembly of pins thru rear body.

Categories	Characteristics	Method of inspection
Critical:	None defined.	
Major:		
101.	Left shim thickness (see 4.4.7)	Gage
102.	Diameter of pin holes in rear body excluding joint	Gage
103.	Diameter of pin holes in joint	Gage
104.	Torque min in assembly of rear body	Gage
105.	Pin hole in line with top plate assembly	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.50 Shipping assembly (see 9204599 covering a detail of dwg 9204598) before painting.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Metal to metal contact (see 4.4.6)	Gage
102.	Pins flush or more than .020 inch below flush in rear body	Gage
103.	Location of scribe mark right end	Visual
104.	Objective evidence (see 6.2) available for protective finish in accordance with dwg 9204599	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

4.3.2.1.51 Shipping assembly (see dwg 9204599 covering a detail of dwg 9204598).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Bourrelet diameter after painting, max	Gage
102.	Weight of shell	Gage
103.	Scribe marks 180° from top plate assembly in line at joint	Visual
104.	Reading of timer agrees with original reading, before assembly of tape	Visual
105.	Tape properly applied	Visual
106.	Undamaged rotating band (before assembly of grommet)	Visual
Minor:		
201.	Marking	Visual
202.	Serial number (see 3.4.2)	Visual
203.	No paint missing, including bare spot	Visual
204.	Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.52 Capsule assembly (see 9205698 covering a detail of dwg 9204598).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
	101. Location of line	Visual
	102. Rear portion not twisted or damaged	Visual
Minor: None defined.		

4.3.3 Testing. - The contractor shall perform all the tests specified in this paragraph. Tests do not have to be performed in the order specified.

Test	Test Classification
a. Adjustment of holding ring	Major
b. Circuit resistance	Major
c. Insulation resistance	Major
d. Push	Major
e. Thickness of shim (9204603)	Major
f. Metal to metal contact	Major
g. Thickness of shim (9204599)	Major
h. Tensile	Major
i. Paint adhesion	Minor

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Adjustment of holding ring (see 3.5). - Each sleeve and ring assembly (see dwg 9205699) shall be checked in accordance with 4.4.1 before assembly in the projectile (see dwg 9204599). If the sleeve and ring assembly does not comply with 3.5, the sleeve and ring assembly and associated capsule assembly shall be rejected.

4.3.3.2 Circuit resistance.

4.3.3.2.1 Circuit resistance (see 3.6.1). - Each assembly shall be tested as specified in 4.4.2.1. If any assembly fails to comply with requirement 3.6.1 the assembly shall be rejected and removed from the lot.

4.3.3.2.2 Circuit resistance (see 3.6.2). - Each assembly shall be tested as specified in 4.4.2.2. If any assembly fails to comply with requirement 3.6.2, the assembly shall be rejected and removed from the lot.

4.3.3.2.3 Circuit resistance (see 3.6.3). - Each projectile assembly before packing for shipment shall be tested as specified in 4.4.2.2. If any assembly fails to comply with requirement 3.6.3, the assembly shall be rejected and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.3.3 Insulation resistance.

4.3.3.3.1 Insulation resistance (see 3.7.1). - Each assembly shall be tested for insulation resistance as specified in 4.4.3.1. If any assembly fails to comply with requirement 3.7.1, the assembly shall be rejected and removed from the lot.

4.3.3.3.2 Insulation resistance (see 3.7.2). - Each assembly before packing for shipment shall be tested for insulation resistance as specified in 4.4.3.2. If any assembly fails to comply with requirement 3.7.2, the assembly shall be rejected and removed from the lot.

4.3.3.4 Push (see dwg 9209348). - Each socket in the connector shall be tested in accordance with 4.4.4. If any socket fails to comply with drawing requirements, the connector shall be rejected and removed from the lot.

4.3.3.5 Thickness of shim (see dwg 9204603). - Each assembly shall be tested in accordance with 4.4.5. Any deviation in process specified or drawing requirements shall reject the assembly which shall be removed from the lot.

4.3.3.6 Metal to metal contact outside joints (see dwgs 9204603 and 9204599). - Each assembly shall be examined as specified in 4.4.6. If any assembly does not have 75% of the joining surfaces in contact, the assembly shall be rejected and removed from the lot.

4.3.3.7 Thickness of shim (see dwg 9204599). - Each assembly shall be tested in accordance with 4.4.7. Any deviation in process specified or drawing requirements shall reject the assembly which shall be removed from the lot.

4.3.3.8 Tensile (see dwg 8857543). - A test specimen shall be prepared and tested as specified in 4.4.8. If the test specimen fails to comply with drawing requirements, the lot of parts shall be rejected.

4.3.3.9 Paint adhesion (see dwg 9204599). - Each part or assembly shall be tested for paint adhesion in accordance with 4.2.6 TT-C-490. Any part or assembly which fails to comply with 3.7 TT-C-490 shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. - Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions and calibration instructions specified on the Equipment Lists (EL). EL's for complete assemblies are listed on the Equipment Tabulation (ET-9204598) when either of the conditions listed below exist, the contractor shall design required equipment or sepcify suitable commercial equipment, and obtain approval of such designs together with any necessary operating instructions and special calibration instructions, from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4:

a. Any deviation from equipment or procedures specified on the EL is desired.

b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor characteristics and tests. - Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. - The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Adjustment of holding ring (see 3.5). - Immediately after receipt inspection, the holding ring set screw shall be sealed to comply with 3.5. Subsequent handling of the sleeve and ring assembly shall comply with 3.5.

4.4.2 Circuit resistance.

4.4.2.1 Circuit resistance (see 3.6.1). - The circuit resistance shall be measured with an approved resistance measuring device applied to pins designated in table IV. The circuit resistance shall comply with 3.6.1.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

TABLE IV

Circuit Resistance Test Points

Connector 9204727 from Pin	Connector 9220308 to Pin
1	1
2	2
3	11
3	12
8	16
8	18
8	20
8	17
8	15
10	4
10	3
11	14
11	13
12	6
12	5

	Connector 9204727 to Pin
3	5
3	6
3	9
11	14
11	15
12	13
8	Ground

4.4.2.2 Circuit resistance (see 3.6.2 and 3.6.3). - The circuit resistance shall be tested with an approved resistance measuring device and comply with requirements 3.6.2 and 3.6.3.

4.4.3 Insulation resistance.

4.4.3.1 Insulation resistance (see 3.7.1). - The insulation resistance shall be measured with an approved resistance measuring device at a potential of 500 ± 50 volts direct current limited to 5 milliamperes applied to pins designated in table V. The insulation resistance shall comply with requirement 3.7.1.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

TABLE V

Insulation Resistance Test Points

Positive Connector 9220308	All other pins, connector shells and stanchion minus potential except
1	1 and 2 (9204727), 2 (9220308)
3	10 (9204727), 4 (9220308)
5	12 and 13 (9204727), 6 (9220308)
11	3, 5, 6 and 9 (9204727), 12 (9220308)
14	11, 14 and 15 (9204727), 13 (9220308)

4.4.3.2 Insulation resistance (see 3.7.2). - The insulation resistance shall be measured between any pin and case with an approved resistance measuring device at a potential of 500 ± 50 volts direct current limited to 5 milliamperes.

4.4.3.3 Insulation resistance (see 3.7.3). - The insulation resistance shall be measured with an approved resistance measuring device at a potential of 500 ± 50 volts direct current limited to 5 milliamperes in accordance with table VI. The insulation resistance for each pin measured shall comply with 3.7.3.

TABLE VI

Insulation Resistance Test Points

Plus potential applied to pin	All other pins minus potential except
1	2
3	5, 6, 9
10	
11	14, 15
12	13

4.4.4 Push (see 4.3.3.4). - Each contact shall be assembled to the connector in accordance with dwg 9205334. After assembly each contact will be tested by pushing against socket end in accordance with drawing 9220312. All sockets shall comply with the requirement on dwg 9220312.

4.4.5 Thickness of shim (4.3.3.5). - The Government inspector will witness the assembly operation outlined below. Any deviation in procedure or drawing requirements shall reject the assembly (see 4.3.3.5).

1. Assemble timer in the housing with the timer bottomed against the end plate with screw holes aligned.
2. Assemble 4 screws loose to serve as guides.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

3. Measure distance from top of housing to top of timer plate immediately adjacent to screw holes and record.

4. Assemble 4 screws and torque until recorded distance at each screw is increased .002 to .004 inch.

5. Substitute a master shim of .026 inch thick for shim 9204721 and place assembly on top of the sequential timer.

6. Measure the gap between stanchion and housing.

7. Determine thickness of shim 9204721 by applying formula below: .026 inch minus (gap determined in step 6 plus .004 inch).

8. Assemble stanchion assembly using shim thickness determined in step 7.

9. Comply with 4.3.3.5.

4.4.6 Metal to metal contact outside joints (see 4.3.3.6). - The assembly shall be examined using a 10 power magnifier. If the assembly has less than 75% of the joining surfaces in contact, the assembly shall be rejected.

4.4.7 Thickness of shim (see 4.3.3.7). - The Government inspector will witness the assembly operation of the rear body to the forward body. Any deviation from the procedure listed below shall reject the assembly.

1. Assemble the rear body and forward body hand tight with rear shim in place.

2. Check gap if visible between rear and forward body with .001 inch thick feeler gage. If gage enters the gap at any point around the circumference reduce the thickness of shim.

3. Disassemble rear body from forward body and examine shim. If pressure marks are not evident, increase the thickness of shim and repeat steps 1 and 2.

4. Repeat steps 1, 2 and 3 until pressure marks are visible on the shim and the gap complies with(4.3.3.6).

4.4.8 Tensile (see 4.3.3.8). - The test specimen shall be selected at random from stock during the production run of parts and shall be included in each heat treated lot of parts. After heat treatment the specimen shall be prepared in accordance with Federal Test Method Standard No. 151, test method 211.1. The specimen shall be tested on approved test equipment.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. - Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. - The shell shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169 (MU).

5.1.2 Level C. - The shell shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169 (MU).

5.2 Packing.

5.2.1 Levels A and C. - The shell shall be packed in accordance with the applicable instructions contained in MIL-STD-1169 (MU).

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:22Z
Check the source to verify that this is the current version before use.

5.3 Marking. - Marking shall be in accordance with MIL-STD-1169 (MU).

6. NOTES

6.1 Ordering data. - Procurement documents should specify the following:
a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. - Records of contractor quality control and inspections which can be verified.

Custodian:
Army - MU

Preparing Activity
Army - MU
Project No - 1190 - A013

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:22Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

GPO 303-226/Z 1003

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-S-60907(MU) Shell, Telementry: T5123E1

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:22Z
Check the source to verify that this is the current version before use.