MIL-T-60645 (MU)
11 August 1967
SUPERSEDING
FA-PD-MI-2285, Rev 1
22 December 1960

MILITARY SPECIFICATION
THRUSTER, CARTRIDGE ACTUATED, M6, METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Thruster, Cartridge Actuated, M6, Metal Parts Assembly, for use with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to this extent specified herein:

SPECIFICATIONS
Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS
Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Inspection Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings
MIL-STD-639	- Surface Roughness Values Preferred for Army Ordnance Materiel
MIL-STD-1167	- Ammunition Data Card

DRAWINGS
Munitions Command

F8593752	- Thruster, Cartridge Actuated, M6, Metal Parts Assembly
C8797437	- Box, Packing, Ammunition for Thruster, Cartridge Actuated, M6, w/ctg M67, in Fiber Container M363
C8797438	- Container, Ammunition, Fiber M363 for Thruster, Cartridge Actuated, M6, w/ctg M67
IEL-8593752	- Inspection Equipment List for Thruster, Cartridge Actuated, M6, Metal Parts Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with all the requirements specified on the applicable drawings, referenced specifications and the following:

3.2 Material.- The contractor shall be responsible for selecting from the classification list contained in the raw material specification, the surface and physical condition of the raw material intended for use in manufacture.

3.3 Physical or mecnanical properties.- Physical or mechanical properties required by the drawing shall be uniform throughout each part within specified tolerances. Mechanical properties for all alloy steel parts shall be achieved by quenching and tempering.

3.4 Hydrostatic pressure.- The body and breech shall withstand a hydrostatic pressure of 4,500 pounds per square inch (psi), minimum, for 15 seconds, minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.1).

3.5 Shear pin strength.- After application of protective finish, the pin shall shear within 36 to 46 pounds upon application of a load at the rate of 0.125 inch per minute.

3.6 Initial lock.- The assembled thruster shall withstand a static tensile force of 250 pounds plus or minus 20 pounds for 15 seconds, minimum, between the mounting points without unlocking and without mechanical failure (see 6.1).

3.7 Metal parts assembly.- Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing.

3.7.1 Breech and body.- The breech and body shall be assembled handtight.

3.7.2 End sleeve rotation.- Upon completion of assembly and after initial lock test the end sleeve shall be free to rotate 360 degrees in a clockwise direction.

3.8 Protective finish.- Protective finish shall be in accordance with the applicable specifications and drawings, and shall apply to all surfaces of the component regardless of contour configuration.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the currentversion before use.

3.9 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than three degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.10 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.10.1 Metal defects.- All components shall be free from cracks, splits, cold shuts, inclusions, porosity or any similar defect.

3.10.2 Burr.- No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.10.3 Foreign matter.- No part or assembly shall contain chips, dirt, grease, rust, corrosion or any other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First Article Sample.

4.2.1 Initial production sample.- At the beginning of regular production, the contractor shall submit an initial production sample to a Government approved facility for evaluation. The sample shall consist of 5 metal parts assemblies, 10 sets of parts and 50 shearpins from the same lot of shearpins tested by the contractor. The samples shall be subjected to the tests in 4.3.4. Test procedures shall be in accordance with 4.4. The samples shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, must be the same as used in regular production and shall be obtained from the same source of supply.

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:21Z
Check the source to verify that this is the current version before use.

4.2.1.1 Examination and test.- After inspection and acceptance at source, the initial production sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility as specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified herein, or by the contracting officer, lots, formation of lots, lot size, and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.3.2 Size of lot.- For the purpose of identification and shipment the lot of metal parts assemblies shall consist of 1200 thrusters, maximum, provided the homogeneity requirements of inspection lots have been retained. A smaller lot may be shipped upon approval of the contracting officer.

4.3.3 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans and criteria in tables I and II. For an individual defect (single characteristic) the criteria in table I shall be used. For total defects within a major or minor group the criteria in Table II shall be used. All non-conforming material shall be rejected. The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for O-rings shall be in accordance with Standard MIL-STD-413.

TABLE I

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination				
301 - 1,300	110	1	2	2	3
1,301 - 3,200	150	2	3	3	4
3,201 - 8,000	225	3	4	4	5
8,001 - 22,000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the currentversion before use.

TABLE II

Total Allowable Defects per Sample Size				
Sample Sizes for Major Defects	110	150	225	300
No. of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
over 43	6	8	11	14
Sample Sizes for Minor Defects	110	150	225	300
No. of Defects in Class				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
over 48	8	11	17	20

4.3.3.1 Body, Dwg D8593753 covering a detail of Dwg F8593752.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of thread, max.	Gage
102. Minor diameter of thread, max.	Gage
103. Concentricity of pitch diameter of thread with counterbore	Gage
104. Concentricity of long cavity with counterbore	Gage
105. Concentricity of throat bore with long cavity	Gage
106. Concentricity of cavity, groove end, with throat bore	Gage
107. Concentricity of key groove with throat bore	Gage
108. Diameter of long cavity, max.	Gage
109. Diameter of throat bore, max.	Gage
110. Diameter of cavity, groove end, max.	Gage
111. Diameter of counterbore, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.3.1 (Cont'd)

	Defect	Method of Inspection
112.	Diameter of key groove	Gage
113.	Depth to bottom of counterbore	Gage
114.	Length of effective thread, min.	Gage
115.	Location of key groove	Gage
116.	Radii at mouth of long cavity	Gage
117.	Straightness of long cavity	Gage
118.	Profile of key groove	Gage
119.	Thread damaged or not full	Visual
120.	Metal defective	Visual
121.	Protective finish inadequate or defective	Visual
122.	Surface finish of long cavity and throat bore, improper	Visual
123.	Burr or sharp corner	Visual
124.	Foreign matter	Visual

MINOR

201.	Pitch diameter of thread, min.	Gage
202.	Pitch diameter of set screw thread	Gage
203.	Minor diameter of set screw thread, max.	Gage
204.	Diameter of long cavity, min.	Gage
205.	Diameter of throat bore, min.	Gage
206.	Diameter of cavity, groove end, min.	Gage
207.	Diameter of counterbore, min.	Gage
208.	Diameter of body, midsection, max.	Gage
209.	Diameter of body, thread end	Gage
210.	Depth of thread cavity, max.	Gage
211.	Thickness of wall, min.	Gage
212.	Diameter of body groove end	Gage
213.	Depth to bottom of long cavity	Gage
214.	Depth of cavity, groove end	Gage
215.	Total length	Gage
216.	Length of body, groove end	Gage
217.	Length of body, thread end	Gage
218.	Width of flats	Gage
219.	Location of set screw holes	Gage
220.	Marking missing, incorrect or illegible	Visual
221.	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
222.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the currentversion before use.

4.3.3.2 Breech, Dwg. D8593754 covering a detail of Dwg. F8593752.

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter of internal thread, max.	Gage
102.	Minor diameter of internal thread, max.	Gage
103.	Pitch diameter of external thread, min.	Gage
104.	Major diameter of external thread, min.	Gage
105.	Concentricity of striker hole with cavity	Gage
106.	Concentricity of body, small end, with cavity	Gage
107.	Concentricity of external thread with body, small end	Gage
108.	Concentricity of boss cavity with cavity	Gage
109.	Symmetry of pin hole with cavity	Gage
110.	Diameter of cavity, max.	Gage
111.	Diameter of datum location	Gage
112.	Diameter of pin hole, max.	Gage
113.	Diameter of body, small end	Gage
114.	Depth of counterbore	Gage
115.	Depth of threaded cavity	Gage
116.	Length of effective internal thread, min.	Gage
117.	Length of thread (internal), max.	Gage
118.	Angle at datum diameter	Gage
119.	Height of boss	Gage
120.	Diameter of chamfer, thread cavity	Gage
121.	Width of undercut	Gage
122.	Angle at mouth of thread cavity	Gage
123.	Radius at root of boss	Visual
124.	Thread damaged or not full	Visual
125.	Metal defective	Visual
126.	Protective finish inadequate or defective	Visual
127.	Surface finish of cavity, internal thread, and mouth chamfers, improper	Visual
128.	Burr or sharp corner	Visual
129.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of internal thread, min.	Gage
202.	Pitch diameter of external thread, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the currentversion before use.

	Defect	Method of Inspection
203.	Pitch diameter of set screw thread	Gage
204.	Minor diameter of set screw thread, max.	Gage
205.	Diameter of cavity, min.	Gage
206.	Diameter of boss cavity	Gage
207.	Diameter of pin hole, min.	Gage
208.	Diameter of striker hole	Gage
209.	Diameter of counterbore	Gage
210.	Diameter of escapement hole	Gage
211.	Depth of striker hole	Gage
212.	Length of effective pin hole thread	Gage
213.	Location of undercut	Gage
214.	Location of pin hole	Gage
215.	Thickness thru boss	Gage
216.	Diameter of undercut, min.	Gage
217.	Diameter of body, large end	Gage
218.	Depth of set screw cavity	Gage
219.	Total length	Gage
220.	Length to external thread	Gage
221.	Width across flats	Gage
222.	Location of escapement hole	Gage
223.	Location of flats	Gage
224.	Marking missing, incorrect or illegible	Visual
225.	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
226.	Surface finish improper, except as otherwise classified	Visual

4.3.3.3 Piston, Dwg. D8593755 covering a detail of Dwg. F8593752.

CRITICAL

None defined

MAJOR

101.	Pitch diameter of thread, min.	Gage
102.	Major diameter of thread, min.	Gage
103.	Concentricity of flange with body	Gage
104.	Concentricity of neck with body	Gage
105.	Concentricity of thread shoulder with body	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.3.3 (Cont'd)

	Defect	Method of Inspection
106.	Concentricity of pitch diameter of thread with body	Gage
107.	Concentricity of groove with body	Gage
108.	Diameter of body, min.	Gage
109.	Diameter of groove	Gage
110.	Diameter of thread shoulder, min.	Gage
111.	Diameter of neck, max.	Gage
112.	Diameter of flange, min.	Gage
113.	Diameter of cavity	Gage
114.	Length from face of thread shoulder to flange	Gage
115.	Length from face of thread shoulder to neck	Gage
116.	Location of thread radius	Gage
117.	Length from face of thread shoulder to body	Gage
118.	Profile of ring groove	Gage
119.	Profile of neck	Gage
120.	Thread damaged or not full	Visual
121.	Metal defective	Visual
122.	Protective finish inadequate or defective	Visual
123.	Surface finish of body, flange and ring groove, improper	Visual
124.	Burr or sharp corners	Visual
125.	Foreign matter	Visual

MINOR

201.	Pitch diameter of thread, max.	Gage
202.	Diameter of body, max.	Gage
203.	Diameter of thread shoulder, max.	Gage
204.	Diameter of neck, min.	Gage
205.	Diameter of flange, max.	Gage
206.	Diameter of lug	Gage
207.	Depth of cavity	Gage
208.	Total length	Gage
209.	Length from face of thread shoulder to face of flange	Gage
210.	Width of ring groove	Gage
211.	Location of ring groove	Gage
212.	Marking missing, incorrect or illegible	Visual
213.	Radius or chamfer missing or incorrect	Visual
214.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the currentversion before use.

4.3.3.4 Trunnion, Dwg. D8593756 covering a detail of Dwg. F8593752.

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter of thread, max.	Gage
102.	Minor diameter of thread, max.	Gage
103.	Concentricity of lugs	Gage
104.	Symmetry of lugs with thread	Gage
105.	Diameter of lug, min.	Gage
106.	Thread damaged or not full	Visual
107.	Metal defective	Visual
108.	Protective finish inadequate or defective	Visual
MINOR		
201.	Pitch diameter of thread, min.	Gage
202.	Diameter of lug, max.	Gage
203.	Length of lug	Gage
204.	Width across flat	Gage
205.	Location of flats	Gage
206.	Location of lugs	Gage
207.	Total length	Gage
208.	Width of body	Gage
209.	Thickness	Gage
210.	Marking missing, incorrect or illegible	Visual
211.	Radius or chamfer missing or incorrect	Visual
212.	Surface finish, improper	Visual
213.	Burr	Visual
214.	Foreign matter	Visual

4.3.3.5 Spring, Piston Locking, Dwg. B8593757 covering a detail of Dwg. F8593752.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the currentversion before use.

4.3.3.5 (Cont'd)

	Defect	Method of Inspection
	MAJOR	
101.	Load at specified heights	Gage
102.	Solid length, max.	Gage
103.	Ends incorrect	Visual
104.	Protective finish inadequate or defective	Visual
105.	Burr or sharp edges	Visual
106.	Foreign matter	Visual
	MINOR	
201.	Outside diameter	Gage

4.3.3.6 Sleeve, End, Dwg. D8593758 covering a detail of Dwg. F8593752.

CRITICAL

None defined

	MAJOR	
101.	Pitch diameter of thread, max.	Gage
102.	Minor diameter of thread, max.	Gage
103.	Concentricity of pitch diameter of thread with body, thread end	Gage
104.	Concentricity of threaded cavity with body, thread end	Gage
105.	Diameter of holes, thread end	Gage
106.	Diameter of body, thread end, min.	Gage
107.	Diameter of threaded cavity, max.	Gage
108.	Diameter of long cavity	Gage
109.	Depth of threaded cavity	Gage
110.	Length of thread	Gage
111.	Length to end of shoulder, thread end, min.	Gage
112.	Length to small body, max.	Gage
113.	Location of holes, thread end	Gage
114.	Depth to bottom of small cavity	Gage
115.	Thread damaged or not full	Visual
116.	Metal defective	Visual
117.	Protective finish inadequate or defective	Visual
118.	Burr	Visual
119.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.3.6 (Cont'd)

MINOR	Defect	Method of Inspection
201.	Pitch diameter of thread, min.	Gage
202.	Diameter of body, thread end, max.	Gage
203.	Diameter of threaded cavity, min.	Gage
204.	Diameter of small cavity	Gage
205.	Length to shoulder, thread end	Gage
206.	Diameter of shoulders	Gage
207.	Diameter of small body	Gage
208.	Depth of long cavity	Gage
209.	Total length	Gage
210.	Length of shoulder, small body	Gage
211.	Marking missing, incorrect or illegible	Visual
212.	Radius or chamfer missing or incorrect	Visual
213.	Surface finish, improper	Visual

4.3.3.7 Pin, Shear, Dwg. B8594506 covering a detail of Dwg. F8593752.

CRITICAL

None defined

MAJOR

101.	Diameter, max.	Gage
102.	Total length, min.	Gage
103.	Metal defective	Visual
104.	Protective finish inadequate or defective	Visual
105.	Surface finish, improper	Visual
106.	Burr	Visual
107.	Foreign matter	Visual

MINOR

201.	Total length, max.	Gage
202.	Profile of end	Gage

4.3.3.8 Firing Pin, Dwg. C8594744 covering a detail of Dwg. F8593752.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.3.8 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Concentricity of groove with body	Gage
102. Concentricity of striker with body	Gage
103. Concentricity of striker shoulder with body	Gage
104. Symmetry of pin hole with body	Gage
105. Diameter of body, min.	Gage
106. Diameter of groove	Gage
107. Diameter of striker	Gage
108. Diameter of pin hole, max.	Gage
109. Profile of striker	Gage
110. Profile of groove	Gage
111. Metal defective	Visual
112. Protective finish inadequate or defective	Visual
113. Surface finish of body and striker tip, improper	Visual
114. Burr or sharp corner	Visual
115. Foreign matter	Visual
MINOR	
201. Diameter of body, max.	Gage
202. Diameter of striker shoulder	Gage
203. Diameter of pin hole, min.	Gage
204. Length from body to tip of striker	Gage
205. Length of striker	Gage
206. Total length	Gage
207. Location of pin hole	Gage
208. Location of groove	Gage
209. Depth of slot in base	Gage
210. Depth of pin hole	Gage
211. Width of groove	Gage
212. Width of slot in base	Visual
213. Location of slot in base	Visual
214. Marking missing, incorrect or illegible	Visual
215. Radius missing or incorrect	
216. Surface finish improper, except as otherwise classified	Visual

4.3.3.9 Breech Sub-Assembly consisting of components 8593754, 8594744 and MS28775-009 covering a detail of Dwg. 8593752.

CRITICAL	
1. Firing pin protrusion	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.3.9 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. "O" ring missing	Visual
102. "O" ring not lubricated	Visual
103. Excessive lubricant	Visual
104. Thread damaged or not full	Visual
105. Metal defective	Visual
106. Protective finish inadequate or defective	Visual
107. Foreign matter	Visual
MINOR	
None defined	

4.3.3.10 Metal Parts Assembly, Dwg. F8593752.

CRITICAL	
None defined	
MAJOR	
101. End sleeve not free to rotate 360 degrees clockwise	Manual
102. Any part missing, except as otherwise classified	Visual
103. Improper assembly	Visual
104. Marking missing, incorrect or illegible	Visual
105. Foreign matter	Visual
MINOR	
201. Shipping cap or plug, missing	Visual
202. Protective finish inadequate or defective	Visual

4.3.3.11 Packing in Fiber Container, Dwg. C8797438.

CRITICAL	
None defined	
MAJOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.3.11 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual
202. Metal ends loose or distorted	Manual
203. Gap between body and cover, max.	Visual
204. Cut or damaged through all impregnated layers	Visual

4.3.3.12 Packing in Wooden Box, Dwg. C8797437.

CRITICAL

None defined

MAJOR

None defined

MINOR

201.	Contents loose	Manual
202.	Hardware missing, loose, broken or improperly engaged	Visual & Manual
203.	Strapping missing, loose, broken or improperly assembled	Visual & Manual
204.	Contents of box exposed	Visual
205.	Box damaged	Visual
206.	Marking missing, incorrect or illegible	Visual
207.	Number of units incorrect	Visual

4.3.4 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4.

4.3.4.1 Hardness.- Fifty units from each heat treated lot of components shall be tested for compliance with the requirements noted in the applicable drawings. Failure of any unit to comply with drawing requirements shall be cause for rejection of the lot.

4.3.4.2 Hydrostatic pressure.- Each body and breech shall be subjected to an internal hydrostatic pressure test. Failure of any unit to comply with the requirements of 3.4 shall be cause for rejection of the component.

4.3.4.3 Shear pin strength.- Fifty pins from each lot shall be tested for shear strength. Failure of any shear pin to comply with the requirements of 3.5 shall be cause for rejection of the lot.

4.3.4.4 Initial lock.- Each thruster shall be subjected to an initial lock test. Failure of any thruster to comply with the requirement of 3.6 shall be cause for rejection of the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.4.5 Protective finish.- The number of units for protective finish tests shall be in accordance with the applicable specifications. Failure of any sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.3.4.6 Residual magnetism.- Each assembly shall be subjected to a test for excessive residual magnetism. Failure of any unit to comply with the requirements of 3.9 shall be cause for rejection of the assembly.

4.3.5 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-8593752.

4.4 Test methods and procedures.

4.4.1 Hardness.- Prior to the application of protective finish, a hardness tester shall be used to determine the values specified on the detail drawing.

4.4.2 Hydrostatic pressure.- Prior to the application of protective finish, the body and breech, individually, shall be mounted in a fixture that internally seals the body and breech, as applicable, at each end without applying any axial load other than that applied by the liquid pressure.

4.4.3 Shear pin strength.- After application of protective finish, the load shall be applied at the steady rate of 0.125 inches per minute. The test shall be performed in a fixture in conjunction with a tensile testing machine.

4.4.4 Initial lock.- A tensile testing machine shall be used to perform the test in accordance with the requirement of 3.6.

4.4.5 Protective finish.- Test procedures for protective finish shall be in accordance with the specification referenced on the component drawing. Samples subjected to the protective finish test shall be scrapped.

4.4.6 Residual magnetism.- The thruster shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the thruster 6 inches from and at the same height as the compass, in a north-south horizontal position with the compass set in an east-west heading. The thruster shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the thruster.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Level A.- Packing and marking shall be in accordance with Drawings C8797437 and C8797438.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A159

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R001

INSTRUCTIONS

This sheet is to be filled out by personnel office Government or contractor, involved in the use of the specification to procurement of products for ultimate use by the Department of Defense. This sheet is provided for submitting information on the use of this specification which will insure that suitable products are procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Detail on items on reverse of this sheet to correspond to number, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:21Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.