NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH POUND

MIL-PRF 39016/19G
AMENDMENT 5
11 August 1992
SUPERSEDING
AMENDMENT 4
21 January 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1 0 AMPERE WITH INTERNAL DIODES FOR COIL TRANSIENT SUPPRESSION AND POLARITY REVERSAL PROTECTION TERMINALS 0 100-INCH GRID PATTERN

This amendment forms a part of MIL-R-39016/19G, dated 20 July 1988 and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1 Delete " 370 SQ MAX" and substitute " 375 SQ MAX"

PAGE 2

FIGURE 2 Delete " 370 SQ MAX" and substitute " 375 SQ MAX"

FIGURE 2 mounting pad Delete " 170 ± 005" and substitute " 140 minimum 175 maximum"

PAGE 3

Requirements resistive, delete in its entirety and substitute

"Resistive
1 0 ampere at 28 V dc
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded
100 milliamperes at 115 V ac 60 and 400 Hz case grounded "

Requirements, overload (high level only), delete and substitute

"Overload (high level only) Two times rated current Not applicable to ac load ratings "

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:39Z
Check the source to verify that this is the current version before use.

PAGE 4

ELECTRICAL DATA, delete footnote 1/ and associated references to footnote 1/ in their entirety

* DIODE CHARACTERISTICS, delete and substitute

"Coil transient suppression Applicable

Diode block integrity (perform this test after coil transient suppression test in all inspection tables of MIL-R-39016) With applicable voltage applied to the relay coil circuit in the reverse direction, monitor leakage current with dc microammeter, oscilloscope, or qualifying activity approved test equipment Leakage current shall not exceed the specified value

Block integrity maximum leakage current 1 μA at 50 V dc.

Maximum negative transient. 1 0 volt

Breakdown voltage 100 V dc minimum at 10 microamperes (μA) (This test may be performed in-process or as final assembly)

Semiconductor in-process screening: Applicable, visual inspection of semiconductors shall be in accordance with MIL-STD-750, methods 2073 or 2074 "

PAGE 5

* TABLE I, add the following new footnote 7/

"7/ Delete "Coil resistance" and substitute "Coil current" test in all inspection tables of MIL-R-39016 "

* TABLE I, add footnote 7/ to the coil circuit current column

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities
Navy - MC

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5945-0837)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:39Z
Check the source to verify that this is the current version before use.