| INCH-POUND |

MIL-R-39016/20H
AMENDMENT 3
18 March 1992
SUPERSEDING
AMENDMENT 2
20 November 1991

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT
LOW LEVEL TO 1.0 AMPERE WITH INTERNAL DIODES FOR COIL
TRANSIENT SUPPRESSION AND POLARITY REVERSAL PROTECTION

This amendment forms a part of MIL-R-39016/20H, dated 13 May 1987 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* FIGURE 1: Delete ".335/.275 DIA" and substitute ".370 MAX".

PAGE 5

Requirements, resistive, delete in its entirety and substitute:

"Resistive:
1.0 ampere at 28 V dc.
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded.
100 milliamperes at 115 V ac 60 and 400 Hz case grounded."

Requirements, overload (high level only), delete and substitute:

"Overload (high level only): Two times rated current. Not applicable to ac load ratings."

PAGE 6

Electrical data, delete footnote 1/ in it's entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-21T17:39Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk (or vertical lines) to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS
Air Force - 17, 99
DLA - ES

User activities:
Navy - MC, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0879-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:39Z
Check the source to verify that this is the current version before use.