NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH-POUND

MIL-PRF-39016/20H
AMENDMENT 5
21 September 1992
SUPERSEDING
AMENDMENT 4
11 August 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1 0 AMPERE WITH INTERNAL DIODES FOR COIL TRANSIENT SUPPRESSION AND POLARITY REVERSAL PROTECTION

This amendment forms a part of MIL-R-39016/20H, dated 13 May 1987, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1 Delete " 335/ 275 DIA" and substitute " 370 MAX"

PAGE 5

REQUIREMENTS, contact data, load ratings, high level (relay case grounded), resistive, delete in its entirety and substitute

"Resistive
1 0 ampere at 28 V dc
250 milliamperes at 115 V ac, 60 and 400 Hz case not grounded
100 milliamperes at 115 V ac 60 and 400 Hz case grounded "

REQUIREMENTS, contact data, overload (high level only), delete and substitute

"Overload (high level only) Two times rated current Not applicable to ac load ratings "

PAGE 6

ELECTRICAL DATA, delete footnote 1/ and all associated references to footnote 1/ in its entirety

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:39Z
Check the source to verify that this is the current version before use.

DIODE CHARACTERISTICS, delete and substitute.

"Coil transient suppression Applicable

"Diode block integrity (perform this test after coil transient suppression test in all inspection tables of MIL-R-39016): With applicable voltage applied to the relay coil circuit in the reverse direction, monitor leakage current with dc microammeter, oscilloscope, or qualifying activity approved test equipment Leakage current shall not exceed the specified value.

"Block integrity maximum leakage current 1 µA at 50 V dc.

"Maximum negative transient: 1 0 volt: =

"Breakdown voltage: 100 V dc minimum at 10 microamperes (µA) (This test may be performed in-process or as final assembly)

"Semiconductor in-process screening: Applicable, visual inspection of semiconductors shall be in accordance with MIL-STD-750, methods 2073 or 2074 "

PAGE 8

TABLE I, add footnote 7/ to the coil circuit current column

TABLE I, add the following new footnote 7/

"7/ Delete "coil resistance" and substitute "coil current" test in all inspection tables of MIL-R-39016 "

PAGE 10

* QUALIFICATION INSPECTION, group A testing for relays supplied with spreader pads (-061 through -066, -073 through -078, and -091 through -096), shall be tested as specified below, delete and substitute

"Perform seal test immediately, preceding the subgroup 3 electrical tests. Relay leads shall be formed and the mounting pad removed before the seal test. After the seal test, the mounting pad shall be rigidly attached to the relay and the remaining group A tests performed "

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - MC, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0900-09)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:39Z
Check the source to verify that this is the current version before use.