NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH-POUND

MIL-PRF-39016/22D
AMENDMENT 1
10 July 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 2 AMPERES (0 200-INCH TERMINAL SPACING)
COIL TRANSIENT SUPPRESSED

This amendment forms a part of MIL-R-39016/22D, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense

, PAGE 3

Requirements contact data, load ratings, high level (relay case grounded) resistive Delete for qualification testing 400 Hz loads not required *

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army AR SL
Navy - AS, OS, SH
Air Force 99
DLA - ES

User activities
Navy - MC
Air Force 19

Preparing activity
Navy EC

Agent
DLA - FS

(Project 5945 0896-04)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimit

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:40Z
Check the source to verify that this is the current version before use.