NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH-POUND

MIL-PRF-39016/23E
AMENDMENT 4
23 June 1993
SUPERSEDING
AMENDMENT 3
21 September 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, SPDT, LOW LEVEL TO 1 0 AMPERE WITH INTERNAL DIODE FOR COIL TRANSIENT SUPPRESSION

This amendment forms a part of MIL-R-39016/23E, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense

, PAGE 3

Load ratings, resistive, delete in its entirety and substitute

"Resistive

1 0 ampere at 28 V dc
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded
100 milliamperes at 115 V ac 60 and 400 Hz case grounded "

Overload (high level only), delete and substitute

"Overload (high level only) Two times rated current Not applicable to ac load ratings "

PAGE 4

Delete footnote 1/ and all associated references to footnote 1/ in their entirety

PAGE 6

" TABLE II, footnote 1/, delete and substitute

"1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-39016/15, /16, /20, /21, /24, /25, and /26 may be used in addition to MIL-R-39016/23 data Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan "

PAGE 7

Group A testing for relays supplied with spread pads, delete both paragraphs and substitute

"Perform seal test immediately, preceding the subgroup 3 electrical tests Relay leads shall be formed and the mounting pad removed before the seal test After the seal test, the mounting pad shall be rigidly attached to the relay and the remaining group A tests performed "

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:41Z
Check the source to verify that this is the current version before use.

* Qualification inspection (reduced testing) and sample size, delete paragraph and substitute:

"If the relays produced for MIL-R-39016/23 are similar in construction and design except for the diodes, coil assembly, and headers, as applicable, to the relays produced for MIL-R-39016/15, /16, /20, /21, /24, /25, and /26, then reduced testing for qualification of MIL-R-39016/23 relays may be performed concurrent with or subsequent to successful qualification of MIL-R-39016/15, /16, /20, /21, /24, /25, and /26. For reduced testing, see table III "

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activity.
Navy - MC

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0916-08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:41Z
Check the source to verify that this is the current version before use.