METRIC


DOD-B-70331/1(AR)
21 April 1983

MILITARY SPECIFICATION SHEET

BOLT, SELF-LOCKING, HEXAGON HEAD, STEEL,
SAE J1199 (10.9) TYPE B, METRIC

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the bolts described herein shall consist of this specification and the latest issue of DOD-B-70331.




1/ See tables II and VI
2/ See table VI
3/ See table IV
4/ See table III
5/ See table V

FIGURE 1. Bolt, self-locking.

FSC 5306

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.



NOTES:
1. Bolt lengths above solid line in table VI are threaded to head.
2. All dimensions are in millimeters.
3. This bolt is covered by U.S. Patent Number 3342236, which expires 19 September 1984. The Government does not have a royalty free license under this patent. This bolt is known as a "place" bolt under this patent.

FIGURE 1. Bolt, self-locking, (detailed sections). Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions.

Dash no	Nom bolt diameter	E Body diameter		F Hexagon width across flats			G Hexagon width across corners		H Head height		I Wrenching height
		Max	Min	Basic	Max	Min	Max	Min	Max	Min	Min
6	M6X1	6.00	5.78	10	10.00	9.76	11.55	11.13	4.47	4.13	3.0
8	M8X1.25	8.00	7.78	13	13.00	12.73	15.01	14.51	5.50	5.10	3.7
10	M10X1.5	10.00	9.78	15	15.00	14.70	17.32	16.76	6.63	6.17	4.5
12	M12X1.75	12.00	11.73	18	18.00	17.67	20.78	20.14	7.76	7.24	5.2
14	M14X2	14.00	13.73	21	21.00	20.64	24.25	23.53	9.09	8.51	6.2
16	M16X2	16.00	15.73	24	24.00	23.61	27.71	26.92	10.32	9.68	7.0
20	M20X2.5	20.00	19.67	30	30.00	29.35	34.64	33.46	12.88	12.12	8.8
24	M24X3	24.00	23.67	36	36.00	35.25	41.57	40.19	15.44	14.56	10.5
30	M30X3.5	30.00	29.61	46	46.00	44.50	53.12	50.73	19.48	17.92	13.1

TABLE I. Dimensions. - Continued

Dash no	Nom bolt diameter	J Large recess diameter		J_1 Small recess diameter		K Large recess depth		K_1 Small recess depth	
		Max	Min	Max	Min	Max	Min	Max	Min
6	M6X1	8.29	8.04	7.80	7.55	0.17	0.10	0.17	0.07
8	M8X1.25	10.82	10.57	10.18	9.93	0.32	0.25	0.32	0.15
10	M10X1.5	12.98	12.73	12.21	11.96	0.32	0.25	0.32	0.15
12	M12X1.75	15.01	14.76	14.13	13.88	0.32	0.25	0.32	0.15
14	M14X2	17.54	17.29	16.51	16.26	0.32	0.25	0.32	0.15
16	M16X2	20.06	19.81	18.88	18.63	0.32	0.25	0.32	0.15
20	M20X2.5	24.94	24.69	23.48	23.23	0.32	0.25	0.32	0.15
24	M24X3	29.96	29.71	28.20	27.95	0.32	0.25	0.32	0.15
30	M30X3.5	37.82	37.57	35.60	35.35	0.32	0.25	0.32	0.15

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions. - Continued

Dash no	Nom bolt diameter	M Head top recess diameter		N Checking height		Q Bearing dia	R Recess corner and fillet radius		R_1 Spherical radius
		Max	Min	Max	Min	Min	Max	Min	±6.35
6	M6X1	4.22	3.72	3.60	3.10	9.0	0.77	0.45	43.75
8	M8X1.25	5.29	4.79	4.37	3.87	11.7	0.77	0.45	43.75
10	M10X1.5	6.55	6.05	5.22	4.72	13.5	0.77	0.45	43.75
12	M12X1.75	7.81	7.31	6.07	5.57	16.2	0.77	0.45	43.75
14	M14X2	9.07	8.57	7.06	6.56	18.9	0.77	0.45	43.75
16	M16X2	10.33	9.83	7.99	7.49	21.6	0.77	0.45	43.75
20	M20X2.5	12.85	12.35	9.91	9.41	27.0	0.77	0.45	43.75
24	M24X3	15.37	14.87	11.83	11.33	32.4	0.77	0.45	43.75
30	M30X3.5	19.15	18.65	14.86	14.36	41.4	0.77	0.45	43.75

TABLE II. Length range tolerance.

Nominal bolt size range	M6X1 thru M8X1.25	M10X1.5 thru M16X2	M20X2.5 and M24X3	M30X3.5
Nominal bolt length	Length range tolerance, mm			
Up to 10 mm, incl	-0.6	-0.6	--	--
Over 10 to 18 mm, incl	-0.7	-0.7	--	--
Over 18 to 30 mm, incl	-0.8	-0.8	-1.3	--
Over 30 to 50 mm, incl	-1.0	-1.6	-2.5	-3.0
Over 50 to 80 mm, incl	-1.2	-1.9	-3.0	-3.5
Over 80 to 120 mm, incl	-1.4	-2.2	-3.5	-4.0
Over 120 to 180 mm, incl	-2.5	-2.5	-4.0	-4.5
Over 180 to 240 mm, incl	-4.6	-4.6	-4.6	-6.0
Over 240 mm	-6.0	-6.0	-6.0	-6.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

TABLE III. Fillet dimensions.

Nominal bolt dia thread pitch	Fillet transition diameter		Fillet length		Fillet radius
	For short bolts	For short and long bolts	For long bolts	For short bolts	For short and long bolts
	Min	Max	Max	Max	Min
M6X1	6.2	6.8	1.1	0.7	0.3
M8X1.25	8.3	9.0	1.2	0.8	0.4
M10X1.5	10.2	11.0	1.2	0.9	0.4
M12X1.75	12.2	13.0	1.2	1.0	0.4
M14X2	14.1	15.0	1.2	1.1	0.4
M16X2	16.5	17.0	1.2	1.1	0.4
M20X2.5	20.7	21.0	1.2	1.2	0.4
M24X3	24.5	25.4	1.4	1.4	0.4
M30X3.5	30.7	31.4	1.6	1.6	0.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

TABLE IV. Thread lengths.

Nom bolt dia thread size	L_T			U					Y
	Full form thread length (ref)			Unthreaded length under head					Transition thread length (ref)
	Basic								
	For bolt lengths			For bolt lengths	Max	For bolt lengths		Max	
	To 125 incl	Over 125 to 200 incl	Over 200	To and incl		Over	To and incl		Max
M6X1	18.0	24.0	37.0	12	1.50	12	25	2.50	5.0
M8X1.25	22.0	28.0	41.0	16	1.88	16	30	3.12	6.2
M10X1.5	26.0	32.0	45.0	20	2.25	20	35	3.75	7.5
M12X1.75	30.0	36.0	49.0	24	2.62	24	40	4.38	8.8
M14X2	34.0	40.0	53.0	28	3.00	28	45	5.00	10.0
M16X2	38.0	44.0	57.0	32	3.00	32	50	5.00	10.0
M20X2.5	46.0	52.0	65.0	40	3.75	40	60	6.25	12.5
M24X3	54.0	60.0	73.0	--	--	--	75	7.50	15.0
M30X3.5	66.0	72.0	85.0	--	--	--	90	8.75	17.5

TABLE V. Point diameter and length.

Nom bolt dia thread size	X	Z	
	Point diameter	Point length	
	Approx	Max	Min
M6X1	4.5	1.50	0.50
M8X1.25	6.1	1.88	0.62
M10X1.5	7.7	2.25	0.75
M12X1.75	9.4	2.62	0.88
M14X2	11.0	3.00	1.00
M16X2	13.0	3.00	1.00
M20X2.5	16.2	3.75	1.25
M24X3	19.5	4.50	1.50
M30X3.5	24.7	5.25	1.75

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

TABLE VI. Maximum grip gaging lengths and minimum body lengths.

Dash no	L	Nom bolt dia									
		M6X1		M8X1.25		M10X1.5		M12X1.75		M14X2	
	Nom length	L_G Max	L_B Min	L_G Max	L_B Min	L_G Max	L_B Min	L_G Max	L_B Min	L_G Max	L_B Min
1	8										
2	10										
3	12										
4	14										
5	16										
6	20										
7	25										
8	30	12.0	7.0								
9	35	17.0	12.0	13.0	6.8						
10	40	17.0	12.0	13.0	6.8	14.0	6.5				
11	45	27.0	22.0	23.0	16.8	19.0	11.5	15.0	6.2		
12	50	27.0	22.0	23.0	16.8	19.0	11.5	15.0	6.2	16.0	6.0
13	55	37.0	32.0	33.0	26.8	29.0	21.5	25.0	16.2	21.0	11.0
14	60	37.0	32.0	33.0	26.8	29.0	21.5	25.0	16.2	21.0	11.0
15	65			43.0	36.8	39.0	31.5	35.0	26.2	31.0	21.0
16	70			43.0	36.8	39.0	31.5	35.0	26.2	31.0	21.0
17	75			53.0	46.8	49.0	41.5	45.0	36.2	41.0	31.0
18	80			53.0	46.8	49.0	41.5	45.0	36.2	41.0	31.0
19	85					59.0	51.5	55.0	46.2	51.0	41.0
20	90					59.0	51.5	55.0	46.2	51.0	41.0
21	100					74.0	66.5	70.0	61.2	66.0	56.0
22	110							80.0	71.2	76.0	66.0
23	120							90.0	81.2	86.0	76.0
24	130									90.0	80.0
25	140									100.0	90.0
26	150										
27	160										
28	170										
29	180										
30	190										
31	200										
32	220										
33	240										
34	260										
35	280										
36	300										

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

TABLE VI. Maximum grip gaging lengths and minimum body lengths. - Continued


Dash no	L	Nom bolt dia							
		M16X2		M20X2.5		M24X3		M30X3.5	
	Nom length	L_G Max	L_B Min	L_G Max	L_B Min	L_G Max	L_B Min	L_G Max	L_B Min
1	8								
2	10								
3	12								
4	14								
5	16								
6	20								
7	25								
8	30								
9	35								
10	40								
11	45								
12	50								
13	55	17.0	7.0						
14	60	17.0	7.0						
15	65	27.0	17.0	19.0	6.5				
16	70	27.0	17.0	19.0	6.5				
17	75	37.0	27.0	29.0	16.5				
18	80	37.0	27.0	29.0	16.5	26.0	11.0		
19	85	47.0	37.0	39.0	26.5	31.0	16.0		
20	90	47.0	37.0	39.0	26.5	36.0	21.0		
21	100	62.0	52.0	54.0	41.5	46.0	31.0	34.0	16.5
22	110	72.0	62.0	64.0	51.5	56.0	41.0	44.0	26.5
23	120	82.0	72.0	74.0	61.5	66.0	51.0	54.0	36.5
24	130	86.0	76.0	78.0	65.5	70.0	55.0	58.0	40.5
25	140	96.0	86.0	88.0	75.5	80.0	65.0	68.0	50.5
26	150	106.0	96.0	98.0	85.5	90.0	75.0	78.0	60.5
27	160	116.0	106.0	108.0	95.5	100.0	85.0	88.0	70.5
28	170			118.0	105.5	110.0	95.0	98.0	80.5
29	180			128.0	115.5	120.0	105.0	108.0	90.5
30	190			138.0	125.5	130.0	115.0	118.0	100.5
31	200			148.0	135.5	140.0	125.0	128.0	110.5
32	220					147.0	132.0	135.0	117.5
33	240					167.0	152.0	155.0	137.5
34	260							175.0	157.5
35	280							195.0	177.5
36	300								

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

Requirements:

1. Part number. The part number consists of the letter "D", the basic number of this specification sheet, followed by a dash number from table I. Add "C" for cadmium plating or "P" for phosphate coating followed by a dash number from table VI.

Example:



Custodians:
Army - AR

Review activities:
Army - MI
DLA - IS
NSA - NS

User activities:
Army - AT, GL, ME
Navy - MC, OS, SH

Agent:
DLA - IS

Preparing activity:
Army - AR

(Project 5306-0749)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armement Research and Development Command
ATTN: DRDAR-TST-S
Dover, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last First MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street City State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:23Z
Check the source to verify that this is the current version before use.