MILITARY SPECIFICATION

CARTRIDGE, DUMMY, 5.56mm INERT LOADED, M857

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document establishes the testing and quality assurance provisions for the Cartridge, Dummy, 5.56mm Inert Loaded, M857.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition, General Specification for
MIL-I-45607	-	Inspection Equipment, Aquisition, Maintenance and Disposition of
MIL-A-48078	-	Ammunition, Standard Quality Specifications for

FSC 1305

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

STANDARD

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-636	-	Visual Inspection Standards for Small Arms Ammunition Through Caliber .50
MIL-STD-1168	-	Lot Numbering of Ammunition

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

7643764	-	Classification of Cartridge Case Defects for Small Arms Ammunition
9342871	-	Cartridge, Dummy, 5.56mm, Inert Loaded, M857
9342872	-	Bullet, Dummy, 5.56mm
* 9378276	-	Case

INSPECTION EQUIPMENT

LI-9342871	-	Index of Inspection Equipment Lists for Cartridge, Dummy, 5.56mm, Inert Loaded, M857

PACKAGING & MARKING

10535858	-	Cartons; Box, Ammunition, M2A1; Box, Wirebound

PUBLICATIONS

SCATP-5.56MM (Heavy Bullet)	-	Small Caliber Ammunition Test Procedures for 5.56mm (Heavy Bullet) Cartridges

(Copies of specifications, standards, handbooks, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Cartridge. The cartridge shall comply with all requirements specified on drawing (dwg.) 9342871, all associated drawings and with all requirements specified in applicable specifications and standards.

3.2 Materials. Materials shall be in accordance with the applicable drawings and specifications.

* 3.3 Bullet extraction. The force required to extract the bullet from the cartridge case shall not be less than 125 pounds.

3.4 Residual stress. The cartridge case shall not split when subjected to a 1% (one percent) mercurous nitrate solution for 15 minutes.

3.5 Waterproofness. The cartridge shall not release more than one bubble of air when subjected to a positive internal pressure of 7.5 pounds per square inch (psi) for 30 seconds.

3.6 Workmanship. The requirements for workmanship shall be as specified on applicable drawings, referenced specifications and in accordance with the following:

a. Metal defects. The cartridge shall be free of metal defects which include, but is not limited to: folds, wrinkles, scratches, scaly metals, dents, perforations, and other discontinuities.

b. Foreign matter. The cartridge shall be free of corrosion, stains, discolorations, dirt, and smears of lacquer.

c. Cleaning. Cleaning methods used shall not be injurious to any part, nor shall the part be contaminated by any cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsbility for inspection. In accordance with MIL-A-48078.

4.1.1 Inspection equipment. In accordance with MIL-A-48078 and MIL-A-2550.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. Quality conformance inspection shall apply.

4.3 Quality conformance inspection.

4.3.1 Lot formation. Lot formation shall be in accordance with MIL-A-48078.

4.3.2 Lot submission. The lot shall be submitted in accordance with MIL-STD-105.

4.3.3 Component parts. Unless otherwise specified, component lots shall be homogeneous and of a size convenient to the contractor and inspected, tested and accepted by the contractor. The cartridge lot shall not contain:

a. Cartridge cases from more than one manufacturer.

b. Bullets from more than one interfix number from one manufacturer.

4.3.4 Lot identification. Each lot of ammunition shall be identified as to type, caliber and model, as well as a lot number in accordance with MIL-STD-1168.

4.3.5 Examination for defects.

a. Major and minor defects. Examination for major and minor defects shall be performed on a class basis in accordance with classification of defects using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptable quality-level (AQL) for the major class shall be 0.25 percent and the AQL for the minor class shall be 1.50 percent. All non-conforming cartridges shall be rejected.

b. Critical defects. Unless otherwise specified, one hundred percent examination shall be performed for all critical defects. If a visual critical defect is found in a test sample the lot shall be rejected. The lot shall then be rescreened and resubmitted for visual inspection of critical defects. If a critical defect is found during packing, the portion of the lot that has been packed or is in the process of being packed shall be rejected. In addition, the portion of the lot remaining to be packed shall be rejected. The lot shall then be rescreened and resubmitted for visual inspection of critical defects.

c. Inspections shall be as stated in paragraph 4.3.6.

4.3.6 Inspections to be performed. Quality conformance inspections and testing shall be as stated in the following paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70468A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9342872
4.3.6.1	Bullet, Dummy, 5.56mm				NEXT HIGHER ASSEMBLY 9342871
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101.	Missing cannelure (2 places)		.25%	3.1	Visual
MINOR:					
201.	Evidence of poor workmanship		1.50%	3.6	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: DoD Assist Document Downloaded: 2026-10-25 10:38 MDT
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70468A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9342871
4.3.6.2	Cartridge, Dummy, 5.56mm Inert Loaded: M857				NEXT HIGHER ASSEMBLY NA
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:					
1.	Primer present		100%	3.1	Visual
2.	Presence of vent hole		100%	3.1	Visual
MAJOR:	(Group AQL=0.25%)				
101.	Perforated case (6) b/			3.1	Visual
102.	Case split in K, L, or M location (7)			3.1	Visual
103.	Weight below min.			3.1	Balance
104.	Length			3.1	Gage
105.	Case split in I, S, or J location (6)			3.1	Visual
106.	Corrosion or stain with etching (2)			3.1	Visual
107.	Chamfer missing on head (rim)			3.1	Visual
108.	Case mouth not crimped in canneture (11)			3.1	Visual
109.	Cartridge profile failure (requiring more than 10 pounds weight to insert in profile and alignment gage)			3.1	Visual

NOTES: a/ Samples shall be from the Bullet Extraction Test.
b/ Numbers after defect descriptions refer to visual defects standards in MIL-STD-636 (NATO Caliber 7.62mm section).

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.6.2	Cartridge, Dummy, 5.56mm Inert Loaded: M857	2 OF 2	9342871
			NEXT HIGHER ASSEMBLY: NA

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
110.	Scratch (8)			3.1	Visual
111.	Split bullet jacket (24)			3.1	Visual
112.	Loose bullet (25)			3.1	Visual
113.	Scaly metal (12)			3.1	Visual
114.	Absence of black oxide (color)			3.1	Visual
115.	Diameter of extractor groove, max			3.1	Gage
116.	Diameter of head			3.1	Gage
117.	Thickness of head			3.1	Gage
118.	Length to shoulder datum			3.1	Gage
MINOR:	(Group AQL=1.50%)				
201.	Discolored, dirty, oily, or smeared (1)			3.1	Visual
202.	Case dented (5)			3.1	Visual
203.	Fold, wrinkle, buckle, or bulge in case (14, 15, 16, 17)			3.1	Visual
204.	Head stamp missing or illegible (18)			3.1	Visual
205.	Defective head (19)			3.1	Visual
206.	Defective mouth			3.1	Visual
207.	Bullet dented (22)			3.1	Visual
208.	Bullet scratched (23)			3.1	Visual
209.	Defective crimp			3.1	Visual
210.	Diameter of extractor groove, min			3.1	Gage

NOTES:

Source: http://assist.dla.mil - Downloaded: 2026-10-23T05:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.3.6.3	Cartridge, Dummy, 5.56mm Inert Loaded: M857 Testing		1 1		9342871
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
TEST NO.					
1.	Bullet extraction	25 75	0-2 1-2	3.3	
2.	Residual stress	50 150	0-2 1-2	3.4	
3.	Waterproofness	50 150	3-10 9-10	3.5	
4.	Inert charge	25a/	0-1	3.1	

NOTES: a/ The contents of each cartridge case obtained from the bullet extraction test shall be emptied and examined. The presence of propellant, in lieu of inert mixture, in any cartridge case shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.3.7 Inspection equipment. The inspections and tests specified in paragraph 4.3.6 shall be made using the equipment prescribed in Equipment List on LI-9342871. Unless otherwise specified, acquisition, maintenance, and disposition of inspection equipment shall be in accordance with MIL-I-45067.

4.12 Methods of inspection. The tests for bullet extraction, residual stress and waterproofness shall be performed as specified in SCATP-5.56mm (Heavy Bullet).

5. PACKAGING

5.1 Level A (worldwide shipment). The cartridges shall be packed in accordance with drawing 10535858 with the exception of marking.

5.2 Marking. Marking shall be as follows: "Cartridge, Dummy, 5.56mm, Inert Loaded, M857".

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in the Cartridge, Dummy, 5.56mm, Inert Loaded, M857.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See MIL-A-48078. Submit designs as required to Commander, ARDC, ATTN: AMSMC-QAF-I(D), Dover, NJ 07801-5001.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, US Army Armament Research and Development Command (ARRADCOM) and Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issues. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AB17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: *In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (DO NOT STAPLE), and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.*

NOTE: *This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.*

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
USA ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: DRSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-70468A	CARTRIDGE, DUMMY, 5.56MM INERT LOADED, M857

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.