MILITARY SPECIFICATION

DISPENSER TEST ADAPTER ASSEMBLY

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the performance and acceptance inspection requirements for the Dispenser Test Adapter Assembly associated with the M-130 Aircraft General Purpose Dispenser.

2. APPLICABLE DOCUMENTS

2.1 The following documents of issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-810 - Environmental Test Methods
MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts
MIL-STD-1460 - Soldering of Electrical Connections and Printed Wiring Assemblies, Procedures For

FSC: 4925

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9311275 - Dispenser Test Adapter Assembly
9322169 - Packing and Marking for Box, Exterior for Dispenser Test Adapter Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Officer, Washington, D.C. 20402. Orders should specify, "49 CFR 100-199 (latest revision)".)

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. - The components and assemblies shall comply with all requirements specified on drawing 9311275 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Circuit resistance. - The maximum circuit resistance shall be 0.1 ohms between the points in Table 1 when tested in accordance with 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

TABLE 1

FROM	TO	FROM	TO	FROM	TO
E1	J1-A	E17	J1-T	P5-A	P2-P
E2	J1-B	E18	J1-U	P5-A	P3-P
E3	J1-C	E19	J1-V	P5-A	P4-8
E4	J1-D	E20	J1-W	P5-A	J1-t
E5	J1-E	E21	J1-X	P5-A	J1-z
E6	J1-F	E22	J1-Y	P5-B	P1-B
E7	J1-G	E23	J1-Z	P5-B	P2-R
E8	J1-H	E24	J1-a	P5-B	P3-R
E9	J1-J	E25	J1-b	P5-B	P4-9
E10	J1-K	E26	J1-c	P5-B	J1-BB
E11	J1-L	E27	J1-d	P2-F	P3-F
E12	J1-M	E28	J1-e	P3-A	P4-1
E13	J1-N	E29	J1-f	P3-M	P4-5
E14	J1-P	E30	J1-g	P4-6	P4-2
E15	J1-R	P5-A	P1-A	P4-6	J1-CC
E16	J1-S				

Mode Select Switch	FROM	TO
Chaff MAN	J1-y	P3-A
Chaff PGRM	J1-y	P3-B
Flare RIPPLE	J1-y	P3-S
Flare MAN	J1-y	P3-M

3.4 Insulation resistance. - The insulation resistance of each isolated pin to all other pins (See Table 2) electrically connected together shall be 20 megohms minimum when tested in accordance with 4.5.2. (NOTE: Mode Select Switch must be in "CHAFF MAN" position during this test.)

TABLE 2

J1 - A, B, C, D, E, F, G, H, J, K, L, M, N, P, R, S, T, U, V, W, X, Y, Z, a, b, c, d, e, f, g, y, z, BB, CC

P3 - F, B, M, S

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

3.5 Environmental requirements. - The dispenser test adapter assembly shall maintain the circuit resistance and insulation resistance as specified in 3.3 and 3.4 respectively after exposure to the environments specified herein.

3.5.1 Transportation vibration. - The dispenser test adapter assembly shall be subjected to the transportation vibration requirements of MIL-STD-810, Method 514.2, Procedure X. The dispenser test adapter assembly shall be vibrated along three mutually perpendicular axes.

3.5.2 Temperature and humidity. - The dispenser test adapter assembly shall perform all functions satisfactorily after being subjected to Test 105 of MIL-STD-331. Two fourteen day cycles shall be completed for a total test period of 28 days.

3.6 Wiring and soldering. - Soldering of electrical wires, cables, connectors, components and assemblies shall be performed in a thorough, workmanlike manner in accordance with MIL-STD-1460.

3.7 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner, and all manufacturing, processing and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Dispenser Test Adapter Assembly	9311275	2

4.3.2 Inspections to be performed. - See MIL-A-48078 and paragraphs 4.4.2.1 through 4.4.2.8, testing per paragraph 4.4.3, and Table I specified herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
	Dispenser Test Adapter Assembly		1	1	9311275
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Examination for Defects		100%	3.2	4.4.2.8
	Circuit Resistance		100%	3.3	4.4.3.1
	Insulation Resistance		100%	3.4	4.4.3.2
	Transportation Vibration		100%	3.5.1	4.4.3.3
	Examination for Defects		100%	3.2	4.4.2.8
	Temperature & Humidity Cycling		100%	3.5.2	4.4.3.4
	Examination for Defects		100%	3.2	4.4.2.8
	Circuit Resistance		100%	3.3	4.4.3.1
	Insulation Resistance		100%	3.4	4.4.3.2

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - (See MIL-A-48078). - Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cover	1 OF 1	9311294
			NEXT HIGHER ASSEMBLY 9311275

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length and width		0.40%	3.2	Gage
102	Dimensions of lower left corner notch		0.40%	3.2	Gage
103	Size and location of stud nut holes (.312 dia ref., 2 holes)		0.40%	3.2	Gage
Minor					
201	Protective finish missing or inadequate		0.65%	3.2	Visual
202	Markings missing, illegible or incorrect		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Base Plate Assembly	1 OF 1	9311278
			NEXT HIGHER ASSEMBLY 9311277

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length and width		0.40%	3.2	Gage
102	Dimensions of lower left corner notch		0.40%	3.2	Gage
103	Location of terminal holes		0.40%	3.2	Gage
104	Dimensions of terminal holes		0.40%	3.2	Gage
105	Location of stud nut holes		0.40%	3.2	Gage
Minor					
201	Protective finish missing or inadequate		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Base Plate Assembly		9311277
			NEXT HIGHER ASSEMBLY 9311275

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Terminals - 30		0.40%	3.2	Visual
102	Height of screws, self-locking - 4		0.40%	3.2	Gage/Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cable Assembly (Prior to Final Assembly)	1 OF 1	9311295
			NEXT HIGHER ASSEMBLY 9311275

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Soldering improper or inadequate		0.40%	3.2	4.4.3.5/Visual
102	Insulation improper or inadequate		0.40%	3.2	Visual
Minor					
201	Marking missing, illegible or		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Dispenser Test Adapter Assembly	1 OF 1	9311275
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Soldering improper or inadequate		0.40%	3.2	4.4.3.5/Visual
102	Identification plate missing or incorrectly annotated		0.40%	3.2	Gage
103	Any component missing, damaged or improperly assembled		0.40%	3.2	Visual
104	Circuit resistance test		100%	3.3	4.4.3.1
105	Insulation resistance test		100%	3.4	4.4.3.2
Minor					
201	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63147(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Packing and Marking for Box, Exterior for Dispenser Test Adapter Assembly	1 OF 1	9322169
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Barrier bag punctured or inadequately sealed		0.40%	5.0	Visual
Minor					
201	Contents loose		0.65%	5.0	Manual
202	Marking missing, illegible or incorrect		0.65%	5.0	Visual
203	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Circuit resistance. - Major Defect - Each dispenser test adapter assembly shall be subjected to this test. The test shall be performed as specified in 4.5.1 using equipment in accordance with 4.4.4. If any unit fails to comply with the applicable requirements, it shall be classified defective and removed from the lot.

4.4.3.2 Insulation resistance. - Major Defect - Each dispenser test adapter assembly shall be subjected to this test. The test shall be performed as specified in 4.5.2 using equipment in accordance with 4.4.4. If any unit fails to comply with the applicable requirements, it shall be classified defective and removed from the lot.

4.4.3.3 Transportation vibration. - Major Defect - Each dispenser test adapter assembly submitted for first article testing shall be subjected to this test. The test shall be performed as specified in 4.5.3 using equipment in accordance with 4.4.4. If any unit fails to comply with the applicable requirements, the first article sample shall be rejected.

4.4.3.4 Temperature and humidity. - Major Defect - Each dispenser test adapter assembly submitted for first article testing shall be subjected to this test. The test shall be performed as specified in 4.5.4 using equipment in accordance with 4.4.4. If any unit fails to comply with the applicable requirements, the first article sample shall be rejected.

4.4.3.5 Improper soldering. - Major Defect - Each dispenser assembly shall be inspected for improper soldering in accordance with 3.5. If any wiring or printed circuit card assembly fails to comply with the requirements of 3.5, the unit shall be classified defective and removed from the lot.

4.4.4 Inspection equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/ Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and Section 6.3 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

4.5 Test methods and procedures

4.5.1 Circuit resistance. - Electrical measurements of the dispenser test adapter assembly shall be performed in accordance with Method 302 of MIL-STD-202.

4.5.2 Insulation resistance. - Electrical measurements of the dispenser test adapter assembly shall be performed in accordance with Method 302, Test Condition B of MIL-STD-202.

4.5.3 Transportation vibration. - Using equipment in accordance with 4.4.4, subject each first article unit to the vibration requirements of MIL-STD-810, Method 514.2, Procedure X to verify conformance to 3.5.1. Following this test, inspect each dispenser test adapter assembly for evidence of damage. Any dispenser which fails to comply to the applicable requirements shall be rejected.

4.5.4 Temperature and humidity. - Using equipment in accordance with 4.4.4, subject each first article unit to Test 105 of MIL-STD-331 to verify conformance to 3.5.2. Following this 28 day test, lower the chamber temperature to 130°F minimum and allow to stabilize for a minimum of four hours. Subject the dispenser test adapter assemblies to the circuit resistance test, 4.4.3.1, and the insulation resistance test, 4.4.3.2, at 130°F. If the test cannot be conducted in the chamber, the test shall be completed within 30 minutes maximum after removal from the chamber. Following this test, place the units in a chamber at -60°F for a minimum of four hours and repeat the circuit resistance and insulation resistance tests. Any item which fails to meet applicable requirements shall cause the First Article Sample to be rejected.

5. PREPARATION FOR DELIVERY

5.1 Packing. - The assemblies shall be packed as specified on Dwg. 9322169.

5.2 Marking. - Marking of the box shall be in accordance with Dwg. 9322169.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

6.1 Intended use. - This dispenser assembly is used in testing the Aircraft General Purpose Dispenser, M-130.

6.2 Ordering data. - Procurement documents shall specify the following:

a. Title, number and data of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - (See MIL-A-48078) Submit equipment designs as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-Q, Dover, New Jersey 07801.

6.5 Drawings. - Drawings listed in Section 2 of this specification under the heading US Army Armament Reserach and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data origianlly prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 4925-A-128

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.