INCH-POUND


MIL-PRF-49142/15A
23 August 2023
SUPERSEDING
MIL-PRF-49142/15
4 December 2019

PERFORMANCE SPECIFICATION SHEET

CONNECTOR, JACK, ELECTRICAL, TRIAXIAL, MIL-STD-1553 DATABUS,
(SERIES TRL, GENDER CHANGEABLE CONTACT , CLASS 2)

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of
this specification sheet and MIL-PRF-49142.






NOTES:
1. Dimensions are in inches.
2. Undimensioned pictorial representations for reference only.
3. Variable configurations based on the intended use (e.g., panel mount, in-line, etc.)

FIGURE 1. General configuration.


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.




ALTERNATE DESIGN

| LTR | Inches | |
|---|---|---|
| | Min | Max |
| A | .239 | .241 |
| B | .210 | .220 |
| C | .010 | -- |
| D | -- | .036 |
| E | .421 | -- |
| F | .303 | .307 |

NOTES:
1. Dimensions are in inches.
2. See Figure 3 and Figure 4 for signal contact polarity options.

FIGURE 2. TRL jack interface dimensions.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: Non-constant.

Signal range: Databus: MIL-STD-1553 databus frequency range.
RF Signaling: as required by the applicable system requirements.

Voltage rating:

At sea level: 400 V rms maximum working voltage.

At 70,000 feet (4.437 kPa): 100 V rms maximum working voltage.

Operating temperature -65°C to +125°C.

Storage temperature: -65°C to +125°C.

REQUIREMENTS:

Dimensions and configuration: See Figure 1 and Figure 2. Mating connector in accordance with MIL-PRF-49142/16.

Materials:

Insulators: PTFE fluorocarbon in accordance with ASTM D4894 or D4895, or POM in accordance with ASTM D6778.

Alternate insulators: ETFE per ASTM D3159 or PES that meet the requirements and pass the tests in Table I.

Key material properties of Polyethersulfone (PES):

Table I.

| Characteristics | Typical Value | ASTM Test Method |
|---|---|---|
| Specific Gravity | 1.37 | D792 |
| Water Absorption, 24hrs @ 23 °C | 0.54 % | D570 |
| Tensile Strength | 12000 psi (83 MPa) | D638 |
| Tensile Elongation | 30 % | D638 |
| Tensile Modulus | 0.39 x 106 psi (2689 MPa) | D638 |
| Dielectric Strength | 380 V/mil (15.0 KV/mm) | D149 |
| Deflection Temperature @ 264 psi (1820 KPa) | 398 °F (203 °C) | D648 |

Connector bodies: Brass in accordance with ASTM B16/B16M, ASTM B36/B36M or ASTM B121/B121M. Or copper beryllium in accordance with ASTM B194, ASTM B196/B196M or ASTM B197/B197M

All other components: In accordance with MIL-PRF-49142.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

Force to engage and disengage:


Longitudinal force: Not applicable.

Torque: 2.5-inch pounds (.28 Nm) maximum.

Coupling proof torque: 10 inch-pounds (1.13 Nm) minimum.

Mating characteristics: See Figure 2, Figure 3 and Figure 4 for dimensions and force testing.

Signal Contact, Pin:




| LTR | Inches | |
|---|---|---|
| | Min | Max |
| B | .072 | .074 |
| E | .040 | .061 |

FIGURE 3. Pin Interface dimensions.

Center contact (socket):

Steel test pin finish: 16 micorinches.
Insertion depth: .050 inches minimum.
Oversize test pin: .025 inches diameter minimum.
Number of insertions: 1.

Insertion force test:


Steel test pin diameter: .0245 inches minimum.
Insertion force: 1 pounds (4.45 N) maximum.

Withdraw force test:

Steel test pin diameter: .0235 inches maximum.
Withdrawal force: 0.5 ounces (.14 N) minimum.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

Signal Contact, Socket:




| LTR | Inches | |
|---|---|---|
| | Min | Max |
| G | .007 | .039 |
| K | .023 | .025 |
| R | - | .107 |

Note 1: Set to meet the engagement and separation force.

FIGURE 4. Socket Interface dimensions.

Intermediate contact (socket):

Steel test pin finish: 16 microinches.
Insertion depth: .125 inches minimum.
Oversize test pin: .075 inches diameter minimum.

Number of insertions: 1.

Insertion force test:

Steel test pin diameter: .074 inches minimum.
Insertion force: 1.25 pounds (5.56 N) maximum.

Withdraw force test:

Steel test pin diameter: .072 inches maximum.
Withdrawal force: 2.0 ounces (.56 N) minimum.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

Permeability: Applicable.

Hermetic seal: Not applicable.

Leakage: Not applicable.

Insulation resistance:

Center conductor to intermediate conductor: 5,000 megohms minimum.

Intermediate conductor to outer conductor: 5,000 megohms minimum.

Conductor retention:

Center conductor retention: 2 pounds (8.90 N) minimum axial force.

Intermediate conductor retention: 6 pounds (26.69 N) minimum axial force.

Dielectric withstanding voltage at sea level:

Center conductor to intermediate conductor: 900 V rms minimum.

Intermediate conductor to outer conductor: 900 V rms minimum.

Salt spray (corrosion): Applicable.

Vibration: Applicable.

Shock: Applicable.

Thermal shock: Applicable.

Moisture resistance: Applicable.

Conductor resistance: In milliohms, maximum.

| | Initial | After environment |
|---|---|---|
| Center conductor: | 6.0 | 8.0 |
| Intermediate conductor | 3.0 | 5.0 |
| Outer conductor (nickel plated) | 5.0 | 8.0 |

Corona level: Not applicable

RF high potential withstanding voltage: Not applicable



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

Cable retention force (for cable outside diameter):

.154 inch (3.93 mm) and smaller: Not applicable

.155 - .189 inch (3.94 – 4.82 mm): 10 pounds (44.48 N) minimum.

.190 - .229 inch (4.83 – 5.83 mm): 20 pounds (88.96 N) minimum.

.230 - .249 inch (5.84 – 6.34 mm): 30 pounds (133.45 N) minimum.

.250 inch (6.35 mm) and larger: 40 pounds (177.93 N) minimum.

Coupling mechanism retention force: 100 pounds (444.82 N) minimum.

Rise time degradation:

Twin conductor cable: 100ns when tested in accordance with MIL-STD-1553 paragraph 4.5.2.1.1.2.

Triaxial cable: Applicable.

NOTE: Triaxial cable approved for use in RF applications.

Connector durability: 500 cycles minimum at 12 cycles per minute maximum.

RF leakage: Not applicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

Part identifying number (PIN): M49142/15- X - X X - XX - X

Body material finish from Table 2

Configuration from Table 3

Gender from Figure 3 or 4 (P=Pin, S=Socket)

Dash number from Table 4

Termination Type from Table 5

Table 2. Body material finish and finish.

| Part identifying number (PIN): M49142/15- A-XX-XX-X | |
|---|---|
| 0 | silver plated brass |
| 3 | passivated corrosion resistant steel |
| 4 | tin plated brass |
| 5 | tin/nickel plated beryllium copper |
| 6 | tin plated beryllium copper |
| 7 | nickel plated brass |
| | |
| | |

Table 3. Configuration.

| Part identifying number (PIN): M49142/15- X-AX-XX-X | |
|---|---|
| 1 | In-line Cable |
| | |

Table 4. Dash Number.

| Part identifying number (PIN): M49142/15- X-XX-AA-X | |
|---|---|
| 00 | Not applicable |
| 01 | M17/176-00001 |
| 02 | 10602 or 10612 Raychem |
| 03 | TWC-78 Trompeter |
| 04 | 10613 Raychem |
| 05 | 10614 Raychem |
| 99 | Per contract |
| | |

Table 5. Termination Type.

| Part identifying number (PIN): M49142/15- X-XX-XX-A | |
|---|---|
| C | Crimping |
| S | Pre-installed Soldering |
| | |

NOTE: Components for Type C and Type S are intermateable but not interchangeable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-PRF-49142, this document references the following:

| | | |
|---|---|---|
| MIL-PRF-49142/16 | ASTM B121/B121M | ASTM D4894 |
| MIL-STD-1553 | ASTM B194 | ASTM D4895 |
| M17/176 | ASTM B196/B196M | ASTM D6778 |
| ASTM B16/B16M | ASTM B197/B197M | ASTM D3159 |
| ASTM B36/B36M | | |

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2023-048)

Review activities:
Army - AR, AT
Navy - AS, MC, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:52Z
Check the source to verify that this is the current version before use.