INCH-POUND

MIL-PRF-49450/5B(CR)
9 October 1997
SUPERSEDING
MIL-B-49450/5A (ER)
8 November 1994

PERFORMANCE SPECIFICATION SHEET

BATTERY, RECHARGEABLE, NICKEL-CADMIUM, VENTED, AIRCRAFT, BB-716/A, HARNESS ASSEMBLY

This specification is approved for use by the USACECOM, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-PRF-49450 in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.




FIGURE 1. Harness configuration (method 1).

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.




FIGURE 2. Harness configuration (method 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.

TABLE I. Reference wire listing for figure 1.

REF LTR	WIRE DESCRIPTION
A	WIRE, BLUE TO PIN C, 18 INCHES LONG
B	WIRE, GREEN TO PIN H, 16.5 INCHES LONG
C	WIRE, WHITE, 2.5 INCHES LONG
D	WIRE, WHITE TO PIN E, 14 INCHES LONG
E	WIRE, WHITE TO PIN F, 12 INCHES LONG
F	WIRE, YELLOW TO PIN A, 10 INCHES LONG
G	WIRE, YELLOW TO PIN B, 10 INCHES LONG
H	WIRE, ORANGE TO PIN K, 10 INCHES LONG
I	WIRE, ORANGE TO PIN J, 10 INCHES LONG
J	WIRE, RED TO PIN G, 6 INCHES LONG
K	WIRE, BLACK TO PIN D, 6 INCHES LONG

TABLE II. Reference wire listing for figure 2.

REF LTR	WIRE DESCRIPTION
A	WIRE, BLUE TO PIN C, 16.0 ± .50 INCHES LONG FROM L TO O
B	WIRE, GREEN TO PIN H, 15.3 ± .50 INCHES LONG FROM L TO P
C	WIRE, WHITE AS REQUIRED
D	WIRE, WHITE TO PIN E, 14.38 ± .5 INCHES LONG FROM L TO Q
E	WIRE, WHITE TO PIN F, 14.38 ± .50 INCHES LONG FROM L TO Q
F	WIRE, YELLOW TO PIN A, 9.12 ± .50 INCHES LONG FROM L TO N
G	WIRE, YELL TO PIN B, 9.12 ± .50 INCHES LONG FROM L TO N
H	WIRE, ORANGE TO PIN K, 9.12 ± .50 INCHES LONG FROM L TO N
I	WIRE, ORANGE TO PIN J, 9.12 ± .50 INCHES LONG FROM L TO N
J	WIRE, RED TO PIN G, 6.50 ± .50 INCHES LONG FROM L TO M
K	WIRE, BLACK TO PIN D, 6.50 ± .50 INCHES LONG FROM L TO M

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.




FIGURE 3. M4950/5-1 thermoswitch assembly.




FIGURE 4. M49450/5-3 thermistor assembly (method 1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.




FIGURE 5. M49450/5-3 Thermistor assembly with sensor plate (method 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.




FIGURE 6. Thermistor or temperature device resistance - temperature characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.

DRAWING NOTES:

1. All dimensions are in inches, unless otherwise specified.

2. Strap shape is optional.

REQUIREMENTS:

1. The harness assembly shall use insulated wires resistant to the battery electrolyte. The length and color of wires shall be in accordance with Figure 1 and Table 1 or Figure 2 and Table 2.

2. All electrical connections made to the MS3474-L12-10PN receptacle and harness devices (thermistors, thermoswitches or equal) shall be potted with a compound that will not support flame, absorb moisture, or be damaged by battery electrolyte. Thermoswitch shall be modified to achieve maximum height of Figure 3.

3. The thermistor or temperature sensor device shall exhibit the resistance temperature characteristics of Figure 6.

4. The harness assembly shall be capable of withstanding the temperature and exposure of the battery electrolyte without damage.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian
Army-CR

Preparing Activity:
Army-CR
(Project 6140-A833)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.