INCH-POUND
MIL-PRF-49471/13A(CR)
AMENDMENT 3
25 April 2002
SUPERSEDING
AMENDMENT 2
14 May 2001

PERFORMANCE SPECIFICATION SHEET

BATTERY, NON-RECHARGEABLE, LITHIUM MANGANESE DIOXIDE,
HIGH PERFORMANCE, BA-5368/U

This amendment forms a part of MIL-PRF-49471/13A(CR), dated 30 November 2000, and is approved for use within the Communications-Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under “REQUIREMENTS”, add: Cell series string short circuit protection: Applicable.

Under “Charge Protection”: Delete “Applicable” and substitute “Not Applicable”

Under “Capacity test” after “LR1, 48”, add: “(to 8 volts)”

PAGE 3

Under “Discharge, Cells”, delete “50 milliamperes” and substitute “40 milliamperes” (2 places).

Under “Discharge, Batteries”, Delete “50 milliamperes” and substitute “40 milliamperes”. For the LR1 test, delete “20 milliamperes” and substitute “15 milliamperes”.

Under “Discharge, Forced Discharge”, delete “50 milliamperes” and substitute “40 milliamperes”.

Under “Discharge, Abuse test predischarge”, delete “50 milliamperes” and substitute “40 milliamperes”.

Closed circuit voltage (battery and cell strings), delete “within 5 seconds” and substitute “after 10 seconds on load”.

Cell closed circuit voltage, delete “in 5 seconds or less” and substitute “in 10 seconds or less”.

Custodian:
Army - CR

Preparing activity:
Army - CR
(Project 6135-0425-12)

AMSC N/A

FSC 6135
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:12Z
Check the source to verify that this is the current version before use.