INCH POUND

MIL-DTL-32188 (OS)
16 September 2005

DETAIL SPECIFICATION
INITIATOR, MECHANICAL ACTUATED JAU-25/A

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. The Initiator, Mechanical Actuated, JAU-25/A was designed to initiate a Shielded Mild Detonating Cord (SMDC) for initiating canopy jettison used in the F-18/TF-18 aircraft aircrew escape system.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices
MIL-I-8500	Interchangeability and Replaceability of Component Parts for Aerospace Vehicles
MIL-L-757	Lead Styphnate, Normal
MIL-L-3055	Lead Azide
MIL-P-20444	Primer, Percussion, M42 parts for and Loading, Assembling and Packing

Comments, suggestions, or questions on this document should be addressed to Commander, Indian Head Division, Naval Surface Warfare Center, Technical Information Branch (Code 4230), 101 Strauss Avenue, Indian Head, Maryland 20640-5035, or emailed to amanda.penn@navy.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-464 Electromagnetic Environmental Effects Requirements For Systems

(Copies of these documents are available online at http://assist.daps.dla.mil/ or from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia PA 19111- 5094.)

2.2.2 Other Government documents, drawings, and publications. (This section is not applicable to this document.)

2.3 Non-Government publications and drawings. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E1742 Standard Practice for Radiographic Examination

(Copies of this document are available online at http://www.astm.org/ or from the American Society for Testing and Materials Customer Service, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE AS5604 Compass: Magnetic, Pilot’s Standby

(Copies of this document are available online at http://www.sae.org/, or from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, Pennsylvania, United States, 15096-001.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, superseded applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article sample. When more than 12 months have elapsed since production of the latest accepted lot, a first article sample of 60 initiators that have met the requirements of 3.2 through 3.5 shall be required. The sample shall be tested as specified in paragraph 4.3.

3.2 Design and construction. The JAU-25/A initiator design and construction shall be identical to that subjected to qualification testing and approved for service use.

3.3 Envelope and installation. The dimensions and configuration of the JAU-25/A initiator shall be as shown on NAVAIR drawing 850AS130. All parts having the same vendor's item number shall be functionally and dimensionally interchangeable in accordance with MIL-I-8500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

3.4 Explosive train assembly. The explosive train assembly shall consist of the following:

OEA P/N 2912103-1: M42C1-979 (PA101) percussion primer, lead styphnate per MIL-L-757, lead azide per MIL-L-3055 and hexanitrostilbene (HNS) type II, grade “A” per NAVAIR drawing 850AS130.

SCOT P/N 6028110-01: M42C1-979 (PA101) percussion primer, lead azide per MIL-I-3055 and HNS type II grade “A” per NAVAIR drawing 850AS130.

Only one lot of explosive shall be used for each explosive train assembly lot manufactured. Only one lot of explosive train assemblies shall be used for each lot of initiators.

3.4.1 Percussion primer. The M42C1-979 (PA101) percussion primer used in the explosive train assembly shall be manufactured and tested in accordance with MIL-P-20444 (primer, percussion - parts for and loading - assembling and packing). The primers shall be loaded into the explosive train assembly within 24 months of new primer acceptance testing or 12 months of primer recertification testing.

3.5 Inspection

3.5.1 Explosive train assembly inspection

3.5.1.1 Visual inspection. All explosive train assemblies manufactured under contract shall be visually inspected and screened for defects as outlined in 4.4.

3.5.1.2 Leakage. Explosive train assemblies shall not exhibit a leak rate in excess of 1×10^{-5} cubic centimeters per second of air when tested in accordance with 4.5.

3.5.1.3 Radiographic inspection. Explosive train assemblies shall be free of imperfections when examined radiographically in accordance with 4.7.

3.5.1.4 Gap test. Prior to assembly of initiators, each lot of explosive train assemblies shall be subjected to ambient temperature testing at a distance four times the maximum production gap in accordance with 4.6

3.5.2 Initiator inspection

3.5.2.1 Visual inspection. All initiators manufactured under contract shall be visually inspected and screened for defects as outlined in 4.4.

3.5.2.2 Radiographic Inspection. Initiators shall be free of imperfections in assembly when examined radiographically in accordance with 4.7.

3.5.2.3 Demagnetization. Initiators shall not deflect an approved pilot’s standby compass more than three degrees in either direction when passed in front of the compass. The initiators shall be tested in accordance with 4.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

3.5.2.4 Electrical bonding resistance. Initiators shall not exhibit an electrical bonding resistance in excess of 0.0025 ohm when tested in accordance with 4.9.

3.6 Ballistic requirements. Initiators from each first article and production lot shall meet the requirements listed below when subjected to the test prescribed in 4.11.

3.6.1 Actuation force. The upper (u) and lower (l) limits for actuation force shall be u = 35 pounds and l = 15 pounds, respectively. See 4.11.1.1.

3.6.2 High order detonation. The minimum plate dent for high order detonation of the output SMDC test tip on the witness plate shall be 0.001 inch. See 4.11.1.2.

3.6.3 Misfire. There shall be no misfires. See 4.11.1.3.

4. VERIFICATION

4.1 Classification of inspections.

a. First article inspection (see 4.3)
b. Lot acceptance inspection (see 4.4 through 4.11)

4.1.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of the inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Samples for ballistic test shall be selected from the production lot in accordance with Table I. Reduced sample size is recommended after 10 consecutive acceptable lots. Sample plan to be used will be normal unless otherwise specified in the contract. Three additional initiators shall be provided with each test sample for investigative purposes. Sample initiators and initiators made available for investigative purposes shall not be applied as part of the quantity specified for delivery by the contract or order. The production lot size shall be 500 maximum initiators.

Table I. Sample sizes for ballistic test.

Lot Size	Normal Sample Size	Reduced Sample Size
2-8	2	2
9-15	3	2
16-25	5	3
26-50	8	5
51-90	13	5
91-150	20	8
151-280	32	13
281-500	50	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

4.3 First article sample. Before entering into quantity production, an acceptable first article sample of 60 initiators shall be prepared using the same procedure and methods proposed for the production lot. Fifty-four of these initiators shall be expended in the tests listed herein and six shall be retained for investigative purposes. A first article sample acceptable for functional and environmental testing shall be defined as a sample which has met the requirements of paragraphs 3.2 through 3.5 of this specification. The contractor shall deliver the initiators to the activity designated by the contracting agency for tests. First article sample inspection shall consist of the following tests: temperature and humidity cycling (18), vibration (6), shock (6), –65 °F ± 5 °F (12), and 200 °F ± 5 °F (12). The numbers in parentheses denote the number of initiators allotted for each test. All tests are done as prescribed in MIL-D-21625 except vibration which is prescribed in 4.9 herein. The initiators shall be fired as described in 4.9 and shall meet the functional requirements referenced in 3.6. Any quantity production prior to notification by the contracting agency of first article sample acceptability shall be at the contractor's risk. The first article initiators will not be applied as part of the quantity specified for delivery by the contract.

4.4 Initiator and explosive train assembly visual inspection. Visually examine all explosive train assemblies prior to initiator assembly and assembled initiators. Reject those with inadequate or illegible descriptive marking or serial numbers, dents, deep scratches, or other defects which may prevent proper assembly installation or function.

4.5 Explosive train assembly leak test. Each explosive train assembly produced under contract shall be leak tested in a dry gas leak tester to determine conformance to 3.5.1.2. Units which exhibit a leak rate in excess of 1×10^{-5} std cc/sec of air at a pressure differential of 1.0 ± 0.1 atmosphere shall be rejected.

4.6 Gap test. Each lot of explosive train assemblies shall be sampled for gap testing as follows. For lots up to 50 test 2 each, for lot sizes of 51 to 90 test 4 each and for lot sizes larger than 91 test 6 each.

4.7 Radiographic inspection. The explosive train assemblies and initiators shall be arranged on trays or boards in consecutive numerical order, and each radiograph shall carry a permanent identification of the explosive train assemblies and initiators displayed thereon. The explosive train assemblies and initiators shall be positioned to give the most revealing cross-section of the explosive train assembly and initiator. All explosive train assemblies and initiators shall be identified with serial numbers prior to radiographic inspection. The radiographic identification shall include the complete lot number for the explosive train assembly and initiator and the span of serial numbers displayed. Discontinuities in serial numbers shall be identified on the radiographic plate. Defective explosive train assemblies and initiators found by the vendor shall be clearly identified on the radiographic plate and shall be removed from the production lot. Radiographs or copies of the entire production lot shall accompany the ballistic sample to the activity conducting the production lot acceptance test. (see 5.1.)

4.7.1 N-ray inspection. Each explosive train assembly shall be n-rayed prior to initiator assembly to confirm the presence of the propellant non-metal parts, no foreign hydrogenous materials and the proper assembly of pyrotechnic/non-metallic materials. Any observable imperfections in assembly shall be cause for rejection.

4.7.2 X-ray inspection. Each explosive train assembly prior to initiator assembly and assembled initiator shall be x-rayed in accordance with ASTM E1742, to confirm the presence and proper assembly of all parts any observable imperfections in assembly shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

4.8 Demagnetization. Each initiator (without the shipping bolt installed) shall be moved past a pilot's standby compass face (per SAE AS5604) by placing the initiator six inches from the compass face, in a north-south horizontal position with the compass set in an east-west heading. The initiator and the compass shall be placed at the same height from the floor. The initiators shall be moved past the compass face in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis, and moved back past the compass face, this procedure shall be repeated for each 90 degrees rotation of the initiator. The initiators shall be acceptable if the requirements of 3.5.2.3 are met.

4.9 Electrical bonding. Each initiator shall be tested using a four point probe milliohmmeter in accordance with MIL-STD-464. The electrical bonding resistance shall be between the .375-24 SMDC port threads and the .875-14 threads on the initiator body. The initiator shall be acceptable if the requirements of 3.5.2.4 are met.

4.10 Vibration test. The initiators shall be mounted in the vibration test fixture NAVAIR drawing 850AS844 and set up shown in figure 1 below. Six initiators shall be mounted on the test fixture at the same time and one shall be monitored for response during the test.




Figure 1. Vibration test fixture set up.

4.10.1 Non-gunfire vibration. The test specimens shall be exposed to the sinusoidal vibration environment shown in Figure 2 and Table II with the frequency varying logarithmically from 5 Hz to 2,000 Hz and returning to 5 HZ in approximately 20 minutes. The specimens will be exposed to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

environment for one hour in each of the three mutually perpendicular axes, at ambient, +200ºF, and -65ºF, for a total of nine hours of testing.

Table II. Sinusoidal vibration environment.

Frequency (hz)	Acceleration/Amplitude
5 to 20	0.10 inch D.A.
20 to 33	± 2 g's peak
33 to 74	0.036inch D.A.
74 to 2000	±10 g's peak




Figure 2. Non gunfire vibration.

4.10.2 Gunfire vibration

4.10.2.1 The gunfire vibration test shall be performed on all six initiators, in each of the three orthogonal axes, and shall be conducted at +70 °F test temperature only, all six initiators shall be mounted on the test fixture at the same time and one shall be monitored for response during the test.

4.10.2.2 Resonance search. A resonance search shall be conducted at +70 °F in each of the three orthogonal axes. The frequency sweep shall be made from 50 hz to 500 hz and back to 50 hz in approximately 7.50 minutes to the vibration test level shown in table III. The resonance points shall be noted. A resonance point is defined as a frequency which has a transmissibility (output/input) of two or greater. If more than three resonant points are noted from the resonance search, only the three more severe will be used for resonance dwell vibration.

4.10.2.3 Resonance dwell. The six initiators shall be vibrated in each of the three orthogonal axes at +70 °F for 7.50 minutes at each resonant point (to a maximum of three) obtained during the resonance

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

search in paragraph 3.8.2.2 herein. The gunfire vibration test levels are shown in table III depending upon the number of Resonance frequencies determined in the resonance search per paragraph 4.8.2.2 herein, the remainder of the sweep time in accordance with table III shall be used for vibration cycling per paragraph 4.8.2.4 herein.

4.10.2.4 Vibration cycling. All six initiators shall be subjected to sinusoidal vibration cycling at +70 °F for a period of time as specified in 4.8.2.3 on each of the three orthogonal axes with the frequency varying logarithmically from 50 hz to 500 hz and back to 50 hz in approximately 7.50 minutes. The gunfire vibration test levels shall be as shown in table III.

Table III. Gunfire vibration test levels.

Frequency (hz)	Acceleration or amplitude
50-54	.036 inch dia.
54-210	± 5 g's
210-300	.00222 inch dia.
300-500	± 10 g's

4.10.2.5 Fixed dwell. After sinusoidal vibration cycling, the initiators shal1 be subjected to a series of fixed dwells as shown in table IV. The fixed narrow band dwells shall be performed by sweeping the frequency about ± 5% of the specified center frequency. For example, the 100 hz dwell should be performed from 95 hz to 105 hz at the logarithmic sweep rate specified in paragraph 4.8.2.4 herein.

Table IV. Gunfire sinusoidal vibration test schedule from 50 hz to 500 hz
(test time in minutes per axis)

Number of Resonances	0	1	2	3
Sweep Time	30.00	22.50	15.00	7.51
Resonance Dwell time	—	7.50	15.00	22.50
Fixed dwells at The following Center frequencies: (fd)				
67 hz	7.50	7.50	7.50	7.50
100 hz	7.50	7.50	7.50	7.50
135 hz	7.50	7.50	7.50	7.50
200 hz	15.00	15.00	15.00	15.00
267 hz	7.50	7.50	7.50	7.50
300 hz	7.50	7.50	7.50	7.50
335 hz	7.50	7.50	7.50	7.50
400 hz	15.00	15.00	15.00	15.00
467 hz	7.50	7.50	7.50	7.50
500 hz	7.50	7.50	7.50	7.50
Total time Each axis	120.00	120.00	120.00	120.00

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

Note: When an equipment resonance occurs within ± 5% of a fixed dwell frequency, the fixed dwell period shall be omitted and only the resonance dwell performed. The omitted fixed dwell time shall then be added to the sweep time.

4.10.2.6 Sinusoidal sweep. After completion of the fixed dwell testing, The initiators shall be subjected to seven (7) sinusoidal vibration sweeps in each of the three orthogonal axes. The frequency shall vary logarithmically from 500 hz to 2000 hz and back to 500 hz. The sweep cycling rate shall be as specified in paragraph 4.8.2.4 herein, with an applied input of ± 10 g's.

4.10.2.7 After completion of the sinusoidal sweeps specified in paragraph 4.8.2.6 herein, the initiators shall be subjected to radiographic inspection (x-ray) per paragraph 3.5.2.2 herein.

4.10.2.8 After radiographic inspection per paragraph 3.5.2.2 herein, the initiators shall be test fired at +70ºF in accordance with paragraph 4.10 herein.

4.11 Ballistic test. Initiators shall be selected from each production lot in accordance with paragraph 4.2. The sample of initiators shall be divided, as nearly as possible, into three equal groups. If the sample of initiators is not equally divisible by three the excess initiator(s) shall be placed in the group that is to be fired at –65 °F ± 5 °F. One group each shall be conditioned for a period of time neither less than 4 hours nor greater than 24 hours at –65 °F ± 5 °F and +200 °F ± 5 °F. The other group shall be conditioned for a period of time not less than 4 hours at + 70 °F ± 5 °F. The initiators shall be fired in test fixture NAVAIR drawing no. 850AS837, set up as shown in Figure 3 below, within 3 minutes after removal from temperature conditioning. One half of the samples at -65ºF and one half of the samples at +200ºF shall be actuated with a 15º off center pull. If any initiator is exposed to the temperature environment for greater than the time allowed or not fired within 3 minutes after removal, it shall be returned to a +70 °F ± 5 °F environment for at least 4 hours and then reexposed to the original environment for not less than 4 hours and not more than 24 hours before test firing. The reexposure may be performed as many times as necessary to complete the required ballistic test. Instrumentation shall be provided to measure and record the actuation force (pounds-force), and the high order detonation (inches). The production lot shall be accepted if the sample fulfills the acceptance criteria in 4.10.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.




Figure 3. Test setup.

4.11.1 Acceptance criteria

4.11.1.1 Actuation force. The firing mechanism of the initiator shall actuate upon the application of the force specified in paragraph 3.6.1. The lot shall be acceptable with respect to actuation Force if the ballistic sample meets the requirements of paragraph 3.6.1.

4.11.1.2 High order detonation. The high order detonation of the output SMDC test tip shall be demonstrated in a 6061-T6 aluminum witness plate. The lot shall be acceptable with respect to high order detonation if the sample meets the requirements of 3.6.2.

4.11.1.3 Misfire. An initiator that does not fire under the conditions specified in 4.10 shall be considered defective and the lot considered unacceptable, unless the misfire is clearly attributable to faulty test equipment or procedure.

4.11.2 Retest. There shall be no retests.

4.11.3 Test failure. If test failure is attributable to an assignable cause, excluding the test initiator, the original test results shall be discarded and that test reconducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. Notes

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory).

6.1 Intended use. The initiator will ultimately be used in conjunction with a SMDC in aircrew emergency escape systems. The initiator was designed for use in military aircraft and has no commercial application.

6.2 Acquisition requirements. Acquisition documents should specify the following:

A. Title, number and date of this specification and NAVAIR drawing 850AS130
B. Whether first article inspection is required, and if so specify the test activity.
C. Production lot size, sample size and test activity
D. Direction for shipping radiographic plates of entire production lot along with ballistic sample (paragraph 3.6) to the activity conducting production lot acceptance tests
E. Items of data required for each first article and production lot

6.3 Safety precautions. The safety precautions requirements of the "contractor's safety manual for ammunition, explosives and related dangerous material" (DOD 4145.26M) are applicable and should be specified in the contract as required by the defense acquisitions regulation (DAR) 1-323. When this specification is used as part of the description of work to be accomplished by a government activity, the safety precaution requirements of "ammunition and explosives ashore," OP 5, should be made applicable,

6.4 Subject term (key word) listing.

Shielded Mild Detonating Cord (SMDC)
canopy jettison
F-18/TF-18

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.

Custodian:
Navy-OS

Preparing activity
Navy - OS
(Project 1377-0240)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T05:11Z
Check the source to verify that this is the current version before use.