MIL-B-1771G
30 June 1988
SUPERSEDING
MIL-B-1771F
8 May 1974

MILITARY SPECIFICATION

BARBER KIT, WITH CASE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type of barber kit with plywood case.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-S-698	- Steel Sheet and Strip, Low Carbon
TT-C-490	- Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coatings
TT-E-529	- Enamel, Alkyd, Semigloss
TT-P-636	- Primer Coating, Alkyd, Wood and Ferrous Metal

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3590

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

GGG-C-475 - Clippers, Hair, Hand
MMM-A-181 - Adhesives, Phenol, Resorcinal, or Melomine Base
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-P-116 - Preservation, Methods Of
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or In Colors
MIL-F-10336 - Fiber Sheet, Vulcanized
MIL-G-13734 - Germicide, Quaternary Ammonium Type

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

UNITED STATES DEPARTMENT OF COMMERCE

Commercial Standard CS 35 - Hardwood Plywood
Product Standard PS-1 Softwood, Plywood, Construction and Industrial

(Copies of product and commercial standards may be obtained upon application to the Superintendent of Documents, Government Printing Office, Washington, DC 20402-0001.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER
2-9-77 - Barber Kit, with Case; Case, Empty; Details
2-9-78 - Barber Kit, with Case; Case, Empty; Tray Details

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Practice for Commercial Packaging

E 18 - Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

UNDERWRITERS LABORATORIES INC. (UL)

Standard No. 73 - Motor-Operated Appliances

(Copies should be obtained from the Underwriters Laboratories, Inc., 333 Pfingstens Road, Northbrook, IL 60062.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Codes and standards. The electric hair clipper shall comply with the applicable requirements of UL Standard No. 73 (see 4.5 and 4.5.1).

3.3 Materials and components. Materials and components shall conform to the requirements specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used for the purpose in standard industry practice. The use of recycled material is encouraged (see 6.6).

3.3.1 Steel, sheet and strip, low carbon. The low carbon steel sheet and strip shall conform to any temper, quality, finish, or edge of QQ-S-698.

3.3.2 Plywood, hardwood. Hardwood plywood shall be type 1, grade 2 face and back veneer, regular sanded, conforming to Commercial Standard CS 35. The plies and thickness shall be as specified on Drawing 2-9-77.

3.3.3 Plywood, softwood. Softwood shall be group 1, exterior type, grade B-B or better, sanded two sides, conforming to Product Standard PS 1. The plies and thickness shall be a specified on Drawing 2-9-77.

3.3.4 Fiber, vulcanized. Vulcanized fiber shall conform to MIL-F-10336. The thickness shall be as specified on Drawing 2-9-77.

3.3.5 Webbing. The cotton webbing shall conform to type IIa, class 7, 3/4 inch wide of MIL-W-530. The color shall be Olive Drab 7 (see 6.4).

3.3.6 Adhesive. Room temperature and intermediate temperature adhesive shall conform to MMM-A-181. High temperature adhesive shall conform to type II of MMM-A-181 except that the shear strength by compression loading requirement shall not apply and that the curing cycle temperature shall be 190°F minimum.

3.3.7 Primer. Primer shall conform to TT-P-636.

3.3.8 Enamel. Enamel shall conform to TT-E-529. The color shall be Olive Drab No. 24087 of FED-STD-595.

3.3.9 Rivets, solid, tubular, and bifurcated. Rivets shall be commercial, oval head, steel, coated with brass, copper, or zinc, of the type shown on Drawings 2-9-77 and 2-9-78. The lengths shall be sufficient to provide a minimum clinch of 1/16 inch for solid and tubular rivets and 1/8 inch for bifurcated rivets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3.3.10 Tacks, trunk. Trunk tacks shall be commercial oval head, with a square steel shank of sufficient length to provide 1/8 inch clinch.

3.3.11 Tray, aluminum. The tray shall be seamlessly die formed from a single sheet of aluminum stock 0.032 nominal thickness. The tray shall be 7-1/4 inches long, 4-1/2 inches wide and 2-1/2 inches high overall. A plus or minus 1/32 inch tolerance shall apply to the above dimensions other than thickness. The tolerance for thickness shall be the mill tolerance. Unless otherwise specified (see 6.2 and 6.5), the trays shall be Government furnished property.

3.4 Construction.

3.4.1 Case. The case shall conform to the design, details, and dimensions of Drawings 2-9-77 and 2-9-78, and to the requirements specified herein. The spacing of the steel bifurcated rivets and trunk tacks, except the bifurcated rivets, on the binding for the lid and bottom of the case shall be as specified on Drawing 2-9-77. The bifurcated rivets shall be spaced at 1-inch on centers.

3.4.1.1 Vulcanized fiber plywood panels. The plywood panels shall be fabricated from material specified in 3.3.2 or 3.3.3. Vulcanized fiber conforming to 3.3.4 shall be bonded to both surfaces of the panels with not more than one piece on any panel. The fiber shall be tightly drawn and brought flush with the edges of the panels, making a smooth surface free from waves or irregularities. Bonding shall conform to 3.4.1.1.1 or 3.4.1.1.2.

3.4.1.1.1 Unit bonding process. The vulcanized fiber and wood veneer shall be glued with adhesive specified in 3.3.6, assembled, pressed, and cured in one operation.

3.4.1.1.2 Two-step bonding process. The vulcanized fiber shall be bonded to the plywood with adhesive specified in 3.3.6.

3.4.1.1.3 Application of adhesive. The adhesive shall be applied in the manner recommended by the manufacturer. Pressure, pressing time, assembly periods, and curing temperature shall conform to recommendations of the adhesive manufacturer.

3.4.1.1.4 Resistance to delamination. There shall be no delamination or weakness of bond in glue line when tested as specified in 4.6.1.2.

3.4.1.1.5 Fiber adhesion. The adhesive bond of the fiber to plywood shall have a fiber failure of 90 percent minimum and minimum 95 percent average of the bonded area when tested as specified in 4.6.1.3.

3.4.1.2 Case, tray. The tray for the barber kit case shall be fabricated from material specified in 3.3.4 and shall conform to the design and the dimensions as shown on Drawings 2-9-77 and 2-9-78. The angles of the formed tray shall not cause bulging, distortion, or prevent the closing of the lid when the tray for the barber kit case is seated in the body of the barber kit case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3.4.1.3 Metal bindings. The metal valance binding shall be fabricated from material specified in 3.3.1 and shall conform to the design and dimensions shown on Drawings 2-9-77 and 2-9-78. The bindings shall be of one piece construction with tight mitered joints at the corners.

3.4.1.4 Fiber bindings. Fiber bindings shall be fabricated from material specified in 3.3.4 and shall conform to the dimensions shown on Drawing 2-9-77.

3.4.1.5 Hardware. The hardware components shall be commercial steel and shall be similar to the components shown on Drawings 2-9-77 and 2-9-78. The edges of the hardware shall be rounded prior to finish applications and assembly to the case. The thickness of the material for the hasp and hinge shall be a nominal 0.0478 inch. The thickness of the material for all other hardware shall be from 0.0239 to 0.0359 inch.

3.4.1.6 Driving of rivets and cut trunk tacks. Holes for rivets shall be drilled through fiber and plywood and shall be no larger than the diameter of the rivet. Rivet holes in the hardware shall provide a clearance of 0.015 inch, maximum. All rivets and trunk tacks shall be driven with head flush against hardware, binding, or fiber, as applicable, and shall be clinched or peened to provide smooth interior surfaces. The diameter and size number for the rivets shall be as recommended by the rivet industry.

3.4.1.7 Gluing and nailing. All joints of the case panels shall be glued with the adhesive specified in 3.3.6 in addition to being tacked.

3.4.1.8 Padlock with clevis and chain. The barber kit case shall have a commercial padlock, 9/16 to 11/16 inch wide with clevis and chain attached to the case in accordance with manufacturer's commercial practice.

3.4.2 Components, barber kit. The components specified in table I shall be arranged in an orderly and secure fashion within the barber kit case.

TABLE I. Barber kit components

Item No.	Component	Quantity
1	Blade set clipper, hair, hand, size No. 0	1 each
2	Clipper, hair, hand, size No. 0	1 each
3	Blade, double edge, razor, safety plastic coated (5 in package)	8 packages

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

TABLE I. Barber kit components (cont'd)

Item No.	Component	Quantity
4	Blade, adaptable, size 3-1/2, "Butch Type", used with clipper, hair, electric, item No. 6	1 each
5	Case, barber kit, empty	1 each
6	Clipper, hair, electric, universal type motor, 115 volts AC-DC, 25-60 Hertz, single-phase, 40-watt (maximum) AC, with detachable cutter head, with cord, blade guard and case, and with the following accessories: 1 each blade, size 1 1 each blade, size 000 1 each brush, blade cleaning 1 each brush set, carbon (set of 2) (if used) 1 each oil, clipper, electric	1 each
7	Cloth, barber, dark green, minimum size 40 x 40 inches, cut edges hemmed	2 each
8	Comb hair, barber type, any color, (professional) 7-1/4 inches long, tapered, manufacturer's commercial plastic or rubber material	2 each
9	Cream, shaving, brushless type 4-6 oz. tube	1 each
10	Germicide, quarternary ammonium type, type-1, crystalline, 1 oz. packet	2 each
11	Razor, safety, two shaving sides, metal	1 each
12	Shears, barber type (professional), 7-1/4 - 7-1/2 inches long	2 each
13	Soap, toilet, soft, 3-1/2 oz. min. (personal size)	2 bars
14	Soapbox, plastic, any color, to accomodate 3-1/2 oz. soap (personal size)	1 each
15	Tray, instrument, aluminum	1 each

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3.4.3 Clipper, hair, hand. The hand hair clippers shall conform to size No. 0 of GGG-C-475, except the clipper cap may be fabricated from steel or any soft plastic material.

3.4.4 Blade, clipper, hair, hand. The blade set for the No. 0 size hand clippers shall conform to GGG-C-475.

3.4.5 Clipper, hair, electric. The electric hair clipper shall have detachable cutting blades and shall be operated by a universal AC-DC motor or a permanent magnet AC motor rated as 115 volt, 40 watt maximum, 25 to 60 Hertz AC, single phase, as applicable. The motor case shall be fabricated from an impact resistant plastic. Motor brushes, if used, shall be accessible for changing. Clippers shall have a bail or hanger, quick make/break switch rated at 3 amps DC (minimum). The cord set shall be 3 conductor type, 8 feet long (minimum) and shall have a strain relief at entry to motor housing. If double insulated motor construction is provided, the cord set may be a 2-conductor type, 8 feet long (minimum) and shall have a strain relief at entry to motor housing. The clipper blades shall have a minimum hardness of Rockwell C58 when tested as specified in 4.6.2, except those blades produced by the sintering process (powder metal) do not have to be tested for hardness. The assembled weight of the clipper shall not exceed 2 pounds.

3.4.6 Disinfectant. The disinfectant shall conform to type I of MIL-G-13734. The disinfectant shall be formulated to contain 10 percent active product, crystalline form.

3.5 Finish.

3.5.1 Preparation of surfaces.

3.5.1.1 Metal surfaces. All unfinished hardware and metal surfaces, including rivets and burrs (when applicable), but excluding tacks, shall be pretreated in accordance with TT-C-490.

3.5.1.2 Wood and fiber surfaces. All wood and vulcanized fiber surfaces shall be thoroughly cleaned of dust, dirt, and grease prior to priming.

3.5.2 Priming. The thoroughly dried surfaces, prepared as specified in 3.5.1.1, shall be coated with primer specified in 3.3.7. All hardware, metal, and fiber components shall be primed on all surfaces and edges prior to assembly. The primer coat on metal parts shall be baked for not less than 45 minutes at 250°F, or for a time-temperature cycle recommended in accordance with standard industry practice. The case body, lid, and tray shall be primed prior to assembly of hardware and bindings. The primer coat shall be thoroughly dried prior to assembly of the hardware, metal, and fiber parts. Force drying is permitted, provided a surface temperature of 140° F is not exceeded and the relative humidity of the surrounding air is maintained at 30 to 50 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3.5.3 Enameling. After attachment of all hardware, metal, and fiber parts to the primed case body, lid, and tray, the exterior and interior surfaces shall be coated with enamel specified in 3.3.8.

3.6 List, barber kit components. The list of the barber kit components, as shown in table I, shall be printed on a waterproof label with waterproof ink. The characters shall be 10 point bold face and the heading characters shall be 12 or 14 point bold face type. The list shall be securely attached as shown on Drawing 2-9-77.

3.7 Label, instructions for care of tools. The instructions for care of tools label shall be printed on waterproof paper with waterproof ink. The printed characters shall be 10 point bold face type for the body and 12 or 14 point bold face type for the headings. Label readings shall be from left to right when case lid is open. The label shall be securely attached to the inside of case lid in the location shown on Drawing 2-9-77. Tool care instructions shall include the following:

"Instructions for the

Proper Care of Tools, Barber

BARBER KIT, WITH CASE

Sterilization. Keep all parts of equipment clean. Detach cutter head from electric clippers and brush away debris. Wash clippers, combs, safety razor, blades, electric clipper detachable cutter head, and shears with soap and water to remove all film and debris immediately after use on each patron. After washing, all instruments shall be immersed for 15 minutes in a solution prepared in accordance with manufacturer's recommended instructions. All instruments disinfected by chemical solution shall be rinsed in water after immersion in the solution to remove the chemical, and dried before being used on patrons. Solutions shall be changed daily. Before putting kit away, dry everything completely.

Sharpening.

(a) Clipper - If clipper blades get dull, replace with extra set and exchange dull blades for a new pair at the first opportunity. Do not attempt to sharpen blades in the field.

Care. Protect metal equipment against rust. Apply light film of oil if kit is to be left unused for several days. Oiling is particularly important in humid climates."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3.8 Marking for identification. The letters "U.S." shall be marked in the size and location on the barber kit case as shown on Drawing 2-9-77. Manufacturer's name or readily identifiable trademark and year of manufacture shall be printed at the bottom of the list of components.

3.9 Workmanship. All surfaces of the finished barber kit case and components shall be free of burrs, slivers and rough or sharp edges. Components shall not be broken, cracked, or malformed. The enamel coating shall level out to a continuous, smooth, dry adherent film thickness without runs, drops, streaks, or area of no film. The coating shall be free from embedded foreign matter and shall show no evidence of peeling, flaking, or blistering.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsiblity for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements (see 4.4.3.2).

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in table III and for the dimensions annotated with an asterisk on Drawing 2-9-77, and shall be tested in accordance with 4.6.2. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Inspection of sub-assemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

4.4.2.1 In-process examination. Examination shall be made during the manufacturing process for compliance with the requirements specified in table II to determine that no deviation is made from indicated requirements. Whenever nonconformance is noted, correction shall be made to the affected item and process.

TABLE II. In-process examination requirements

Requirement	Requirement paragraph
Diameter of rivet holes and rivet clinching length	3.4.1.6
Surface preparation	3.5.1.1 and 3.5.1.2
Priming	3.5.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

4.4.2.2 In-process testing. Prior to painting, the panels shall be tested for resistance to delamination as specified in 4.6.1.2 and fiber adherence to plywood as specified in 4.6.1.3. The sample unit shall be one plywood panel with fiber bonded to both sides. The lot shall be all of the panels glued and bonded under the same process and control, offered for inspection at one time. Three sample units shall be selected from each lot and tested. Two test specimens conforming to 4.6.1.1 shall be cut from each sample unit and tested as specified in 4.6.1.2 and 4.6.1.3. Any test failure shall be cause for rejection of the lot.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table III. The lot size shall be expressed in units of barber kits, complete with case and components. The sample unit shall be one completely fabricated barber kit case and assembled barber kit components. The inspection level shall be II and the accetpable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE III. End item visual defects

Examine	Defect	Classification Major	Minor
Finish (applicable to case)	Not uniform color		X
	Not color enamel specified		X
	Area of no film		X
	Not smooth, continuous, or adherent	X	
	Has runs, drops, or streaks		X
	Evidence of peeling, flaking, or blistering	X	
	Embedded foreign matter		X
Construction, assembly, and workmanship of case	Part not in proper alignment	X	
	Component not type specified	X	
	Component loose or insecurely attached		X
	Fiber covered panel not smooth or free from waves or irregularities		X
	More than one sheet of fiber on each panel		X
	Lid binds or will not close	X	
	Sharp edge or burr	X	
Hardware	Broken, malformed, or corroded areas, burrs or sharp edges	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Attachment of hardware	Mating hardware not aligned		X
	Not attached as shown on Drawings 2-9-77 and 2-9-78		X
Attachment of rivets	Any rivet missing		X
	Not oval head		X
	Rivet not peened or curled		X
	Rivets not completely seated	X	
	Rivet head missing		X
	Any rivet reversed, e.g., head is not on the intended side of component as required	X	
Attachment of valances and bindings	Not riveted tightly to edges		X
	Ends visible after hardware attachment		X
	More than two on any edge	X	
Kit components and component arrangement in kit	Kit component missing	X	
	Not as specified	X	
	Incorrect quantity		X
	Kit component damaged	X	
	Component will not fit into proper place	X	
Identification marking	Missing, illegible, incorrect, wrong location, or not as specified		X
	"U.S." not detailed as shown on Drawing 2-9-77		X
Webbing	Edges frayed or scalloped		X
Padlock and keys	Padlock missing	X	
	Padlock will not function	X	
	Two keys missing	X	
	One key missing		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. The end items shall be examined for compliance with the dimensions annotated with an asterisk on Drawing 2-9-77. The lot size shall be expressed in units of barber kits, complete with case and components. The sample unit shall be one completely fabricated barber kit case and assembled barber kit components. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing. When a first article is not required, the first produced barber kit with case shall be tested as specified in 4.6.2. A test failure shall be cause for rejection of the unit. The rejection shall be investigated to determine the cause, corrections made, and the next produced unit shall be tested.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.5 Certification compliance examination. Certificates, certified test reports, or listing marks for codes and standards, as applicable, submitted in accordance with 3.2, shall be examined and validated as proof of compliance.

4.5.1 Underwriters' Laboratories, Inc. (UL). Acceptable evidence of meeting the applicable requirements of the Underwriters' Laboratories standards specified in 3.2 shall be the UL label, a UL listing mark, or a certified test report from a recognized independent laboratory, acceptable to the Government, indicating that the barber kit with case conforms to the applicable requirements of the specified UL standard (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

4.6 Methods of inspection.

4.6.1 Vulcanized fiber to plywood bond.

4.6.1.1 Test specimens. Two test specimens shall be cut from each sample unit. The test specimens shall be 4 inch square plywood panels having fiber bonded to both sides. The specimens shall be untreated and unpainted.

4.6.1.2 Boiling and quench test. The test specimens conforming to 4.6.1.1 shall be immersed in boiling water for 3 hours, followed by quenching in water at room temperature (70°F ± 5°F). The specimens shall be examined immediately after quenching. Any nonconformance with the requirements in 3.4.1.1.4 shall constitute a test failure.

4.6.1.3 Fiber adhesion test. Specimens conforming to 4.6.1.1 shall have a sharp knife blade or similar instrument inserted at the glue line and the vulcanized fiber shall be peeled off. The percentage of fiber failure for each specimen shall be estimated and the average fiber failure for all specimens tested shall be computed. Any nonconformance with the requirements in 3.4.1.1.5 shall constitute a test failure.

4.6.2 Hardness test. Hardness of blades, size 1 and 000 based on the average of three readings shall be tested in accordance with ASTM E 18 to determine compliance with hardness requirements of 3.4.5. Any nonconformance shall constitute a test failure.

5. PACKAGING

5.1 Preservative application. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Preservative application. All clipper blades, detachable cutter head for electric clippers, and exposed, uncoated, ferrous metal surfaces of the clippers, shears, and razor shall be cleaned process C-1, thoroughly dried, and coated with preservative conforming to P-14 of MIL-P-116. Preserved items shall be individually wrapped in barrier material conforming to type II, grade A, class 1 or 2 of MIL-B-121 and the wrap secured with tape. Each clipper blade shall be placed in a paperboard box.

5.1.1.2 Unit packing. The two bars of toilet soap shall be individually unit packed in accordance with the industry's practice. Each comb shall be wrapped in minimum 30-pound basis weight (24 x 36 - 500) kraft paper and the wrap secured with tape. The two barber cloths shall each be compactly folded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

5.1.1.3 Placement of components. The components of the barber kit shall be placed in the case. The two hand clippers shall be placed in their respective compartments in the case tray, and the combs and shears shall be placed in the retainers in the lid. The two folded barber cloths shall be placed over the case tray. The remaining components of the kit shall be immobilized with single-wall corrugated fiberboard pads or forms. The kit case shall then be closed and secured with the latches and padlock. The two keys shall be placed in a cotton cloth drawstring bag and bag tied securely to the padlock.

5.1.2 Commercial. Barber kits shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Four barber kits, preserved as specified in 5.1, shall be packed flat in two layers with the handles facing the center, in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except that type II, class F loads.

5.2.2 Level B packing. Four barber kits preserved as specified in 5.1, shall be packed flat, in two layers with the handles facing the center, in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant grade fiberboard. When specified (see 6.2), the shipping container shall be a V3c or V3s or V4s, fabricated and closed in accordance with PPP-B-636.

5.2.3 Commercial packing. Barber kits, preserved as specified in 5.1.2, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The barber kit with case is intended for use by military personnel in the field.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When first article is not required (see 3.1, 4.3, and 6.3).
c. When trays are not furnished as Government furnished property (see 3.3.11).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit loads required (see 5.2.1).
f. When weather-resistant grade fiberboard is required for level B packing (see 5.2.2.1).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Standard samples. Samples of the approved shade of olive drab cotton webbing may be obtained from the procuring office (see 3.3.5).

6.5 Government furnished property. The contracting officer should arrange to furnish the tray specified in 3.3.11.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

6.7 Subject term (key word) listing.

Barber kit
Clipper, hair, hand
Clipper, hair, electric

6.8 Changes from previous issues. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - MC
Air Force - 99

Review activities:

Army - MD
Navy - SA
Air Force - 84

Preparing activity:

Army - GL

Project No. 3590-0031

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-1771G	Barber Kit, With Case

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.