INCH-POUND

MIL-B-1771H
28 December 1992
SUPERSEDING
MIL-B-1771G
30 June 1988

MILITARY SPECIFICATION

BARBER KIT, WITH PLASTIC CASE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of barber kit with plastic case.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

GGG-C-475 - Clippers, Hair, Hand
PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3590

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	-	Preservation, Methods Of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-G-13734	-	Germicide, Quaternary Ammonium Type
MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-M-43719	-	Marking Materials and Markers, Adhesive, Elastomeric, Pigmented; General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members For Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-9-341	-	Barber Kit; Case, Plastic, Empty
2-9-342	-	Barber Kit; Tray, Case

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging
E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

UNDERWRITERS LABORATORIES INC. (UL)

Standard No. 73 - Motor-Operated Appliances

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Codes and standards. The electric hair clipper shall comply with the applicable requirements of Underwriters Laboratories (UL) Standard No. 73 (see 4.5 and 4.5.1).

3.3 Materials and components. Materials and components shall conform to the requirements specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used for the purpose in standard industry practice. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Tray, aluminum. The tray shall be seamless and die formed from a single sheet of aluminum stock 0.032 nominal thickness. The tray shall be 7-1/4 inches long, 4-1/2 inches wide and 2-1/2 inches high overall. A plus or minus 1/32 inch tolerance shall apply to the above dimensions other than thickness. The tolerance for thickness shall be the mill tolerance. Unless otherwise specified (see 6.2 and 6.4), the trays shall be Government furnished property.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

3.4 Construction.

3.4.1 Case. The case shall conform to the design, details, and dimensions of Drawing 2-9-341 and to the requirements specified herein.

3.4.1.1 Case, tray. The tray for the barber kit case shall conform to the design and the dimensions as shown on Drawing 2-9-342 and to the requirements specified herein. The tray shall not cause bulging, distortion, or prevent the closing of the lid when it is seated in the body of the barber kit case.

3.4.1.2 Gasket. A 0.188 inch diameter rubber gasket shall be embedded, using a commercial adhesive, a minimum of 0.094 inches, into the base edge. When the case is closed, the gasket shall not be visible from the outside of the case. The gasket shall provide a water-resistant seal between the lid and base when the case is closed.

3.4.1.3 Hardware. The hardware components shall be made of commercial steel and shall be similar to the components shown on Drawing 2-9-341.

3.4.1.4 Padlock with clevis and chain. The barber kit case shall have a commercial padlock, 9/16 to 11/16 inch wide with clevis and chain attached to the case in accordance with manufacturer's commercial practice. Two keys shall be supplied with each padlock.

3.4.2 Components, barber kit. The components specified in table I shall be arranged in an orderly and secure fashion within the barber kit case.

TABLE I. Barber kit components

Item No.	Component	Quantity
1	Blade set clipper, hair, hand, size No. 0	1 each
2	Clipper, hair, hand, size No. 0	1 each
3	Blade, adaptable, size 3-1/2, "Butch Type", used with clipper, hair, electric, item No. 5	1 each
4	Case, barber kit, empty	1 each
5	Clipper, hair, electric, universal type motor, 115 volts AC-DC, 25-60 Hertz, single-phase, 40-watt (maximum) AC, with detachable cutter head, with cord, blade guard and case, and with the following accessories: Blade, size 1 Blade, size 000 Brush, blade cleaning	1 each

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

TABLE I. Barber kit components (cont'd)

Item No.	Component	Quantity
	Brush set, carbon (set of 2) (if used) Oil, clipper, electric	
6	Cloth, barber, dark green, minimum size 40 x 40 inches, cut edges hemmed	2 each
7	Comb hair, barber type, any color, (professional) 7-1/4 inches long, tapered, manufacturer's commercial plastic or rubber material	2 each
8	Cream, shaving, brushless type 4-6 oz. tube	1 each
9	Germicide, quaternary ammonium type, type-III, liquid, 2 oz. plastic bottle	2 each
10	Disposable razors	80 each
11	Shears, barber type (professional), 7-1/4 to 7-1/2 inches long	2 each
12	Soap, toilet, soft, 3-1/2 oz. min. (personal size)	2 bars
13	Soapbox, plastic, any color, to accommodate 3-1/2 oz. bar of soap (personal size)	1 each
14	Tray, instrument, aluminum	1 each

3.4.3 Clipper, hair, hand. The hand hair clippers shall conform to size No. 0 of GGG-C-475, except the clipper cap may be fabricated from steel or any soft plastic material.

3.4.4 Blade, clipper, hair, hand. The blade set for the No. 0 size hand clippers shall conform to GGG-C-475.

3.4.5 Clipper, hair, electric. The electric hair clipper shall have detachable cutting blades and shall be operated by a universal AC-DC motor or a permanent magnet AC motor rated at 115 volt, 40 watt maximum, 25 to 60 Hertz AC, single phase, as applicable. The motor case shall be fabricated from an impact resistant plastic. Motor brushes, if used, shall be accessible for changing. Clippers shall have a bail or hanger, quick make/break switch rated at 3 amps DC (minimum). The cord set shall be a 3 conductor type, 8 feet long (minimum) and shall have a strain relief at the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

entry to the motor housing. If double insulated motor construction is provided, the cord set may be a 2 conductor type, 8 feet long (minimum) and shall have a strain relief at the entry to the motor housing. The clipper blades shall have a minimum hardness of Rockwell C58 when tested as specified in 4.6.1, except for those blades produced by the sintering process (powder metal), which do not have to be tested for hardness. The assembled weight of the clipper shall not exceed two pounds.

3.4.6 Disinfectant. The disinfectant shall conform to type III of MIL-G-13734. The disinfectant shall be formulated to contain 10 percent active product, liquid form.

3.5 Label, list of barber kit components. The list of the barber kit components, as shown in table I, shall be printed on an adhesive-backed waterproof label per MIL-M-43719, type I, class 1, color white, with waterproof ink. The characters shall be 10 point bold face type and the heading characters shall be 12 or 14 point bold face type. Label readings shall be from left to right when case lid is open. The list shall be securely attached to the inside of the case lid in the location shown on Drawing 2-9-341.

3.6 Label, instructions for care of tools. The instructions for care of tools label shall be printed on adhesive backed waterproof paper per MIL-M-43719, type I, class 1, color white, with waterproof ink. The printed characters shall be 10 point bold face type for the body, and 12 or 14 point bold face type for the headings. Label readings shall be from left to right when case lid is open. The label shall be securely attached to the inside of the case lid in the location shown on Drawing 2-9-341. Tool care instructions shall include the following:

"Instructions for the

Proper Care of Tools, Barber

Sterilization. Keep all parts of equipment clean. Detach cutter head from electric clippers and brush away debris. Immediately after use on each patron, wash the clippers, combs, blades, electric clipper detachable cutter head, and shears with soap and water to remove all film and debris. After washing, all instruments shall be immersed for 15 minutes in a solution prepared in accordance with manufacturer's recommended instructions. All instruments disinfected by chemical solution shall be rinsed in water after immersion in the solution to remove the chemical, and dried before being used on patrons. Solutions shall be changed daily. Before putting the kit away, dry everything completely.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

Sharpening.

(a) Clipper - If clipper blades get dull, replace with extra set and exchange dull blades for a new pair at the first opportunity. Do not attempt to sharpen blades in the field.

Care. Protect metal equipment against rust. Apply light film of oil if kit is to be left unused for several days. Oiling is particularly important in humid climates."

3.7 Marking for identification. The letters "U.S." shall be marked in the size and location on the barber kit case as shown on Drawing 2-9-341. The manufacturer's name or readily identifiable trademark and the year of manufacture shall be printed at the bottom of the list of components.

3.8 Workmanship. All surfaces of the finished barber kit case and components shall be free of burrs, slivers, and rough or sharp edges. Components shall not be broken, cracked, or malformed. The case shall be free from embedded foreign matter. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and shall be tested for the characteristic specified in 4.4.4. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the electric hair clipper conforms to the requirement specified in 3.2.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of barber kits, complete with case and components. The sample unit shall be one completely fabricated barber kit case and assembled barber kit components. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor
Construction, assembly, and workmanship of case	Part not in proper alignment	101	
	Component missing, or not type specified	102	
	Component loose or insecurely attached		201

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction, assembly, and workmanship of case (cont'd)	Lid binds or will not close	103	
	Sharp edge or burr	104	
	Not uniform color		202
	Embedded foreign matter		203
Hardware	Broken, malformed, or corroded areas, burrs or sharp edges	105	
Attachment of hardware	Mating hardware not aligned		204
	Not attached as shown on Drawing 2-9-341		205
Kit components and component arrangement in kit	Kit component missing	106	
	Not as specified	107	
	Incorrect quantity		206
	Kit component damaged	108	
	Component will not fit into proper place	109	
Identification marking	Missing, illegible, incorrect, wrong location, or not as specified		207
	"U.S." not detailed as shown on Drawing 2-9-341		208
Padlock and keys	Padlock missing	110	
	Padlock will not function	111	
	Two keys missing	112	
	One key missing		209

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of barber kits, complete with case and components. The sample unit shall be one completely fabricated barber kit case and assembled barber kit components. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 End item testing. When a first article is not required, the electric hair clipper in the first produced barber kit with case shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

tested as specified in 4.6.1. A test failure shall be cause for rejection of the unit. The rejected unit shall be investigated to determine the cause, corrections made, and the next produced unit shall also be tested.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Code and standard compliance. Certificates, certified test reports, or listing marks for codes and standards, as applicable, submitted in accordance with 3.2, shall be examined and validated as proof of compliance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

4.5.1 Underwriters' Laboratories, Inc. (UL). Acceptable evidence of meeting the applicable requirements of the Underwriters' Laboratories (UL) standard specified in 3.2 shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the electric hair clipper conforms to the applicable requirements of the specified UL standard.

4.6 Methods of inspection.

4.6.1 Hardness test. Hardness of the electric clipper blades, sizes 1 and 000, based on the average of three readings shall be tested in accordance with ASTM E 18 to determine compliance with the hardness requirement of 3.4.5. Any nonconformance shall constitute a test failure.

5. PACKAGING

5.1 Preservative application. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation.

5.1.1.1 Preservative application. All clipper blades, detachable cutter head for electric clippers, and exposed, uncoated, ferrous metal surfaces of the clippers and shears shall be cleaned by process C-1, thoroughly dried, and coated with preservative conforming to P-14 of MIL-P-116. Preserved items shall be individually wrapped in barrier material conforming to type II, grade A, class 1 or 2 of MIL-B-121 and the wrap secured with tape. Each clipper blade shall be placed in a paperboard box.

5.1.1.2 Unit packing. The two bars of toilet soap shall be individually unit packed in accordance with the industry's practice. Each comb shall be wrapped in minimum 30 pound basis weight (24 x 36 - 500) kraft paper and the wrap secured with tape. The two barber cloths shall each be compactly folded.

5.1.1.3 Placement of components. The components of the barber kit shall be placed in the case. The case tray shall contain the disposable razors. The aluminum tray shall sit in the right half of the base. The aluminum tray shall contain the soap, plastic soap container, shaving cream, germicide, and oil for the electric clipper. The remaining components shall be placed in the base. The kit case shall then be closed and secured with the latches and padlock. The two keys shall be placed in a cotton cloth drawstring bag, and the bag tied securely to the padlock.

5.1.2 Commercial preservation. Barber kits shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Four barber kits, preserved as specified in 5.1, shall be packed flat in two layers with the handles facing the center, in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Approximate inside dimensions of the box shall be 24 inches in length, 18 inches in width, and 17 inches in depth. Each shipping container shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four barber kits preserved as specified in 5.1, shall be packed flat, in two layers with the handles facing the center, in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. Approximate inside dimensions of the box shall be 24 inches in length, 18 inches in width, and 17 inches in depth. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a V3c or V3s or V4s, fabricated and closed in accordance with PPP-B-636.

5.2.3 Commercial packing. Barber kits, preserved as specified in 5.1.2, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), barber kits packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way) entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 6 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The barber kit with case is intended for use by military personnel in the field.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. When trays are not furnished as Government furnished property (see 3.3.1).
e. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
f. Type and class of unit load required (see 5.2.1).
g. When weather-resistant grade fiberboard is required for level B packing (see 5.2.2.1).
h. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Government furnished property. The contracting officer should arrange to furnish the tray specified in 3.3.1.

6.5 Subject term (key word) listing.

Clipper, hair, electric
Clipper, hair, hand
Comb
Haircutting tools
Razor
Shears

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - MC
Air Force - 99

Review activities:

Navy - SA
Air Force - 84

Civil agency coordinating activity:

GSA - FSS

Preparing activity:

Army - GL

(Project 3590-0032)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-1771H	1992 December 28

3. DOCUMENT TITLE
BARBER KIT, WITH PLASTIC CASE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP3, JUL 91 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:44Z
Check the source to verify that this is the current version before use.