MILITARY SPECIFICATION

BAG, VALUABLES: NUMBERED, WITH TAG, METAL IDENTIFICATION

1. SCOPE

*1.1 This specification covers requirements for one type valuables bag made of cotton duck and provided with a metal identification tag.

2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

T-C-571	- Cord, Cotton, General And Special Purpose, Sash And Venetian Blind.
V-T-285	- Thread, Polyester.
TT-I-559	- Ink, Marking Stencil, Opaque, For Porous Surfaces (Wood Boxes, Fiber Cartons, Etc.).
UU-P-268	- Paper, Kraft, Untreated, Wrapping.
CCC-C-419	- Cloth, Duck, Cotton, Unbleached, Plied-yarns, Army And Numbered.
CCC-D-950	- Dyeing And Aftertreating Processes For Cotton Cloths.
DDD-L-20	- Label, For Clothing, Equipage And Tentage, (General Use).
DDD-T-86	- Tape, Textile, Cotton, General Purpose, (Unbleached, Bleached Or Dyed).

MILITARY

MIL-T-842	- Tag, Identification, Personnel.
MIL-G-16491	- Grommet, Metallic.
MIL-B-17757	- Boxes, Fiber, Corrugated (Modular Sizes).

STANDARDS

FEDERAL

FED-STD-751	- Stitch, Seam And Stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage.

DRAWINGS

Marine Corps

P-229	- Bag, Valuables: Numbered, With Tag, Metal, Identification.

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

*2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids, or request for proposal, shall apply.

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, 202 Chicago Union Station, Chicago, Illinois 60606.)

3. REQUIREMENTS

*3.1 Samples. Samples are furnished solely for guidance and information to the supplier (see 6.3). Variation from this specification may appear in the sample, in which case the specification shall govern.

*3.2 First article. Unless otherwise specified (see 6.2) before production is commenced, a finished bag shall be submitted, or made available, to the contracting officer or his authorized representative for approval. The approval of the first article authorizes the commencement of production but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The first article shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

*3.3 Materials.

*3.3.1 Cloth, cotton duck. The cotton duck shall be, before finishing, 8.25 ounce per square yard, conforming to type III of CCC-C-419 (see 6.3). The cloth shall be dyed olive drab No. 7, water repellent and mildew resistant treated, conforming to type 1, class B of CCC-D-950.

*3.3.2 Tape, cotton. The cotton tape shall be 7/16 inch wide, preshrunk, conforming to type I, class 2 of DDD-T-86, except the requirements for nonfibrous material shall not apply.

*3.3.3 Thread, polyester. The thread shall conform to type I, class 1, size E of V-T-285. The thread shall be dyed olive drab shade S-1 (cable No. 66022). The dyed thread shall show good fastness to chlorine bleaching and laundering when tested as specified in V-T-285.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

*3.3.4 Cord, cotton. The cotton cord shall conform to type I, class 2, size 4 of T-C-571, except that the color of the cord shall be that naturally resulting from the mildew and water resistant treatment. The cord shall be treated with copper-8-quinolinolate in accordance with T-C-571, except that the concentration of the inhibitor shall be 0.18 to 0.40 percent copper as metal from copper-8-quinolinolate.

*3.3.5 Ink, stencil. The stencil ink shall be black conforming to TT-I-559.

*3.3.6 Grommets, metallic. The metallic grommets shall conform to type III, class 3, size No. 2 of MIL-G-16491.

*3.3.7 Tag, identification. The identification tag shall conform to MIL-T-842.

*3.4 Design and construction. The design and construction shall conform to Drawing No. P-229 and the following:

*3.4.1 Stitching, machine. All stitching and types shall conform to FED-STD-751, except overedge stitching and stitching on neck band shall be type 301, 10 to 14 stitches per inch; all other overedge stitching shall be type 304, 14 to 16 stitches per inch. All thread ends shall be trimmed.

*3.4.1.1 Type 301 stitching. Thread breaks in stitching shall be backstitched not less than 1 inch at each break. Stitching shall be backstitched at the ends to prevent raveling, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained properly so that there will be no loose stitching and that the lock will be embedded in the center of the materials sewed.

*3.4.1.2. Type 304 stitching. Thread breaks in stitching shall be overlocked not less than 3/4 inch at each break. Thread tension shall be maintained properly so that there will be no loose stitching.

*3.4.2 Numbering of bags. A serial number shall be printed or stenciled on the outside of each bag in the size characters and in the location shown on Drawing No. P-229. Solid face numbers shall be used and the bags shall be marked consecutively in series from 1 to 800 inclusive. Black stencil ink specified in 3.3.5 shall be used for all numbering.

*3.4.3 Assembly of identification tags. The metal identification tags shall have a serial number on one side only. The tags shall be marked consecutively in series from 1 to 800 inclusive. Each tag shall be assembled to a neck band as shown on Drawing No. P-229. Each tag shall then be matched to a bag having the same number as on the tag and the tag securely fastened to the bag by sliplooping the neck band to the loop of one of the drawstrings of the bag.

*3.4.4 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be tightly clinched without cutting the material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

*3.5 Finished measurements. The finished bag shall be 12 ±1/2 inches in height and 21-1/2 ±1/2 inches in circumference.

*3.6 Identification marking. The application of the letters "US" and the serial number of each bag, marked consecutively in series from 1 to 800 inclusive, on the outside of the bag, shall be in accordance with type IV, class 9 of DDD-L-20. Fastness of the class 9 labels shall be as specified for class 5 labels. The size characters and location shall be as shown on Drawing No. P-229. The identification marks shall be as follows:

Nomenclature (item description)
Contract number
Stock number

Black stencil ink specified in 3.3.5 shall be used for all marking.

*3.7 Workmanship. The finished bag shall conform to the quality and grade of product established by this specification. Occurrence of defects shall not exceed the applicable acceptance quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

*4.2 Inspection. Inspection shall be in accordance with provisions of MIL-STD-105 except where otherwise indicated herein. For purpose of sampling, an inspection lot for examinations and test shall consist of all bags submitted for inspection and delivery at one time.

*4.2.1 First article inspection. When first article is required, inspection and testing shall be performed to determine conformance with design, construction, workmanship, and dimensional requirements.

*4.2.2 Components and material inspection. In accordance with 4.1, the supplier is responsible for insuring the components and materials used are manufactured, tested and inspected in accordance with requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification.

*4.2.2.1 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether operations or assemblies are in accordance with requirements indicated on Drawing No. P-229. Care shall be taken that holes punched to receive grommets are as specified herein. Whenever nonconformance is noted, correction shall be made to the items affected and lot in process.

*4.2.3 Inspection of the end item. The bags shall be examined for defects (one class) listed in 4.2.3.1 and 4.2.3.2. The lot size for the purpose of determining the sample size shall be expressed in units of one bag each. The inspection level and the AQL shall be as indicated in 4.2.3.3. The sample unit for this examination shall be one completely fabricated bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

*4.2.3.1 Examination for visual characteristics. The bags shall be examined for the following visual defects:

Examine	Defect
Material	Any component or material not as specified.
	Any component missing or malformed.
Construction and appearance	Not one-piece body and one-piece bottom.
	Any detail of construction and design not as specified.
	Drawstring not two piece construction.
	Material not sufficiently lapped at all seams; seam width less than specified.
	Seams and stitching not type specified.
	Any hole, cut, tear or other fabric defect affecting appearance or serviceability.
	Any cut, fray or abrasion in drawstring.
Workmanship	Any open seam.
	End of continuous row of stitches (including end due to thread break) not anchored by backstitching not less than 3/4 inch unless an anchorage is provided by other seam or stitching.
	Stitching lock not imbedded in the middle of material sewed.
	Seam and stitching not uniform and straight; stitching not evenly spaced.
	Grommet improperly located; grommet does not completely encompass fabric.
	Grommet not securely and uniformly compressed into material.
	Grommet reinforcement not as specified.
	Grommet cutting into material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

Examine	Defect
	Warp not parallel with length of bag.
	Thread tension not uniform; evidence area of loose stitching resulting in loose or exposed top or bobbin thread; too much tension resulting in pucker of material; thread end not trimmed.
	Drawstring caught fast in hemstitching, preventing proper closing of bag.
	Any burr or rough edge of grommet not ground smoothly.
	Metal tag not legibly marked with number to match bag number; tag not securely assembled to neck band as shown in drawing; tag not secured to the bag as specified (see 3.4.3.).
	Not clean.
Identification marking	Omitted, incomplete, incorrect, illegible; of improper size, location and method of application.

*4.2.3.2 Examination of the end item for dimensional defects. The sample unit for the examination shall be one bag and it shall be examined for the following defects:

Examine	Defect
Overall dimensions	
Length	Not within tolerance specified.
Diameter	Not within tolerance specified.
Seam	Not width specified.
Stitching	Not number of stitches per inch specified.
Grommets	Not size specified.
Drawstrings	Not length and diameter specified.
Tags	Not size specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

*4.2.3.3 Acceptable quality levels and inspection levels. The AQL's expressed in defects per hundred units (DHU) and inspection levels shall be as follows:

	AQL's	Inspection level
For 4.2.3.1		
One class	2.5	II
For 4.2.3.2		
One class	2.5	S-3

*4.2.4 Examination of preparation for delivery requirements. An examination shall be made to determine compliance with packaging, packing and marking requirements of Section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 DHU.

Examine	Defect
Marking	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling, bulging, distortion of containers.
Content	Number of bundles per container is more or less than required.
	Number of bags per bundle is more or less than required. For this defect, one bundle from each shipping container in the sample shall be examined.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. The number of the tag shall be matched to the number of the bag, and the tag securely fastened to the bag by slip-looping the neck band to one of the loops of the bag drawstrings. The tag shall then be dropped inside the bag and the bag neatly smoothed out so that it will lie flat. The bags shall then be cross-tied in bundles of 10 with cotton tape or twine.

5.1.2 Level C. The bags shall be packaged in accordance with industry's practice.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

*5.2.1.1 Method 1. Forty (40) bags, packaged as specified in 5.1, shall be packed in a fiberboard shipping container with liner, conforming to class weather-resistant, size No. 2A of MIL-B-17757, except the bursting strength for the fiberboard shall be grade 275. The contents of each shipping container shall completely covered on top and bottom with 60 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be assembled closed and reinforced as specified in the appendix to the box specification.

*5.2.1.2 Method 2. When specified (see 6.2), three level B shipping containers (20 bags) shall be overpacked in a fiberboard shipping container, conforming to class weather -resistant, size No. 4 of MIL-B-17757, assembled, closed and reinforced as specified in the appendix thereto.

*5.2.2 Level B. Forty (40) bags, packaged as specified in 5.1, shall be packed in a fiberboard shipping container with liner, conforming to class-domestic, size No. 2A of MIL-B-17757, except the bursting strength of the fiberboard shall be grade 275. The contents of each shipping container shall be completely covered on top and bottom with 60 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be assembled and closed as specified in the appendix to the box specification.

5.2.3 Level C. Bags, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Shipping containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by contract or order, the shipping containers shall be marked in accordance with requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. The bag, valuables, is intended to be issued to male personnel of the U. S. Marine Corps for the safe keeping of his valuables while he is being processed through fumigation and bath units. Each bag is numbered and is provided with an identification tag attached to a neck band. The number on the tag matches the number on the bag so that the tag serves as a check or receipt for the bag. The basis of issue is 800 per fumigation and bath company.

*6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

*6.2.1 Procurement requirements.

(a) Title, number and date of this specification.
(b) Availability of sample (3.1).
(c) Whether first article is required (3.2).
(d) Selection of applicable levels of packaging and packing (5.1 and 5.2).
(e) When level A, method 2, packing is required (5.2.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

*6.2.2 Contract data requirements. Data conforming to Data Item Descrip DI-R-4803, DI-R-4805, DI-T-4901, DI-T-4902, DI-T-4903 and DI-T-4905 will usually be required for delivery in connection with this specification. When so required, such data will be specified for delivery on a DD Form 1 included in the contract.

*6.3 Sample. For information regarding the availability of sample of t valuables, specified, address inquiry to procuring activity issuing the Invitation for Bids.

*6.4 First article. Examinations, test and approval shall be as specifi by the contracting officer (see 3.2).

*6.5 Marginal notations. The margins of this specification are marked an asterisk to indicate where changes (additions, modifications, correcti deletions) from the previous issue were made. This was done as a convenie only and the Government assumes no liability whatsoever for any inaccurac in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship of the last previous issue.

Preparing activity:
Navy - MC
Project No. 8105-N197

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:54Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12502 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding General (Code 826)
Marine Corp Supply Activity
1100 South Broad Street
Pbiladelphia, Pa 19146

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-01-16 13:54:22
Check the source to verify that this is the current version before use.