MIL-P-1747G
23 May 1980
SUPERSEDING
MIL-P-1747F
30 June 1972

MILITARY SPECIFICATION

PAN, BAKING AND ROASTING, ALUMINUM; PAN, COVER, AND WARMER ADAPTER: FOR RANGE, FIELD, GASOLINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an aluminum baking and roasting pan, with cover and an aluminum adapter to convert the pan to a warming table.

1.2 Classification. The pan, the pan cover, the adapter and the complete set shall be of the following items as specified (see 6.2).

Item 1 - Pan only
Item 2 - Cover only
Item 3 - Adapter only
Item 4 - Pan, pan cover, and adapter

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

FF-R-556	-	Rivet, Solid, Small; Rivet, Split, Small; Rivet, Tubular, Small; Burr; and Cap, Rivet; General Purpose
QQ-A-250/2	-	Aluminum Alloy 3003, Plate and Sheet
QQ-A-250/8	-	Aluminum Alloy 5052, Plate and Sheet
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads for 40" x 48" Pallets
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

2-9-37 - Pan, Baking and Roasting, Aluminum: Pan, Cover, and Warmer Adapter; for Range, Field, Gasoline: Pan and Cover
2-9-286 - Pan, Baking and Roasting, Aluminum: Pan, Cover, and Warmer Adapter: for Range, Field, Gasoline; Warmer Adapter

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A 580 - Stainless and Heat-Resisting Wire
B 209 - Aluminum-Alloy Sheet and Plate

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 20260-16T13:42Z
Check the source to verify that this is the current version before use.

DOCUMENTATION TABLE FOR SUCH SUBUNITS. CONTAINERS AND PACK AT THE LOWEST LEVEL

3.2 Materials and components. Materials and components shall be as specified herein. Material not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial product provided the completed item complies with all provisions of this specification (see 6.4).

3.2.1 Aluminum.

3.2.1.1 Alloy 3003. Aluminum alloy 3003 sheet shall conform to temper 0 or F of QQ-A-250/2.

3.2.1.2 Alloy 5052. Aluminum alloy 5052 sheet shall conform to temper 0 of QQ-A-250/8.

3.2.1.3 Alloy 3004. Aluminum alloy 3004 sheet shall conform to temper 0 or F of ASTM B 209.

3.2.2 Stainless steel.

3.2.2.1 Sheet. Stainless steel sheet shall conform to type 302 or 304 of ASTM A 167.

3.2.2.2 Wire. Stainless steel wire shall conform to type 302 or 304 of ASTM A 580.

3.2.3 Rivets. Rivets shall conform to type VI, grade C of FF-R-556.

3.3 Design and construction. The design and construction of the pan, pan cover, and adapter shall conform to the requirements specified herein and Drawings 2-9-37 and 2-9-286.

3.3.1 Welding. Welding shall be continuous, smooth, and uniform and shall not be porous, cracked, or incompletely fused. All flux deposits and scale shall be removed.

3.3.2 Rivets. Rivets shall conform to 3.2.3 and shall be securely set. The heads shall be smooth and in full contact with the surface of the riveted member, concentric with holes, and neatly headed.

3.3.3 Handle retainers. The retainers shall be fabricated of stainless steel specified in 3.2.2.1. The retainers shall have handle stops to prevent handles from elevating beyond a horizontal position and the handle assembly shall not fail or permanently deform when the pan is load tested as specified in 4.5.1. The handle stops shall not extend beyond the overall dimension of the retainer when attached to the pan. Each retainer shall be attached to the pan with a minimum of four rivets specified in 3.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

3.3.4 Handles. The body handles shall have a minimum diameter of 0.300 inches and be fabricated of stainless steel wire specified in 3.2.2.2. The handle configuration for the retainer used shall have inside dimensions of 4 inches wide and 2 inches deep, plus or minus 1/4 inch, when in the horizontal position.

3.4 Finish. The inside surfaces of the pan and cover shall have a No. 3 (100 grit) finish. The adapter, and outside surfaces of the pan and cover shall have a satin finish.

3.5 Marking for identification. Each pan and cover shall be marked with the letters "US" and the manufacturer's name, trade name, or trademark in the size and location shown on Drawing 2-9-37. The surface opposite the markings shall show no signs of penetration, unevenness or distortion of the surfaces.

3.6 Workmanship. The finished pans, covers, and adapters shall be free of cracks, dents, malformation, or deep scratches. All burrs, slivers, splinters, sharp edges, dirt, grease, and foreign matter shall be removed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required, it shall be examined for the defects listed in table I, compliance with dimensions specified on referenced drawings, and the pan (item 1) tested as specified in 4.5.1. The presence of any defect listed in table I or any dimension not within specified requirements shall be cause for rejection of the first article. Failure to pass the test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise indicated herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:42Z
Check the source to verify that this is the currentversion before use.

for delivery. An examination shall

4.4.2 End item inspection. The inspection lot shall consist of all pans, covers, or adapters, as applicable, offered for inspection at one time. The sample unit shall be one pan (item 1), one cover (item 2), one adapter (item 3), or one pan, cover, and adapter (item 4), as applicable.

4.4.2.1 Visual examination. The pans, covers, and adapters, as applicable, shall be examined for defects in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not as specified	X	
Construction and workmanship (general)	Cracked, dented, or malformed	X	
	Burrs, slivers, splinters, or sharp edges not removed	X	
	Dirt, grease, or foreign matter	X	
	Scratches on exterior surfaces	X	
	Scratches deep enough to impede progress of fingernail when drawn across on interior of body or cover	X	
Welding	Weld not properly fused, not continuous, flux deposits or scale not removed, cracked, porous	X	
Rivets	Not securely set	X	
	Rivet head not smooth	X	
	Rivet head not in full contact with surface of part riveted	X	
Handle retainers	Not equipped with handle stops	X	
	Not attached to pan with at least four rivets	X	
Handle	Body handles do not move freely		X
	Body handles do not move at all	X	
Marking	Missing, incomplete, illegible, not in proper location		X
	Surface opposite marking is penetrated, uneven, or distorted		X

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:42Z
Check the source to verify that this is the currentversion before use.

4.4.2.2 Dimensional examination. Examination shall be made of the pans, covers, or adapters, as applicable, to determine compliance with dimensions specified on applicable drawings. Any nonconformance to dimension specified shall be considered a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in defects per hundred units.

4.4.2.3 End item testing. The pan (item 1) shall be tested in accordance with 4.5.1. Failure to pass the test shall be cause for rejection of the pan. The inspection level shall be S-1 with an AQL of 4.0, expressed in defects per hundred units.

4.4.3 Packaging inspection. An examination shall be made to determine that packing and marking as required by section 5 are complied with. Defects shall be as specified in table II. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 with an AQL of 6.5, expressed in terms of defects per hundred units.

TABLE II. Packaging inspection

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing or damaged.
Contents	Not as specified.

4.4.4 Examination of palletization. An examination shall be made to determine that palletization is in compliance with 5.2. Defects shall be as indicated in table III. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in defects per hundred units.

TABLE III. Examination of palletization

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Loads not bonded with required straps specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

4.5 Test method.

4.5.1 Load test. The completed pan (item 1) shall be uniformly loaded to 130 pounds (including the weight of the pan) and lifted three times by the two end handles from the floor to a table height of 36 inches, plus or minus 3 inches. The retainer handle stops and handle elevation shall be examined to determine compliance with 3.3.3. Any nonconformance with specified requirements shall constitute failure of this test.

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Pans with covers and adapters. Each pan with adapter placed in the pan and cover in place shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V3s of PPP-B-636. The handle on the cover shall be blocked with fiberboard forms to prevent damage to the shipping container. Components shall be cushioned as necessary to prevent movement or damage while in transit. Each shipping container shall be closed, in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.1.1.2 Covers only. Two covers shall be offset nested and packed in a snug-fitting fiberboard shipping container as specified in 5.1.1.1. The handles shall be blocked and the covers cushioned as specified in 5.1.1.1.

5.1.1.3 Adapters only. Two adapters shall be offset nested and packed in a snug-fitting fiberboard shipping container as specified in 5.1.1.1. The adapters shall be cushioned as specified in 5.1.1.1.

5.1.1.4 Pans only. Two pans, placed top to top, shall be packed in a snug-fitting fiberboard shipping container as specified in 5.1.1.1. A fiberboard separator pad shall be placed between the two pans.

5.1.2 Level B.

5.1.2.1 Pans with covers and adapters (item 4). Each pan with adapter placed in the pan and cover in place shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety optional, or type SF, class domestic, grade 200 of PPP-B-636. Blocking and cushioning shall be as specified in 5.1.1.1. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.1.2.2 Covers only (item 2). Two covers shall be offset nested and packed in a snug-fitting fiberboard shipping container as specified in 5.1.2.1. The handles shall be blocked and the covers cushioned as specified in 5.1.1.1.

5.1.2.3 Adapters only (item 3). Two adapters shall be offset nested and packed in a snug-fitting fiberboard shipping container as specified in 5.1.2.1. The adapters shall be cushioned as specified in 5.1.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

5.1.2.4 Pans only (item 4). Two pans, placed top to top, shall be packed in a snug-fitting fiberboard shipping container as specified in 5.1.2.1. A fiberboard separator pad shall be placed between the two pans.

5.1.2.5 Weather-resistant fiberboard shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.1.3 Commercial. The pans, covers, and adapters shall be packed in accordance with MIL-STD-1188.

5.2 Palletization. When specified (see 6.2), pans, covers, and adapters, or pans alone, covers alone, or adapters alone packed as specified shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.3 Marking. In addition to any special marking required by the contract, shipping containers and pallet loads shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The pans and covers are for baking and roasting in field kitchens, with the gasoline field range. The pan cover may also be used as a griddle for frying. The adapter is intended for use with inserts from the insulated food container covered in MIL-F-10870 to adapt the baking and roasting pan for use as a warming table.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Items and number of items required (see 1.2).
(c) When first article is required (see 3.1, 4.3, and 6.3).
(d) Selection of applicable level of packing (see 5.1).
(e) When weather resistant fiberboard shipping containers are required for level B packing (see 5.1.2.5).
(f) When palletization is required (see 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample and should consist of one unit. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:42Z
Check the source to verify that this is the current version before use.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD
Navy - CG, MC

Preparing activity:

Army - GL

Project No. 7330-0518

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES (Mr. D. Juppino)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:42Z
Check the source to verify that this is the current version before use.