20 September 1976
SUPERSEDING
MIL-P-1814D
14 April 1969

MILITARY SPECIFICATION

PAD, SHOULDER, PACKBOARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size shoulder pad made of cotton drill, webbing, and wool felt. The pad is equipped with shoulder strap loops.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

C-F-206	-	Felt, Sheet: Cloth, Felt, Wool, Pressed
V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
CCC-C-426	-	Cloth, Drill, Cotton
CCC-D-950	-	Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20	-	Label; for Clothing, Equipage and Tentage, (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:45Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-F-2312	-	Felt, Hair or Wool: Mildew Resistant, and Moisture Resistant Treatment for
MIL-T-43566	-	Tape, Textile, Cotton, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads for 40" x 48" Pallets

DRAWING

ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

2-10-36	-	Pad, Shoulder, Packboard

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:45Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Cloth, drill, cotton. The cloth, before finishing, shall conform to type 1, class 1 of CCC-C-426.

3.1.1.1 Color and treatment. The cloth shall be dyed Olive Drab 7 and shall conform to type I, class B of CCC-D-950. The physical requirements for twills specified in CCC-D-950 shall apply to the finished cloth, except that the hydrostatic resistance requirement shall not apply.

3.1.2 Tape, cotton. The cotton tape shall be dyed Olive Drab 7 and shall conform to type I, class 4, 3 inches wide of MIL-T-43566.

3.1.3 Webbing, cotton. The cotton webbing shall be dyed Olive Drab 7 and shall conform to type IIa, class 4, 3/4 inch wide of MIL-W-530.

3.1.4 Thread, polyester. The polyester thread shall conform to type I, class 1, sub-class A, size F of V-T-285.

3.1.4.1 Color. The thread shall be dyed Olive Drab S-1 (C.A. 66022).

3.1.5 Felt, sheet, wool. The wool felt shall be 3/16 inch thick conforming to type I, classification 9R5 of C-F-206.

3.1.5.1 Treatment. The felt shall be mildew resistant and moisture resistant treated conforming to type III of MIL-F-2312.

3.2 Construction. The construction shall conform in all respects to Drawing 2-10-36 and shall be as specified herein.

3.2.1 Stitches, seams and stitching. All seams and stitching shall conform to FED-STD-751, and shall be stitch type 301 with 6 to 8 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:45Z
Check the source to verify that this is the current version before use.

3.2.1.1 Type 301 stitching. Thread breaks in stitching shall be overstitched not less than 1 inch back of the break. Ends of all stitching shall be backstitched or backtacked not less than 1 inch except where ends are caught in other seams and stitching. Thread tension shall be maintained so that there will be no loose or tight stitching and the lock will be imbedded in the materials sewed. All thread ends shall be trimmed.

3.3 Marking. The identification marking shall be applied in the location shown on the drawing and shall conform to type IV, class 5 of DDD-L-20. The marking "US" shall be applied in the size characters and in the location indicated on the drawing, and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.4 Workmanship. The finished pad shall conform to the quality and grade of product established by this specification. Occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 In-process inspection. Inspection shall be made at any phase of the manufacturing process to determine whether cut parts, dimensional and material requirements, operations and assemblies are as specified. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T13:45Z
Check the source to verify that this is the current version before use.

4.2.3 Examination of the end item. Defects found during this examination shall be scored as listed in 4.2.3.1 and 4.2.3.2. The sample unit shall be one completely fabricated shoulder pad. The acceptable quality level (AQL) and inspection level for this examination shall be as specified in 4.2.3.3.

4.2.3.1 Examination for visual characteristics.

Examine	Defect	Classification Major	Classification Minor
Webbing, cloth, and tape	Any hole, cut, tear or smash	X	
	Any abrasion mark, or broken or missing yarn		X
	Any mend, darn, patch or splice	X	
Webbing	Nor firmly or tightly woven, edge frayed or scalloped	X	
Open seam	1/2 inch or less		X
	More than 1/2 inch	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more continuous skipped stitches or run-offs occur.		
Raw edge (on edge required to be turned under)	Any raw edge when securely caught in stitching		X
	NOTE: Raw edge not securely caught in stitching shall be scored as "Open seam".		
Run-off	(To be scored as "Open seam")		
Stitch or seam type	Wrong seam or stitch type	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:45Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Stitch tension	Loose tension, resulting in a loose seam		X
	Tight tension, resulting in puckering of seam		X
Stitches per inch	One stitch less than minimum specified		X
	Two or more stitches less than minimum specified	X	
	One stitch in excess of maximum specified		X
	Two or more stitches in excess of maximum specified	X	
Stitch margin	Not as specified, affecting serviceability	X	
End of stitching	Not backstitched or secured as specified	X	
Thread break	Not backstitched as specified		X
	NOTE: Thread breaks not backstitched shall be scored as "Open seam".		
Stitching	Any required row of stitching omitted	X	
	Needle chews		X
Components and assembly	Any component part omitted or not as specified, or any required operation omitted (unless otherwise classified herein)		X
	Ends of webbing not turned under and caught in stitching	X	
	Component part not of one piece construction		X
Cleanness	Noticeable grease or oil stains, 3/4 inch or more in longest dimension		X
	Thread ends not trimmed		X

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:45Z
Check the source to verify that this is the currentversion before use.

4.2.3.2 Dimensional examination. The pad shall be examined for defects in dimensions. Any dimension not within the established tolerance shall be classified as a defect.

4.2.3.3 Inspection level and AQL. The inspection levels and AQLs expressed in defects per hundred units shall be as follows:

Examination	Inspection level	AQL	
		Major	Total (major and minor)
For defects applicable to 4.2.3.1	II	2.5	6.5
For defects applicable to 4.2.3.2	S-3	---	4.0 (one class)

* 4.2.4 Packaging inspection.

* 4.2.4.1 Examination for preservation-packaging, packing and marking. An examination shall be made to determine that preservation-packaging, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it shall not be palletized and need not be closed. Shipping containers fully prepared for delivery that have not been palletized shall be examined for defects of closure. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing Any component damaged, affecting serviceability
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling Bulged or distorted container

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:45Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number of bundles per shipping container is more or less than required Number of pads per bundle is more or less than required 1/

1/ For this defect, five bundles shall be examined from each shipping container in the sample.

4.2.4.2 Examination for palletization. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimensions	Length, width or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application

* 5. PACKAGING

* 5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Ten pads shall be neatly stacked in a bundle with the identification marking visible. The bundle shall be securely tied at each end with cotton tape or twine.

* 5.1.2 Level C. Pads shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice when it meets these requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:45Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

* 5.2.1 Level A packing. Five hundred pads, preserved-packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A bundles shall be packed on edge, two in length, five in width, and five in depth within a shipping container. The inside dimensions of each shipping container shall approximate 24 inches in length, 18-3/4 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

* 5.2.2 Level B packing. Five hundred pads, preserved-packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A bundles shall be packed on edge, two in length, five in width, and five in depth within a shipping container. The inside dimensions of each shipping container shall approximate 24 inches in length, 18-3/4 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.2.3 Level C packing. Pads, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

* 5.3 Palletization. When specified (see 6.2), pads packed as specified in 5.2 shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:45Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The shoulder pad is designed for attachment to shoulder straps of packboards to protect the wearer of the packboards from the cutting action of the shoulder straps.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(c) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2).
(d) When palletization is required (see 5.3).

6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Preparing activity:

Army - GL

Project No. 8465-0436

Review activities:

Navy - MC
DSA - CT

User activity:

Army - MI

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-703-020/035

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

PAD, SHOULDER, PACKBOARD MIL-P-1814E

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:45Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD T
Natick, MA 01760

NATICK OP 1 Apr 76

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:45Z
Check the source to verify that this is the current version before use.