MIL-R-1982F
31 March 1986
SUPERSEDING
MIL-R-1982E
29 December 1977

MILITARY SPECIFICATION

ROLLS, CUTLERY, CANVAS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers canvas cutlery rolls.

1.2 Classification. Cutlery rolls shall be of the following types, as specified (see 6.2):

Type I - Component of Cooking Outfit, Field, Small Detachment
Type II - Component of Accessory Outfit, Field Range, Gasoline

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester
KK-L-271 - Leather, Cattlehide, Strap, Vegetable-Tanned

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

CCC-C-419 - Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army and Numbered
CCC-D-950 - Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20 - Label; For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-T-43566 - Tape, Textile, Cotton, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-7-44 - Roll, Cutlery, Canvas, Type I; Assembly and Sections
5-7-45 - Roll, Cutlery, Canvas, Type I; Details
5-7-102 - Roll, Cutlery, Canvas, Type II; Assembly and Sections
5-7-103 - Roll, Cutlery, Canvas, Type II; Patterns and Details

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following document of the issue in effect on the date of invitation for bids or request for proposal forms a part of this document to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, (except for associated detail specifications, specification sheets or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials and components. The materials specified shall conform to applicable documents and requirements specified herein.

3.2.1 Cloth, duck, cotton. Cloth, before finishing, shall conform to type I, No. 6 hard texture and No. 10 hard texture of CCC-C-419.

3.2.1.1 Color and treatment. Cloth shall be dyed Olive Drab 7 and shall conform to type I, class B of CCC-D-950.

3.2.2 Tape, textile, cotton. Tape shall be 3/4- and 1-inch widths, Olive Drab 7 and shall conform to type I, class 4 of MIL-T-43566.

3.2.3 Webbing, textile, cotton. Webbing shall be 2-inch width, Olive Drab 7 and shall conform to type IIb, class 4 of MIL-W-530.

3.2.4 Thread, polyester. Thread for all stitching shall conform to type I, class 1, size FF of V-T-285. The thread shall be dyed shade S-1 (CA 66022).

3.2.5 Leather, cattlehide. Leather for the scabbards, in the thicknesses specified on Drawings 5-7-45, 5-7-102, and 5-7-103, shall conform to type I, II, III, or IV, class 1 of KK-L-271, except that the colorfastness

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

requirements shall not be applicable. The color of the leather shall be natural as produced by the tanning agents. A top finish need not be applied to the leather.

3.3 Construction. Construction of the cutlery rolls shall conform to the drawings listed in section 2 and shall be as specified herein.

3.3.1 Stitching, machine.

3.3.1.1 Stitch type. All stitching shall conform to type 301, 6 to 8 stitches per inch, of FED-STD-751.

3.3.1.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch at each break.

3.3.1.3 Stitching ends. Stitching at the ends shall be overstitched not less than 1 inch, except where ends are turned under in a hem or held down by other stitching. Where stitching is performed automatically on stitch patterns such as box, box with cross-stitch, "W" stitching, or straight line tacking, at least three or more tying, overlapping, or backstitches shall be used to secure the ends.

3.3.1.4 Skipped stitches. Two or more skipped stitches occurring consecutively in type 301 stitching shall be overstitched not less than 1 inch.

3.4 Marking. All marking and labels shall conform to DDD-L-20.

3.4.1 Identification marking. Identification marking shall be in the location shown on Drawing 5-7-44 or 5-7-102, as applicable, and shall conform to type IV, class 5.

3.4.2 Special marking. The item nomenclature, the letters "US", the pocket numbers, and marking on the contents labels, in the location shown on Drawings 5-7-44 for type I or 5-7-102 for type II, shall conform to type IV, class 9, except that fastness shall be as specified for class 5 labels. Copy for the contents lists for types I and II rolls shall be as listed in tables I and II, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

TABLE I. Contents list for type I rolls

Pocket No.	Item	Quantity
1	Fork, food preparation, 2-tine 15 inch	1
2	Stone, sharpening, pocket, 3 1/2 inch by 1 1/4 inch by 13/16 inch	1
3	Spoon, basting, 15 inch	1
4	Knife, cooks, 12 inch blade	1
5	Knives, paring	2
6	Openers, can, hand	2

TABLE II. Contents list for type II rolls

Pocket No.	Item	Quantity
1	Spoon, basting, 15 inch	2
2	Fork, food preparation, 15 inch	2
3	Knife, steak, scimitar	1
4	Knife, cook's	1
5	Knife, boning	1
6	Knife, paring	2
7	Peeler, potato, hand	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

TABLE II. Contents list for type II rolls - Continued

Pocket No.	Item	Quantity
8	Steel, butcher's, smooth	1
9	Measuring set, spoon	1
10	Saw, butcher's	1

3.5 Workmanship. Cloth components shall be free of holes, cuts, tears, or cloth defects such as multiple floats or broken or missing yarns. Webbing and tape shall not have frayed or scalloped edges. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained with seams properly sewed so that no runoffs, pleats, twists, or open seams shall result. Care shall be taken in sewing to see that no needle chews occur. All thread ends shall be trimmed to 1/2 inch or less. Scabbards shall be free from any hole, cut, or loose spongy leather.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1), it shall be examined for the defects specified in table III and the specified dimensions. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Component dimensional examination. Examination shall be made of the cut dimensions of pocket pieces as shown on Drawings 5-7-45 and 5-7-103 for types I and II, as applicable. The lot shall be all pieces of the same letter designation offered for inspection at one time. The sample unit shall be one pocket piece. The inspection level shall be S-2, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.2 End item visual examination. The end item shall be examined for the defects listed in table III. The lot size shall be expressed in units of rolls. The sample unit shall be one roll. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Fabric	Any hole, cut, or tear	X	
	Broken or missing yarn, multiple floats visible at normal inspection distance (approximately 3 feet)		X
	Shade bar		X
	Fine or coarse filling bar		X
Seams and stitching	Open seam:		
	-for more than 1 inch	X	
	-for not more than 1 inch		X
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when one or more skipped or runoff stitches occur. On double-stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.		
	Raw edge more than 1/2 inch	X	
	Thread break overstitched less than 1 inch		X
	NOTE: Thread breaks not overstitched shall be classified as open seams.		
	Skipped stitches overstitched less than 1 inch (when two or more consecutive skipped stitches occur)		X
	NOTE: Skipped stitches not overstitched shall be classified as open seams.		
	Needle chew resulting in cut or tear larger than 1/8 inch in length or hole larger than 1/8 inch in diameter		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Seams and stitching (continued)	One or more required rows of stitching omitted	X	
Stitching ends	Overstitched less than 1 inch (except where ends are held down by other stitching or turned under in a hem)		X
Seams	Seam pleated		X
Seam type	Wrong seam type	X	
Stitch type	Wrong stitch type	X	
Stitch tension	Loose, resulting in exposed bobbin or top thread, for more than 2 inches		X
	Tight, as evidenced by puckering of fabric on seams, for more than 2 inches		X
Stitches per inch	Less than minimum specified		X
	More than maximum specified		X
Stitching gage	Not as specified		X
Stitching margin	Variation from specified margin by more than 1/16 inch	X	
Binding	Loosely or improperly applied		X
Scabbard	Hole, cut, or loose spongy leather		X
Components and assembly	Any component part not fabricated of applicable referenced material	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Markings	Omitted, incorrect, illegible, or misplaced		X
Cleanness	Grease or oil stains, thread ends not trimmed to 1/2 inch or less		X

* 4.4.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of rolls. The sample unit shall be one roll. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

* 4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed in table IV. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Table IV. Packaging defects

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

Table IV. Packaging defects - Continued

Examine	Defect
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

* 4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed in table V. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Table V. Palletization defects

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Type I. Each roll shall be folded in half the length, with the tie tapes tucked under the cover. Fifteen folded rolls stacked one on another and alternated side to side shall then be cross-tied with cotton tape or twine to form a bundle measuring approximately 15 1/2 by 15 1/4 by 15 inches.

5.1.1.2 Type II. Each roll shall be folded in a closed position with the tie tapes tucked under the cover. Each roll shall then be folded in half the length. Ten rolls shall be alternately stacked end-for-end to form a bundle measuring approximately 17 1/2 inches in length, 10 3/4 inches in width, and 8 3/4 inches in depth. The bundle shall be securely tied at each end with cotton tape or twine.

5.1.2 Commercial. Rolls shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Type I. Thirty rolls, preserved as specified in 5.1, shall be packed in a shipping container conforming to overseas type, style A or I, type 2 load of PPP-B-601. Level A unit packs shall be packed flat, two in length, one in width, and two in depth within a shipping container. Inside dimensions of the shipping container shall be approximately 31 inches in length, 15 1/4 inches in width, and 15 1/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed and reinforced in accordance with the appendix of PPP-B-601.

5.2.1.2 Type II. Forty rolls, preserved as specified in 5.1, shall be packed in a shipping container conforming to overseas type, style A or I, type 2 load of PPP-B-601. Level A unit packs shall be packed flat, two in length, one in width, and two in depth, within a shipping container. Inside dimensions of the shipping container shall be approximately 22 inches in length, 18 inches in width, and 17 1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed and reinforced in accordance with the appendix of PPP-B-601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing.

5.2.2.1 Type I. Thirty rolls, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to type CF, class domestic, variety SW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, two in length, one in width, and two in depth within a shipping container. Inside dimensions of the shipping container shall approximate 31 inches in length, 15 1/4 inches in width, and 15 1/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.2 Type II. Forty rolls, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each fiberboard shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, two in length, one in width, and two in depth, within a shipping container. Inside dimensions of the shipping container shall approximate 22 inches in length, 18 inches in width, and 17 1/2 inches in depth. Approximate dimensions are furnished as a guide only. Shipping containers shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.3 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial Packing. Rolls, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), cutlery rolls packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia, as applicable, of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be Number 94 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The type I roll is a component of the Cooking Outfit, Field, Small Detachment; the type II roll is a component of the Accessory Outfit, Field Range, Gasoline; and both are intended to carry and store various food preparation utensils (see 3.4.2).

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type required (see 1.2).
c. When a first article is required (see 3.1, 4.2, and 6.3).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B shipments (see 5.2.2.3).
f. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, it shall be inspected and approved under appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for inspection and approval of the first article.

6.4 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
Navy - MS, MC
Air Force - 84
DLA - GS

Preparing activity:

Army - GL

Project No. 7360-0155

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-1982F	Rolls, Cutlery, Canvas

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil - Downloaded: 2026-10-16T13:55Z
Check the source to verify that this is the current version before use.