MIL-S-1837H
25 March 1977
SUPERSEDING
MIL-S-1837G
12 August 1969

MILITARY SPECIFICATION

SPRAY GUN, INSECTICIDE DUSTING POWDER AND CONTAINER, POWDER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an insecticide dusting powder spray gun and powder container.

1.2 Classification. The spray gun and container covered by this specification shall be of the item specified (see 6.2):

Item 1 - Spray gun, including container, powder.

Item 2 - Container, powder.

* 2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command (GL), Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3740

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-390	-	Plastic, Molding and Extrusion Material, Polyethylene and Copolymers (Low, Medium, and High Density)
QQ-A-250/11	-	Aluminum Alloy 6061, Plate and Sheet.
QQ-A-596	-	Aluminum Alloy Permanent and Semipermanent Mold Castings
QQ-A-601	-	Aluminum Alloy Sand Castings
QQ-B-613	-	Brass, Leaded and Nonleaded; Flat Products (Plate, Bar, Sheet, and Strip)
QQ-B-626	-	Brass, Leaded and Nonleaded: Rod, Shaped, Forgings, and Flat Products with Finished Edges, (Bar and Strip)
QQ-B-654	-	Brazing Alloys, Silver
QQ-S-637	-	Steel Bar, Carbon, Cold Finished, (Standard Quality, Free Machining)
QQ-S-698	-	Steel, Sheet and Strip, Low-Carbon
QQ-W-423	-	Wire, Steel, Corrosion-Resisting
TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings
TT-E-529	-	Enamel, Alkyd, Semigloss
TT-P-636	-	Primer Coating, Alkyd, Wood and Ferrous Metal
WW-T-791	-	Tube, Brass, Seamless
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-F-320	-	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

MILITARY

MIL-R-3065	-	Rubber, Fabricated Products
MIL-C-4109	-	Coupling Assembly, Low Pressure, Air Hose, Quick-Disconnect
MIL-A-8625	-	Anodic Coatings, for Aluminum and Aluminum Alloys
MIL-P-10971	-	Pins, Spring Tubular (Coiled and Slotted)

STANDARDS

FEDERAL

FED-STD-595	-	Colors
FED-STD-601	-	Rubber: Sampling and Testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-417 - Rubber Compositions, Vulcanized General Purpose, Solid (Symbols and Tests)

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

2-5-37 - Spray Gun, Dusting Powder, Insecticide, and Container, Assembly and Details
2-5-59 - Spray, Gun, Dusting Powder, Insecticide; and Container; Details
2-5-78 - Spray Gun, Dusting Powder, Insecticide; and Container; Container Support and Cover and Assembly

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL BUREAU OF STANDARDS (NBS)

Handbook H-28 - Screw Thread Standards for Federal Services

(Application for copies of Handbook H-28 should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 108 - Steel Bars, Carbon Cold Finished, Standard Quality

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. Unless otherwise specified (see 6.2), the contractor shall furnish a sample unit for first article inspection and approval, (see 4.3 and 6.3).

3.2 Materials and components. Materials and components not definitely specified shall be of the quality normally used for the purpose in commercial practice.

3.2.1 Steel.

3.2.1.1 Steel, sheet and strip, low carbon. Low carbon steel sheet and strip shall be cold rolled conforming to QQ-S-698.

* 3.2.1.2 Steel, bar, carbon, cold finished standard quality. Carbon steel bar shall be cold rolled half hard, 1010, flat with rounded edges conforming to ASTM A 108.

3.2.1.3 Steel bar, carbon, cold finished, standard quality, free machining. Free machining, standard quality, cold finished, carbon steel bars shall be grade 12L14, round, conforming to QQ-S-637.

3.2.2 Aluminum.

* 3.2.2.1 Sand castings. The aluminum sand castings shall conform to 295-T6, 208-F, or 356-T6 of QQ-A-601.

3.2.2.2 Mold castings. The aluminum mold castings shall be alloy B195, any temper of QQ-A-596.

3.2.2.3 Plate. The aluminum plate shall conform to QQ-A-250/11.

* 3.2.3 Plastic material. The plastic material shall be type I, class H, grade 2, 4 or 5 of L-P-390.

* 3.2.4 Silver solder. The silver solder shall conform to grade IV of QQ-B-654.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

3.2.5 Brass.

3.2.5.1 Bar stock. The brass bar stock shall conform to either copper alloy No. 260, half-hard of QQ-B-613 or alloy No. 360, half hard of QQ-B-626.

* 3.2.5.2 Tubing. The brass tubing shall conform to grade A, type 1, semi-annealed of WW-T-791.

3.2.6 Spring pins. The spring pins shall be of the size shown on Drawing 2-5-37 and shall conform to type 1, class, composition A or B of MIL-P-10971. Composition A and B pins shall be cadmium plated.

3.2.7 Machine and set screws. The machine and set screws shall be either corrosion-resisting steel or zinc or cadmium plated carbon steel and shall conform to the requirements specified on the drawings. The threads shall conform to the requirements of Handbook H-28.

* 3.2.8 Gaskets. The gaskets shall be the dimensions shown on Drawing Nos. 2-5-37 and 2-5-59 and shall be type S, class SC, grade 515 of MIL-STD-417 and MIL-R-3065.

3.2.9 Corrosion-resisting steel wire. The corrosion-resisting steel wire shall be composition 304, condition B conforming to QQ-W-423.

* 3.2.10 Air hose coupling. The air hose coupling shall conform to type II class A, style 1 of MIL-C-4109 and shall be 1/4 inch (6.4 mm) size.

3.2.11 Primer. Primer shall conform to TT-P-636.

3.2.12 Enamel. The enamel shall be semigloss and shall conform to class A or B of TT-E-529. The color shall match color No. 24087 (olive drab) of FED-STD-595.

* 3.3 Construction. The spray gun shall be of the pistol type and shall consist of a handle containing a trigger air control and a removable powder container. The spray gun assembly and components shall conform to the design, detail and construction requirements of Drawings 2-5-37, 2-5-59, and 2-5-78 and as specified herein.

3.3.1 Container support and cover assembly. The container support and cover shall be fabricated from steel specified in 3.2.1.1. Lugs shall be fabricated from steel bar specified in 3.2.1.2. The nuts shall be fabricated from steel specified in 3.2.1.3.

3.3.2 Handle. The handle shall be cast of aluminum specified in 3.2.2.1 or 3.2.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

3.3.3 Trigger. The trigger shall be either cast or stamped. The trigger when cast shall be aluminum specified in 3.2.2.1 or 3.2.2.2. The trigger when stamped shall be fabricated from aluminum plate specified in 3.2.2.3.

3.3.4 Container. The powder container shall be fabricated of plastic specified in 3.2.3.

* 3.4 Brazing. The discharge nozzle shall be brazed to the discharge tube with solder specified in 3.2.4, and as shown on Drawing 2-5-37.

* 3.5 Cementing. The rubber gasket shall be cemented to the inside of the spray gun cover in the location shown on Drawing 2-5-37 in accordance with commercial practice.

3.6 Finish.

* 3.6.1 Zinc plating. Prior to assembly, the dusting gun nuts and the threaded area of the weld screws shall be given a bright zinc coating, 0.0002 to 0.0003 inch (0.005 to 0.008 mm) thick in accordance with commercial practice.

3.6.2 Aluminum components. Prior to assembly, components fabricated of aluminum shall be anodized in accordance with type II of MIL-A-8625.

3.6.3 Pretreatment. Steel components, except for zinc plated nuts and threaded area of weld screws, shall be pretreated in accordance with type I or II of TT-C-490. Brass components shall be cleaned in accordance with the manufacturers commercial practice.

3.6.4 Priming. Components pretreated as specified in 3.6.3 shall be given a coat of primer specified in 3.2.11.

3.6.5 Enameling. After anodizing specified in 3.6.2 and priming specified in 3.6.4, components with the exception of the powder container shall be assembled for enameling. A coat of the enamel specified in 3.2.12 shall be applied to the exterior surfaces of the spray gun, except that the zinc coated nuts and the threaded area of the weld screws shall not be enameled.

3.7 Performance.

* 3.7.1 Leakage. The spray gun, with a pressure of 10 pounds per square inch gage (69 kPa), shall show no evidence of air leakage when tested as specified in 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

3.7.2 Discharge capacity. When tested as specified in 4.5.2, the spray gun shall have the minumum discharge capacities of talcum powder specified in table I.

TABLE I. Discharge capacity of spray gun

Minimum discharge ounces per minute (grams per minute)	Inlet pressure p.s.i.g. (kPa)
3 (85)	30 (207)
1.5 (42.5)	15 (103)

* 3.8 Marking. The letters "U.S." shall be silk screened on the powder container.

3.9 Workmanship. All surfaces shall be free of burrs, slivers, and rough or sharp edges. Components shall not be broken, cracked, malformed, or loose. Welds shall be free from pits, flashes, and burn through. Enamel shall level out to a uniform dry film thickness without runs, drops, or areas of no film. The coating shall be free from imbedded foreign matter and shall show no evidence of peeling, flaking, or blistering.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required, it shall be examined for the defects listed in table II, dimensions specified, and tested as specified in 4.5.1 and 4.5.2. The presence of any visual defect or any dimension not within the specified requirements or failure to pass the tests shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Except as otherwise specified herein sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever non-conformance is noted, correction shall be made to the items affected and to the operation.

4.4.2.1 Visual examination of operations.

a. Anodizing of aluminum before assembly (see 3.6.2).
b. Pretreatment of steel and cleaning of brass components (see 3.6.3).
c. Brazing of nozzle discharge to tube discharge on spray gun (see 3.4).
d. Priming of steel and brass components (see 3.6.4).

4.4.2.2 In-process testing.

4.4.2.2.1 Durometer hardness of rubber gasket. The durometer hardness number of the rubber gasket shall be determined by Method 3021 of FED-STD-601.

4.4.3 End item inspection. The lot shall consist of all the spray guns including powder container (item 1) or all of the containers only (item 2) offered for inspection at one time. The sample unit shall be a completely fabricated spray gun with container, or one container, as applicable.

4.4.3.1 Visual examination. The end item shall be examined for defects listed in table II. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not as specified	X	
	Not color specified		X
	Area of no film		X
	Not continuous or is not smooth		X
	Contains runs, drops, or streaks		X
	Foreign matter imbedded		X
	Evidence of peeling, flaking, or blistering	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship	Any component missing	X	
	Burrs, slivers, rough or sharp edges	X	
	Any component broken, cracked, malformed, or loose	X	
Spray gun (except for container)	Handle core pin holes not soldered (where applicable)		X
	Cover gasket not cemented in place	X	
Container	Not of plastic as specified	X	
	Not white (transparent)		X
Threads	Missing, broken, stripped, or fractured	X	
Threaded fasteners	Loose		X
	Missing	X	
Welding	More than one spot weld missing, broken or not fused where specified	X	
	One spot weld missing, broken, or not as specified		X
	Spot welds not spaced as specified		X
	Not sound and free from porosity		X
	Contains flashes or burn through		X
Marking	Missing, incomplete, not legible, not specified type or size, not applied in the prescribed manner		X

4.4.3.2 Dimension and thickness of zinc plating inspection. Inspection shall be made of the end item for compliance with dimensions and thickness of zinc plating specified. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.4.4 End item testing. Each end item shall be tested as specified in 4.5.1 and 4.5.2. Any evidence of failure shall be cause for rejection of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

* 4.4.5 Packaging inspection. An inspection shall be made to determine that packaging, packing, and marking as required by section 5 are complied with. Defects shall be as indicated in table III. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The lot shall be all of the containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 4.0 expressed in terms of defects per hundred units.

TABLE III. Examination of preparation for delivery

Examine	Defect
Markings (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components, such as insufficient tape, or bulging or distortion of boxes.
Contents	Number per container not as specified.

* 4.4.5.1 Examination of shipping containers. Examination for defects in closure and strapping of shipping containers shall be in accordance with the appendix of the applicable container specification.

4.5 Test methods.

4.5.1 Air leaks. The spray gun shall have an air pressure of not less than 10 p.s.i.g. (69 kPa) applied to the inlet, with the discharge nozzle blocked. The spray gun then shall be immersed in water. The trigger shall be depressed and the spray gun observed for at least one minute for air bubbles to determine compliance with the requirements specified in 3.7.1. Any nonconformance shall constitute failure of the test. The spray gun then shall be removed from the water and dried.

4.5.2 Discharge capacity. The spray gun container shall be filled to the fill line with talcum powder and attached to the spray gun, the spray gun shall be weighed and then connected to an inlet air pressure of 15 p.s.i.g. (103 kPa).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

The trigger shall be depressed and the talcum powder discharged for one minute. The gun shall be held in a stationary horizontal position during this test. The spray gun shall then be reweighed. The weight of the talcum powder discharged shall be obtained to determine compliance with the minimum discharge requirement of 1.5 ounces (42.5 grams) per minute specified in 3.7.2. The above test shall be repeated using an inlet pressure of 30 p.s.i.g. (207 kPa) to determine compliance with the minimum discharge requirement of 3.0 ounces (85 grams) per minute specified in 3.7.2. Any noncompliance with discharge capacity requirements of 3.7.2 shall constitute failure of the test.

* 5. PACKAGING

* 5.1 Preservation-packaging. Preservation-packaging shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Item 1 (spray gun, including container). The discharge tube shall be disassembled from each spray gun and securely taped to the wide portion of the handle with pressure sensitive tape. The two openings into the spray gun shall be sealed with tape or other means. Each spray gun shall be packaged in a snug-fitting fiberboard box conforming to grade W6c or W5c, class Wr style RSC of PPP-B-636. The spray gun shall be placed in the box with the handle positioned in one corner. Each box shall be closed and waterproofed by means of tape in accordance with the appendix of PPP-B-636.

5.1.1.2 Item 2 (container). Containers shall require no packaging.

* 5.1.2 Commercial. Items shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Twenty spray guns, packaged as specified in 5.1, shall be packed upright in a snug-fitting cleated-plywood shipping container conforming to overseas type, style A or J, type 2 load of PPP-B-601. Closure and strapping shall be in accordance with the appendix of PPP-B-601. Forty containers of item 2, packaged as specified in 5.1, shall be packed upright in two layers in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Two fiberboard pads, with dimensions of one-eighth of an inch (3.2 km) less than the inside length and width of the shipping container shall be placed one between the two layers and one on the top layer. Closure, waterproofing by means of tape, and reinforcing shall be in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B packing. Twenty spray guns, packaged as specified in 5.1, shall be packed upright in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. Forty containers, packaged as specified in 5.1, shall be packed upright in two layers in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. Two fiberboard pads, with dimensions of one-eighth of an inch (3.2 km) less than the inside length and width of the shipping container shall be placed one between the two layers and one on the top layer. Closure of the containers for item 1 and item 2 shall be in accordance with method II of the appendix of PPP-B-636.

* 5.2.2.1 Weather-resistant shipping containers. When specified (see 6.2) the shipping container for items 1 and 2 shall be a grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix thereto. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Commercial packing. Items, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

* 5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The spray gun covered by this specification, when used as a component of the mass delousing insecticide duster covered by MIL-D-2457 is intended to delouse fully clothed personnel.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Item required (see 1.2).
(c) First article. When a preproduction sample is not required (see 3.1).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

6.4 Changes from previous issue. The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 3740-0077

Review activities:

Army - MD
Navy - MS

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TDG

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD G
Natick, MA 01760

NATICK OP 1 Apr 76

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-S-1837H Spray Gun, Insecticide Dusting Powder and Container, Powder

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/S

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:47Z
Check the source to verify that this is the current version before use.