MIL-T-1926G
30 June 1986
SUPERSEDING
MIL-T-1926F
12 November 1968

MILITARY SPECIFICATION

TENT, MOUNTAIN, TWO-MAN, COMPLETE WITH PINS AND POLES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size mountain tent.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

A-A-203	- Paper, Kraft, Untreated
V-T-285	- Thread, Polyester
DDD-L-20	- Label: for Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-501	- Pins, Tent, Metal
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-P-608	- Pole Section, Tent: Upright and Adapter, Tent Pole
MIL-L-1709	- Lines, Tent
MIL-C-3395	- Cloth, Netting; Nylon or Polyester
MIL-C-20696	- Cloth, Coated, Nylon, Waterproof
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-T-43566	- Tape, Textile, Cotton, General Purpose, Natural or in Colors
MIL-C-43627	- Cloth, Duck, Cotton, Plied Yarns, Fire, Water, Weather and Mildew Resistant Treated, Lightdry Finish
MIL-C-43847	- Cloth, Oxford, Cotton Warp and Cotton and Nylon Blend Filling, for Tent, Mountain, Two Man
MIL-W-44049	- Webbing, Textile and Tape, Textile, Polypropylene, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-573	- Tent, Mountain, Two-Man; Assembly, Illustration and Sections
5-4-574	- Tent, Mountain, Two-Man; Details "A" and Sections
5-4-575	- Tent, Mountain, Two-Man; Details and Sections
5-4-576	- Tent, Mountain, Two-Man; Erection Instructions

OTHER GOVERNMENT DOCUMENTS

Department of the Army Field Manual FM 10-16 - General Repair of Tents, Canvas and Webbing

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following document of the issue in effect on the date of invitation for bids or request for proposal forms a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard sample. Samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this document may appear in the sample, in which case this document shall govern.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:50Z
Check the source to verify that this is the current version before use.

3.2 Materials.

* 3.2.1 Cloth, oxford, cotton warp and cotton and nylon blend filling. The cloth used to fabricate the tent, with the exception of the floor, shall conform to MIL-C-43847.

3.2.2 Cloth, coated nylon, waterproof. The coated cloth used to fabricate the floor shall conform to type I, class 3 of MIL-C-20696. The color of the coated cloth shall match an approved standard shade sample of Olive Drab 7 (see 6.3).

* 3.2.3 Cloth, cotton duck. The cotton duck used to fabricate the floor shield shall conform to MIL-C-43627. The color shall be Olive Drab 7.

3.2.4 Cloth, nylon, netting. The netting shall conform to type I of MIL-C-3395.

3.2.5 Webbing, textile, cotton. The webbing shall be Olive Drab 7 and conform to type III, class 4, 5/8 inch width of MIL-W-530. Alternatively, the webbing shall be polypropylene conforming to type III, class 4, Olive Drab 7 of MIL-W-44049.

3.2.6 Tape, textile, cotton (dyed). The tape shall be Olive Drab 7 and conform to type I, class 4, 3/4-inch and 1 1/2-inch widths of MIL-T-43566. Alternatively, the tape shall be polypropylene conforming to type I, class 4 of MIL-W-44049.

3.2.7 Tape, textile, cotton (natural). The tape shall be natural (unbleached) and conform to type I, class 1a, 3/4-inch and 1 1/2-inch widths of MIL-T-43566.

3.2.8 Thread, polyester. The thread shall conform to type I, class 1, sub-class B, size E, natural or in color, of V-T-285.

3.2.9 Pole, tent, single section and adapter. The pole sections and adapters shall conform to MIL-P-608 and shall be furnished in the following quantities:

Pole, tent, single section	-	12
Adapter, tent pole	-	2

3.2.10 Pins, tent, aluminum, 9 inches. The pins shall conform to type I of MIL-P-501. Six pins shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the current version before use.

3.2.11 Lines, tent. The lines shall conform to types LIX and LX, class F of MIL-L-1709.

3.3 Construction. The construction shall conform in all respects to Drawings 5-4-573 through 5-4-576 and as specified herein.

3.3.1 Stitching machine. Unless otherwise specified, all stitching, except bartacking, shall conform to FED-STD-751, type 301 with 6 to 8 stitches per inch.

3.3.1.1 Type 301 stitching. Ends of all stitching, except box-X and W-W, shall be backstitched or overstitched 1-inch minimum except where ends are turned under in a hem or held down by other stitching. On box-X and W-W stitching, all ends shall be backstitched or overstitched 1/2-inch minimum. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the sewn materials. The lock shall be embedded in the materials sewn.

3.3.1.1.1 Repair of type 301 stitching. On all stitching, except box-X and W-W, thread breaks and two or more consecutive skipped stitches or run-offs shall be overstitched not less than 1 inch in each direction beyond the defective stitching area. On box-X and W-W stitching, thread breaks and two or more consecutive skipped stitches or run-offs shall be overstitched not less than 1/2 inch in each direction beyond the defective stitching area. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and by restitching in the required manner.

3.3.1.2 Bartacking. Bartacks shall be 5/8 ± 1/16 inch in length and 1/8 ± 1/32 inch in width and shall contain 28 stitches. Bartacking shall be free of thread breaks and loose stitching.

3.3.1.3 Stitch margins. Unless otherwise specified, all stitching margins shall be 1/8 ± 1/16 inch.

3.3.1.4 Automatic stitching. Automatic machines may be used to perform any of the required stitch patterns provided that the requirements for the stitch pattern, stitches per inch, size, and type of thread are met, and at least three or more tying, overlapping, or back stitches are used to secure the ends of the stitching.

3.3.1.5 Thread ends. All thread ends shall be trimmed.

3.3.1.6 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the current version before use.

3.3.2 Piecing seams. Unless otherwise specified, location of seams for piecing end, body, and floor panels is optional.

3.3.3 Attachment of loops. The flat, short (side and corner), and long loops shall be attached to panels by stitching the inside and outside loops on simultaneously, as shown on Drawing 5-4-573, or each loop may be stitched on individually.

3.3.4 Attachment of tie tapes. Unless otherwise specified, the tie tapes at point of attachment to the end panel shall be the center of the tie tape plus or minus one inch.

3.3.5 Finishing of tent lines. Each end of the guy and eave lines shall have an overhand knot tied approximately 3/4 inch from the end to prevent raveling. The eave and guy lines shall be attached to the tent by the use of bowline knots in the locations shown on the drawings.

3.3.6 Repairs. Repairs, whenever necessary and when authorized by the contracting officer, shall be effected in accordance with the Department of the Army Field Manual FM 10-16, except that hand sewn or glued patches will not be acceptable.

3.3.7 Location marks. Location and notice marks shall not be drilled unless the holes will be covered up in the finished assembly by component parts.

3.3.8 Tolerances. Unless otherwise specified, dimensional tolerances shall be as listed in table I.

TABLE I. Dimensional Tolerances

Measure (inches)	Tolerance (inches)
1/16	± 1/32
More than 1/16 but less than 2 inches	± 1/16
2 inches or more but less than 10 inches	± 1/8
10 inches or more but less than 30 inches	± 1/4
30 inches or more but less than 60 inches	± 3/8
60 inches or more	± 1/2

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:50Z
Check the source to verify that this is the current version before use.

3.4 Marking.

3.4.1 Identification. The identification marking shall be applied in the location shown on Drawing 5-4-575 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the location and in the size characters indicated on Drawing 5-4-575 and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for the class 5 marking.

3.4.2 Instruction label, erection. The erection instruction label shall be rolled and inserted in and with a suitable length of cord securely tied to one of the long loops at the ridge of the tent. The size of the label overall shall be 8 inches (± 1/4 inch) by 12 inches (± 1/4 inch) with a 1/2-inch margin all around. The information on the labels shall be proportionate copies of Drawing 5-4-576. The labels shall conform to type VI, class 7 of DDD-L-20.

* 3.4.3 Replacement of defective components. During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in 4.2.3 shall be removed from production and replaced with nondefective and properly matched components.

3.5 Workmanship. The finished tent shall conform to the quality and grade of product established by this document, and the occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z
Check the source to verify that this is the current version before use.

contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.2.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details that cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

* 4.2.3 End item visual examination. The end item shall be examined for the visual defects listed in table II. The lot size shall be expressed in units of tents. The sample unit shall be one finished tent. The inspection level shall be II, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 15.0 for major defects, 40.0 for combined major and minor A defects, and 100.0 for total combined major and minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects

Examine	Defect	Classification		
		Major	Minor A	Minor B
Cloth	Any hole (except drill holes), cut, or tear	X		
	Exposed drill holes (i.e, not covered by attached parts)		X	
	Any abrasion marks, broken or missing yarns, or multiple floats clearly visible at normal inspection distance (3 feet)	X		
	Needle chews:			
	-any on body, end, or floor panels	X		
	-on reinforcement pieces, pole sleeves, tunnel and ventilator that are 1/8 inch or more in length	X		
	-on reinforcement pieces, pole sleeves, tunnel, and ventilator that are up to 1/8 inch in length		X	
Webbing and tape	Any hole, cut, or tear	X		
	Frayed or scalloped edges, not firmly or tightly woven		X	
	Needle chews:			
	-up to 1/8 inch in length			X
	-over 1/8 inch in length		X	
Netting	Cut, tear, or hole noticeably larger than mesh openings	X		
Seams and stitching:				
Open seams	More than one inch	X		
	Up to and including 1/2 inch			X
	More than 1/2 inch but not more than one inch		X	

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - Continued				
	NOTE: A seam shall be classified as an open seam when one or more stitches joining a seam are broken, or when two or more consecutive skipped stitches or run-offs occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.			
Joining seams	Any ply of cloth or duck not securely caught in seam stitching by:			
	-more than 1 inch	X		
	-more than 1/2 inch up to and including 1 inch		X	
	-more than 1/4 inch up to and including 1/2 inch			X
Raw edges exposed (not otherwise classified under joining seams)	When securely caught in stitching:			
	-more than 1/2 inch but not more than 1 inch			X
	-more than 1 inch		X	
	NOTE: Raw edges not securely caught in stitching shall be classified as open seams.			
Seams and stitch type	Wrong seam or stitch type	X		
	Seams pleated or badly puckered		X	

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - Continued				
Stitching	Loose, resulting in loose bobbin or top thread		X	
	Tight, resulting in tightness or puckering of material		X	
Stitches per inch	One stitch less than minimum specified			X
	Two or more stitches less than minimum specified		X	
	One or more stitches in excess of maximum specified			X
	NOTE: Variation in the number of stitches per inch caused by operator speeding up the machine and pulling the material in order to sew over heavy places, or in turning corners shall be classified as follows: (a) Within the minor B defect classification - no defect (b) Within the minor A defect classification - minor B defect			
Thread breaks, skipped stitches or run-offs (on type 301 stitching)	On stitching other than box-X and W-W stitching, overstitched less than one inch in each direction beyond defective stitching area			X
	On box-X and W-W stitching, overstitched less than 1/2 inch in each direction beyond the defective stitching area			X

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - Continued				
	NOTE: Thread breaks or two or more consecutive skipped stitches or run-offs, not overstitched shall be classified as open seams.			
Stitching ends (on type 301 stitching)	Ends of stitching not secured as specified (except when caught in other stitching or turned under in a hem)		X	
Box-X and W-W stitching	Two or more rows of stitching missing	X		
	One row of stitching missing		X	
Bartacks	Any bartack omitted	X		
	Stitching loose, incomplete, or broken		X	
	Number of stitches not as specified		X	
Stitching margin	Larger than specified by more than 3/16 inch:			
	-for more than 2 inches but not more than 4 inches in length			X
	-for more than 4 inches in length		X	
	Less than specified:			
	-for more than 2 inches but not more than 4 inches in length			X
	-for more than 4 inches in length		X	

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the currentversion before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Components and assembly	Any component or required operation omitted (unless otherwise classified herein)	X		
Mends, darns, or patches	Not authorized by the contracting officer, or not in accordance with Department of the Army Field Manual 10-16, when authorized (see 3.3.6)	X		
Color of fabric and tape	Any wrong color fabric or tape component (i.e., olive drab material placed where white material is required, except floor or floor shield)	X		
	Strike-through exceeds the standard sample	X		
	Wrong color floor or floor shield			X
Binding	Loosely applied exposing raw edge of material	X		
	Loosely applied but not exposing raw edge of material			X
	Ends of binding not finished as specified			X
Guy and eave lines	Cut, chafed, or abraded	X		
	Insecurely knotted or not knotted as specified			X
Short loop - side	Any row of stitching attaching short loops to eave ends not stitched through reinforcement straps		X	

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Upper diagonal reinforcement straps	Lower ends of straps not caught under horizontal reinforcement strap	X		
	Upper ends of straps not caught under ridge reinforcement tape		X	
Lower diagonal reinforcement	Ends not caught in stitching of binding tape			X
Ridge reinforcement	Ends not caught in stitching of binding tape			X
Label, erection instructions	Omitted, incorrect, illegible, or not inserted and tied to one of the long loops on ridge reinforcement	X		
Identification markings	Omitted, incorrect, illegible, misplaced, or size of characters not as specified			X
Cleanness	Clearly noticeable grease or oil stains			X
	Thread ends not trimmed throughout			X

* 4.2.4 End item dimensional examination. The end item shall be examined for the dimensional defects listed in table III. The lot size shall be expressed in units of tents. The sample unit shall be one tent. The inspection level shall be S-3, and the AQL, expressed in terms of defects per hundred units, shall be 10.0 for major defects and 40.0 for total combined major and minor defects.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:50Z
Check the source to verify that this is the current version before use.

TABLE III. End item dimensional defects

Examine	Defect	Classification	
		Major	Minor
Overall dimensions	Smaller than nominal dimensions less twice the applicable minus tolerance	X	
	Smaller than nominal dimensions less applicable minus tolerance, but not smaller than twice the applicable minus tolerance		X
	Larger than nominal dimensions and applicable plus tolerance		X
All dimensions other than overall	Not within specified tolerance		X

4.2.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling
	Bulged or distorted container
Content	Number per container is more or less than required

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:50Z
Check the source to verify that this is the currentversion before use.

* 4.2.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

* 5.1.1.1 Hardware components. The hardware components for each tent, consisting of 6 tent pins, 2 adapters, and 12 tent pole sections, shall be completely and separately wrapped in like-item groups with 60-pound minimum basis weight kraft paper conforming to A-A-203. Each bundle shall have the wrapping secured with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45.

5.1.1.2 Tent. Each tent shall be spread out flat with the lines laid on top and the ridge in the center forming a rectangle approximately 6 feet 10 inches by 4 feet 6 inches. The tent width shall then be folded in thirds with the last fold positioned on top of the first fold, producing a folded width of approximately 19 inches. The bundled hardware components shall be placed at one end of the folded tent. The tent shall then be compactly rolled around the hardware components forming a bundle measuring approximately 19 inches in length and 7 1/2 inches in diameter. Each rolled tent shall be secured with cotton tape or twine and completely wrapped in two thicknesses of

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z
Check the source to verify that this is the current version before use.

60-pound minimum basis weight kraft paper conforming to A-A-203. The paper wrap shall be secured with 2-inch minimum width gummed tape conforming to type III, grade B of PPP-T-45.

* 5.1.2 Commercial. Tents shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Six tents, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed flat three in length, one in width, and two in depth within a shipping container. The inside dimensions of each shipping container shall be approximately 23 inches in length, 19 1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. Six tents, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat three in length, one in width, and two in depth within a shipping container. The inside dimensions of each shipping container shall be approximately 23 inches in length, 19 1/2 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

* 5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Tents, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:50Z
Check the source to verify that this is the currentversion before use.

* 5.3 Palletization. When specified (see 6.2), tents packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. The pallet pattern shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size that does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be first approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. This reversible tent is intended for use in mountainous and Arctic regions.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
c. Type and class of unit load required (see 5.2.1).
d. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
e. When palletization is required (see 5.3).

6.3 Standard sample. For access to samples, address the contracting office issuing the invitation for bids.

* 6.4 International standardization agreements. Certain provisions of this document are the subject of international standardization agreement as cited in NATO, STANAG NO. 2882, relative to camouflage requirements for tents, shelters, and subsidiary components. When amendment, revision, or cancellation of this document is proposed that will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force -99

Preparing activity:

Army - GL

Project No. 8340-0477

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-1926G	Tent, Mountain, Two-Man, Complete with Pins and Poles

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 82 MAR

PREVIOUS EDITION IS OBSOLETE.

NATICK OP, Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:50Z