INCH-POUND

MIL-DTL-39024/10E
3 February 2003
SUPERSEDING
MIL-J-39024/10D
25 May 1984

DETAIL SPECIFICATION SHEET

JACK, TIP (TEST POINT TYPE, PANEL TYPE; SINGLE TEST POINT (THREADED) LOW VOLTAGE, .080)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-39024.



Inches	mm	Inches	mm
.016	0.41	.125	3.18
.026	0.66	.128	3.25
.030	0.76	.132	3.35
.031	0.79	.250	6.35
.040	1.02	.281	7.14
.047	1.19	.312	7.92
.050	1.27	.34	8.64
.054	1.37	.375	9.52
.060	1.52	.41	10.41
.062	1.57	.438	11.12
.080	2.03	.922	23.42
.088	2.24	1.000	25.40
.09	2.29		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± .010 (0.25 mm) for three place decimals and ± .03 (0.76 mm) for two place decimals.
4. One hex nut and one washer are to be supplied unassembled.

FIGURE 1. Configuration and dimensions.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.

TABLE I. Design and identification data.

Dash number	Supersedes MS16108	Style	Insulation	
			Color	Number in accordance with FED-STD-595
-01	-1A, -11A, -12A	Turret	White	17875
-02	-2A		Red	11105
-03	-3A		Black	17038
-04	-4A		Brown	10075
-05	-5A		Green	14110
-06	-6A		Orange	12246
-07	-7A		Blue	15123
-08	-8A		Yellow	13655
-09	-9A		Gray	16187
-10	-10A		Purple	27144
-11	-1C, -11C, -12C	Eyelet	White	17875
-12	-2C		Red	11105
-13	-3C		Black	17038
-14	-4C		Brown	10075
-15	-5C		Green	14110
-16	-6C		Orange	12246
-17	-7C		Blue	15123
-18	-8C		Yellow	13655
-19	-9C		Gray	16187
-20	-10C		Purple	27144

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1 and table I.

Insulation: Material shall be polyamide in accordance with L-P-410 or ASTM D4066.

Terminals: Shall be capable of being wired with two type E, AWG 20 wires in accordance with NEMA-HP3.

Metals and finishes: Shall conform to requirements of MIL-DTL-39024, except that the minimum nickel plating thickness for copper and copper alloys, except for contacts and terminals, shall be .0002 inch.

Test probe: 0.080 ± 0.001 inch in diameter and ½ -inch (min) length.

Contact current rating: 5 amperes (max).

Contact resistance: A test probe in accordance with MIL-DTL-39024 shall be fully inserted into the connector.

Test current: 5 amperes.

Points of measurement: Between the connector terminal and the extreme end of the solder cup on the test probe.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.

Measured values: See table II.

Dielectric withstanding voltage (at sea level):

Test voltage: 3,000 volts rms, 60 hertz, shall be applied to insulating material for a period of 15 seconds.

Insertion and withdrawal forces:

Insertion force: 5.0 pounds (max).
Withdrawal force: 0.4 pounds (min).

Durability: One thousand insertion-withdrawal cycles shall be performed. After the tests, connectors shall meet the initial measurements of insertion and withdrawal force, and contact resistance in table II.

TABLE II. Potential drop (max) with 5 amperes of current.

Test	Voltage drop (max)
Initial	6 mV
After durability	8 mV
After vibration	10 mV
After salt spray (corrosion)	15 mV

Operating conditions:

Operating voltage: 2,000 volts rms, 60 hertz at sea level; 350 volts rms, 60 hertz at 80,000 feet.

Note: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4438-001)

Review activities:
Army - AR, CR4, EA, MI
Navy - AS, CG, MC, OS
Air Force - 19

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.