
INCH-POUND
MIL-DTL-39024/12F
22 September 2018
SUPERSEDING
MIL-DTL-39024/12E
3 February 2003

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, TEST POINT TYPE, PANEL TYPE; SINGLE TEST POINT (HOLE MOUNTING, PUSH-FIT), LOW VOLTAGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-39024.



NOTES:
1. Dimensions are in inches. Metric equivalents are given for general information only.
2. Unless otherwise specified, tolerances are ± .010 (0.25 mm) for three place decimals and ± 3.0° for angles.

FIGURE 1. Configuration and dimensions.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.

TABLE I. Design and identification data.

Dash number	Dimensions 1/								Insulation
	A ±.010 (0.25)	B	C	D	E Dia	F Dia ± .002 (0.05)	G Dia	H Dia	Color
-01	.453 (11.51)	.317 (8.05)	.047 (1.19)	.037 (0.94)	.074 (1.88)	.185 (4.70)	.219 (5.56)	.054 (1.37)	White
-02	"	"	"	"	"	"	"	"	Red
-03	"	"	"	"	"	"	"	"	Black
-04	"	"	"	"	"	"	"	"	Brown
-05	"	"	"	"	"	"	"	"	Green
-06	"	"	"	"	"	"	"	"	Orange
-07	"	"	"	"	"	"	"	"	Blue
-08	"	"	"	"	"	"	"	"	Yellow
-09	"	"	"	"	"	"	"	"	Gray
-10	"	"	"	"	"	"	"	"	Purple
-11	"	"	"	"	"	"	"	"	Natural
-12	.390 (9.91)	.265 (6.73)	.046 (1.17)	.023 (0.58)	.068 (1.73)	.149 (3.78)	.172 (4.37)	.040 (1.02)	White
-13	"	"	"	"	"	"	"	"	Red
-14	"	"	"	"	"	"	"	"	Black
-15	"	"	"	"	"	"	"	"	Brown
-16	"	"	"	"	"	"	"	"	Green
-17	"	"	"	"	"	"	"	"	Orange
-18	"	"	"	"	"	"	"	"	Blue
-19	"	"	"	"	"	"	"	"	Yellow
-20	"	"	"	"	"	"	"	"	Gray
-21	"	"	"	"	"	"	"	"	Purple
-22	"	"	"	"	"	"	"	"	Natural

1/ Metric equivalents are in parentheses.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1 and table I.

Insulation: Material shall be polytetrafluoroethylene in accordance with ASTM D1710.

Operating temperature: -65°C to +200°C.

Test probe: Connectors shall be .500 inch (minimum) length and accept test probe tips as follows:

Dash numbers	Probe dia. (±.001)
-01 thru –11	.080 inch
-12 thru –22	.040 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.

Contact current rating: 5.5 amperes (maximum).

Dielectric withstanding voltage (at sea level):

Test voltage shall be as follows:

Dash numbers	Volts, rms (60 Hz)
-01 thru –11	1,800
-12 thru –22	1,600

Insertion and withdrawal forces:

Insertion force: 5.0 pounds (max).

Withdrawal force: 0.4 pound (min).

Thermal shock: Shall be in accordance with MIL-STD-202-107, condition C.

Identification marking:

Part or Identifying Number (PIN): M39024/12-(dash number from table I).

Operating conditions:

Operating voltage is as follows:

Dash numbers	At sea level	At 50,000 feet
-01 thru –11	800 volts rms, 60 Hz	450 volts rms, 60 Hz
-12 thru –22	700 volts rms, 60 Hz	450 volts rms, 60 Hz

Maximum thickness of panel on which these connectors may be used is as follows:

Dash numbers	Max panel thickness
-01 thru –11	.230 inch
-12 thru –22	.139 inch

Application data:

Dash numbers –01 thru –11. Countersink installation side .172 ± .002 inch mounting hole with a 60° countersink to .195 + .005, -.000 inch diameter when used with a .040 inch or thicker chassis.

Dash numbers –12 thru –22. Countersink installation side .136 ± .002 inch mounting hole with a 60° countersink to .160 + .005, -.000 inch diameter when used with a .040 inch or thicker chassis.

An 82° countersink shall be used with a chassis under 0.040 inch thick.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.

Qualification: Not applicable.

Quality conformance inspection. Group A and B tests of MIL-DTL-39024 shall be applicable.

Revision notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this revision. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-39024, this document references the following:

MIL-STD-202-107
ASTM-D1710

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2018-124)

Review activities:
Army - AR, AT, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:25Z
Check the source to verify that this is the current version before use.