MIL-E-1/280D
23 March 1970
SUPERSEDING
MIL-E-1/280C
24 July 1963

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5672

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, power amplifier

(D) Outline --- 2-1 (EIA)

Base --- Pinch press

Envelope --- T2X3

Cathode --- Coated filament

Base connections:

Pin No.	---	1	2	3	4	5
Element	---	a Red dot	g2	+f	g1	-f, g3

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ik	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	mAdc	ft
Maximum:	1.5 (see note 1)	100	---	100	5.5	10,000
Minimum:	1.0	---	---	---	---	---
TEST CONDITIONS:	1.25	67.5	-6.5	67.5	---	---

GENERAL:

Qualification - Required

(D) denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:09Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						MIN	MAX	
	Quality conformance inspection, part 1							
1266	Total grid current	See note 2	1.0	II	Ic1	0	-0.8	μAdc
1341	Power output (2)	Ef = 1.0 Vdc (see note 2)	1.0	II	Po	25	---	mW
(D) 1246	Audio frequency noise	Esig = 200 mVac; Rp = 2,000 ohms (see note 3)	1.0	II	---	---	---	---
1256	Electrode current (anode)		1.0	II	Ib	2.1	4.1	mAdc
(D) 1201	Tap shorts		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1211	Insulation of electrodes		4.0	S3	R	100	---	Meg
1116	Lead fatigue		4.0	S3	---	3	---	Arcs
1031	Low-frequency vibration	Rp = 2,000 ohms	---	---	Ep	---	200	mVac
1256	Electrode current (screen)		---	---	Ic2	0.5	1.4	mAdc
1301	Filament current		---	---	If	44	56	mAdc
1306	Transconductance		---	---	Sm	475	825	μmhos
1341	Power output (1)	Esig = 4.55 Vac; Rp = 20,000 ohms	---	---	Po	50	---	mW
1341	Power output (3)	Ef = 1.0 Vdc; take reading after 15 minutes	4.0	S3	Po	25	---	mW
(D) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A; Ef = 1.25 Vdc or Vac, with equivalent bias	---	---	---	---	---	---
---	Intermittent life-test end points (500 hours)	Power output (1) Total grid current	--- ---	--- ---	Po Ic1	35 ---	--- -1.5	mW μAdc
	Periodic-check test							
(D) 1202	Filament burnout		---	---	---	---	---	---

NOTES:

1. Do not use series filament circuits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:09Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

2. This test to be performed at the conclusion of the holding period.

3. The rejection level shall be set at the VU meter reading obtained during calibration.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - EL

DSA - ES

User activities:
Army - WC, ME
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Army - EL

Agent: DSA - ES

(Project 5960-2401-35)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:09Z
Check the source to verify that this is the current version before use.