A-A-2352
November 29, 1985

COMMERCIAL ITEM DESCRIPTION

NIBBLERS, ELECTRIC, PORTABLE

The General Services Administration has authorized the use of this commercial item description as a replacement for Military Specification MIL-N-19703, which is canceled.

This commercial item description covers portable electric nibblers intended for use in cutting ferrous and non-ferrous sheets and plates.

Salient characteristics:

The nibblers supplied in accordance with this description shall be of the manufacturer's current design.
The nibblers shall conform to the requirements of Underwriters' Laboratories Standard No. 45.
The nibblers shall have basic insulation.
The nibblers shall be double insulated or have a 2 pole, 3 wire grounding system that meets the requirements of Underwriters' Laboratories Standard No. 498.
The motor shall be continuous duty, universal series type, operable on 115 VDC or 120 VAC.
The switches shall be of the quick-break design, conveniently located, and capable of being locked in the "ON" position. The switches shall be plainly marked "ON" and "OFF".
All parts shall be manufactured to standards that will permit replacement or adjustment without modification of the parts or the nibblers.
The nibblers shall be supplied in the following classes as specified:
Class 0 - Extra heavy duty
Class 1 - Heavy duty
Class 2 - Standard duty
Class 3 - Light duty
The nibblers shall comply with the requirements of the table.

National Stock Number (NSN)	Class	Cutting capacity mild steel thickness (inch)	gage	Rated current (min. amps)	Minimum cutting speed (in/min)	Maximum cutting radius (inch)	Maximum weight w/o cord (lbs)
5130-01-014-0983	0	0.250	--	13	40	8	24.0
5130-00-989-6424	1	0.125	--	6	40	6	18.5
5130-01-028-5206	1	0.125	--	6	40	6	18.5
5130-01-039-5089	1	0.125	--	6	40	6	18.5
5130-00-540-3079	2	0.0747	14	3	35	1-1/4	10.5
5130-00-990-3639	3	0.0478	18	1.2	60	1	8.0

Classes 0 and 1 handles shall be the closed loop type.
Classes 2 and 3 handles may be body type handles in lieu of the closed loop type.
The nibblers shall be constructed so as to withstand the shocks and stresses encountered during normal use.
The punch shall have a hardness of not less than 60 on the Rockwell "C" scale. The die shall have a hardness of not less than 45 on the Rockwell "C" scale. The punch and die shall be easily adjustable and easily removable without the use of special tools.
The nibblers supplied under NSN 5130-01-039-5089 shall be provided with a special head for slitting nibbling.
The nibblers supplied under NSN 5130-01-028-5206 shall be provided with a special head for corrugated nibbling.
With the exception of NSN 5130-00-989-6424, the nibblers shall be electromagnetic interference suppressed in accordance with MIL-STD-1337 for portable electric tools.
All exposed surfaces shall be smooth. Corners shall be rounded or beveled. All exposed surfaces shall be coated, polished, or otherwise finished in accordance with the manufacturer's standard practice.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:22Z
Check the source to verify that this is the current version before use.

The nibblers shall be furnished with one extra punch, one extra set of brushes, a complete set of the manufacturer's current operating and maintenance instructions, a parts list breakdown, and any tools, equipment, and accessories necessary to assure efficient operation in accordance with the operating instructions and any tools, equipment, and accessories normally supplied commercially.

The nibblers shall be marked in a plain, permanent, and legible manner with the manufacturer's name, trademark, country of origin, model and serial number, cutting capacity, type of current, voltage, and rated load in amperes.

Testing requirements. The nibblers shall pass the following performance and service tests.

Performance test: The class 0 nibblers shall cut 20 feet of 0.250 inch mild steel in a period of six minutes. The class 1 nibblers shall cut 20 feet of 0.125 inch mild steel in a period of six minutes. The class 2 nibblers shall cut 15 feet of 0.0747 inch mild steel in a period of five minutes. The class 3 nibblers shall cut 20 feet of 0.0478 inch mild steel in a period of four minutes.

Service test: The nibblers shall satisfactorily complete a service test of at least forty hours of actual operation. Operation is not required to be continuous, but may be intermittent for a total of forty actual operating hours. The nibblers shall conform to the requirements of the performance test before and after the forty-hour service test. After the performance and service tests, the nibblers shall be examined for wear of motor components, gears, bearings, cam and plunger mechanism, and punch and die assembly. The nibblers shall also be examined for possible lubricant leakage and insecure fastenings.

Workmanship. The nibblers and accessory components shall be free of any defects which may impair serviceability, durability, or appearance.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes:

When 2 pole, 3 wire grounding is specified, a double insulated model will be acceptable.

The issue of UL Standards No. 45 and 498, and MIL-STD-1337, in effect on the date of invitation for bid or request for proposals shall be used to determine compliance with the stated requirements.

Copies of Underwriters' Laboratories Standards may be obtained from Underwriters' Laboratories Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11747.

Copies of MIL-STD-1337 may be obtained from Commanding Officer, U. S. Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 10120.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:22Z
Check the source to verify that this is the current version before use.