A-A-2398
August 9, 1985

Commerical Item Description
Curtain, Shower and Window Plastic

The General Services Administration has authorized the use of this Commerical Item Description in lieu of Federal Specificiation L-C-780 a dated June 11, 1965. This Commercial Item Description covers individual and matched sets of curtains, shower and window plastic.

Salient characteristics.
The shower and window curtain shall be a vinyl film not less than 8 gauge and shall not harden or become sticky in use. It shall be mildew and rot proof.

Top hem. The top hem shall be of triple thickness or reinforced material with a minimum one (1) inch hem, secured with either a stitcher or thermoelectrically heat welded method through which rust proof grommets (eight pronged) are set a minimum of six (6) inches apart and must have a 12 grommets in a 72 inch width shower curtain. The grommets shall be postioned in each corner, 1/2 inch from top and 1 inch ± 1/2 inch from side edge. The top mesh weave, when used, shall be twenty (20) inches wide and continue solid as one piece or attached to a solid bottom section with or without bottom hem.

Sides and lower edge. The side shall have a one quarter (1/4) inch minimum hem. The lower edge shall have either no hem or a reversed hem one quarter (1/4) inch minimum width, securely, stitched or sealed.

Size. 72" x 72" standard size for tub sizes, 36" x 72" standard size for stall type shower. The following tolerances will be permitted in the dimensions: Length ± 1/2 inch, width ± 1/2 inch.

Window curtain. The window curtain material shall be the same fabric content as the shower curtain, matching in color and appearance.

Panels. Each panel shall be sewn with a locked stitch or thermoelectrically heat weld to create a tailored rod pocket so as to accommodate up to a 1 inch diameter curtain rod. Sides to be bound in manner used by individual manufacturer.

Each pair of curtains may be 32 inches by 45 inches, 34 inches by 45 inches, 32 inches x 60 inches or 34 inches by 60 inches with tolerances in length ± 1/2 inch and width ± 1/2 inch.

Each pair of curtains shall have tow matching tie - backs finished with two reinforced sewn eyelets in each. Minimum 3" x 18" double thick, 4 guage vinyl binding on one side, other side to be folded material.

Shower and window curtain shall match in color and appearance Matte finish white opaque vinyl film or colorless frosted vinyl as specified in orders. With print or plain.

All labels shall be in conspicuous place and show size of article.

This fabric shall have a maximum flame time of 3.0 seconds in both the warp and filling directions when tested in accordance with Method 5903 of Federal Testing Method Standard #191.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

Characteristics:

Break Strength - Warp and Fill - 100 pound minimum - using Method 5100 of Federal Testing Method Standard #191.

Tear Strength - Warp and Fill - 18 pound minimum - using Method 5134 of Federal Testing Method Standard #191.

Char Length - Warp and Fill - 7 inches maximum - using Method 5903 of Federal Testing Method 76-1969 of ATTCC (USASL 14.112-1961).

Stiffness - Warp only @ 70 degrees F - 8.5 maximum - @ 20 degrees F - 13.0 maximum - using Method 5204 of Federal Testing Method Standard #191.

Blocking - No. 2 maximum - using Method 5872 of Federal Testing Method Standard #191.

Break Strength after Abrasion - Warp and Fill - 15 pounds minimum - using Method 5304/5102 of Federal Testing Method Standard #191.

Testing adhesion - Warp and Fill - 15 pounds minimum - using Method 5970 of Federal Testing Method Standard #191.

Workmanship. The curtains and components shall be free from defects or blemishes affecting appearance or serviceability of the item.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or order.

Purchasers shall specify and include the following information in the order

Style I Shower curtain (only) tub or shower.
Style II curtain - Window curtain only.
Style III Shower and Window curtain combination.

Size
Color - Matte finish white opague vinyl or colorless frosted vinyl Printed or plain

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.