A-A-884A
September 21, 1981
SUPERSEDING
A-A-884
October 3, 1980

COMMERCIAL ITEM DESCRIPTION

TAPE, PRESSURE-SENSITIVE ADHESIVE, BOX CLOSURE

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification PPP-T-60, Type III, Class I.

This description covers tape intended for single strip closure of fiberboard boxes, multiple strip sealing of fiberboard boxes.

Salient characteristics.

The film furnished under this description shall be pressure-sensitive, film backed tape, and shall meet the requirements of table I and the requirements of the Uniform Freight Classification, Rule 41, Section 7(e).

Colors: As specified in contract or order.

TABLE I

Characteristic	Requirement	Method of Test
Adhesion, oz./in., minimum	45	ASTM D 3330 Procedure A
Holding Power, 1/ minutes, minimum	700	ASTM D 3654
Tensile, lb./in., minimum		ASTM D 3759
Machine direction	45	
Cross direction	58	
Bursting, lb. minimum	160	ASTM D 3662
Unwind, lb./in., minimum	2	ASTM D 3811

1/ Substrate shall be NBS Standard Reference Material 1810, area 1/2" x 1/2", 23°C, weight shall be 1000g.

Sampling and examination shall be in accordance with the producer's standard practice so long as it provides equivalent assurance to that found in ASTM D 3715, with end item testing at an acceptance level (AQL) of 4 percent.

The issues of the ASTM standards in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Workmanship. The adhesive shall be coated in a smooth, uniform layer over the entire surface of one side of the tape backing. When unwound, the tape shall not tear, nor shall be adhesive separate from the backing. The tape shall be evenly and uniformly wound with no voids. The edges of the roll shall be clean cut.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:10Z
Check the source to verify that this is the current version before use.

Packaging, packing, and marking shall be as specified in the contract or order.

Notes: Purchaser shall specify dimensions (length and width), and color.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Type IV tape is covered by A-A-1586.

MILITARY INTERESTS:

Military Coordinating Activity

Navy - AS

PREPARING ACTIVITY:

GSA-FSS

Custodians

Army - GL
Navy - AS
Air Force - 69

Review Activities

Army - AR, AV, EA, ER
ME, SM
Navy - YD, SH, OS
Air Force - 99

User Activities

Army - AL, AT
Navy - ME

GSA DC-01201118

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.