[METRIC]
A-A-55562/3C
10 April 2023
SUPERSEDING
A-A-55562/3B
27 April 2018

COMMERCIAL ITEM DESCRIPTION

RESISTOR, VOLTAGE SENSITIVE (VARISTOR, METAL OXIDE), CHIP, STYLE 1206

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

The complete requirements for procuring a surface-mount, voltage sensitive, metal oxide, style 1206 chip varistor described herein shall consist of this document and the issue in effect of CID A-A-55562.

CLASSIFICATION OR PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the PIN as shown in the following example (see NOTES).

AA5556203-001P

AA55562	-	Abbreviated CID number
03	-	Applicable CID sheet (two digits)
-001	-	Dash number (see applicable CID sheet)
P	-	Termination finish

SALIENT CHARACTERISTICS

Interface and physical dimensions. Varistors supplied to this CID shall be as specified herein (see figure 1).

Working voltage (dc). The working voltage (dc) shall be as specified in table I.

Breakdown voltage. The breakdown voltage shall be as specified in table I.

Clamping voltage. The clamping voltage shall be as specified in table I.

Peak current. The peak current shall be as specified in table I.

Transient energy. The transient voltage shall be as specified in table I.

Capacitance. The capacitance shall be as specified in table I.

Inductance. The inductance shall be as specified in table I.

Termination finish. The termination finish shall be Nickel barrier with Tin alloy plated finish (Ni/Sn), code letter P.

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime ATTN: VAT, Post Office Box 3990, Columbus, OH 43218-3990, or emailed to Resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.


FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.

Marking. Resistors supplied to this CID specification sheet shall be marked as specified in A-A-55562.

NOTE

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See CLASSIFICATION for PIN format example.



L	W	D	E
3.20 ±0.2	1.60 ±0.2	1.02 max	0.71 max

mm	Inches	mm	Inches	mm	Inches
0.2	0.01	1.02	0.040	3.20	0.126
0.71	0.028	1.60	0.063		

NOTES:
1. Dimensions are in millimeters. Inch-pound equivalents are given for information only.
2. The US government preferred system of measurement is the metric SI system. However, this item was originally designed using inch-pound units of measurement. In the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.

FIGURE 1. Interface and physical dimensions, style 1206.

Source of documents.

Commercial Item Description

A-A-55562	-	Resistor, Voltage Sensitive (Varistor, Metal Oxide), Chip

(Copies of these documents are available online at https://quicksearch.dla.mil/.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.

TABLE I. Performance characteristics.

Dash number	Working Voltage (dc) Max	Breakdown Voltage	Clamping Voltage (max) 1/	Peak current A (max)	Transient energy Joule (max)	Cap (pF) typical		Inductance (nH) typical
Test Condition	<50 μA	1 mA dc	8/20 μs	8/20 μs	10/1000 μs	0.5 V rms @ 1kHZ	1MHz	di/dt= 100 mA/ns
001P	3.3 2/	4.1 - 6.0	10	40	0.1	2000	1500	<1.7
002P	3.3 2/	3.7 - 5.6	10	150	0.4	4700	3800	1.7
003P	5.6	7.6 - 9.3	15.5	40	0.1	1200	870	<1.7
004P	5.6	7.1 - 8.7	15.5	150	0.4	3000	2300	1.7
005P	14.0	16.5 - 20.3	30	40	0.1	600	500	<1.7
006P	14.0	15.9 - 19.4	30	150	0.4	1200	900	1.7
007P	18.0 3/	22.9 - 28.0	40	30	0.1	350	270	<1.7
008P	18.0 3/	22.5 - 27.5	40	150	0.4	800	635	1.7
009P	26.0	30.5 - 37.3	58	120	0.4	550	450	1.7
010P	30.0	36.0 - 45.0	65	120	0.4	500	400	1.7
011P	48.0	56.0 - 68.0	100	100	0.4	225	185	1.7

1/ Maximum peak voltage across the varistor measured at a specified pulse current and waveform.

Transient Energy Rating	Pulse Current and Waveform
0.1 Joule	2A 8/20 μs
≥0.4 Joules	10A 8/20 μs

2/ Test condition <100μA

3/ Withstands 24.5 V dc for 5 minutes (automotive applications).

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown).

MFR's CAGE	MFR's name and address
16299	AVX Corporation One AVX Boulevard Fountain Inn, SC 29644-9039 Phone: 864-967-2150 Email: inquiry@avx.com Website: http://www.avx.com

Part number (P/N) supersession data. This CID specification sheet PINs supersedes the following manufacturers P/N as shown in table II. This information is being provided to assist in reducing proliferation in the Government inventory system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.

TABLE II. P/N supersession data.

CID coded number AA5556203-	MFR's CAGE	MFR's P/N 1/
001P	16299	VC120603A100
002P		VC120603D100
003P		VC120605A150
004P		VC120605D150
005P		VC120614A300
006P		VC120614D300
007P		VC120618A400
008P		VC120618D400
009P		VC120626D580
010P		VC120630D650

1/ The manufacturers P/N shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see paragraph 3.5 of A-A-55562.

National Stock Number. This section is not applicable to this CID specification sheet.

Changes from previous issue. The margins of this CID specification sheet are marked with a vertical line to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

MILITARY INTERESTS:

Custodian
NAVY - EC
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FAS

Preparing Activity:

DLA - CC

Project 5905-2023-006

NOTE: The activities listed above were interested in this document as the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.