[METRIC]
A-A-55562/5A
27 April 2018
SUPERSEDING
A-A-55562/5
30 August 2001

COMMERCIAL ITEM DESCRIPTION

RESISTOR, VOLTAGE SENSITIVE (VARISTOR, METAL OXIDE), CHIP, STYLE 0402

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

The complete requirements for procuring a surface-mount, voltage sensitive, metal oxide, style 0402 chip varistor described herein shall consist of this document and the issue in effect of CID A-A-55562.

* CLASSIFICATION OR PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the PIN as shown in the following example (see NOTES).

AA55562	05	-001	P
Abbreviated CID number	Applicable CID sheet	Dash number	Termination finish

SALIENT CHARACTERISTICS

* Interface and physical dimensions. Varistors supplied to this CID shall be as specified herein (see figure 1).

Working voltage (dc). The working voltage (dc) shall be as specified in table I.

Breakdown voltage. The breakdown voltage shall be as specified in table I.

Clamping voltage. The clamping voltage shall be as specified in table I.

Peak current. The peak current shall be as specified in table I.

Transient energy. The transient voltage shall be as specified in table I.

Capacitance. The capacitance shall be as specified in table I.

Inductance. The inductance shall be as specified in table I.

Termination finish. The termination finish shall be Nickel barrier with Tin alloy plated finish (Ni/Sn), code letter P.


Marking. Resistors supplied to this CID specification sheet shall be marked as specified in A-A-55562.

NOTES

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See CLASSIFICATION for PIN format example.

AMSC N/A FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.



L	W	D	E
1.0 ±0.10	0.5 ±0.10	0.60 max	0.25 ±0.15

mm	Inches
0.10	0.004
0.15	0.006
0.25	0.010
0.50	0.020
0.60	0.024
1.0	0.040

NOTES:
1. Dimensions are in millimeters. Inch-pound equivalents are given for information only.

FIGURE 1. Interface and physical dimensions, style 0402.

Source of documents.

Commercial Item Description

A-A-55562 - Resistor, Voltage Sensitive (Varistor, Metal Oxide), Chip

* (Copies of these documents are available online at http://quicksearch.dla.mil/.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.

TABLE I. Performance characteristics.

Dash number	Working Voltage (dc) Max	Breakdown voltage	Clamping Voltage (max) 1/	Peak current A (max)	Transient energy Joule (max)	Cap (pF) typical	Inductance (nH) typical
Test Condition	<50 μA	1 mA dc	8/20 μs	8/20 μs	10/1000 μs	0.5 V rms @ 1MHz	di/dt= 100 mA/ns
001P	5.6	7.6 - 9.3	15.5	20	0.05	360	<1.0
002P	9.0	11.0 - 14.0	20	20	0.05	230	<1.0
003P	14.0	16.5 - 20.3	30	20	0.05	120	<1.0
004P	18.0	22.9 – 28.0	40	20	0.05	90	<1.0

1/ Maximum peak voltage across the varistor measured at a specified pulse current and waveform.

Transient Energy Rating	Pulse Current and Waveform
0.05 Joule	1A 8/20 μs

* Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown).

MFR's CAGE	MFR's name and address
16299	AVX Corporation One AVX Boulevard Fountain Inn, SC 29644-9039 Phone: 864-967-2150 Email: inquiry@avx.com Website: http://www.avx.com

Part number (P/N) supersession data. This CID specification sheet PINs supersedes the following manufacturers P/N as shown in table II. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE II. P/N supersession data.

CID coded number AA5556205-	MFR's CAGE	MFR's P/N 1/
001P	16299	VC040205X150
002P		VC040209X200
003P		VC040214X300
004P		VC040218X400

1/ The manufacturers P/N shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see paragraph 3.5 of A-A-55562.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.

* National Stock Number. This section is not applicable to this CID specification sheet.

Changes from previous issue. The margins of this CID specification sheet are marked with an asterisk to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

MILITARY INTERESTS:

Custodians:
NAVY - EC
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA – FAS

Preparing activity:
DLA - CC

Project 5905-2018-015

NOTE: The activities listed above were interested in this document as the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:52Z
Check the source to verify that this is the current version before use.