INCH-POUND
A-A-59183
27 May 1998

COMMERCIAL ITEM DESCRIPTION

ICEMAKER-DISPENSER WITH WATER DISPENSER ATTACHMENT (NAVAL SHIPBOARD)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE

This commercial item description (CID) covers counter mounted, corrosion-resisting, air-cooled condenser type icemakers-dispensers with water dispenser attachments. The icemaker-dispensers are intended for use in messrooms, galleys, and other areas where a continuous supply of dispensed ice and water is needed for Naval shipboard use.

2. CLASSIFICATION

Type 1: 200 pounds per day minimum
Size 1: 8 pound storage bin capacity
Size 2: 30 pound storage bin capacity

Type 2: 525 pounds per day minimum
Size 3: 25 pound storage bin capacity
Size 4: 45 pound storage bin capacity
Size 5: 90 pound storage bin capacity

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The icemaker-dispenser shall be a completely self-contained unit, capable of making and storing ice and dispensing ice and water. The icemaker-dispenser shall have a water circulating system, electric motor, and necessary piping, wiring, control, and safety devices. The icemaker-dispenser shall be totally enclosed in a structural frame and sheet metal housing with removable panels. The cabinet shall be provided with four 4-inch high stainless steel legs suitable for mounting the equipment to a countertop.

3.1.1 Exterior. The thickness of the exterior of the icemaker-dispenser shall be not less than 24-gauge stainless steel.

3.1.2 Capacities. The icemaker-dispenser shall meet the icemaking capacity requirements under the conditions listed in table I.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: Commander, Naval Sea Systems Command, 2531 Jefferson-Davis Highway, Arlington, VA 22242-5160.

AMSC N/A FSC 4110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

TABLE I. Capacity conditions.

TYPE	AMBIENT AIR TEMPERATURE DEGREES	POTABLE WATER SUPPLY TEMPERATURE DEGREES (F)	MINIMUM CAPACITY PER POUND/24 HOURS
1	70 100	70 90	200 140
2	70 100	70 90	525 400

3.1.3 Valves. The front of the icemaker-dispenser shall be equipped with one ice-dispensing valve and one water-dispensing valve. A removable drain pan with a perforated tray shall be provided under the dispensing valves. The drain pan shall be removable without special tools and shall have a drain fitting in the bottom of the pan and a drain line shall be provided. The drain line shall lead outside the cabinet and shall terminate in a fitting suitable for continuing the line to a vented deck drain.

3.2 Storage bin. The storage bin shall be an integral part of the icemaker-dispenser, and shall have a thickness of not less than 24-gauge stainless steel or impact resistant plastic. The ice storage bin shall have a drain fitting in the bottom of the pan and a drain line shall be provided. The drain line shall lead outside the cabinet and shall terminate in a fitting suitable for continuing the line to a vented deck drain. The storage bin shall be provided with a stainless steel hasp and staple, suitable for a padlock. An automatic ice level control shall be installed in the storage bin to shut off the ice maker when the storage bin is full.

3.2.1 Insulation. Insulation shall be foam-in-place cellular polyurethane in accordance with ASTM C 1029. Ozone-depleting substances to propel the insulation shall not be used during manufacturing.

3.3 Refrigeration unit. The refrigeration unit shall be an integral part of the complete icemaker-dispenser. The assembled refrigeration unit shall be self-contained, wired, dehydrated, and charged with the amount and type of refrigerant and oil necessary for operation. The refrigerating system shall be fitted with a process tube as a means of recovering and adding refrigerant to the system. The compressor and compressor motor shall be of the type and size to obtain the capacities given in paragraph 3.1.3. When starting or running, motors shall be protected against damage from overloads and voltage fluctuations.

3.3.1 Refrigerant (ozone depleting substance). The refrigerant shall be in accordance with ASHRAE 15, Group A1 (nonflammable), be in accordance with ARI 700 (purity), and be approved by the Environmental Protection Agency under the Significant New Alternate Program. The refrigerants permitted for use, in order of preference, shall be of one of the following: R134A, R-401A, or R-401B.

3.3.2 Cooling condenser. The icemaker-dispenser shall be provided with an air-cooled condenser.

3.4 Metal joints. Joints between metal surfaces which may become wet in service, as well as bolts, nuts, pins, screws, and other fastening and fittings of metal shall be of compatible material as that being joined to preclude electrolytic or galvanic corrosion.

3.5 Electrical requirements. The unit shall operate on 115 VAC, 60 Hz, single-phase power, as defined in MIL-STD-1399, Section 300, and shall have provisions for making direct (hardwired) connections for electric power (2 conductors) and for equipment grounding (1 conductor). All exposed

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

metallic surfaces shall be grounded via the equipment grounding connection. The grounding resistance between any exposed metallic surfaces and the common ground point shall be not greater than 0.1 ohm. Electrical components, other than the hermetically sealed motor, shall be provided in accordance with NEMA 250, Type 13 or equivalent enclosure protection. Metal parts of electrical components and enclosures shall be inherently corrosion resistant or shall be treated and processed for corrosion resistance in accordance with IEEE Standard 45. Mercury-type float switches shall not be used. (Shipboard requirement, see 7.2)

3.6 Inclined operation. The unit shall operate satisfactorily (in accordance with the requirements of this CID) with no spillage of liquid or product when test-operated for 30 seconds inclined at an angle of 15° (30° when specified for submarines) each side of the vertical, in each of two vertical planes at right angles to each other. (Shipboard requirement, see 7.2)

3.7 Environmental suitability. The unit shall be capable of withstanding ship's vibration and motion. Controls, switches, moving parts, and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage, when tested in accordance with MIL-STD-167/1, type I equipment. The unit shall be secured to the test machine in the same manner that it will be secured on shipboard. (Shipboard requirement, see 7.2)

3.8 Physical size limitations. The unit shall pass or shall disassemble so that it can pass through a shipboard access measuring 26 x 66 inches with 8-inch radius corners. When specified for submarines, the cabinet shall pass or shall disassemble so that it can pass through a 30 inch diameter submarine access. The refrigeration system shall not require disassembly to pass through access openings. (Shipboard requirement, see 7.2)

3.9 Envelope dimensions. The unit envelope dimensions shall be not greater than 24 inches wide by 29 inches deep by 41 inches high.

3.10 Accessibility. The unit shall be physically and visually accessible from the front for operation and for normal maintenance with tools, test equipment, and replacement parts. No special tools shall be required for access or parts replacement.

3.11 Standards compliance. The unit shall be in accordance with and certified to meet the applicable requirements of NSF 12 and UL 563.

3.12 Label plates. The unit shall be provided with a data nameplate and an instruction plate, both attached to the front of the unit. They shall be readily visible during normal operating use and shall not adversely affect the life and utility of the unit.

3.12.1 Data nameplate. The data nameplate shall contain the manufacturer's name, model, serial number, date manufactured, and any other information needed to uniquely identify the unit.

3.12.2 Instruction plate. The instruction plate shall provide instructions for start-up, operation, and shut-down.

4. REGULATORY REQUIREMENTS

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The product provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market, or the same product that has been delivered to the Government for shipboard use on a previous procurement. The Government reserves the right to require proof of such compliance.

6. PACKAGING

Preservation, packing, and marking shall be as specified in the contract or purchase order.

7. NOTES

7.1 Ordering data.

- Title, number, and date of this CID
- Type and size required
- When required, manuals shall be in accordance with ASTM F 760

7.2 Shipboard requirement. Whenever a "(Shipboard requirement)" is included in a paragraph under SALIENT CHARACTERISTICS, it is meant that the requirement is something that is not normally offered to the commercial market by the manufacturer.

7.3 Source of documents.

7.3.1 Military documents. Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.

MIL-STD-1399	-	Interface Standard for Shipboard Systems Section 300A Electric Power, Alternating
MIL-STD-167/1	-	Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally excited)

7.3.2 American Society for Testing and Materials (ASTM) Standards. ASTM Standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohoken, PA 19428-2959.

ASTM F 760	-	Food Service Equipment Manuals
ASTM C 1029	-	Spray-Applied Rigid Cellular Polyurethane Thermal Insulation

7.3.3 American Refrigeration Institute (ARI) Standards. ARI Standards are available from the Air-Conditioning & Refrigeration Institute, 4301 North Fairfax Drive, Suite 425, Arlington, VA 22203.

ARI 700	-	Specifications for Fluorocarbons and Other Refrigerants

7.3.4 The American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE) Standards. ASHRAE Standards are available from the American Society of Heat, Refrigerating and Air-Conditioning Engineers, 1791 Tullie Circle, N.E., Atlanta, GA 30329-2305.

AHSRAE 15	-	Safety Code for Mechanical Refrigeration

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

7.3.5 National Sanitation Foundation International (NSF) Standards. NSF Standards are available from the National Sanitation Foundation International, 3475 Plymouth Road, P.O. Box 130140, Ann Arbor, MI 48113-0140.

NSF 12 - Automatic Ice Making Equipment

7.3.6 Underwriters Laboratories (UL) Standards. UL Standards are available from the Underwriters Laboratories Inc., 333 Pfingston Road, Northbrook, IL 60062.

UL 563 - Ice Makers

7.3.7 The Institute of Electrical and Electronic Engineers (IEEE) Standards. IEEE Standards are available from The Institute of Electrical and Electronic Engineers, 445 Hose Lane, P.O. Box 1331, Piscataway, NJ 08855-1331.

IEEE 45 - IEEE Recommended Practice for Electric Installations on Shipboard

7.4 Suggested sources of supply. Manufacturers of products known to meet the requirements of this CID are listed below. However, competition is not limited to these companies.

Remcor Products Co.
500 Regency Drive
Glendale Heights, IL 60139

Scotsman Ice Systems
775 Corporate Woods Parkway
Vernon Hills, IL 60061

Wilshire Corporation
2401 North Palmer Drive
Schaumburg, IL 60196

MILITARY INTERESTS:

Military Coordinating Activity

Navy - SH

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

Preparing activity:
Navy - SH
(Project 4110-0523)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.