INCH-POUND
A-A-59186
9 September 1998

COMMERCIAL ITEM DESCRIPTION

WELL, HOT FOOD STORAGE, ELECTRIC (NAVAL SHIPBOARD)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE

This commercial item description (CID) covers electrically heated hot food storage wells of the drop-in type, with temperature control and drain. Wells shall be suitable for wet or dry operation. They are intended for Naval shipboard use in serving lines to keep food warm in steam table pans.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The well shall be the drop-in type for counter or table installation. It shall consist of a seamless, drawn stainless steel pan and shall include:

- Top perimeter supporting flanges
- Integral drain
- Means of attaching the pan in the counter or table
- Counter gasket
- Heat distributing plate
- Heating element attached beneath the pan
- Insulation below the heating element and along the sides

The well shall be encased by an outer housing of galvanized steel or other corrosion-resisting metal. A thermostatic control suitable for mounting in the counter front shall be provided, adjacent to the well. The heating element and pilot light shall both energize when the control is turned on. Inside dimensions of the well pan shall be: 19-7/8 inches long by 11-7/8 inches wide by 6-1/8 inches deep (all with + 1/4 / - 0 inch tolerances). The perimeter flange shall be not less than 1/2 inch wide. The well pan shall be a food zone as defined in the NSF standards.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: Commander, Naval Sea Systems Command, 2531 Jefferson-Davis Highway, Arlington, VA 22242-5160.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

2.2 Heating system. A heat distributing plate, 1/8 ± 1/32 inch thick and of adequate size to cover the flat surface of the bottom of the well, shall be welded or securely clamped to the underside of the well. The heating element shall be the enclosed tubular type rated at not less than 1500 watts and shall be securely clamped to the underside of the heat distributing plate. The heating element shall be removable without the use of special tools. (Shipboard requirement, see 6.2)

2.3 Temperature control unit. A thermostat of the infinite temperature control type with a clearly marked OFF position shall be provided. The temperature control unit shall provide temperature adjustment within a range of not less than 120 to 190°F, and at an intermediate setting (approximately 150°F), it shall limit temperature variation to not more than ± 20°F. The temperature control unit shall be suitable for mounting in the counter front adjacent to the well pan. The adjustment knob on the temperature control unit panel shall either be recessed or have a protective shield to prevent accidental breakage. An indicator light shall also be provided on the temperature control unit panel and shall be illuminated when the heating element is energized.

2.4 Gasket. A gasket shall be provided to give the joint between the top perimeter flange of the well pan and the mounting surface a positive moisture seal.

2.5 Thermal insulation. Blanket-type thermal insulation shall be provided between the heating element and the base of the outer casing, and between the sides of the well pan and outer casing. The temperature of the base of the outer casing shall be not greater than 125°F.

2.6 Drain. A drain shall be provided in the base of the well pan for draining water when wet operation is required. The drain shall be a stainless steel pipe welded to the well pan or a brass pipe brazed to the pan, and shall have standard 3/4 NPT threads on the outlet end. The inlet end of the drain pipe shall be smooth and flush with the surface of the well pan. An integral stainless steel inlet strainer screen shall be provided. (Shipboard requirement, see 6.2)

2.7 Electrical requirements. The unit shall operate on 115 VAC, 60 Hz, single-phase power, as defined in MIL-STD-1399, Section 300, and shall have provisions for making direct (hardwired) connections for electric power (2 conductors) and for equipment grounding (1 conductor). All outermost metallic surfaces shall be grounded via the equipment grounding connection. The grounding resistance between any exposed metallic surfaces and the common ground point shall be not greater than 0.1 ohm. Electrical components, other than the hermetically sealed motor, shall be provided in accordance with NEMA 250, Type 13 or equivalent enclosure protection. Metal parts of electrical components and enclosures shall be inherently corrosion resistant or shall be treated and processed for corrosion resistance in accordance with IEEE Standard 45. (Shipboard requirement, see 6.2)

2.8 Accessibility. The unit shall be physically and visually accessible from the front for operation and for normal maintenance with tools, test equipment, and replacement parts. No special tools shall be required for access or parts replacement.

2.9 Environmental suitability. The unit shall be capable of withstanding ship's vibration and motion. Controls, switches, moving parts, and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage, when tested in accordance with MIL-STD-167-1, type I equipment. The unit shall be secured to the test machine in the same manner that it will be secured on shipboard. (Shipboard requirement, see 6.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

2.10 Standards compliance. The unit shall be in accordance with and certified to meet the applicable requirements of NSF 4 and UL 197.

2.11 Finish. Stainless steel shall have a type 2B or smoother finish, in accordance with ASTM A 480.

2.12 Label plates. The well shall be provided with a data nameplate and an instruction plate. They shall be attached to the unit, readily visible during normal operating use, and shall not adversely affect the life and utility of the unit.

2.12.1 Data nameplate. The data nameplate shall contain the manufacturer's name, model, serial number, date manufactured, and any other information needed to uniquely identify the unit.

2.12.2 Instruction plate. The instruction plate shall provide instructions for start-up, operation, and shut-down.

3. REGULATORY REQUIREMENTS

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation.

4. QUALITY ASSURANCE PROVISIONS

4.1 Product conformance. The product provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market, or the same product that has been delivered to the Government for shipboard use on a previous procurement. The Government reserves the right to require proof of such compliance.

5. PACKAGING

Preservation, packing, and marking shall be as specified in the contract or purchase order.

6. NOTES

6.1 Ordering data.

- Title, number, and date of this CID.
- When required, manuals shall be in accordance with ASTM F 760

6.2 Shipboard requirement. Whenever a "(Shipboard requirement)" is included in a paragraph under SALIENT CHARACTERISTICS, it is meant that the requirement is something that is not normally offered to the commercial market by the manufacturer.

6.3 Source of documents.

6.3.1 Military documents. Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

MIL-STD-167-1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally excited)
MIL-STD-1399 - Interface Standard for Shipboard Systems Section 300A Electric Power, Alternating

6.3.2 American Society for Testing and Materials (ASTM) Standards. ASTM Standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohoken, PA 19428-2959.

ASTM A 480 - General Requirements for Flat-Rolled Stainless and Heat-Resisting Steel Plate, Sheet, and Strip
ASTM F 760 - Food Service Equipment Manuals

6.3.3 National Sanitation Foundation International (NSF) Standards. NSF Standards are available from the National Sanitation Foundation International, 3475 Plymouth Road, P.O. Box 130140, Ann Arbor, MI 48113-0140.

NSF 4 - Commercial Cooking, Rethermalization and Powered Hot Food Holding and Transport Equipment

6.3.4 Underwriters Laboratories (UL) Standards. UL Standards are available from the Underwriters Laboratories Inc., 333 Pfingston Road, Northbrook, IL 60062.

UL 197 - Commercial Electric Cooking Appliances

6.3.5 The Institute of Electrical and Electronic Engineers (IEEE) Standards. IEEE Standards are available from The Institute of Electrical and Electronic Engineers, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331.

IEEE 45 - IEEE Recommended Practice for Electric Installations on Shipboard

6.3.6 The National Electrical Manufacturers Association (NEMA) Standards. NEMA Standards are available from the National Electrical Manufacturers Association, 1300 North 17th Street, Suite 1847, Rosslyn, VA 22209.

NEMA 250 - Enclosures for Electrical Equipment (1000 Volts Maximum)

6.4 Suggested sources of supply. Manufacturers of products known to meet the requirements of this CID are listed below. However, competition is not limited to these companies.

American Permanent Ware
729 3rd Avenue
Dallas, TX 75226

Food Equipment Corporation
400 Humboldt Avenue
St. Louis, MO 63147

Hobart Corporation
World Headquarters Avenue
Troy, OH 45374

Low Temp Mfg. Company
9191 Tara Boulevard
P.O. Box 795
Jonesboro, GA 30237

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.

8. CONCLUDING MATERIAL

Custodian:
Navy - SH

Preparing activity:
Navy - SH
(Project 7310-0895)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:05Z
Check the source to verify that this is the current version before use.