INCH-POUND


MIL-DTL-15370/10D
7 May 2008
SUPERSEDING
MIL-DTL-15370/10C
18 June 2003

DETAIL SPECIFICATION SHEET

COUPLERS, DIRECTIONAL (COAXIAL, SMA CONNECTORS)
(.50 to 18 GHz)

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The requirements for acquiring the couplers described herein shall consist of this specification sheet and MIL-DTL-15370.



Inches	mm
.010	0.25
.093	2.36

FIGURE 1. Dimensions and configuration for part numbers M15370/10-001 through M15370/10-011, and M15370/10-019.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.



Inches	mm
.015	0.38
.125	3.18
.38	9.65

FIGURE 2. Dimensions and configuration for part number M15370/10-012.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.



Inches	mm
.003	0.08
.105	2.67
.38	9.65

FIGURE 3. Dimensions and configuration for part numbers M15370/10-013, M15370/10-021, M15370/10-023, and M15370/10-024.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.




Inches	mm
.003	0.08
.105	2.67
.38	9.7

NOTES:
1. Sealant thickness, .031 maximum for dash numbers M15370/10-016, M15370/10-017, and M15370/10-018.
2. Four mounting holes are permitted, providing they are symmetrical with the two holes shown.

FIGURE 4. Dimensions and configuration for part numbers M15370/10-014 through M15370/10-018, and M15370/10-020.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.




Inches	mm
.010	.25
.140	3.56

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 5. Dimensions and configuration for part numbers M15370/10-022, M15370/10-025, M15370/10-026, and M15370/10-028 through M15370/10-030.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.



Inches	mm
.003	0.08
.105	2.67
.38	9.7

FIGURE 6. Dimensions and configuration for part number M15370/10-027.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions and physical requirements.

Dash No.	Mounting config-uration (figure)	Dimensions 1/ 2/ 3/												Weight (max)		
		A (max)	B ±.005 (0.13)	C ±.02 (0.51)	D ±.020	E ±.02 (0.51)	F (max)	G (max)	H ±.02 (0.51)	J (max)	K +.010 -.000	L ±.010	M (max)	lbs	g	oz
001NS	1	3.320 (84.33)	3.130 (79.50)	2.710 (68.83)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
002NS	1	3.320 (84.33)	3.130 (79.50)	2.710 (68.83)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
003NS	1	3.320 (84.33)	3.130 (79.50)	2.710 (68.83)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
004NS	1	2.563 (65.10)	2.391 (60.73)	1.954 (49.63)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
005NS	1	2.563 (65.10)	2.391 (60.73)	1.954 (49.63)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
006NS	1	2.563 (65.10)	2.391 (60.73)	1.954 (49.63)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
007NS	1	1.715 (43.56)	1.525 (38.74)	1.105 (28.07)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.16	71	2.5
008NS	1	1.210 (30.73)	1.020 (25.91)	.600 (15.24)	.290 (7.37)	1.495 (37.97)	.530 (13.46)	.405 (10.29)	.580 (14.73)	---	---	.080 (2.03)	---	.06	29	1.02
009NS	1	1.100 (27.94)	.920 (23.37)	.500 (12.70)	.290 (7.37)	1.620 (41.15)	.655 (16.64)	.405 (10.29)	.642 (16.31)	---	---	.080 (2.03)	---	.06	29	1.02
010NS	1	1.100 (27.94)	.920 (23.37)	.500 (12.70)	.290 (7.37)	1.620 (41.15)	.655 (16.64)	.405 (10.29)	.642 (16.31)	---	---	.080 (2.03)	---	.06	29	1.02
011NS	1	1.100 (27.94)	.920 (23.37)	.500 (12.70)	.290 (7.37)	1.620 (41.15)	.655 (16.64)	.405 (10.29)	.642 (16.31)	---	---	.080 (2.03)	---	.06	29	1.02
012NS	2	1.560 (39.62)	.375 4/ (9.53)	1.090 5/ (27.69)	.220 5/ (5.59)	---	.843 5/ (21.41)	.530 (13.46)	.605 5/ (15.37)	.281 4/ (7.14)	.130 (3.30)	.770 5/ (19.56)	1.380 (35.05)	.16	71	2.5
013NS	3	1.040 (26.42)	---	.500 5/ (12.70)	.250 5/ (6.35)	---	.843 5/ (21.41)	.415 (10.54)	---	.410 5/ (10.41)	.125 (3.18)	.521 5/ (13.23)	.800 (20.32)	.08	29	1.02
014NS	4	3.20 (81.3)	1.500 (38.10)	2.700 (68.58)	.270 (6.86)	1.45 (36.8)	.800 (20.32)	.415 (10.54)	---	.585 (14.85)	.080 (2.03)	.800 (20.32)	.650 (16.5)	.46	207	7.3
015NS	4	3.030 (76.96)	1.000 (25.40)	2.500 (63.50)	.270 (6.86)	1.00 (25.4)	.750 (19.05)	.415 (10.54)	---	.440 (11.17)	.110 (2.79)	1.013 (25.73)	.250 (6.35)	.09	43	1.5
016NS	4	3.050 (77.47)	1.500 (38.10)	2.520 (64.01)	.270 (6.86)	1.00 (25.4)	.590 (14.00)	.415 (10.54)	---	.340 (8.64)	.110 (2.79)	.790 (20.06)	.470 (11.93)	.09	43	1.5
017NS	4	3.050 (77.47)	1.750 (44.45)	2.500 (63.50)	.270 (6.86)	1.00 (25.4)	.530 (13.46)	.415 (10.54)	---	.300 (7.62)	.110 (2.79)	.650 (16.51)	.470 (11.93)	.09	43	1.5
018NS	4	3.050 (77.47)	1.750 (44.45)	2.500 (63.50)	.270 (6.86)	1.00 (25.4)	.530 (13.46)	.415 (10.54)	---	.300 (7.62)	.110 (2.79)	.650 (16.51)	.470 (11.93)	.09	43	1.5
019NS	1	2.651 (67.34)	2.391 (60.73)	1.969 (50.01)	.385 (9.78)	1.628 (41.35)	.530 (13.46)	.415 (10.54)	.578 (14.68)	---	---	.125 (3.18)	---	.09	43	1.5
020NS	4	1.200 (30.48)	.340 (8.64)	.660 (16.76)	.270 (6.86)	1.45 (36.8)	.800 (20.32)	.415 (10.54)	---	.585 (14.85)	.080 (2.03)	.410 (10.41)	.650 (16.51)	.46	207	7.3

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions and physical requirements - Continued.

Dash Number	Mounting configuration (figure)	Dimensions 1/ 2/ 3/												Weight (max)		
		A (max)	B ±.005 (0.13)	C ±.02 (0.51)	D ±.020	E ±.02 (0.51)	F (max)	G (max)	H ±.02 (0.51)	J (max)	K +.010 -.000	L ±.010	M (max)	lbs	g	oz
021NS	3	1.04 (26.4)	---	.50 (12.7)	.25 (6.4)	---	.54 (13.7)	.44 (11.9)	---	.30 (7.6)	.110 (2.79)	.520 (13.20)	.75 (19.1)	.04	17	0.60
022NS	5	2.02 (51.3)	1.75 (44.5)	---	.30 (7.6)	---	1.27 (32.3)	.44 (11.2)	---	.30 (7.6)	.625 (15.87)	.125 (3.18)	.35 (8.9)	.09	43	1.5
023NS	3	1.04 (26.4)	---	.50 (12.7)	.25 (6.4)	---	.50 (12.7)	.395 (10.0)	---	.30 (7.6)	.093 (2.36)	.507 (12.87)	.06 (1.5)	.19	85	3.0
024NS	3	1.04 (26.4)	---	.50 (12.7)	.25 (6.4)	---	.54 (13.7)	.395 (10.0)	---	.30 (7.6)	.093 (2.36)	.521 (13.23)	.812 (20.62)	.04	17	0.60
025NS	5	2.02 (51.3)	1.75 (44.5)	---	.25 (6.4)	2.0 (51.)	1.6 (41.)	.395 (10.0)	---	.30 (7.6)	.625 (15.87)	.125 (3.18)	.40 (10.2)	.09	43	1.5
026NS	5	2.02 (51.3)	1.75 (44.5)	---	.25 (6.4)	2.0 (51.)	1.6 (41.)	.395 (10.0)	---	.30 (7.6)	.625 (15.87)	.125 (3.18)	.40 (10.2)	.09	43	1.5
027NS	6	1.04 (25.4)	---	---	.250 (6.35)	---	.50 (12.7)	.395 (10.0)	---	.30 (7.6)	.093 (2.36)	,500 (12.70)	---	.06	28	1.0
028NS	5	2.02 (51.3)	1.75 (44.5)	---	.35 (8.9)	---	1.27 (32.3)	.44 (11.2)	---	.30 (7.6)	.625 (15.87)	.125 (3.18)	.35 (8.9)	.09	43	1.5
029NS	5	2.02 (51.3)	1.75 (44.5)	---	.30 (7.6)	---	1.27 (32.3)	.44 (11.2)	---	.30 (7.6)	.625 (15.87)	.125 (3.18)	.35 (8.9)	.09	43	1.5
030NS	5	2.02 (51.3)	1.75 (44.5)	---	.30 (7.6)	---	1.27 (32.3)	.44 (11.2)	---	.30 (7.6)	.625 (15.87)	.125 (3.18)	.35 (8.9)	.09	43	1.5

1/ Dimensions are in inches.
2/ Metric equivalents are given for general information only.
3/ Metric equivalents are in parentheses.
4/ Tolerance is ± .010 (0.25).
5/ Tolerance is ± .030 (0.76).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical requirements.

Dash number	Frequency range	Coupling (dB)		Coupling variation (dB) max	Effective directivity (dB) min	Insertion loss (dB) max	VSWR max		RF input power to primary			Reflected power (avg) max
		Nominal	Tolerance				Primary line	Secondary line	Over frequency range	Avg	Peak	
	GHz								Watts	Watts	KW	Watts
001NS	0.5 - 1.0	6	±1.0	±0.6	20	0.2	1.25:1	1.25:1	50	50	0.25	2
002NS	0.5 - 1.0	10	±1.0	±0.75	20	0.2	1.25:1	1.25:1	50	50	0.25	5
003NS	0.5 - 1.0	20	±1.0	±1.0	20	0.2	1.25:1	1.25:1	50	50	0.25	50
004NS	1.0 - 2.0	6	±1.0	±0.5	20	0.2	1.25:1	1.25:1	50	50	0.25	2
005NS	1.0 - 2.0	10	±1.0	±0.75	20	0.2	1.25:1	1.25:1	50	50	0.25	5
006NS	1.0 - 2.0	20	±1.0	±1.0	20	0.2	1.20:1	1.20:1	50	50	0.25	50
007NS	2.0 - 4.0	6	±1.0	±0.5	18	0.2	1.20:1	1.20:1	50	50	0.25	2
008NS	4.0 - 8.0	6	±1.0	±0.5	18	0.2	1.20:1	1.20:1	50	50	0.25	2
009NS	8.0 - 12.4	10	±1.0	±0.5	15	0.25	1.30:1	1.30:1	50	50	0.25	2
010NS	8.0 - 12.4	20	±1.0	±0.75	15	0.25	1.30:1	1.30:1	50	50	0.25	2
011NS	12.4 - 18.0	6	±1.0	±0.5	12	0.25	1.35:1	1.35:1	50	50	0.25	2
012NS	7.0 - 11.0	10	±1.0	±0.75	15	0.85	1.25:1	1.25:1	100	100	2.0	10
013NS	7.0 - 11.0	20	±1.0	±1.0	15	0.40	1.25:1	1.30:1	100	100	2.0	100
014N 1/ S	0.5 - 1.0	10	±1.25	±0.75	25	0.20	1.10:1	1.10:1	50	50	3.0	5
015NS	0.5 - 1.0	30	±1.0	±0.75	25	0.15	1.10:1	1.10:1	50	50	4.0	50
016NS	0.5 - 1.0	10	±1.0	±0.75	25	0.2	1.15:1	1.15:1	50	50	3.0	5
017NS	0.5 - 1.0	20	±1.0	±0.75	25	0.2	1.15:1	1.15:1	50	50	3.0	50
018NS	0.5 - 1.0	30	±1.0	±0.75	25	0.2	1.15:1	1.15:1	50	50	3.0	50
019NS	1.5 - 1.9	15	±1.0	±0.75	20	0.2	1.20:1	1.20:1	5	5	2.0	2
020N 2/ S	2.0 - 4.0	6	±1.0	±0.5	20	0.2	1.30:1	1.30:1	50	50	2.0	2

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.

TABLE II Electrical requirements.

Dash number	Frequency range	Coupling (dB)		Coupling variation (dB) max	Effective directivity (dB) min	Insertion loss (dB) max	VSWR max		RF input power to primary			Reflected power (avg) max
		Nominal	Tolerance				Primary line	Secondary line	Over frequency range	Avg	Peak	
	GHz								Watts	Watts	KW	Watts
021NS	2.6 - 5.2	20	±1.25	±0.75	20	0.25	1.25:1	1.25:1	50	50	3.0	50
022NS 3/	2.6 - 5.2	20	±1.25	±0.75	20	0.25	1.25:1	1.25:1	50	50	7.5	50
023NS	4.4 - 5.0	10	±0.45	±0.2	20	0.2	1.25:1	1.25:1	20	20	2	1
024NS	7.0 - 11.0	6	±1.0	±0.6	17	0.5	1.30:1	1.30:1	50	50	3	2
025NS	8.75 - 9.65	6	±0.5	±0.3	17	0.3	1.20:1	1.20:1	1	1	1	2
026NS	8.75 - 9.65	30	±1.0	±0.5	17	0.3	1.20:1	1.20:1	1	1	1	50
027NS	9.0 - 9.2	20	±0.6	±0.3	18	0.4	1.35:1	1.35:1	50	50	1	20
028NS 4/	8.0 - 12.4	10	±1.0	±0.5	15	0.3	1.30:1	1.30:1	5	5	5	2
029NS	8.0 - 12.4	25	±0.5	±0.3	20	0.3	1.25:1	1.25:1	35	35	5	50
030NS	8.0 - 12.4	30	±1.0	±0.5	20	0.3	1.25:1	1.25:1	35	5	5	50

1/ Inactive for new design, use dash number -002 for new design.
2/ Inactive for new design, use dash number -007 for new design.
3/ Inactive for new design, use dash number -021 for new design.
4/ Inactive for new design, use dash number -009 for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See figures 1 through 6 and table I.

Operating temperature range:

-54°C to +85°C for dash numbers 022 through 028.
-55°C to +100°C for dash numbers 014 and 020.
-54°C to +110°C for dash numbers 001 through 013, 015 through 019, 021, 023 through 027, 029, and 030.

Weight: See table I.

Electrical: See table II.

Marking: Part number (see tables I and II) shall be located as shown on figures 1 through 6.

Part number: M15370/10- (and a dash number from table I).

Referenced Documents: In addition to MIL-DTL-15370, this document references the following:
MIL-PRF-39012/55

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Navy - AS, CG, MC, OS, SH
Air Force - 99

(Project 5985-2008-032)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:10Z
Check the source to verify that this is the current version before use.