FEDERAL SPECIFICATION

WASHCLOTH, TERRY, COTTON

This amendment, which forms a part of Federal Specification DDD-W-80b, dated September 4, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 1.1-In line 2, delete "cotton washcloths" and substitute "two types of cotton washcloths."

Paragraph 2.1-Under Federal Specifications, delete: "I-P-378-Plastic Film (Polyethlene Thin Gage)." and "UU-T-111-Tape; Paper, Gummed, (Sealing and Securing)."; and add: "PPP-T-45-Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing."

Under Federal Standards, delete "Fed. Std. No. 102-Preservation, Packaging and Packing Levels."

PAGE 2

Table I-Delete and substitute:

TABLE I. Physical requirements

Type	Weight per dozen minimum	Yarns per inch		Ply Warp		Filling	Finished dimensions		Break strength (minimum)	
		Warp (min.)	Filling (min.)	Ground	Pile		Each	Tolerance	Warp	Filling
	Ounce						Inch	Inch	Lbs.	Lbs.
I	16	68 1/	35 1/	2 or 1	2 or 1	1	12 by12	± 1/2	40	35
II	11	59	29	2 or 1	2 or 1	1	12 by12	± 1/2	25	25

1/ Either of these values may fall below this minimum by not more than three yarns, provided the combined warp and filling yarn total does not fall below 100 yarns per square inch.

Paragraph 3.2.1-In line 1 after "Weave", add, "type I".

Add new paragraph as follows:

3.2.1.1 Type II. The cloth shall consist of a ground warp, pile warp, and filling yarns woven as single-loop terry weave. The border measurement from edge towards the body on all 4 sides of the washcloth shall be in this order: 3/8 to 5/8 inch plain weave; 1/8 to 3/8 inch terry; 1/16 to 3/16 inch plain weave; 1/8 to 3/8 inch terry; 1/16 to 3/16 inch plain weave; terry body.

Paragraph 3.2.2-Delete and substitute:

3.2.2 Thread. The thread for stitching the type I washcloth shall be cotton, ticket No. 30, 3 ply, type IA2 of V-T-276. The yarn for stitching the type II washcloth shall be 2 ply 20's cotton count.

PAGE 3

Paragraph 4.2.1-Delete and subsitute:

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable procurement documents.

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:33Z
Check the source to verify that this is the current version before use.

Paragraph 4.2.2.1.1-Delete and substitute:

4.2.2.1.1 Visual examination. The required number of washcloths shall be inspected and defects classifed as follows. The defects found shall be counted regardless of their proximity to each other, except where two or more defects represent a single local condition of the washcloth in which case only the most serious shall be counted. The inspection level shall be level I of MIL-STD-105 and the AQL shall be 4.0 percent defective.

Defects

Cut, hole, tear, or smash.
Three or more contiguous broken or missing yarns (clearly visible).
Terry loops improperly formed over an area of 1 inch or bald areas of 1/2 inch or more.
Spot, stain, streak, clearly visible.
Any trash, motes, leaf, or seed coat fragments.
Objectionable odor.
Color or shade not as specified.
Wrong stitch type or stitches per inch not as specified.
Overstitching missing or loose stitch tension, resulting in a loosely secured edge.
Identification label missing, incorrect, illegible, insecurely attached, or misplaced.
Border not as specified.

PAGE 4

Paragraph 4.2.2.1.2-Delete "Width of border-less than 1/4 inch-more than 1/2 inch".

Paragraph 4.3-In last sentence, delete "4.0" and substitute "2.5".

Table III-In "Requirement reference" column, after "3.2.1", add "or 3.2.1.1".

Paragraph 5-Under "PREPARATION FOR DELIVERY", delete parenthetical preamble.

Paragraph 5.1.1-Delete and substitute:

5.1.1 Level A. Twelve washcloths of one type only, shall be evenly stacked, flat or center-folded, and completely wrapped in 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each wrapped bundle shall be cross-tied with cotton tape or twine, or secured with gummed paper tape conforming to type III, grade B of PPP-T-45. Alternatively, the stack of twelve washcloths may be placed in a snug-fitting clear polyethylene film bag of 0.00125 inch thickness (±20 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight, continous, and parallel to each other and the formed edges of the bag. The bag closure shall be effected by heat sealing with the heat seal as close as possible to the open end. A 1/4-inch diameter hole shall be made at one corner of each bag to allow the excess air to escape.

Paragraph 5.1.2-Delete and substitute:

5.1.2 Level C. Washcloths shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

Paragraph 5.2.1-Delete and substitute:

5.2.1 Level A. Three hundred washcloths of one type only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V3s of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to grade V3c of PPP-B-636. Each shipping container shall be closed, waterproofed and reinforced with flat strapping or tape banding in accordance with the appendix of the container specification.

Paragraph 5.2.2-Delete and substitute:

5.2.2 Level B. Three hundred washcloths, of one type only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF or SF, variety SW, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, variety SW, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:33Z
Check the source to verify that this is the current version before use.

Add new paragraph as follows:

5.2.2.1 When specified, shipping containers shall be fabricated from grade V3c or V3s fiberboard (see 6.2).

Paragraph 5.2.3-Delete and substitute:

5.2.3 Level C. Washcloths packaged as specified in 5.1 shall be packed to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

PAGE 6

Paragraph 6.2-Add new subparagraphs as folloes:

"(d) Type required (see 1.1 and table I).
(e) When V-board shipping containers are required for level B shipment (see 5.2.2.1)."

MILITARY CUSTODIANS:

Army - GL
Navy - SA
Air Force - 82

Review activities:

Army - MD
Navy - SA
Air Force - 82, 85

Preparing activity:

Army - GL

CIVIL AGENCIES INTEREST:

GSA-FSS
HEW-PHS
INT
VA
JUS-FPI
OEO
DHS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.