O-B-420a
AMENDMENT-1
July 21, 1967

FEDERAL SPECIFICATION

BLEACH, LAUNDRY, ORGANIC CHLORINE

This amendment, which forms a part of Federal Specification O-B-420a, dated December 2, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 2.1, under "Federal Standards". Delete "Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels."

PAGE 2

Paragraph 2.2, under "ASTM Designations". Delete "D2022-62T - Methods of Sampling and Chemical Analysis of Chlorine Containing Bleaches (Tentative)" and substitute "D2022-64 - Standard Methods of Sampling and Chemical Analysis of Chlorine-Containing Bleaches." Delete the word "Labeling" from "Federal Hazardous Substances Labeling Act (Public Law 86-613, 86th Congress 5.1283 approved July 12, 1960)."

PAGE 4

Paragraph 4.3.1.5, line 12, opposite "4.3.1.4", under heading "AQLs". Delete "4.0" and substitute "2.5".

PAGE 5

Paragraphs 4.4.2 and 4.4.3. Delete and substitute:

4.4.2 Carbonates as Na_2CO_3. Carbonate content, expressed as Na_2CO_3, shall be determined in accordance with method 1401 of Fed. Test Method Std. No. 536 except that the fifth sentence under "Procedure" shall be modified

Source: https://assist.dla.mil -- Downloaded: 2025-06-04Z
Check the source to verify that this is the current version before use.

PAGE 5 (cont'd.)

to read as follows: "Weigh to the nearest 0.001 g. one hundred grams of the ground and mixed bleach sample, transfer the bleach to the Knorr flask, add 40 ml. of freshly boiled distilled water, add hydroxylamine sulfate (approximately equal in weight to the bleach sample - use flask large enough to accommodate sample and reagents and increase size of tube carrying acid into the sample flask as required), and close the apparatus with the entire train in place". Continue with the sixth sentence under "Procedure", except delete "20 milliliters" and substitute "40 milliliters" in sentence six.

4.4.3 Reaction with carbonate ion. Dissolve 2.00 + 0.01 g. of ground and mixed bleach sample in 200 ml. of distilled water (at 25° + 2°C.). Filter the solution to remove insoluble material. To 100 ml. of the filtered solution add 2.00 + 0.02 g. of anhydrous sodium carbonate (Na_2CO_3). Stir or shake the system for five minutes. Allow to stand for an additional five minutes. Compare this solution with the remaining filtered solution. Any visually observed evidence of a precipitate or a definite increase in turbidity shall constitute failure.

PAGE 6

Paragraph 4.4.6. Delete and substitute:

4.4.6 Moisture content. The moisture content shall be determined in accordance with ASTM D 2022-64, sections 50 through 53. The sample designated in 4.3.2.2, ground and mixed, shall be used for the moisture determination.

PAGE 8

Section 5. Delete "Fed. Std. No. 102 shall be referred to for definitions and application of the various levels of packaging and packing for civil agency procurements."

Paragraph 5.1.1, line 16. Delete "type III,".

Paragraph 5.2.1.1, line 5, after "RSC". Delete "or" and substitute "of".

Paragraph 5.2.1.2.1, line 20. Delete "type III,".

PAGE 9

Paragraph 5.3.1, lines 3 and 4. Delete "MIL-STD-129, and". Line 5. Delete "Labeling".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Navy - SH
Air Force - 68

Review activities:

Army - GL, MD, MU
Navy - SH
Air Force - 68

User activities:

Army - SM
Navy - MC

Preparing activity:

Army - GL

Civil Agencies interest:

AGR
COM
GSA
GPO
HEW
INT
JUS
VA

Review and User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Standardization Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.