Int. Fed. Std. No. 00139 (GSA-FSS)
April 15, 1959
(W-B-133, Issue in Effect)

INTERIM FEDERAL STANDARD

BATTERY, STORAGE, LEAD-ACID, FOR ELECTRIC OPERATED INDUSTRIAL TRUCK AND TRACTORS

This Interim Federal Standard was developed from currently available technical information by the General Services Administration, Federal Supply Service, Washington 25, D.C. It is issued for optional use by all Federal agencies. Recommendations for changes should be sent to the preparing activity at the address shown above, so that, if appropriate, the Interim Federal Standard can be coordinated into a mandatory Federal Specification.

S1. Purpose and scope. - This standard, when subsequently coordinated as a Federal Standard, will establish the capacities (minimum ampere hour ratings) and maximum dimensions of lead-acid storage batteries for use in electrically operated industrial trucks and tractors.

S2. Application. - Purchases from commercial sources under Interim Federal Specification W-B-00133, of the issue in effect on date of invitation for bids, should be limited to items which conform with the characteristics specified below:

S3. Standard characteristics and item identification. - The standard items with the Federal Stock numbers should conform to the characteristics listed below:

Federal Stock Number*	Voltage	Capacity ampere hours (minimum)	Maximum dimensions Inches L	W	H
6140	12	450	29-1/4	13-1/8	23-1/2
6140	12	720	39-9/16	12-11/16	31
6140	36	360	31-13/16	24-1/8	24-5/8
6140	36	450	39	31-1/4	24-5/8
6140	36	720	39	30-5/16	24-5/8

*Complete Federal Stock Numbers when available, will be included in succeeding Federal Standard. In the interim, procurement documents should show voltage, ampere hour capacity and maximum dimensions.

6140
FSC ~~5140~~

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:54Z
Check the source to verify that this is the current version before use.

S4. Changes. - As Federal agencies use this Interim Federal Standard and determinedchanges are advisable for its continued use, these changes should be sent in duplicate, to the preparing activity.

S5. Conflict with referenced specification. - If the requirements specified in this standard conflict with any requirement in a referenced specification, the nature of conflict between the standard and the referenced specification, should be submitted, in duplicate, to the preparing activity.

Single copies of this Interim Federal Standard are available without charge at the GSA Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:54Z
Check the source to verify that this is the currentversion before use.