Fed. Std. No. 128B
December 9, 1976
SUPERSEDING
Fed. Std. No. 128a
October 18, 1961

FEDERAL STANDARD

JUNCTION BOX; EXTENSION, JUNCTION BOX: COVER, JUNCTION BOX, (STEEL, CADMIUM OR ZINC COATED)

This standard was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. Scope. The purpose of this standard is the establishment of a standard stock list of junction boxes, junction box extensions, and junction box covers for use with rigid metallic conduit, electrical metallic tubing, flexible metallic conduits, armored cable and, when installed in accordance with the National Electrical Code, nonmetallic-sheathed cable and nonmetallic tubing, for ordinary maintenance and extension of circuit purposes as required by Government maintenance activities. This standard will keep the varieties of such boxes, extensions, and covers which are procured and stocked to a minimum consistent with such requirements. It does not cover nonmetallic junction boxes, cast metal boxes, conduit outlets, or hinged covered boxes.

2. Application. Purchases from commercial sources under W-J-800, of the issue in effect on date of invitation for bids, shall be limited to items which have characteristics conforming to the standard items specified herein. Existing Government stocks of items with other characteristics shall continue to be utilized until exhausted. In those cases where this Federal Standard eliminates supply items and the items so eliminated are under contract, if the contract cannot be negotiated or amended to conform to the standard items, the Federal Standard becomes mandatory at the contract expiration date.

3. Standard characteristics and item identification. The standard items with their applicable National Stock Numbers (NSN) shall conform to the characteristics listed below:

Type I - Octagon junction box.

Size A - 3-1/4 inch by 1-1/2 inch deep.

Style 2. Knockouts: Bottom: one 1/2 inch; Sides four 1/2 inch: NSN 5975-00-153-6392.
Style 3. Knockouts: Bottom: one 1/2 inch; Sides four 3/4 inch: NSN 5975-00-194-8862.

FSC 5975

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.

Size B - 4 inch by 1-1/2 inch deep.

Style 4. Knockouts: Bottom: two 1/2 inch; four 21/32 inch; Sides: two 1/2 inch, four 21/32 inch: NSN 5975-00-194-8858.
Style 5. Knockouts: Bottom: four 21/32 inch; Sides: four 21/32 inch with integral cable clamps; two 1/2 inch, 3/8 inch fixture stud: NSN 5975-00-281-0663.
Style 6. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: four 3/4 inch: NSN 5975-00-153-6396.
Style 7. Knockouts: Bottom: five 1/2 inch; Sides: four 1/2 inch: NSN 5975-00-153-6395.

Size C - 4 inch by 2-1/8 inch deep.

Style 8. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: four 3/4 inch: NSN 5975-00-255-4483.
Style 9. Knockouts: Bottom: five 1/2 inch; Sides: four 1/2 inch: NSN 5975-00-153-6397.

Type II - Square junction box.

Size D - 4 inch by 4 inch by 1-1/2 inch deep.

Style 10. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: eight 1/2 inch, four 3/4 inch: NSN 5975-00-153-6398.
Style 11. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: eight 3/4 inch: NSN 5975-00-194-8864.
Style 12. Knockouts: Bottom: five 1/2 inch; Sides: twelve 1/2 inch: NSN 5975-00-194-8878.

Size E - 4 inch by 4 inch by 2-1/8 inch deep.

Style 13. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: eight 3/4 inch: NSN 5975-00-194-8880.
Style 14. Knockouts: Bottom: two 3/4 inch, three 1/2 inch; Sides: eight 1 inch: NSN 5975-00-280-4121.
Style 15. Knockouts: Bottom: five 1/2 inch; Sides: twelve 1/2 inch: NSN 5975-00-194-8877.

Size F - 4-11/16 inch by 4-11/16 inch by 1-1/2 inch deep.

Style 16. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: eight 3/4 inch: NSN 5975-00-194-8852.
Style 17. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: twelve 1/2 inch: NSN 5975-00-223-4277.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.

Size G - 4-11/16 inch by 4-11/16 inch by 2-1/8 inch deep.

Style 18. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: eight 1 inch: NSN 5975-00-194-8879.
Style 19. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: four 1/2 inch, six 3/4 inch: NSN 5975-00-194-8874.
Style 20. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: eight 1/2 inch, two 3/4 inch: NSN 5975-00-194-8873.
Style 21. Knockouts: Bottom: three 1/2 inch, two 3/4 inch; Sides: twelve 1/2 inch: NSN 5975-00-224-6022.

Type III - Handy junction box (nongangable).

Size H - 4 inch by 2-1/8 inch by 1-1/2 inch deep.

Style 22. Knockouts: Bottom: three 1/2 inch; Sides: eight 1/2 inch: NSN 5975-00-194-8871.

Size I - 4 inch by 2-1/8 inch by 1-7/8 inch deep.

Style 23. Knockouts: Bottom: three 1/2 inch; Sides: eight 1/2 inch: NSN 5975-00-281-0090.
Style 24. Knockouts: Bottom: two 3/4 inch; Sides: six 3/4 inch: NSN 5975-00-194-8870.

Size J - 4 inch by 2-1/8 inch by 2-1/8 inch deep.

Style 25. Knockouts: Bottom: three 1/2 inch; Sides: eight 1/2 inch: NSN 5975-00-284-5827.

Type IV - Switch box, sectional type (gangable).

Size K - 3 inch by 2 inch by 2 inch deep.

Style 29. Knockouts: Bottom: one 1/2 inch; Sides: six 1/2 inch: NSN 5975-00-153-6387.
Style 30. Knockouts: Bottom: one 1/2 inch, four 21/32 inch; Sides: four 21/32 inch with integral cable clamps: NSN 5975-00-153-6386.

Size X - 3 inch by 2 inch by 2-1/4 inch deep.

Style 74. Knockouts: Bottom: one 1/2 inch; Sides: two 21/32 inch with integral cable clamps: NSN 5975-00-581-8122.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.

Size L - 3 inch by 2 inch by 2-1/2 inch deep.

Style 31. Knockouts: Bottom: one 1/2 inch; Sides: six 1/2 inch: NSN 5975-00-153-6388.
Style 32. Knockouts: Bottom: one 1/2 inch; Sides: eight 21/32 inch with integral cable clamps: NSN 5975-00-194-8856.
Style 33. Knockouts: Bottom: one 1/2 inch; Sides: eight 21/32 inch with integral cable clamps and lateral bracket: NSN 5975-00-194-8855.

Size M - 3 inch by 2 inch by 2-3/4 inch deep.

Style 35. Knockouts: Bottom: one 1/2 inch; Sides: eight 21/32 inch with integral cable clamp: NSN 5975-00-153-6389.

Type V - Octagon junction box ring.

Size M-N - 3-1/4 inch by 1-1/2 inch deep.

Style 35.5 Knockout: four 1/2 inch: NSN 5975-00-557-2688.

Size N - 4 inch by 1-1/2 inch deep.

Style 36. Knockouts: four 1/2 inch: NSN 5975-00-194-8848.
Style 37. Knockouts: four 3/4 inch: NSN 5975-00-194-8847.

Size O - 4 inch by 2-1/8 inch deep.

Style 38. Knockouts: four 3/4 inch: NSN 5975-00-280-6054.

Type VI - Square junction box ring.

Size P - 4 inch by 4 inch by 1-1/2 inch deep.

Style 39. Knockouts: ten 1/2 inch: NSN 5975-00-194-8868.
Style 40. Knockouts: eight 3/4 inch: NSN 5975-00-194-4997.

Type VII - Handy junction box ring.

Size Q - 4 inch by 2-1/8 inch by 1-1/2 inch deep.

Style 41. Knockouts: eight 1/2 inch: NSN 5975-00-194-4998.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.

Type VIII - Covers.

Size R - For 3-1/4 inch octagon box.

Style 42. Flat, closed: NSN 5975-00-153-6773.

Size S - For 4 inch octagon junction box.

Style 43. Flat, closed: NSN 5975-00-153-6775.
Style 44. Flat, with 1/2 inch knockout in the center: NSN 5975-00-296-1113.
Style 45. Raised, with 1/2 inch knockout in center, 5/8 inch high: NSN 5975-00-153-6774.
Style 46. Raised with 27/64 inch metal eyelet for drop cord: NSN 5975-00-188-1153.
Style 47. Raised with 2-3/4 inch opening, 5/8 inch high: NSN 5975-00-281-0055.

Size T - 4-11/16 inch square junction box.

Style 50. Flat, closed: NSN 5975-00-280-7445.
Style 51. For 1 inch flush device: NSN 5975-00-682-0343.

Size U - For 4 inch square junction box, surface mounted.

Style 52. For toggle switch - 1/8 inch depth: NSN 5975-00-280-7187.
Style 53. For duplex receptacle - 1/8 inch depth: NSN 5975-00-284-6285.
Style 54. For toggle switch - 1/2 inch depth: NSN 5975-00-284-6652.
Style 55. For single receptacle - 1/2 inch depth: NSN 5975-00-284-6283.
Style 56. For duplex receptacle - 1/2 inch depth: NSN 5975-00-284-6284.
Style 57. For two toggle switches - 1/2 inch depth: NSN 5975-00-284-6287.
Style 58. For two duplex receptable - 1/2 inch depth: NSN 5975-00-281-0051.
Style 59. For toggle switch and single receptacle - 1/2 inch depth: NSN 5975-00-281-0052.
Style 60. For toggle switch and duplex receptable - 1/2 inch depth: NSN 5975-00-281-0053.

Size V - For 4 inch square junction box flush mounted.

Style 61. Flat, closed: NSN 5975-00-281-0056.
Style 62. Flat, with 1/2 inch knockout: NSN 5975-00-281-0057.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.

Style 63. Raised, with 2-3/4 inch opening; NSN 5975-00-188-1168.
Style 64. For one flush device - 1/4 inch depth: NSN 5975-00-682-0344.
Style 65. For one flush device - 1/2 inch depth: NSN 5975-00-504-7670.
Style 66. For two flush devices - 1/2 inch depth: NSN 5975-00-188-1158.
Style 67. For one flush device - 3/4 inch depth: NSN 5975-00-153-6770.
Style 68. For two flush devices - 3/4 inch depth: NSN 5975-00-176-9028.

Size W - For handy junction box, Style Numbers 69 through 73 are covered by W-P-455, Plate, Wall, Electrical.

Style 69. Blank cover: NSN 5975-00-280-7921.
Style 70. For single receptable: NSN 5975-00-280-3836.
Style 71. For duplex receptacle: NSN 5975-00-188-1164.
Style 72. For toggle switch: NSN 5975-00-501-4924.
Style 73. Multiple wiring device: NSN 5975-00-284-8837.

4. Changes. When a Federal agency considers that this standard does not provide for its essential needs, written request for changing or adding to the standard supported by adequate justification, shall be submitted to the Administration. This justification will explain wherein the standard does not provide for essential needs. The request should be sent in duplicate to the General Services Administration, Federal Supply Service, Washington, DC 20406. The Administration will determine the appropriate action to be taken and will notify the agency.

5. Conflict with referenced specification. Where the requirements specified in this standard conflict with any requirements in a referenced specification, the requirements of the standard shall apply. Nature of conflict between the standard and the referenced specification, shall be submitted in duplicate, to the General Services Administration, Federal Supply Service, Washington, DC 20406.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.

Fed. Std. No. 128B

MILITARY CUSTODIANS:

Army - EL
Navy - YD
Air Force - 85

Review activities:

Army - MI
Air Force - 99

User activity:

Army - MU

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY: NAVY - YD

Project No. 5975-0462

This document is available from the General Services Administration (GSA), acting as an agent for the Superintendent of Documents. A copy for bidding and contracting purposes is available from GSA Business Service Centers. Copies are for sale at the GSA, Specification & Consumer Information Distribution Branch, Building 197 (Washington Navy Yard), Washington, DC 20407 for [illegible] cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:54Z
Check the source to verify that this is the current version before use.