PPP-F-690D
November 20, 1981

SUPERSEDING
Fed. Spec. PPP-F-690C
March 9, 1972

FEDERAL SPECIFICATION

FROZEN FRUITS, FROZEN FRUIT JUICES, AND FROZEN VEGETABLES: PACKAGING OF

This specification is approved by the U.S. Department of Agriculture, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers the preservation, packing, labeling and marking requirements for the domestic and overseas shipment of frozen fruits, frozen fruit juices, and frozen vegetables.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PP-T-425	-	Tinplate (Electrolytic)
TT-C-495	-	Coatings Exterior, for Tinned Food Cans
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-1163	-	Box, Corrugated Fiberboard, High Compression Strength, Weather-Resistant, Wax-Resin Impregnated
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter
PPP-C-1581	-	Cans, Composite, with Metal Ends, For Liquid Items

Federal Standards:

FED-STD-101	-	Preservation, Packaging and Packing Materials: Test Procedures
FED-STD-123	-	Marking for Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, standards and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

FSC PACK
8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

(Single copies of this specification, other Federal specifications, standards, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston; New York; Washington, DC: Philadelphia; Atlanta; Chicago; Kansas City, MO; Fort Worth; Houston; Denver; San Francisco; Los Angeles; and Seattle, WA.

Federal Government activities may obtain copies of Federal specifications, standards and commercial item descriptions and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

(Copies of Military specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

U.S. Department of Health and Human Services

21 CFR - Federal Food, Drug, and Cosmetic Act

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

U.S. Standards for Condition of Food Containers

(Single copies may be obtained without charge from the U.S. Department of Agriculture, AMS, Washington, DC 20250.)

3. REQUIREMENTS

3.1 Materials. All packaging materials shall be new and of good commercial quality and as herein specified, and shall conform to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

3.2 General. Frozen fruit, fruit juices, and vegetables shall be prepared for shipment in accordance with the requirements of this specification. When the product specification requirements are in conflict with the requirements of this specification, the requirements in the specification of latest date shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:50Z
Check the source to verify that this is the current version before use.

3.3 Preservation. The product shall be preserved in accordance with level B or Commercial, as specified (see 6.1).

3.3.1 Level B. The product shall be unit packed in accordance with 3.3.1.1, 3.3.1.1.1, 3.3.1.2, 3.3.1.2.1, or 3.3.1.3, as applicable.

3.3.1.1 Frozen fruits. The amount of frozen fruit specified (see 6.1), shall be unit packed in a metal can as specified in a, b, or c below.

a. Up to 10-pound capacity can. No more than 10 pounds of product shall be unit packed in an open style, round, metal can with soldered or welded side seam and compound lined, double-seamed ends. The can shall be made throughout from not less than 0.25 pound per base box electrolytic tinplate (see 4.3.3) and where necessary, an inside enamel that is normally specified by the can manufacturer for the specific product being unit packed. The can shall have a sufficient base weight and temper to protect the product during shipment and storage. The can shall be hermetically sealed and shall not leak when examined in accordance with 4.3.1.

b. Thirty-pound capacity can. Thirty-pounds of product shall be unit packed in a new, round, full opening, slip-cover style, tapered or straight side metal can. The side of the tapered can shall be as follows: Top O.D. 1007. Bottom O.D. 911. Height (overall cover on) 1214 or 1300. The size of the straight sided can shall be 914 by 1210 or 1300; or 1000 by 1209. The body and end of the can shall be made from not less than 100-pound nominal base weight plate (see 4.3.8) and shall be corrugated or beaded for additional rigidity and the slip covers may be made from not less than 80-pound base weight plate. The side seam shall be soldered or welded, the bottom shall be cement lined and double seamed, and the can rim shall be curled outward. When side seams are welded, the entire interior seam of the container shall be covered with enamel. The slip cover shall be snug-fitting and shall have a flange not less than 11/16 inch long with a curled edge. The can shall be made throughout from not less than commercial 0.25 pound per base box electrolytic tinplate (see 4.3.3). The inside of the can and cover shall be coated with an enamel supplied by the manufacturer for the specific product being packaged. The can and cover shall be coated overall outside with a coating conforming to type I of TT-C-495.

c. Alternative 30-pound capacity can. Alternatively, the can shall be made as specified in 3.3.1.1.b, except that body shall be made from not less than 107-pound nominal base weight plate (see 4.3.8), the ends may be made from 107-pound or 100-pound nominal base weight plate, but the 100-pound bottoms shall be corrugated or beaded for additional rigidity, and the bottom seams shall be compound-lined.

3.3.1.1.1 Individually quick frozen berries. Twenty pounds of individually quick frozen berries, without a packing medium or coating, shall be unit packed in a polyethylene bag. The polyethylene shall be not less than 0.003-inch thick (see 4.2.2.1). The bag shall be gusseted and shall be of sufficient length to allow closure by heat sealing or with a commercial plastic wire tie. Excess air shall be removed from the bag prior to closing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

3.3.1.2 Frozen fruit juices unit packed in cans. Frozen fruit juices, single strength and concentrated, shall be unit packed in the size can specified (see 6.1) and in accordance with the fill requirements of table I. The can shall be constructed from one of the following materials:

a. An open top style, round metal can with a soldered or welded side seam and compound lined, double-seamed ends. Cans containing 6, 12, 30, or 32 fluid ounces of product shall be made from not less than 0.10 pound per base box electrolytic tinplate. Cans containing greater amounts shall be made throughout from not less than 0.25 pound per base box electrolytic tinplate. The can shall have a sufficient base plate weight and temper to protect the product during shipment and storage. The metal cans shall be coated with an inside enamel that is normally specified by the can manufacturer for the specific fruit juice being unit packed. The can shall be hermetically sealed and shall not leak when examined in accordance with 4.3.1.

b. A composite can conforming to class 1, type I, II or III, style I of PPP-C-1581 for 6, 12, 30 or 32 fluid ounce capacity sizes.

c. A plastic can consisting of a molded, one piece body made of high impact polystyrene with a like plastic, easy open, pull tab lid for 6, 12, 30 or 32 ounce capacity sizes. The can shall have a minimum wall thickness of 0.040 inches when measured in accordance with 4.3.4.

TABLE I. Can sizes, fill number, and arrangement in shipping container for frozen fruit juices

Can size	Volume of contents (fluid)	No. in container	Arrangement Length	Width	Depth
202 x 314	6 ounces	48	6	4	2
211 x 413-14	12 ounces	48	6	4	2
401 x 411	1 pint 10 ounces	24	4	3	2
401 x 509-10	1 quart 1/	12	4	3	1
404 x 414	1 quart 1/	12	4	3	1
404 x 500	1 quart 1/	12	4	3	1
404 x 700	1 quart 14 ounces	12	4	3	1
603 x 700	3 quarts	6	3	2	1

1/ For concentrated fruit juices only. Thirty fluid ounces of single strength fruit juice shall be filled into a quart can.

3.3.1.2.1 Frozen fruit juices unit packed in cartons. Six, 12, 30 or 32 fluid ounces as specified (see 6.1), of single strength or concentrated product shall be unit packed in a polyethylene coated paperboard milk carton. The carton shall be fabricated from folding grade bleached sulfate paperboard which has a minimum basis weight of 94.3 pounds per 1,000 square feet when tested in accordance with 4.3.5. The minimum outside polyethylene thickness shall be 0.0005 inch, the minimum inside

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:50Z
Check the source to verify that this is the current version before use.

polyethylene thickness shall be 0.00075 inch, and the minimum thickness of the paperboard carton after coating shall be 0.022 inches when tested in accordance with 4.3.6. Cartons shall be tuck bottom (corner side seam) pitcher-pour style with the machine direction of the paperboard running perpendicular to the score line of the carton opening. The body seam shall be securely bonded by a coating-to-coating heat seal the full depth of the carton. The seam shall not fail when tested in accordance with 4.3.7.

3.3.1.3 Frozen vegetables. The amount of frozen vegetables specified (see 6.1) shall be unit packed in accordance with 3.3.1.3.1 or 3.3.1.3.2.

3.3.1.3.1 Frozen vegetables, unit packed in cartons. The frozen vegetables shall be unit packed in cartons, the size, style, and net contents of which shall be the same as that normally used by the packer. The carton shall be overwrapped and completely heat sealed in one of the materials specified below. Alternatively, the frozen vegetables may be inclosed in a heat sealable bag made from one of the materials specified below and the completely heat sealed bag inclosed in a carton. If a bag is used, the carton need not be overwrapped. The overwrapping or bag materials shall be plastic film or waxed paper of the types normally used in packaging frozen foods.

3.3.1.3.2 Alternative methods of unit packing vegetables in cartons for level B. Alternatively, the carton may be a seal end box in accordance with style I, type A, class a of PPP-B-566 fabricated from minimum 0.014 inch thick solid bleached sulphate with a minimum 0.0005 inch medium density polyethylene (treated for gluing) extruded to the inside of the board with an overprint varnish (or polyethylene) applied to the outside of the board. The box shall be closed with a hot melt adhesive, applied so that the outside flap is thoroughly bonded to the opposite flap of the box. Alternatively, the box may be closed with the outside flap thoroughly bonded to the opposite flap of the box with a polyethylene to polyethylene heat seal closure. The closure shall not fail when tested in accordance with 4.3.7.

3.3.2 Commercial. The product shall be preserved in accordance with MIL-STD-1188.

3.4 Packing. The product shall be packed in accordance with level B or Commercial as specified (see 6.1).

3.4.1 Level B packing. One 30 pound capacity can of fruit product, not more than 60 pounds of fruit product in up to 10 pound capacity cans or in polyethylene bags, nor more than 50 pounds of vegetable product shall be packed in a snug-fitting fiberboard box constructed, closed and reinforced in accordance with style RSC, V3c, V3s, or V4s of PPP-B-636. Alternatively, a wax impregnated corrugated box, constructed, closed and reinforced in accordance with style RSC, class I, type SWCFI, grade 275 of PPP-B-1163 may be used. Cans of fruit juices, in the number and arrangements specified in table I, shall be packed in a snug-fitting fiberboard box

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:50Z
Check the source to verify that this is the current version before use.

constructed, closed and reinforced in accordance with (a), (b), or (c), as applicable. Forty-eight 6- or 12-ounce cartons of frozen fruit juice or twelve 30- or 32-ounce cartons of frozen fruit juice arranged the same as for cans as specified in table I, shall be packed upright in a snug-fitting fiberboard box constructed, closed and reinforced in accordance with (d).

a. Metal cans - Style RSC, V3c, V3s or V4s of PPP-B-636

b. Composite cans - Style RSC-L, V3c, V3s or V4s of PPP-B-636

c. Plastic cans - Style RSC-L, end loading, V3c, V3s or V4s of PPP-B-636

d. Cartons - Style RSC-L, V3c, V3s or V4s of PPP-B-636

3.4.1.1 Nonmetallic reinforcement of shipping containers. When specified (see 6.1 and 6.3), the shipping container specified in 3.4.1 shall be reinforced with nonmetallic strapping or pressure sensitive adhesive, filament reinforced tape in accordance with the appendix of PPP-B-636, except that two reinforcing bands may be used, one lengthwise and one girthwise.

3.4.2 Commercial packing. Packing shall be in accordance with MIL-STD-1188.

3.5 Labeling and marking.

3.5.1 Unit containers. Each unit pack shall be labeled in accordance with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder. Labeling for each unit pack of vegetables shall include cooking instructions and each can of juice shall have mixing instructions. Additional commercial labeling is acceptable.

3.5.2 Shipping containers. In addition to the markings specified in 3.5.2.1 and any special markings specified in the contract, shipping containers shall be marked in accordance with FED-STD-123, MIL-STD-129 or MIL-STD-1188, as applicable.

3.5.2.1 Precautionary markings. Each shipping container shall be marked on the sides in letters between 1 and 1-1/2 inches high, all letters being of the same height, with the following:

KEEP FROZEN
(0°F, OR BELOW)

In addition, shipping containers for plastic cans and cartons shall be marked on the sides in letters between 1 and 1-1/2 inches high, all letters being of the same height, with the following:

THIS SIDE UP

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.1.1 Component testing. In addition to any testing required by 4.2.1, components shall be tested as indicated in table II. Any test failure shall be cause for rejection of the related component lot.

TABLE II. Component tests

Component	Sample unit	Lot size expresssed in	Inspection level	Characteristics	Results reported	Requirements and test reference para.
Cans and lids	1 can and 1 lid	Cans and lids	S-2	Tin plate weight	Nearest .01-lb/ base box	3.3.1.1, 3.3.1.2 and 4.3.3
Plastic cans and lid	1 plastic can and lid	Cans and lids	S-2	Thickness	Nearest 0.001 inch	3.3.1.2 and 4.3.4
Cartons	One carton	Cartons	S-1	Basis weight carton stock	lb/1000 sq. ft.	3.3.1.2.1 and 4.3.5
				Thickness carton stock after coating	0.001 in.	3.3.1.2.1 and 4.3.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

TABLE II. Component tests (cont'd)

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Requirements and test reference para.
Cartons (cont'd)				Body seam heat seal	Pass or fail	3.3.1.2.1,
				Flap separation	Pass or fail	3.3.1.3.2 and 4.3.7
Thirty-pound capacity can	One end and one 4 by 4 inch panel from side	Cans and covers	S-1	Base weight plate	1 lb/base box	3.3.1.1b, 3.3.1.1c, and 4.3.8

4.2.1.2 Inspection of polyethylene bags. Conformance of polyethylene bags to thickness requirements of 3.3.1.1.1 shall be ascertained by examination of pertinent labels, invoices or other valid documents. Use of nonconforming bags shall be cause for rejection of the involved item.

4.2.2 Container and packing inspection. The classification of defects found during inspection shall be in accordance with tables IV through VIII. The inspection criteria shall be as shown in table III. The acceptable quality levels (AQLs) shall be expressed as defects per hundred units.

TABLE III. Inspection criteria

Table	Sample unit	Lot size expressed in	Inspection level	AQLs Major	Minor	Total
IV	One filled and closed can	Cans	S-3	2.5		
V	One filled primary container	Containers	S-3	2.5		
VI	One filled and marked shipping container	Shipping containers	S-3	2.5	6.5	
VII	One metal can	Cans	S-2	1.5	10.0	
VIII	One filled primary container	Containers	S-3	0.65		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

TABLE IV. Can leakage defects 1/

Category	Defect
Major	
151	Steady progression of bubbles.

1/ See 4.3.1 for procedure.

4.2.2.1 Inspection for net weight and fill of primary container. When inspection for net weight or fill of the primary container is not provided for in the commodity specification, inspection shall be in accordance with table V.

TABLE V. Net weight or fill of primary container defects 1/

Category	Defect
Minor	
201	Net weight more than 5 percent under specified weight when container is required to have a net weight of 1 pound or less. 2/
202	Net weight more than 2 percent under specified weight when container is required to have a net weight of more than 1 pound. 3/
203	Volume more than 5 percent under specified volume when container is required to have a net content of 1 pint or less. 4/ 5/
204	Volume more than 2 percent under specified volume when container is required to have a net content of more than 1 pint. 4/ 6/

1/ Lot shall be rejected if sample average indicates lot average net weight or fill is less than specified.

2/ Make determination to nearest 1/10 ounce.

3/ Make determination to nearest 1/10 ounce.

4/ Volume shall be determined on the finished product at 68°F ± 3°F.

5/ Make determination to nearest 1/10 fluid ounces.

6/ Make determination to nearest 2/10 fluid ounces.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:50Z
Check the source to verify that this is the current version before use.

4.2.2.2 Inspection of packaging. Inspection of unit packs for condition and labeling shall be in accordance with criteria in the United States Standards for Condition of Food Containers.

TABLE VI. Packing defects

Category		Defect
Major	Minor	
	201	Net weight greater than allowable net weight as indicated by marking (see 3.4.1). 1/ 2/
	202	Number or arrangement not as specified (see table I). 1/ 3/
151		National stock number, item description, contract number or date of pack markings missing, incorrect, or illegible
152		Precautionary marking omitted, or not as specified (see 3.5.2.1).
	203	Other required markings missing, incorrect or illegible.

1/ Level B pack only.

2/ Frozen fruits or frozen vegetables only.

3/ Frozen fruit juices only.

TABLE VII. Can interior enamel coating defects (when applicable)

Category		Defect
Major	Minor	
151		Missing.
152		Blistered or softened area which can be peeled by fingertip abrasion.
	201	Blistered or softened areas which cannot be peeled by fingertip abrasion.
	202	Scratches through enamel. 1/
	203	Denuded areas (other than scratches). 1/

1/ Scratches or the absence of enamel resulting from normal fabrication and handling or from opening the sealed can for inspection shall not be considered defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

TABLE VIII. Inspection for flap separation

Category	Defect
Major	
151	Any flap separation from carton (see 3.3.1.3.2) at closure points. 1/

1/ When inspected in accordance with 4.3.7.

4.2.2.4 Inspection of polyethylene coating. Conformance of polyethylene coating thickness to the requirements specified in 3.3.1.2.1 shall be ascertained by examination of invoices or other valid documentation from the supplier of the carton material. Nonconformance shall indicate unacceptable material and use of such shall be cause for rejection of the involved end item.

4.3 Methods of inspection. Filled and sealed cans of the thawed product shall be inspected for leakage in accordance with 4.3.1 or 4.3.2, as applicable.

4.3.1 Leakage test of metal cans. The filled and sealed metal can shall be inspected for leakage by submerging on end in water contained in a vacuum desiccator, Mead tester, or equivalent device and maintaining a vacuum of 10 inches of mercury (atmospheric pressure 29.9 inches) for at least 30 seconds. A leak consists of a steady stream of bubbles. Isolated bubbles caused by air entrapped in the double seam are not considered signs of leaks. The inspection shall be repeated after inverting the can.

4.3.2 Leakage test of composite cans. Inspection for leakage of composite cans shall be conducted in accordance with PPP-C-1581.

4.3.3 Tin coating weight test. Tin coating shall be determined by any method specified in PPP-C-96.

4.3.4 Thickness of plastic cans test. Thickness of plastic can wall and lid shall be measured with a dial caliper gauge, accurate to plus or minus 0.001 inch. The gauge shall be an anvil type used for measurement of cylindrical tubing. A minimum of six measurements shall be made at evenly spaced intervals around the perimeter of the container to determine the minimum wall thickness. A minimum of six measurements of the can lid shall be made to determine minimum lid thickness.

4.3.5 Basis weight test. Basis weight shall be tested in accordance with Method 5022 of FED-STD-101.

4.3.6 Thickness of carton stock test. Thickness of carton stock after coating shall be measured in accordance with Method 1003 of FED-STD-101.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:50Z
Check the source to verify that this is the current version before use.

4.3.7 Carton body seam heat seal and box flap closure test. The carton body seam (see 3.3.1.2.1) and the box flap (see 3.3.1.3.2) shall be inspected for seal separation at point of contact after placing the carton in a cold box with a temperature of minus 20°F ± 2°F for a minimum of two hours.

4.3.8 Base plate weight. Base plate weight shall be determined in accordance with QQ-T-425.

5. PACKAGING

5.1 This section is not applicable to this specification.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Weight of frozen fruit, frozen vegetables, and volume of frozen juice per unit pack (see 3.3.1.1, 3.3.1.1.1, 3.3.1.2.1 and 3.3.1.3).
(c) Selection of applicable levels of preservation and packing (see 3.3 and 3.4).
(d) Can size desired for frozen fruit juice (see 3.3.1.2 and table I).
(e) When nonmetallic reinforcement is required for level B packing (see 3.4.1.1 and 6.3).

6.2 Level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the contracting officer should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/ DLAR 4145.7, as applicable.

6.3 Selection of nonmetallic reinforcement. The nonmetallic reinforcement specified in 3.4.1.1 should be selected for shipping containers that are destined for transfer at sea or other specific overseas operations.

6.4 Environment. Environmental pollution prevention measures are contained in the packaging material specification referenced herein. Refer to material specifications or preparing activity for recommended disposability methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 50

Review Activities

Army - MD, SM
Navy - MC, MS
DLA - SS

CIVIL AGENCY COORDINATING ACTIVITIES:

USDA-AMS

PREPARING ACTIVITY:

Army - GL

Project No. PACK-0673

Orders for this publicaltion are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:50Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:50Z
Check the source to verify that this is the current version before use.