PPP-T-1150B
September 28, 1978
SUPERSEDING
PPP-T-1150A
September 17, 1971

FEDERAL SPECIFICATION

TOOLS AND TOOL ACCESSORIES FOR POWER DRIVEN, METAL AND WOODWORKING, MACHINERY, PACKAGING AND PACKING OF

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers requirements for materials, methods of preservation, packaging, packing, and marking of tools and tool accessories (power driven, metal, and woodworking machinery) for various degrees of protection required for shipment and storage.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

O-P-99 - Paradichlorobenzene, Technical (Dichlorobenzene, Para)

R-N-91 - Naphthalene, Technical

OO-M-340 - Milling, Grinding, Drilling, Slotting Attachment

QQ-A-1876 - Aluminum Foil

GGG-P-446 - Plate, Lapping

NNN-P-40 - Paper, Lens

PPP-B-26 - Bag, Plastic, (General Purpose)

PPP-B-566 - Boxes, Folding, Paperboard

PPP-B-576 - Boxes, Wood, Cleated, Veneer, Paper Overlaid

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

PPP-B-585 - Boxes, Wood, Wirebound

PPP-B-591 - Boxes, Shipping, Fiberboard, Wood-Cleated

PPP-B-601 - Boxes, Wood, Cleated-Plywood

PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner

PPP-B-636 - Boxes, Shipping, Fiberboard

PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall

PPP-B-665 - Boxes: Paperboard, Metal Edged and Components

PPP-B-676 - Boxes, Setup

PPP-B-1055 - Barrier Material, Waterproofed, Flexible

PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes

PPP-P-40 - Packaging and Packing of Hand Tools

PPP-T-60 - Tape: Packaging, Waterproof

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-P-116 - Preservation-Packaging, Methods of

MIL-B-117 - Bags, Sleeves and Tubing-Interior Packaging

MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible

MIL-P-149 - Plastic Coating Compound, Strippable (Hot Dipping)

MIL-P-3420 - Packaging Materials, Volatile Corrosion Inhibitor Treated, Opaque

MIL-A-3816 - Abrasives and Abrasive Products; Packaging of

MIL-C-3955 - Cans, Composite, Spirally Wound

MIL-I-8574 - Inhibitors, Corrosion, Volatile, Utilization of

MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-vaporproof or Waterproof, Flexible

MIL-B-13239 - Barrier Material, Waterproofed, Flexible, All Temperatures, Heat Sealable

MIL-B-22191 - Barrier Materials, Transparent, Flexible, Heat Sealable

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; With Appropriate Test Methods

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Traffic Department, 1616 P Street, N.W. Washington, DC 20036.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish one complete packaged and packed item for first article inspection in accordance with 4.1. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the supplier of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Material. Material used in preservation, packaging, and packing shall be as specified herein. Material shall be free of defects and imperfections which may affect the serviceability of the preservation, packaging, and packing.

3.3 Preservation and packaging. Preservation and packaging shall be level A, or Commercial, as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Cleaning. Noncritical surfaces shall be cleaned by process C-1 of MIL-P-116. Critical or close tolerance surfaces shall be cleaned in accordance with process C-5.

3.3.1.2 Drying procedures. All parts shall be dried in accordance with one or more procedures specified in MIL-P-116 that will not damage the item or reduce the effectiveness of the applied preservative compound.

3.3.1.3 Type of preservative. Tools and accessories shall be preserved with the type of preservative specified in table I, column 2 and in accordance with criteria of MIL-P-116. When the table specifies two or more preservatives, the type used will be at the option of the supplier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging

(Table I is on pages 14 through 22.)

3.3.1.3.1 Volatile corrosion inhibitor (VCI). VCI treated material specified herein shall be utilized in accordance with the criteria of MIL-I-8574. The application of a contact preservative will not be required when VCI material is used.

3.3.1.4 Intimate wrap. A greaseproof wrap of material conforming to grade A of MIL-B-121, type II of MIL-B-22191, or QQ-A-1876 (type, class, and grade optional) shall be utilized for tools and accessories coated with a preservative of MIL-P-116 except when items are coated with type P-1 or P-19 preservative. Preserved items placed directly into a greaseproof barrier bag do not require the aforementioned wrap unless sharp corners or projections are subject to puncturing the barrier bag. Parts and items coated with P-1 and P-19 preservatives and subsequently dried, or parts enclosed in P-18 (VCI treated barrier style C, D, or G of MIL-P-3420) are exempt from wrapping as specified herein. Closure of VCI barrier (P-18) wrapped items shall be accomplished by taping all seams so as to form an air-tight enclosure.

3.3.1.5 Protective coatings. Items completely plated, painted, or prime coated; nonferrous items; and those items that may be damaged by contact preservatives shall not have a preservative applied. Intimate wraps as specified in MIL-P-116 shall be used when physical protection is required.

3.3.1.6 Cushioning and cushioning materials. Tools and accessories shall be cushioned, as required, to prevent damage to the items as determined by the criteria of MIL-P-116, and to prevent puncture or tearing of the barrier materials utilized in preservation. Excessive use of cushioning within the unit pack shall be avoided since an unnecessary increase in tare weight and cube will otherwise result. The performance requirements of MIL-P-116 shall be given consideration when determining the quantity of cushioning material actually required. Excelsior, shredded newspaper, and similar materials which have not been chemically refined for noncorrosiveness are unacceptable for interior preservation unless they are enclosed in a sealed waterproof barrier conforming to MIL-B-121 or MIL-B-13239.

3.3.1.7 Methods of preservation. Unless otherwise specified (see 6.2), methods of preservation (unit protection) shall be as specified in table I, column 3 and in accordance with guidelines of MIL-P-116. In the event two or more methods of preservation are listed in table I, the method selected will be at the option of the supplier.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.7.1 Method IB. Unless otherwise specified (see 6.2), the plastic coating utilized in method IB preservation shall conform to type II of MIL-P-149. After the compound sets, the item shall be boxed, canned, or wrapped in a greaseproof barrier material conforming to MIL-B-121, grade A, to retain the oil which exudes from the compound. Coated items must be blocked, braced, or cushioned as necessary to insure that the static load does not exceed 30 pounds per square inch. The compound shall be applied in such a manner that, when removed, none will be retained in crevices, oil holes, or similar cavities. Directions for removal of coating shall be included in each package. The caution marker shall read as follows: "CAUTION: To remove protective coating, split and peel, using a wood or plastic chisel. DO NOT use sharp metal tools or solvents to remove coating." Identification markings may be applied to submethod IB-2 packs prior to the application of the strippable compound.

3.3.1.8 Unit pack quantities. Unless otherwise specified (see 6.2), tools and accessories shall be placed in unit packs, in quantities specified in table I, column 4.

3.3.1.9 Sets or kits. When tool sets or kits are furnished, preservation of individual tools shall be in accordance with table I, except as follows:

(a) Sets or kits furnished in a plastic or leather case and not exceeding 10 pounds shall have each tool preserved as specified in table I and processed method IC-1; sets and kits exceeding 10 pounds shall be processed method IC-2.

(b) Sets or kits furnished in finished wooden cases, such as varnished wood micrometer cases intended for use as a tool box or chest, shall have each tool preserved as specified in table I. The unit packages shall be processed method IC-2, utilizing the wooden case as the inner container. Projections such as hinges and catches on the inner container shall be cushioned with material in accordance with 3.3.1.6.

(c) Tools in a kit which may be damaged by preservatives from other tools shall be wrapped or bagged.

(d) Sets and kits which are not furnished in a carrying case shall be packaged in a unit container. Selection of unit container shall be from table II. The container selected shall accommodate the load and size to be packed therein.

Each tool preserved, wrapped, and cushioned as required shall be placed and secured in the individual slots or contour cut-outs provided in the carrying case, or shall be arranged within the set or kit-container in a compact manner so as to prevent damage during handling, shipment, and storage.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

3.3.1.10 Unit containers. Unless otherwise specified (see 6.2), unit containers not specifically required for the method of preservation shall conform to the requirements of specification listed in table II, at the option of the supplier. Unit containers shall be of minimum cube and tare. The container shall be closed in accordance with the applicable specification and the appendix thereto.

TABLE II. Unit container

Specification	Description	Footnote
PPP-B-26	Bag, Plastic (General Purpose)	
PPP-B-566	Boxes, Folding, Paperboard	1/
PPP-B-636	Boxes, Fiberboard	2/
PPP-B-665	Boxes, Paperboard, Metal Stayed	2/
PPP-B-676	Boxes, Setup	1/
MIL-B-117	Bags, Sleeves and Tubing-Interior Packaging	3/
MIL-C-3955	Can, Fiber, Spirally Wound	

1/ Army - Not acceptable for procurement unless placed in a waterproof barrier material.
2/ Army - Class domestic boxes are not acceptable for procurement unless placed in a waterproof barrier material.
3/ Net weight of contents for MIL-B-117 bags shall not exceed 10 pounds except that there are no weight restrictions for the following bags: type 1, class B, style 2; type 1, class C, style 2; and type 1, class E, styles 1, 2, and 3. Closure shall be in accordance with MIL-P-116 for the applicable method of preservation.

3.3.1.11 Intermediate packages. Unless otherwise specified (see 6.2), unit packs shall be intermediate packaged in containers selected from table III when either of the following conditions exist:

(a) The exterior surface of the unit container is a bag or wrap of any kind, regardless of size.

(b) The unit pack volume is less than 64 cubic inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE III. Intermediate container

Specification	Variety, class, and form	Footnote
PPP-B-566 PPP-B-636 PPP-B-665 PPP-B-676	Variety 2, process II Class WR Class 2 Variety 2 or 4	1/

1/ Army - Not acceptable for procurement unless placed in a waterproof barrier material.

3.3.1.11.1 Limitations of intermediate packages. Unless otherwise specified (see 6.2), unit packages requiring intermediate packaging shall be packaged in containers governed by the following except when the total quantity to be shipped will result in one intermediate container:

(a) Maximum of 100 unit packs.

(b) Maximum net load of 35 pounds.

(c) Maximum size of 1.5 cubic feet with at least each of two dimensions not exceeding 16 inches.

3.3.2 Commercial packaging. Tool and tool accessories shall be preserved and packaged in accordance with normal commercial practice. The complete package shall be designed to protect the items against damage during shipment, handling and storage.

3.4 Packing. Packing shall be level A, or Commercial, as specified (see 6.2).

3.4.1 General requirements. Shipping containers shall be of similar construction, uniform size, and so far as practicable shall be packed to contain like quantities. The boxes shall be constructed to meet the requirements for the loads designed to be packed therein and be of minimum cube and tare. Containers exceeding 200 pounds gross weight shall be modified with skids in accordance with the applicable box specification except that fiberboard and wirebound boxes exceeding 200 pounds gross weight shall be modified with a wooden pallet base fabricated from nominal 1-inch lumber deckboards and nominal 3- by 4-inch lumber skids. Closure shall be in accordance with the applicable box specification and the appendix thereto.

3.4.1.1 Weight limitations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.4.1.1.1 Army requirements. The gross weight of the exterior shipping container shall be governed by the limitations of the applicable container specification.

3.4.1.1.2 Navy and Air Force requirements. Unless otherwise specified (see 6.2), the gross weight of each shipping container shall not exceed approximately 200 pounds except when a single item exceeds the weight limitation.

3.4.1.2 Cushioning, blocking, and bracing. Cushioning, blocking, and bracing shall be provided to restrict movement of the packed items within the shipping container and to prevent physical damage due to transmission of shock and vibration. Application shall be in accordance with the criteria of MIL-P-116 and MIL-STD-1186, as applicable.

3.4.2 Level A.

3.4.2.1 Shipping container. Tools and accessories preserved in accordance with 3.3 shall be packed in shipping containers listed in table IV. The container selected will be at the option of the supplier.

TABLE IV. Shipping container

Specification	Class or type	Footnote
PPP-B-576	Class 2	1/
PPP-B-585	Class 3	
PPP-B-591	Class II	1/
PPP-B-601	Overseas type	
PPP-B-621	Class 2	
PPP-B-636	Class WR	1/
PPP-B-640	Class 2	2/

1/ Army - Not acceptable for level A.
2/ Army and Navy - Not acceptable for level A.

3.4.2.2 Case liner. Except as otherwise specified hereinafter, case liners are required for Navy and Air Force procurement when nonweather resistant containers are being overpacked into exterior shipping containers. The material shall conform to PPP-B-1055 or MIL-B-13239 and the fabrication and assembly shall be in accordance with MIL-L-10547.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

3.4.2.2.1 Case liners will not be required when shipping containers are packed with tools, accessories, or packs meeting the following:

(a) Tools or accessories are completely painted.

(b) Tools or accessories are coated with type P-1 or P-19 preservative provided the interior critical surfaces, if any, are adequately preserved and all openings sealed with sealing materials approved by the procuring activity.

(c) Method IA, method IC, and method II packages.

(d) Unit or intermediate packages employing fiberboard boxes conforming to PPP-B-636, class WR are waterproofed as specified in the appendix thereof.

3.4.3 Commercial packing. Tools and tool accessories shall be packed in shipping containers to insure safe delivery at destination, to provide for safe redistribution by the initial receiving activity, and shall be acceptable by common carrier under National Motor Freight Classification or Uniform Freight Classification.

3.4.3.1 Unitization. When shipments to Government depots are full car or truckload, the shipping containers shall be unitized for shipment and handling in accordance with normal commercial practice. The unitized load shall not exceed 2,500 pounds in weight, 63 inches in height, 56 inches in length, and 45 inches in width.

3.6 Marking.

3.6.1 Military. In addition to any special marking required by the contract or order, marking shall be in accordance with MIL-STD-129.

3.6.2 Civil agencies. Packages and shipping containers shall be marked in accordance with FED-STD-123.

3.7 Workmanship. Workmanship shall be such that when the proper procedure is followed, materials and equipment being processed will receive the required protection against corrosion, deterioration, and damage during shipment and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection classification. Inspection of a complete pack shall be in accordance with 4.2.1 or 4.2.2.

4.2.1 First article inspection. When a first article sample is required (see 3.1 and 6.2), the supplier shall submit the first article sample to all applicable examinations and test specified in MIL-P-116 and other referenced subsidiary specifications to determine conformance with the requirements of this and referenced specifications. Failure of the first article sample to pass any of the tests shall be cause for rejection.

4.2.2 Quality conformance inspection. Quality conformance inspection consists of examining the preservation, packaging, packing, and marking in accordance with the classification of defects set forth in table V and the inspection levels and acceptable quality levels (AQL's) specified herein. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for shipment. The lot shall be the number of shipping containers presented for delivery at one time. The inspection level shall be S-2 with AQL's of 2.5 defects per 100 units for major defects and 4.0 defects per 100 units for minor defects.

4.2.3 Rough handling tests. When specified (see 6.2), the completed packages, packed for shipment, shall be subjected to rough handling tests specified in MIL-P-116 and MIL-STD-1186 as applicable.

5. PREPARATION FOR DELIVERY

5.1 This section is not applicable to this specification.

6. NOTES

6.1 Intended use. It is intended that this specification be used for reference in section 5 of applicable commodity specifications and for direct reference in contracts or orders. The cleaning, drying, preservation, packaging, packing, and marking requirements specified herein are intended to insure proper and safe storage and transportation of tools and accessories for direct shipment to Government activities, or for shipments processed at a military activity or by a civil agency.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the currentversion before use.

TABLE V. Classification of defects

Categories	Defects
MAJOR:	Preservation and packaging. Level or levels not as specified. Close tolerance operating surfaces not cleaned and preserved as specified. Disassembly of tools not in accordance with manufacturer's recommendations. Preservation not of type specified. Greaseproof wrap not as specified. Method of preservation not as specified. Warning marking not provided. Cushioning not provided as required. Tools, in sets or kits, not secured in carrying case of container. Tools not arranged in a compact manner or are loose. Containers do not conform to referenced specifications. Closure of containers not as specified. Gross weight of intermediate containers exceed limit specified. Preservative compound applied when method IB is selected. Tape or other materials do not conform to referenced specifications. Quantity per unit or intermediate container not as specified. Packing. Level not as specified. Container contents not blocked, braced, and cushioned to prevent damage from handling, shipment, and storage. Intermediate fiber boxes (when authorized as level A shipping containers or unit containers for sets of tools packaged IC-2) not closed as specified. Containers nonconforming to applicable specification. Closure banding or strapping (level A) not as specified. Steel strapping not as specified. Caseliner when required, not as specified. Gross weight of shipping container exceeds specified limits for service or agency for which intended. Skids not provided or not as specified in applicable box specification. Commercial packing does not conform to rules or regulations of applicable common carrier. Quantity per shipping container not as specified.
MINOR:	Plastic coating compound not as specified. Marking not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) First article sample, when required (see 3.1).
(c) Selection of applicable degree of protection required (see 3.3 and 3.4).
(d) Unit method of protection, if different (see 3.3.1.7).
(e) Plastic coating, if different (see 3.3.1.7.1).
(f) Unit package quantities, if different (see 3.3.1.8).
(g) Unit containers, if different (see 3.3.1.10).
(h) Intermediate containers, if different (see 3.3.1.11).
(i) Intermediate packaging limitations, if different (see 3.3.1.11.1).
(j) Weight limitations for Navy and Air Force if different (see 3.4.1.1.2).
(k) Submit first article sample, when required (see 4.2.1).
(ℓ) Rough handling tests, when required (see 4.2.3).

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Abrasive wheel dresser, diamond point	P2, P7, P3	I	1	2/
Adapter:				
Base assembly	P2, P3, P18	I	1	9/
Collet	P2, P7, P18	IC-1	1	
Spindle end, milling machine	P2, P7, P3	IC-2	1	
Arbor (various types)				
Up thru 10 lbs	P2, P7, P18	IC-1	1	
Over 10 lbs	P2, P6, P18	IC-2	1	
Attachment:				
Grinder (electric)	P7, P9	IIa, IIb	1	9/
Grinder (nonelec)	P2, P3, P7	IC-2	1	1/ 9/
Milling machine (electric)	P7, P9	IIa, IIb	1	9/
Milling machine (nonelec)	P2, P3, P7	IA-14, IA-15	1	9/
Taper (lathe)	P7	IA-14	1	9/ 3/
Bar:				
Boring tool	P2	I	1	1/
Driving, spotfacer	P3, P7	IC-2	1	See 3.3.1.9
Belt, abrasive	None	IC-2	1	
Bit:				
Hollow chisel				See PPP-P-40
Routing machine				See PPP-P-40
Bit set, cutter	P2, P7, P18	IC-2	1	See 3.3.1.9
Blade:				
Band saw				
Thru 1-inch width	P7, P18	IC-2	1	
Over 1-inch width	P2	I	1	
Circular saw	P1, P2, P19	I	1	1/ 6/
Dado head	P1, P2, P19	I	1	
Jig saw	P7, P18	I	12	
Hole saw	P1, P2, P19	I	1	
Power hack saw				See PPP-P-40
Saw, round				See PPP-P-40

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Block, tool post	P2	I	1	
Box, tool grinder	None	III	1	
Broach set, keyway	P2, P7, P18	IC-2	1	See 3.3.1.9
Button, toolmaker	P2, P7, P3	I	1	
Cabinet, saw and file	None	III		
Cap, end, boring bar	P2, P7, P18	I	1	1/
Center lathe	P2, P7, P18	IC-1, IB-1	1	8/
Chisel, mortising hollow				See PPP-P-40
Chucks:				
Centering lathe	P2, P7, P18	IC-2	1	
Collet	P2, P7, P18	IC-2	1	
Collet, tubeless	P2, P7, P18	IC-2	1	
Draw-in-lathe	P2, P7, P18	IC-2	1	
Drill	P2, P7, P18	IC-2	1	1/
Drill (with arbor and key)	P2, P7, P18	IC-2	1	1/
Grinding wheel	P2, P6	I	1	
Independent jaw	P2, P6	I	1	1/
Lathe, balance	P7, P18	IC-2	1	
Lathe, collet	P2, P7, P18	IC-2	1	
Lathe, metal working	P2, P6	I	1	1/
Universal jaw	P2, P6	I	1	1/
Clamp:				
Machine strap	P1, P2, P19	I	1	
Parallel, machinists				See PPP-P-40
Parallel, toolmakers				See PPP-P-40
Toggle	P2, P7	I	1	2/
Clamping cylinder	P2, P7, P3	IC-2	1	1/ 9/
Collar set, spacing circular saw	P1, P2, P19	I	1	See 3.3.1.9

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Collet:				
Machine	P2, P7, P18	IC-1	1	1/
Machine, flexible, rubber jaws	None	IC-3	1	
Solid, taper hole	P2, P7, P18	IC-1	1	
Spring draw-in	P2, P7, P18	IC-1	1	
Spring force-in	P2, P7, P18	IC-1	1	
Collet set, machine	P2, P7, P18	IC-2	1	See 3.3.1.9
Countersink and drill	P2, P7, P18	IC-1, IB-1	1	8/
Cutter:				
Dovetail	P2, P7, P18	IC-2	1	
Groove circular	P2, P7, P18	IC-2	1	1/
Hole	P2, P7	IC-2	1	
Hole taper shank	P2, P7, P18	IC-2	1	
Hollow mill	P2, P7	IC-2	1	
Inside dado heads	P2	I, IB-1	1	1/ 6/ 8/
Milling	P2, P7, P18	IC-1, IB-1	1	8/
Wooden plug	P2, P7, P18	IC-2	1	7/
Cutter-bit, tool holder cutter bit blanks: (size in inches)				5/
3/8 and under	P2	I	12	
7/16 thru 1/2	P2	I	6	
5/8 thru 3/4	P2	I	2	
over 3/4	P2	I	1	
straight cut off blades:				
3/32 x 1 and under	P2	I	12	
1/8 x 1/2 thru 3/16 x 11/16	P2	I	6	
3/16 x 7/8 thru 1/4 x 1-1/4	P2	I	4	
Cutter set, milling	P2, P7, P18	IC-2, IB-1	1	8/ See 3.3.1.9
Diamond, emery wheel dresser	P7, P18	I	1	
Die, metal punching machine	P2, P6	I	10	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Die, metal working, press brake	P2, P18	I	1	1/ 9/
Disk, abrasive	None	IC-3	1	
Dog, lathe:				
Single screw	P2, P7, P18	I	1	
Double screw	P2, P7, P18	I	1	
Dresser:				
Abrasive wheel	P2, P3, P7	I	1	
Emery wheel	P2, P3, P7	I	1	
Radius	P2, P3, P7	I	1	
Drilling and locating fixture	P3	IC-2	1	
Driving mechanism electric	P7, P9	IIa, IIb	1	
Electrode, shroud	None	IC-2	1	
Edge finder double end	P3, P7	IC-2	1	1/ 2/ 3/ See 3.3.1.9
Face plate, metal-working lathe	P2, P6, P18	I	1	6/
File:				
Band	P7, P18	IC-2	1	
Rotary	P7, P18	IC-1	1	
File guide	P2, P3	IC-2	1	2/
File set, machine	P7, P18	IC-2	1	See 3.3.1.9
Fixture:				
Drill	P7	IC-2	1	
Lathe, metal	P2, P7	IA-14	1	See 3.3.1.9
Follow rest, lathe				See Rest
Gear, lathe, metric transposing	P2, P3, P18	IA-15	1	1/
Grinding attachment, drill				(nonelec) See Attachment

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Grinding machine, tool attachment				(electric) See Attachment
Holder:				
Counterbore	P2, P7, P3	IC-2	1	
Countersink	P2, P7, P3	IC-2	1	
Cutting tool	P2, P7, P3	IC-2	1	1/
Drill	P2, P7, P3	I	1	9/
End mill	P2, P6	IC-2	1	
Lathe turning tool	P2, P7, P3	IC-2	1	1/
Threading and tapping tool	P2, P7	IC-2	1	1/ See 3.3.1.9
Holding fixture, collet chucking machine	P2, P7, P3	IC-2	1	1/
Indexing fixture	P2, P7, P3	IA-14	1	1/
Jacks:				
Bracing	P2, P6	I	1	See PPP-P-40
Planer				
Vertical	P2, P6	I	1	
Jaws, shrinking	P2, P3, P7	I	1	1/
Jig:				
Drill	P6	IC-2	1	
Drill, front camshaft bearing	P18	IC-2	1	
Drill, front counterweight	P18	IC-2	1	
Drill, rear camshaft bearing	P18	IC-2	1	
Key, drill chuck	P1, P2, P19	I	1	
Knurl, machine	P2, P7, P18	IC-1	1	
Knurling tool	P2, P7, P18	IC-2	1	
Mandrel:				
Up thru 10 lbs	P2, P7, P18	IC-1, IB-2	1	1/
Over 10 lbs thru 20 lbs	P2, P7, P18	IC-2	1	
Over 20 lbs	P2	I	1	

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Mandrel and block set	P2, P7, P18	IC-2	1	See 3.3.1.9
Mandrel set:				
Expansion	P2, P7, P18	IC-2	1	See 3.3.1.9
Machine, solid	P2, P7, P18	IC-2	1	See 3.3.1.9
Milling attachment vertical				(nonelec) See Attachment
Milling-grinding drilling-slotting attachment				See 00-M-340
Nib, diamond wheel dressing	P7, P18	I	12	
Pilot, counterbore:				
Thru 1/2 inch	P2, P7, P18	IC-1	4	
Over 1/2 inch	P2, P7, P18	IC-2, IB-1	1	8/
Pilot:				
Countersink dresser				
Thru 1/2 inch	P2, P7, P18	IC-1	1	
Over 1/2 inch	P2, P7, P18	IC-2	1	
Plate, angle, solid	None	IC-2	1	
Plate, lapping:				
Rectangular				See GGG-P-446
Round	P2, P3, P18	IC-2	1	9/
Plug, collet, rubber	None	III	1	
Preparing tool, rotary shaft	P2, P7, P3	IC-2	1	
Protractor, base core box (brass)	None	III	1	
Punch, metal punching machine	P2, P6	I	10	
Reamer, machine				See PPP-P-40
Reamer set, machine				See PPP-P-40

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Rest:				
Follower	P7, P2	IC-2	1	
Steady	P7, P2	IC-2	1	
Tool rest, woodworking lathe	P1, P19, P2	I	1	
Rotary table	P2	IA-14	1	9/ 7/
Saw, hole				See blade, hole saw
Saw set, hole	P2, P7	IC-2	1	See 3.3.1.9
Shafts:				
Drive, universal joint	P2, P3, P7	I	1	9/
Extension drive	P2, P3, P7	I	1	9/
Shield, eye, magnetic grip	None	III	1	
Sleeve, truing	P2, P7, P18	I	1	
Socket, taper shank tool	P1, P2, P19	I	1	
Spacer, milling arbor:				
Thru 3/4 inch thick	P1, P2, P19	I	4	
Over 3/4 inch thick	P1, P2, P19	I	1	
Stand, abrasive wheel dresser	P2, P7	IC-2	1	
Steady rest, lathe				See Rest
Stone:				
Abrasive				See MIL-A-3816
Finish grinding				See MIL-A-3816
Rough grinding				See MIL-A-3816
Stone and holder fine grit	P7, P3, P9	IC-2	1	2/
Stone and holder set:				
Finishing	P7, P3, P9	IC-2	1	2/ See 3.3.1.9
Roughing	P7, P3, P9	IC-2	1	2/ See 3.3.1.9

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Stone set:				
Finishing				See MIL-A-3816
Roughing				See MIL-A-3816
Stop, carriage:				
Micrometer	P3, P7, P2	IC-2	1	9/
Dial indicator	P3, P7, P2	IC-2	1	9/ 3/
Taper attachment lathe				(taper) See Attachment
Taper attachment telescopic				(taper) See Attachment
Template:				
Turrent lathe	P7	IC-2	1	
Vane	None	IC-1	1	
Tool post, lathe	P2, P7	IC-2	1	9/
Tool rest, woodworking				See Rest
Tool set, cutting	P2, P7, P18	IC-2	1	See 3.3.1.9
Tray drill, twist	None	III	1	
Trepanning tool, machine	P2, P7, P18	IC-2	1	1/
V-block	P2	IC-1	1	9/
V-block (clamp type)	P2	IC-2	1	1/ 9/
V-blocks, matched pair	P2	IC-2	1	1/
V-block set (match pr, clamp type)	P2	IC-2	1	See 3.3.1.9
V-block set, matched (clamp type)	P2	IC-2	1	See 3.3.1.9
Vise:				
Machine				See PPP-P-40
Clamp toolmakers	P2, P7, P18	IC-2	1	2/
Wedge honing mandrel	P2, P7, P18	IC-2	1	
Wheel, abrasive				See MIL-A-3816

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:51Z
Check the source to verify that this is the currentversion before use.

TABLE I. Preservation and packaging (cont'd)

Nomenclature	Type preservative of MIL-P-116 (see 3.3.1.3)	Method of preservation (see 3.3.1.7)	Quantity per unit package (see 3.3.1.8)	Special requirements
1	2	3	4	5
Wheel, buffing	None	IC-1	1	4/
Wheel dresser, diamond lathe	P2, P7, P18	I	1	
Wheel guard, grinder	None	III	1	

1/ Wrap parts individually in greaseproof barrier material conforming to MIL-B-121, grade A or MIL-B-22191, type II.
2/ Apply contact preservative to metallic surfaces only.
3/ Wrap parts individually in greaseproof barrier material as specified in footnote 1, and protect precision surface with a sheet of fiberboard, conforming to PPP-F-320, secure fiberboard with pressure-sensitive adhesive tape conforming to PPP-T-60, class optional.
4/ Wheels requiring protection from moths shall be provided with naphthalene flakes or paradichlorobenzene crystals conforming to R-N-91 or O-P-99, respectively.
5/ In case of rectangular tool bit size, greatest cross section (that is, height or width) determines the size of tool.
6/ Place items between two sheets of fiberboard conforming to PPP-F-320, class weather-resistant and secure with tape conforming to PPP-T-60, class optional.
7/ Wrap optic lens with paper conforming to NNN-P-40 to prevent scratching of lens.
8/ Contact preservative specified in column 2 is not required for method IB-1.
9/ No contact preservative shall be applied to electrical equipment, non-ferrous tools, or surfaces of tools that are painted, coated, or plated with corrosion resistant material or are inherently resistant to corrosion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AL
Navy - YD
Air Force - 99

Review activity:
Army - SM

User activity:
Navy - SH

Preparing activity:
Army - AL

Civil Agency Coordinating Activity:
GSA-FSS

Project No. PACK-0538

Orders for this publication are to be placed with General Services Administration, acting as agent for the Superintendent of Documents. See section 2 of this specification to obtain copies of documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

FOLD

Dept. of the Army
US Army Armament Materiel
Readiness Command
Rock Island, IL 61299

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Armament Materiel
Readiness Command
ATTN: DRSAR-LEE-S
Rock Island, IL 61299

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.

FOLD

Dept. of the Army
US Army Armament Materiel
Readiness Command
Rock Island, IL 61299

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Armament Materiel
Readiness Command
ATTN: DRSAR-LEE-S
Rock Island, IL 61299

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:51Z
Check the source to verify that this is the current version before use.