**FED. SUP CLASS**
**5133**

## STANDARD DRILL SIZES

| DRILL SIZE | DEC EQUIV | DRILL SIZE | DEC EQUIV | DRILL SIZE | DEC EQUIV | DRILL SIZE | DEC EQUIV |
|---|---|---|---|---|---|---|---|
| 80 | .0135 | 43 | .089 | 8 | .199 | 25/64 | .3906 |
| 79 | .0145 | 42 | .0935 | 7 | .201 | X | .397 |
| 1/64 | .0156 | 3/32 | .0938 | 13/64 | .2031 | Y | .404 |
| 78 | .016 | 41 | .096 | 6 | .204 | 13/32 | .4062 |
| 77 | .018 | 40 | .098 | 5 | .2055 | Z | .413 |
| 76 | .020 | 39 | .0995 | 4 | .209 | 27/64 | .4219 |
| 75 | .021 | 38 | .1015 | 3 | .213 | 7/16 | .4375 |
| 74 | .0225 | 37 | .104 | 7/32 | .2188 | 29/64 | .4531 |
| 73 | .024 | 36 | .1065 | 2 | .221 | 15/32 | .4688 |
| 72 | .025 | 7/64 | .1094 | 1 | .228 | 31/64 | .4844 |
| 71 | .026 | 35 | .110 | A | .234 | 1/2 | .500 |
| 70 | .028 | 34 | .111 | 15/64 | .2344 | 33/64 | .5156 |
| 69 | .0292 | 33 | .113 | B | .238 | 17/32 | .5312 |
| 68 | .031 | 32 | .116 | C | .242 | 35/64 | .5469 |
| 1/32 | .0312 | 31 | .120 | D | .246 | 9/16 | .5625 |
| 67 | .032 | 1/8 | .125 | 1/4(E) | .250 | 37/64 | .5781 |
| 66 | .033 | 30 | .1285 | F | .257 | 19/32 | .5938 |
| 65 | .035 | 29 | .136 | G | .261 | 39/64 | .6094 |
| 64 | .036 | 28 | .1405 | 17/64 | .2656 | 5/8 | .625 |
| 63 | .037 | 9/64 | .1406 | H | .266 | 41/64 | .6406 |
| 62 | .038 | 27 | .144 | I | .272 | 21/32 | .6562 |
| 61 | .039 | 26 | .147 | J | .277 | 43/64 | .6719 |
| 60 | .040 | 25 | .1495 | K | .281 | 11/16 | .6875 |
| 59 | .041 | 24 | .152 | 9/32 | .2812 | 45/64 | .7031 |
| 58 | .042 | 23 | .154 | L | .290 | 23/32 | .7188 |
| 57 | .043 | 5/32 | .1562 | M | .295 | 47/64 | .7344 |
| 56 | .0465 | 22 | .157 | 19/64 | .2969 | 3/4 | .750 |
| 3/64 | .0469 | 21 | .159 | N | .302 | 49/64 | .7656 |
| 55 | .052 | 20 | .161 | 5/16 | .3125 | 25/32 | .7812 |
| 54 | .055 | 19 | .166 | O | .316 | 51/64 | .7969 |
| 53 | .0595 | 18 | .1695 | P | .323 | 13/16 | .8125 |
| 1/16 | .0625 | 11/64 | .1719 | 21/64 | .3281 | 53/64 | .8281 |
| 52 | .0635 | 17 | .173 | Q | .332 | 27/32 | .8438 |
| 51 | .067 | 16 | .177 | R | .339 | 55/64 | .8594 |
| 50 | .070 | 15 | .180 | 11/32 | .3438 | 7/8 | .875 |
| 49 | .073 | 14 | .182 | S | .348 | 57/64 | .8906 |
| 48 | .076 | 13 | .185 | T | .358 | 29/32 | .9062 |
| 5/64 | .0781 | 3/16 | .1875 | 23/64 | .3594 | 59/64 | .9219 |
| 47 | .0785 | 12 | .189 | U | .368 | 15/16 | .9375 |
| 46 | .081 | 11 | .191 | 3/8 | .375 | 61/64 | .9531 |
| 45 | .082 | 10 | .1935 | V | .377 | 31/32 | .9688 |
| 44 | .086 | 9 | .196 | W | .386 | 63/64 | .9844 |

## STANDARD DRILLED HOLE TOLERANCES:

FOR HOLES DRILLED WITH A DRILLING MACHINE USING SUITABLE JIGS AND FIXTURES, THE HOLE TOLERANCES DEPEND UPON THE DIAMETER OF THE HOLE AND INCREASE AS THE HOLE DIAMETER INCREASES. THE FOLLOWING ARE STANDARD TOLERANCES FOR GENERAL MACHINE WORK AND APPLY IN ALL CASES EXCEPT WHERE GREATER OR LESSER ACCURACY IS REQUIRED BY THE DESIGN:

| HOLE DIA | TOLERANCES |
|---|---|
| .0135 THRU .125 | +.004<br>-.001 ④ |
| .126 THRU .250 | +.005<br>-.001 |
| .251 THRU .500 | +.006<br>-.001 |
| .501 THRU .750 | +.008<br>-.001 |
| .751 THRU 1.000 | +.010<br>-.001 |
| 1.001 THRU 2.000 | +.012<br>-.001 |

APPROVED 26 Jul 44 REVISED ① 26 May 45 ② 22 Jan 47 ③ 15 Sep 52 ④ 25 May 53 ⑤ 9 OCT 73 ⑥ 16 SEP 74

THIS DRAWING FORMS A PART OF THE AIR FORCE-NAVY AERONAUTICAL STANDARD DRAFTING ROOM MANUAL.

# ⑥ STANDARD REACTIVATED 16 SEP 1974

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTE. This drawing was approved by joint action of the AIR FORCE and Navy Departments as standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new design, not later than six months after the latest date of approval shown. It may be put into effect at an earlier date after promulgation.

| AIR FORCE-NAVY AERONAUTICAL DESIGN STANDARD | | | AND10387 |
|---|---|---|---|
| P.A.<br>NAVY-AS | OTHER CUST:<br>USAF-71 | DRILL SIZES AND DRILLED HOLE TOLERANCES-TWIST | |

NOT A PART NUMBER

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:29Z
Check the source to verify that this is the current version before use.