NOT MEASUREMENT SENSITIVE

MIL-DTL-14639/32
20 December 1996
SUPERSEDING
MIL-I-3949/12H
20 March 1995

DETAIL SPECIFICATION SHEET

# INSIGNIA, RANK, LIEUTENANT COLONEL AND MAJOR, ARMY AND AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-14639 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: Lieutenant Colonel, Regular Size
-2: Lieutenant Colonel, Miniature Size (AF)
-3: Major, Regular Size
-4: Major, Miniature Size (AF)
-5: Lieutenant Colonel, Regular Size, Subdued
-6: Major, Regular Size, Subdued

MATERIAL:
-1,-2: Red Brass or Nickel Silver
-3,-4: Red Brass
-5,-6: Red Brass or Zinc Aluminum

DIMENSIONS:
HEIGHT (Overall):
-1,-3,-5,-6: 1-1/8 inches (2.86 cm) (REF)
-2,-4: 23/32 inch (1.83 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1,-3,-5,-6: 1 inch (2.54 cm) (REF)
-2,-4: 11/16 inch (2.75 cm) (REF)
THICKNESS (Overall):
-1,-3,-5,-6: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)
-2,-4: 0.096 inch ± 0.005 inch (0.243 cm ± 0.012 cm)

FINISH:
-1,-2: Nickel Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 18.
-3,-4: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
-5: Dull Flat Black Baked Enamel.
-6: Dull Flat Brown Baked Enamel.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and the following distance apart:

-1,-3,-5,-6: 7/8 inch + 1/64 inch (2.22 cm + 0.04 cm)
-2,-4: 19/32 inch ± 1/64 inch (1.51 cm ± 0.04 cm)

3. A forcer may be used to bring up the design for Dash No. -2, -3, -5 and -6. There shall be a minimum thickness of 0.085 inch ± 0.005 inch (0.215 cm ± 0.012 cm) at the high point of the forced area.

4. The dull flat enamel for Dash No. -5 and -6 shall match the chip numbers of FED-STD-595 listed below:

| COLOR | CHIP NUMBER |
|---|---|
| Black | 37038 |
| Brown | 20095 |

5. Dash No. -3 and -4 may be manufactured using 22 karat gold plate with nickel underplating, matte finish with polished highlights and shall match TIOH Metal Finish Chip Number 11 for commercial sale only.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0874)


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.