NOT MEASUREMENT SENSITIVE


MIL-DTL-14639/32B
18 December 2020
SUPERSEDING
MIL-DTL-14639/32A
16 February 2016

DETAIL SPECIFICATION SHEET

INSIGNIA, RANK, LIEUTENANT COLONEL AND MAJOR, U.S.ARMY AND U.S.AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-14639.



DASH NO.
-1: Lieutenant Colonel, Regular Size
-2: Lieutenant Colonel, Miniature Size (AF)
-3: Major, Regular Size
-4: Major, Miniature Size (AF)
-5: Lieutenant Colonel, Regular Size, Subdued
-6: Major, Regular Size, Subdued

MATERIAL:
-1,-2: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No. C-752)
-3,-4: Red Brass 85/15 (UNS Alloy No. C-230)
-5,-6: Red Brass 85/15 (UNS Alloy No. C-230) or Zinc Aluminum

DIMENSIONS:
HEIGHT (Overall):
-1,-3,-5,-6: 1-1/8 inches (REF)
-2,-4: 23/32 inch (REF)
WIDTH (Overall):
-1,-3,-5,-6: 1 inch (REF)
-2,-4: 11/16 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.

THICKNESS (Overall):
-1,-3,-5,-6: 0.150 inch ± 0.010 inch
-2,-4: 0.096 inch ± 0.005 inch

FINISH:
-1,-2: Nickel Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 18.

-3,-4: 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

-5: Dull Flat Black shall match the TIOH Metal Finish Chip Number 21.

-6: Dull Flat Brown shall match TIOH Metal Finish Chip Number 22.

ATTACHING DEVICE:
1. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and the following distance apart:
A. For -1,-3,-5,-6: 7/8 inch ± 1/64 inch
B. For-2,-4: 19/32 inch ± 1/64 inch

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. . A forcer may be used to bring up the design for -2, -3, -5 and -6. There shall be a minimum thickness of 0.085 inch ± 0.005 inch at the high point of the forced area.

3. The dull flat enamel for -5 and -6 shall match the chip numbers of SAE-AMS-STD-595 listed below:

4. For -3 and -4 may be manufactured using 22 karat gold plate with nickel under plating, Matte Finish with Polished Highlights and shall match TIOH Metal Finish Chip Number 11 for commercial sale only.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-112)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:05Z
Check the source to verify that this is the current version before use.