NOT MEASUREMENT SENSITIVE

MIL-I-14639/26C
14 September 1990
SUPERSEDING
MIL-I-14639/26B
18 April 1989

MILITARY SPECIFICATION SHEET

INSIGNIA, GRADE, DISTINCTIVE DEVICE, FIRST SERGEANT, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-14639.



MATERIAL: Gilding metal

DIMENSIONS:
HEIGHT (Overall): 1/4 inch (0.64 cm) (REF)
WIDTH (Overall): 15/32 inch (1.19 cm) (REF)
THICKNESS (At edge): .060 inch ± .005 inch (0.152 cm ± 0.012 cm)

FINISH: Hard enameled, nickel plated, mirror-like polished finish

NOTES:
1. Enamel area shall be as indicated. The color shall conform to TIOH chip Blue 18 or the standard sample.
2. Attaching device shall be a prong with pick and clutch type. The prong shall be 1/4 inch ± 1/32 inch (0.64 cm ± 0.08 cm) long and shall be centered on the back of the device.
3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85, and incorporate an ultraviolet inhibitor.
4. Insignia may be rhodium plated, mirror like-polished at the option of manufacturer.

Custodian:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Air Force - 82,99
DLA - CT

(Project No. 8455-0543)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:03Z
Check the source to verify that this is the current version before use.