
FED. SUP CLASS
5315



FLAT

FLAT, SLIGHTLY CSK

TABLE I. DASH NUMBERS AND DIMENSIONS.

UNDERLAYMENT NAIL						
DASH NUMBER		COMM. SIZE	ØD ±.004	ØH (SEE REQT 5)	L	NUMBER PER LB (APPROX)
FLAT	CSK					
1	1A		.080	.188 ±.018	1 1/4	600
2	2A		.099	.250 ±.025	1 1/4	399
3	3A		.080	.188 ±.018	1 1/2	496
4	4A		.099	.250 ±.025	1 1/2	328
5	5A		.099	.250 ±.025	1 3/4	279
6	6A	6d	.106	.266 ±.026	1 7/8	175
7	7A	7d	.109	.266 ±.026	2 1/8	171
8	8A	8d	.113	.297 ±.029	2 3/8	141

REQUIREMENTS:

1. MATERIAL: NAIL, TYPE II, STYLE 25 SHALL BE MANUFACTURED FROM STEEL WIRE IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
2. CHARACTERISTICS. NAIL SHALL HAVE FLAT OR FLAT SLIGHTLY COUNTERSUNK HEAD, DIAMOND POINT, ROUND MECHANICALLY DEFORMED SHANK (RING STYLE) AND BRIGHT FINISH (SEE NOTE 2).
3. SHANK DIAMETERS. TOLERANCES ON SHANK DIAMETERS SHALL BE ±.004 INCH. DIAMETERS OF MECHANICALLY DEFORMED SHANKS SHALL BE MEASURED BEFORE DEFORMATION.
4. LENGTHS. TOLERANCES ON LENGTHS SHALL BE ±1/32 INCH FOR LENGTHS UP TO AND INCLUDING 1 INCH; ±1/16 INCH FOR LENGTHS OVER 1 INCH UP TO AND INCLUDING 2 1/2 INCHES; ±3/32 INCH OVER 2 1/2 INCHES UP TO AND INCLUDING 7 INCHES AND ±1/8 INCH FOR LENGTHS OVER 7 INCHES.
5. HEAD DIAMETERS. THE DIFFERENCE IN DIAMETER ACROSS THE LONG AXIS SHALL NOT EXCEED THAT ACROSS THE SHORT AXIS BY MORE THAN 10 PERCENT. A FILLET SHALL BE PROVIDED UNDER THE HEAD; AN ANGLE OR RADIUS WILL BE ACCEPTABLE. HEADS WILL BE WELL CENTERED.

REVIEWER ACTIVITIES: CIVIL AGENCIES COORDINATING ACTIVITIES
ARMY- CE, GL, ME
NAVY- MC, SA
GSA-FSS

USER ACTIVITIES:
ARMY- AV, MI
NAVY- AS, SH

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense.
Selection for all new engineering and design applications and for repetitive uses shall be made from this document when applicable.

P.A. ARMY-AR Other Cust NAVY-YD AIR FORCE-99	INTERNATIONAL INTEREST	TITLE NAIL, UNDERLAYMENT	MILITARY STANDARD MS 51542
PROCUREMENT SPECIFICATION FF-N-105	SUPERSEDES:		PAGE 1 OF 2

AMSC N/A DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5315-0399

REVISED
Approved 28 OCT 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:06Z
Check the source to verify that this is the current version before use.

6. PART NUMBER. THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS51542-2
- DASH NUMBER
- BASIC MS SHEET NUMBER

MS51542-2 INDICATES - NAIL, UNDERLAYMENT, .099 SHANK DIAMETER, .250 HEAD DIAMETER, 1 1/4 LONG, FLAT HEAD

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. BRIGHT FINISH IS A TERM APPLIED TO NAILS WITH NATURAL BARE FINISH RESULTING FROM CLEANING OF NAILS WHICH HAVE NOT UNDERGONE TREATMENTS AFFECTING FINISH SUCH AS HARDENING, BLUING, COATING, PLATING, ETCHING AND PAINTING.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

REVIEWER ACTIVITIES: CIVIL AGENCIES COORDINATING ACTIVITIES
ARMY-CE, GL, ME GSA-FSS
NAVY-MC, SA

USER ACTIVITIES:
ARMY-AV, MI
NAVY-AS, SH

APPROVED 28 OCT 86 REVISED

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P. A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
ARMY-AR Other Cust NAVY-YD AIR FORCE-99		NAIL, UNDERLAYMENT	MS 51542
PROCUREMENT SPECIFICATION FF-N-105	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:06Z
Check the source to verify that this is the current version before use.